

# 402 - Introduction to Digital Humanities Design and Programming

Spring Semester 2016

Week 14

### Final Presentation - Wednesday 27th April 2016

- create DH project resource
  - text, images, audio, video, maps...
- individual or group
  - if group, each member must clearly identify work and role to gain credit
- ~ 15 minutes in length plus questions
  - peer-reviewed (your answers and assessment will only be shared with myself)
- offer a practical demonstration of their online resource
- answer questions on its development and publication
  - taxonomy, metadata, content structure, design choices, code additions...
- teach the class about a chosen resource and subject material
  - tests weekly reading, understanding of taxonomy, metadata, content structure...
  - content can be age specific or open any subject, genre...
    - eg: history, literature, culture, music, video etc
    - you may use 3rd party APIs to populate content (good idea for a plugin,,,)

Object Oriented Programming - Abstract overview of current framework structure

#### Recent updates to v0.7 include:

- Update DB for adding site menus
  - new DB tables for menu and menu lookup
- Adding a main menu to the framework site
  - new MenuController class
  - updated View class
- Handling requests for generic controller and params URI
  - Load all content for requested params id in URI
  - updated Loader class and load\_controller() method
  - updated taxonomy query, output...
  - updated content controller, viewer...
  - plugins available for generic controller and params URI

Object Oriented Programming - Abstract overview of current framework structure adding a menu - database tables

- two new database tables for menu and menu\_lookup
- menu allows us to specify different menus for the framework
  - for example a persistent site-wide menu in the header
  - content menus in the sidebar...
- menu\_lookup table allows us to associate a menu with a node and define the menu's tree
  - uses a node set in the new table 'node'
  - eg: parent links and child links
  - no grandchild links at the moment
- node table allows us to specify menu and content nodes to link to static pages
  - links can be to any page with format
  - could be static page with html, image or text etc from DB table content

Object Oriented Programming - Abstract overview of current framework structure

#### adding a main menu

- new main menu rendered to header section of framework template
- load\_menu() method added to Loader class
  - new constant is set for known menu ids in DB
  - accepts menu id as parameter allowing us to build any required site menu
  - loads MenuController class
  - instantiates object for class
  - gets menu using menu\_id parameter
  - sets menu output to static property in Loader class
- load\_menu() called in draw\_theme() method
- property set in load\_menu() is now passed to draw\_header() method

Object Oriented Programming - Abstract overview of current framework structure adding a main menu - new MenuController class

- getter method returns structured menu links for menu\_id parameter
- menu\_links\_query() queries the DB for all parent links for the required menu\_id
  - then menu\_child\_query() queries the DB for all child links for specified parent\_id
- child links are pushed into an array with parent links
  - parent links and child links, then next parent and child links etc...
- each combined parent and child array is then pushed into the main menu\_links array
- we can now use menu\_links array to output our menu

Object Oriented Programming - Abstract overview of current framework structure adding a main menu - updated View class

- draw\_menu() method added to View class allows us to abstract menu output
  - uses the menu\_links array from MenuController class
  - checks for parent links and then each child link
  - structures the links as and in HTML
- main menu is drawn from the draw\_header() method
  - site wide persistent menu for links such as home, about, contact, help etc...
- css is currently in the frame.css file
- links are based on node link in node table in DB
  - allows creation of holder pages for site content etc based on Router URI standard
    - eg: page for image galleries could list info on all site galleries etc...
  - create link to a specific content item in content table in DB
  - links can be to single items, such as image or text, or holder pages etc...

Object Oriented Programming - Abstract overview of current framework structure

handling requests for generic controller and params URI

- updated Loader class and load\_controller() method to handle controller and params URI
  - eg: content&id=22 taxonomy&id=3
- new conditional check for controller and params
- loads class for frame/controller (eg: taxonomy, content...)
- then loads applicable frame/view
  - eg: frame/view/taxonomy.php frame/view/content.php

Object Oriented Programming - Abstract overview of current framework structure

handling requests for generic controller and params URI - taxonomy.php

- this loads a tabular view of all content for the specific params id in URI
- eg: <a href="mailto:taxonomy&id=3">taxonomy&id=3</a> will load all content (images, texts etc) for taxa\_id=3 from content table using content\_lookup
- new taxonomy\_content\_query() method in TaxonomyController class
  - TaxonomyController class in frame/controller/taxonomy.php
- TaxonomyViewer class is used to render the tabular output for the DB result
  - TaxonomyController class in frame/view/taxonomy.php

Object Oriented Programming - Abstract overview of current framework structure

handling requests for generic controller and params URI - content.php

- follows same pattern as taxonomy.php for loading content&id=?
- ContentController class has now been updated with get controller content() method
  - accepts controller and params
- returns requested content for content and params['id']
- ContentViewer class formats content for output
  - currently outputs split content view to match image and text content options in DB
  - parallel display of image and text
- can be updated to only handle contentformat (eg: contentimage) where content is available for requested id
  - simply checks DB returned result for values

eg: content&id=15

Object Oriented Programming - Abstract overview of current framework structure handling requests for generic controller and params URI - plugins

- plugins are also available for controller and params view
- checks plugin\_type in plugins\_lookup table for available plugins
- adds available plugins to the rendered view

Object Oriented Programming - Abstract overview of current framework structure

#### More framework examples

- taxonomy page
- content page

#### 402framework - v0.8

- update framework to v0.8 available on GitHub
  - <u>GitHub v0.8</u>
- update database SQL to v0.8 available on GitHub
  - GitHub SQL v0.8

Object Oriented Programming - Abstract overview of current framework structure

More framework examples - v0.8

- taxonomy page
- content page

Object Oriented Programming - Abstract overview of current framework structure

#### Recent updates to v0.8 include:

- Update DB with sets of data for site content
- Update taxonomy controller
  - new checks for child content relative to query, eg: parent and content query
  - new taxonomy\_content\_check() and taxonomy\_child\_query() methods
  - get related links for selected taxa id, format, and content id
- Update View class in view.php to handle related links for selected taxa id
- Update ContentController in content.php
  - content check and output for multiple formats in DB, eg: image, text...
- New option for site wide Search
  - new controller and view for initial search option
  - highlighter plugin for search...
- New maps controllers and view
- Maps in a group with the addition of 'atlas' group...
- jQuery tabs option added for content view

Object Oriented Programming - Abstract overview of current framework structure

Adding our first sets of data to the framework DB

- content, content\_group, content\_type and content\_lookup
- content\_meta
- menu and menu\_lookup
- node
- plugins and plugins lookup
- taxonomy and taxonomy\_lookup
- users

Object Oriented Programming - Abstract overview of current framework structure updated frame/controller/taxonomy.php - part 1

- taxonomy&id=1 type query now checks DB for children if no content available
  - used as a check for all content for overall parent taxa
  - eg: Devon (id=1) which also contains Brixham (id=3) and Torquay (id=4)
- new taxonomy\_content\_check() and taxonomy\_child\_query() methods
- getter method queries taxonomy\_content\_check() method
  - if content is available for the taxa itself, then db results is returned as expected
  - if no content, then child taxa are found and content checked and returned

Object Oriented Programming - Abstract overview of current framework structure

<u>updated frame/controller/taxonomy.php - part 2</u>

related links for selected taxa id - get\_taxonomy\_related()

- uses taxa\_id in URI to query DB for parent and child related links from taxonomy and taxonomy\_lookup
  - eg: taxonomy&id=1 or taxonomy&id=3
- checks if parent is available for taxa id
  - if parent then it outputs parent and child links (no repetition of current taxa id in URI)
  - if no parent simply outputs child links
  - eg: Brixham outputs Devon and Torquay
    Devon outputs Brixham and Torquay
- 'groups' works in the same manner and outputs parent and child or just child links for taxa\_id in URI

Object Oriented Programming - Abstract overview of current framework structure

<u>updated frame/controller/taxonomy.php - part 3</u>

related links for selected format and content id - get\_content\_related()

- similar implementation and functionality as taxonomy&id=3
- new getter method and content\_related\_check() method in frame/controller/taxonomy.php
  - requires params['id'] and new params['format'] parameters from params array
- gets taxa\_id for given format and content\_id using new method contentformat\_taxa\_query()
  - then passes taxa\_id to taxonomy\_related\_check() method
- examples
  - text&id=15
  - <u>image&id=15</u>

Object Oriented Programming - Abstract overview of current framework structure

updated system/library/view.php

related links for selected taxa id - updated view

- related\_links array passed to draw\_middle() method in View class
  - then passed to draw sidebar()
  - option to draw\_related\_content() or draw\_related\_links()
    - render links for related content or related taxa
- new draw related links() method in View class
  - checks for array in passed parameter
  - sets HTML for required rendering of related links in vertical menu layout
  - iterates over related\_links array and outputs each link as list item in unordered list

Object Oriented Programming - Abstract overview of current framework structure

updated frame/controller/content.php

content check and output for multiple material - check formats

- checks content table for contentid and returns available formats
  - eg: image, text...
- new getter and method content\_format\_query() to check for available content formats
  - accepts format and content id as parameters
  - queries DB to get all formats for the content id
  - checks returned results against format parameter and refines results
  - returns results to Loader
  - check for current controller and format, then unset/remove from related content array
- related content array is then passed to draw\_theme() method
  - allows us to decide where to output and render our related content links
  - passed as parameter to draw\_middle() method

Object Oriented Programming - Abstract overview of current framework structure updated system/library/view.php

content check and output for multiple material - view related content links

- returned related content such as contentimage, contenttext etc is now passed to View class
- related content is then passed from draw\_middle() to draw\_sidebar()
- related content links are then drawn using draw related content() method
  - rendered as now standard unordered list using vertical menu class

Object Oriented Programming - Abstract overview of current framework structure search form - basic site wide option

- new controller and view for basic search option
- search form added as draw method within View class, which is rendered in header section of site
- frame/controller/search.php accepts user search query and controller as parameters
  - search row query() method performs full-text query of content table in DB
  - results returned to Loader class

GitHub Code

Object Oriented Programming - Abstract overview of current framework structure search form - basic site wide option

- new frame/view/search.php handles the rendering of the returned results
- outputs search results as a table using the same template as taxonomy etc
- modified title and description in sidebar to reflect search results and search query
- appends query result as highlight parameter to URI for view text page
  - highlighter plugin highlights search query within matched search result texts

Object Oriented Programming - Abstract overview of current framework structure search controller and viewer

- same design pattern as other controllers and viewers
  - frame/controller/search.php and frame/view/search.php
- plugins\_lookup updated to enable pager etc for search viewer
- frame/view/search.php outputs search results in a table layout
  - follows same design pattern as frame/view/taxonomy.php
  - link for text modified to include extra parameter for user search query
    - eg: query=brixham
- queries currently match lower and upper case word, query strings are not case sensitive

Object Oriented Programming - Abstract overview of current framework structure search controller and viewer

- <u>search example returned results</u> (search query = brixham)
- <u>search example returned results</u> (search query = town)
- highlighted search results in content page

Object Oriented Programming - Abstract overview of current framework structure

#### maps controller and view

- new column in content table and new content type 'map' in content\_type table
- new column 'contentmap' accepts latitude and longitude as comma separated value
  - eg: 50.39747,-3.51490
  - this value is used to render map at correct latitude and longitude coordinates
- map controller gets required DB results for specified content id requested by user in URI eg: map&id=31 (NB: no matching map viewer at the moment...)
- map viewer renders the required map\_canvas div for Google Maps API
  eg: content/map&id=31
- map plugin gets coordinates from map\_canvas attribute 'coordinates
  - renders coordinates to sidebar and adds them to maps output
  - map is drawn to map\_canvas div

Object Oriented Programming - Abstract overview of current framework structure <u>maps</u>

- plugins, taxa, related content all applicable in sidebar...
- example can be found at the following URL

**Brixham Harbour map** 

Object Oriented Programming - Abstract overview of current framework structure maps in a group - addition of 'atlas'

- maps are now grouped into an 'atlas'
- viewer added for group 'atlas'
  - follows the same pattern as book etc
  - eg: Brixham maps
- plugins etc can also be developed and easily added for this new group, same as books etc...

GitHub Code 1

Object Oriented Programming - Abstract overview of current framework structure

.

version 0.8 of 402framework

#### <u>402framework - v0.8-tabs</u>

- update framework to v0.8-tabs available on GitHub
  - GitHub v0.8-tabs
- update database SQL to v0.8-tabs available on GitHub
  - GitHub SQL v0.8-tabs

Object Oriented Programming - Abstract overview of current framework structure

jQuery UI - Adding tabs to a view

- frame/view/content
- tabs plugin
  - show tabs div for content rendering
  - hide tabs span output for plugin name...
- plugins and plugins lookup tables

Object Oriented Programming - Abstract overview of current framework structure

Final version of 402framework - with tabs