

# **Comp 388/424 - Client-side Web Design**

---

Fall Semester 2015 - Week 5

Dr Nick Hayward

# Contents

---

- JS core

- *this* keyword

- JS extras

- *best practices*
- *performance*
- *JSON*

- HTML5, CSS, & JS

- *example*
- *final thoughts*

- jQuery

- *basics*

## JS core - this

---

- `this` keyword - correct and appropriate usage
  - *commonly misunderstood feature of JS*
- value of `this` is not inherently linked with the function itself
- value of `this` determined in response to how the function is called
- value itself can be dynamic, simply based upon how the function is called
- if a function contains `this`, its reference will usually point to an **object**
- manipulate and update the underlying context using `.apply()`, `.bind()`, and `.call()`

# JS core - this default - part I

---

## *global, window object*

- when we call a function, we can bind the `this` value to the window object
- resultant object refers to the root, in essence the global scope

```
function test1() {  
  console.log(this);  
}  
  
test1();
```

- **NB:** the above will return a value of `undefined` in strict mode.
- also check for the value of `this` relative to the global object,

```
var a = 49;  
  
function test1() {  
  console.log(this.a);  
}  
  
test1();
```

- JSFiddle - this - window
- JSFiddle - this - global

## JS core - this default - part 2

---

### *object literals*

- within an object literal, the value of `this`, thankfully, will always refer to its own object

```
var object1 = {  
  method: test1  
};  
  
function test1() {  
  console.log(this);  
}  
  
object1.method();
```

- return value for `this` will be the object itself
- we get the returned object with a property and value for the defined method
- other object properties and values will be returned and available as well
- JSFiddle - this - literal
- JSFiddle - this - literal 2

## JS core - this default - part 3

---

### events

- for events, value of `this` points to the owner of the bound event

```
<div id="test">click to test...</div>
```

```
var testDiv = document.getElementById('test');

function output() {
  console.log(this);
};

testDiv.addEventListener('click', output, false);
```

- element is clicked, value of `this` becomes the clicked element
- also change the context of `this` using built-in JS functions
  - such as `.apply()`, `.bind()`, and `.call()`
- JSFiddle - this - events

# JS extras - best practices - part I

---

## ***a few best practices...***

### ***variables***

- limit use of global variables in JavaScript
  - *easy to override*
  - *can lead to unexpected errors and issues*
  - *should be replaced with appropriate local variables, closures*
- local variables should always be declared with keyword `var`
  - *avoids automatic global variable issue*

### ***declarations***

- add all required declarations at the top of the appropriate script or file
  - *provides cleaner, more legible code*
  - *helps to avoid unnecessary global variables*
  - *avoid unwanted re-declarations*

### ***types and objects***

- avoid declaring numbers, strings, or booleans as objects
- treat more correctly as primitive values
  - *helps increase the performance of our code*
  - *decrease the possibility for issues and bugs*

# JS extras - best practices - part 2

---

## type conversions and coercion

- weakly typed nature of JS
  - *important to avoid accidentally converting one type to another*
  - *converting a number to a string or mixing types to create a NaN (Not a Number)*
- often get a returned value set to NaN instead of generating an error
  - *try to subtract one string from another may result in NaN*

## comparison

- better to try and work with === instead of ==
  - *== tries to coerce a matching type before comparison*
  - *=== forces comparison of values and type*

## defaults

- when parameters are required by a function
  - *function call with a missing argument can lead to it being set as **undefined***
  - *good coding practice to assign default values to arguments*
  - *helps prevent issues and bugs*

## switches

- consider a default for the switch conditional statement
- ensure you always set a default to end a switch statement



# JS extras - performance - part I

---

## loops

- try to limit the number of calculations, executions, statements performed per loop iteration
- check loop statements for assignments and statements
  - *those checked or executed once*
  - *rather than each time a loop iterates*
- for loop is a standard example of this type of quick optimisation

```
// bad
for (i = 0; i < arr.length; i++) {
  ...
}
// good
l = arr.length;
for (i = 0; i < l; i++) {
  ...
}
```

- source - W3

## JS extras - performance - part 2

---

### DOM access

- repetitive DOM access can be slow, and resource intensive
- try to limit the number of times code needs to access the DOM
- simply access once and then use as a local variable

```
var testDiv = document.getElementById('test');  
testDiv.innerHTML = "test...";
```

### JavaScript loading

- not always necessary to place JS files in the <head> element
- adding JS scripts to end of the page's body
  - *allows browser to load the page first*
- HTTP specification defines browsers should not download more than two components in parallel

# JS extras - JSON - part I

---

- JSON is a lightweight format and wrapper for storing and transporting data
- inherently language agnostic, easy to read and understand
- growing rapidly in popularity
  - *many online APIs have updated XML to JSON for data exchange*
- syntax of JSON is itself derived from JS object notation
  - *text-only format*
- allows us to easily write, describe, and manipulate JSON in practically any programming language
- **JSON syntax** follows a few basic rules,
  - *data is recorded as name/value pairs*
  - *data is separated by commas*
  - *objects are defined by a start and end curly brace*
  - *{ }*
  - *arrays are defined by a start and end square bracket*
  - *[ ]*

## JS extras - JSON - part 2

---

- underlying construct for JSON is a pairing of name and value

```
"city": "Marseille"
```

### **JSON Objects**

- contained within curly braces
- objects can contain multiple name/value pairs

```
{  
  "country": "France",  
  "city": "Marseille"  
}
```

## JS extras - JSON - part 3

---

### JSON Arrays

- contained within square brackets
  - *arrays can also contain objects.*

```
{
  "cities": [
    {
      "name": "Marseille",
      "region": "Provence-Alpes-Côte d'Azur"
    },
    {
      "name": "Paris",
      "region": "Île-de-France"
    }
  ]
}
```

- use this with JavaScript, and parse the JSON object.
  - *JSFiddle - Parse JSON*

# HTML5, CSS, & JS - example - part I

---

## Structure

- combine HTML5, CSS, and JavaScript, to create an example application
- outline of our project's basic directory structure

```
.
|- assets
|  |- images //logos, site/app banners - useful images for site's design
|  |- scripts //js files
|  |- styles //css files
|- docs
|  |- json //any .json files
|  |- txt //any .txt files
|  |- xml //any .xml files
|- media
|  |- audio //local audio files for embedding & streaming
|  |- images //site images, photos
|  |- video //local video files for embedding & streaming
|- index.html
```

- each of the above directories can, of course, contain many additional sub-directories
  - */- images may contain sub-directories for albums, galleries...*
  - */- xml may contain sub-directories for further categorisation..*
  - *and so on...*

# HTML5, CSS, & JS - example - part 2

---

## *index.html*

```
<!DOCTYPE html>
<html>
  <head>
    <meta charset="UTF-8">
    <title>travel notes - v0.1</title>
    <meta name="description" content="information on travel destinations">
    <meta name="author" content="ancientlives">
    <!-- css styles... -->
    <link rel="stylesheet" type="text/css" href="assets/styles/style.css">
  </head>
  <body>
    ...
    <!-- js scripts... -->
    <script type="text/javascript" src="https://code.jquery.com/jquery-2.1.4.min.js">
    <script type="text/javascript" src="assets/scripts/travel.js"></script>
  </body>
</html>
```

- JS files at foot of body
  - *hierarchical rendering of page by browser - top to bottom*
  - *JS will now be one of the last things to load*
  - *JS files often large, slow to load*
  - *helps page load faster...*

# HTML5, CSS, & JS - example - part 3

---

## index.html - body

```
<body>
  <!-- document header -->
  <header>
    <h3>travel notes</h3>
    <p>record notes from various cities and places visited...</p>
  </header>
  <!-- document main -->
  <main>
    <!-- note input -->
    <section class="note-input">
    </section>
    <!-- note output -->
    <section class="note-output">
    </section>
  </main>
  <!-- document footer -->
  <footer>
    <p>app's copyright information, additional links...</p>
  </footer>
  <!-- js scripts... -->
  <script type="text/javascript" src="https://code.jquery.com/jquery-2.1.4.min.js"></script>
  <script type="text/javascript" src="assets/scripts/travel.js"></script>
</body>
```



# HTML5, CSS, & JS - example - part 4

---

## style.css

```
body {
  width: 850px;
  margin: auto;
  background: #fff;
  font-size: 16px;
  font-family: "Times New Roman", Georgia, Serif;
}
h3 {
  font-size: 1.75em;
}
header {
  border-bottom: 1px solid #dedede;
}
header p {
  font-size: 1.25em;
  font-style: italic;
}
footer p {
  font-size: 0.8em;
}
```

# HTML5, CSS, & JS - example - part 5

---

## travel.js

```
//overall app logic and loader...
function travelNotes() {
    "use strict";

    $(".note-output").html("<p>first travel note for Marseille...</p>");
};

$(document).ready(travelNotes);
```

- a simple JS function to hold the basic logic for our app
- call this function any reasonable, logical name
- in initial function, we set the `strict` pragma
- add an example call to the jQuery function, `html ( )`
  - sets some initial note content
- function `travelNotes ( )` loaded using the jQuery function `ready ( )`
  - many different ways to achieve this basic loading of app logic
- DEMO I - travel notes - v0.1

# HTML5, CSS, & JS - example - part 6

---

## ***add a note***

- app's structure includes three clear semantic divisions of content
  - `<header>`, `<main>`, and `<footer>`
- `<main>` content category - create and add our notes for our application
- allow a user to create a new note
  - *enter some brief text, and then set it as a note*
- output will simply resemble a heading or brief description for our note
- add HTML element `<input>` to allow a user to enter note text
  - *new attributes in HTML5 such as `autocomplete`, `autofocus`, `required`, `width`...*
  - *set accompanying*

```
<h5>add note</h5>  
<input>
```

# HTML5, CSS, & JS - example - part 7

---

## *tidy up styling*

- additional styles to create correct, logical separation of visual elements and content
- add a border to the top of our footer
  - *perhaps matching the header in style*
- update the box model for the `<main>` element
- add some styling for `<h5>` heading

```
h5 {  
  font-size: 1.25em;  
  margin: 10px 0 10px 0;  
}  
main {  
  overflow: auto;  
  padding: 15px 0 15px 0;  
}  
footer {  
  margin-top: 5px;  
  border-top: 1px solid #dedede;  
}
```

## HTML5, CSS, & JS - example - part 8

---

### *input update*

```
<input><button>add</button>
```

```
.note-input input {  
  width: 40%;  
}  
.note-input button {  
  padding: 2px;  
  margin-left: 5px;  
  border-radius: 0;  
  border: 1px solid #dedede;  
  cursor: pointer;  
}
```

- also update css for input and button
- remove button's rounded borders to match style of input
- match border for button to basic design aesthetics
- set cursor appropriate for a link style...
- DEMO 2 - travel notes - v0.2

## HTML5, CSS, & JS - example - part 9

---

### *interaction - add a note*

- added and styled our input and button for adding a note
- use jQuery to handle click event on button
- update `travel.js` file for event handler

```
//handle user event for `add` button click
$(".note-input button").on("click", function(e) {
    console.log("add button clicked...");
});
```

# HTML5, CSS, & JS - example - part 10

---

## **interaction - add a note - output**

- update this jQuery code to better handle and output the text from the input field
- what is this handler actually doing?
  - *jQuery code has attached an event listener to an element in the DOM*
  - *referenced in the selector option at the start of the function*
  - *uses standard CSS selectors to find the required element*
- jQuery can select and target DOM elements using standard CSS selectors
  - *then manipulate them, as required, using JavaScript*

```
//handle user event for `add` button click
$(".note-input button").on("click", function(e) {
    $(".note-output").append("<p>sample note text...</p>");
});
```

- output some static text to note-output
- DEMO 3 - travel notes - v0.3

# HTML5, CSS, & JS - example - part II

---

## interaction - add a note - output

```
//overall app logic and loader...
function travelNotes() {
    "use strict";

    //handle user event for `add` button click
    $(".note-input button").on("click", function(e) {
        //object for wrapper html for note
        var $note = $("

");
        //get value from input field
        var note_text = $(".note-input input").val();
        //set content for note
        $note.html(note_text);
        //append note text to note-output
        $(".note-output").append($note);
    });
};

$(document).ready(travelNotes);


```

- DEMO 4 - travel notes - v0.4



# HTML5, CSS, & JS - example - part 12

---

## interaction - add a note - clear input

```
//overall app logic and loader...
function travelNotes() {
    "use strict";

    //handle user event for `add` button click
    $(".note-input button").on("click", function(e) {
        //object for wrapper html for note
        var $note = $("

");
        //define input field
        var $note_text = $(".note-input input");
        //conditional check for input field
        if ($note_text.val() !== "") {
            //set content for note
            $note.html($note_text.val());
            //append note text to note-output
            $(".note-output").append($note);
            $note_text.val("");
        }
    });
};

$(document).ready(travelNotes);


```

- DEMO 5 - travel notes - v0.5

## HTML5, CSS, & JS - example - part 13

---

### *interaction - add a note - keyboard listener*

- need to consider how to handle keyboard events
- listening and responding to a user hitting the return key in the input field
- similar pattern to user click on button

```
$(".note-input input").on("keypress", function (e) {  
  if (e.keyCode === 13) {  
    ...do something...  
  }  
});
```

- need to abstract handling both button click and keyboard press
- need to be selective with regard to keys pressed
- add a conditional check to our listener for a specific key
- use local variable from the event itself, eg: e, to get value of key pressed
- compare value of e against key value required
- example recording keypresses - Demo Editor

# HTML5, CSS, & JS - example - part 14

---

## ***interaction - add a note - abstract code***

- need to create a new function to abstract
  - *creation and output of a new note*
  - *manage the input field for our note app*
- moving logic from button click function to separate, abstracted function
- then call this function as needed
  - *for a button click or keyboard press*
  - *then create and render the new note*

```
//manage input field and new note output
function createNote() {
  //object for wrapper html for note
  var $note = $("

");
  //define input field
  var $note_text = $(".note-input input");
  //conditional check for input field
  if ($note_text.val() !== "") {
    //set content for note
    $note.html($note_text.val());
    //append note text to note-output
    $(".note-output").append($note);
    $note_text.val("");
  }
}


```

# HTML5, CSS, & JS - example - part 15

---

## interaction - add a note - travel.js

```
//overall app logic and loader...
function travelNotes() {
  "use strict";

  //manage input field and new note output
  function createNote() {
    //object for wrapper html for note
    var $note = $("

");
    //define input field
    var $note_text = $(".note-input input");
    //conditional check for input field
    if ($note_text.val() !== "") {
      //set content for note
      $note.html($note_text.val());
      //append note text to note-output
      $(".note-output").append($note);
      $note_text.val("");
    }
  }

  //handle user event for `add` button click
  $(".note-input button").on("click", function(e) {
    createNote();
  });

  //handle user event for keyboard press
  $(".note-input input").on("keypress", function(e){
    if (e.keyCode === 13) {
      createNote();
    }
  });
};
$(document).ready(travelNotes);


```

- DEMO 6 - travel notes - v0.6

# HTML5, CSS, & JS - example - part 16

---

## ***interaction - add a note - animate***

- jQuery well-known for its simple ability to animate elements
- many built-in effects available in jQuery
  - *build our own as well*
- to `fadeIn` an element, effectively it needs to be hidden first
- we hide our newly created note
- then we can set it to `fadeIn` when ready
- many additional parameters for jQuery's `fadeIn` function
  - *customise a callback*
  - *change the speed of the animation*
  - *and so on...*
- jQuery API - `fadeIn`

# HTML5, CSS, & JS - example - part 17

---

## *interaction - add a note - animate js*

```
//manage input field and new note output
function createNote() {
    //object for wrapper html for note
    var $note = $("

");
    //define input field
    var $note_text = $(".note-input input");
    //conditional check for input field
    if ($note_text.val() !== "") {
        //set content for note
        $note.html($note_text.val());
        //hide new note to setup fadeIn...
        $note.hide();
        //append note text to note-output
        $(".note-output").append($note);
        //fadeIn hidden new note
        $note.fadeIn("slow");
        $note_text.val("");
    }
}


```

- DEMO 7 - travel notes - v0.7

# HTML5, CSS, & JS - example - part 18

---

## *style and render notes*

- we have some new notes in our app
- add some styling to help improve the look and feel of a note
- can set background colours, borders font styles...
- set differentiating colours for each alternate note
- allows us to try some pseudoclasses in the CSS
  - *specified paragraphs in the `note-output` section*

```
.note-output p:nth-child(even) {  
  background-color: #ccc;  
}  
.note-output p:nth-child(odd) {  
  background-color: #eee;  
}
```

- DEMO 8 - travel notes - v0.8

# HTML5, CSS, & JS - final thoughts

---

- a basic app that records simple notes
- many additional options we can add
- some basic functionality is needed to make it useful
  - *autosave - otherwise we lose our data each time we refresh the browser*
  - *edit a note*
  - *delete a note*
  - *add author information*
- additional functionality might include
  - *save persistent data to DB, name/value pairs...*
  - *organise and view collections of notes*
  - *add images and other media*
  - *local and APIs*
  - *add contextual information*
  - *again, local and APIs*
  - *structure notes, media, into collection*
  - *define related information*
  - *search, sort...*
  - *export options and sharing...*
- security, testing, design patterns



# jQuery - basics - part I

---

## **intro**

- jQuery offers us a number of useful tools and options for building web apps
- packaged, prepared JavaScript library
  - *a lot easier to work with, and develop for, than standard JavaScript*
- features simpler syntax and a concise set of options for manipulating the DOM
  - *often simply quicker and easier to write our apps with jQuery than JavaScript*
- jQuery is an inherently expressive approach to working with JavaScript
  - *in particular, manipulating the DOM*
- consistent approach to handling events in the DOM
- includes useful, simplified approach to adding AJAX functionality

## jQuery - basics - part 2

---

### selectors

- jQuery works with selectors using a similar concept as CSS
- we can use CSS selectors as a jQuery selector

```
$("div")
$("p")
$(".note-input")
$(".note-input button")
$("p:nth-child(even)")
...
```

- jQuery may share many selectors with CSS
  - some cases where jQuery will slightly differ
- adds useful set of pseudoclasses and pseudoelements not in CSS

```
$("p:parent")
```

- use the above to find all paragraphs with children, including text
- a jQuery extension, and not part of the CSS specification

# jQuery - basics - part 3

---

## *manipulate the DOM*

```
<body>
  <!-- document header -->
  <header>
    <h3></h3>
    <p></p>
  </header>
  <!-- document main -->
  <main>
    <!-- note input -->
    <section class="note-input">
      <h5>add note</h5>
      <input><button></button>
    </section>
    <!-- note output -->
    <section class="note-output">
    </section>
  </main>
  <!-- document footer -->
  <footer>
    <p></p>
  </footer>
</body>
```

- benefits of using jQuery is the ease it offers for manipulating the DOM
- add elements, delete them, move them around...

# jQuery - basics - part 4

---

## add elements

- add a new element to our app
  - *simply append or prepend to a given position in the DOM*

```
//append note text to note-output  
$(".note-output").append($note);
```

- adds our new element, and content to the DOM
  - *end of the selected element in document*

```
//append note text to note-output  
$(".note-output").prepend($note);
```

- prepend to the document
  - *adds to the end of the selected element*
- additional options in JQuery, such as `prependTo ( )`
- differ slightly on the target for the content
- useful to select an element, then add to another elsewhere in DOM

## jQuery - basics - part 5

---

### **remove elements**

- also remove elements from the DOM
- easiest option is to use the `remove()` function on a given selector

```
$("p:nth-child(even)").remove();
```

- also empty an element, remove all child elements from selected element
  - *remove all of the notes, those we added in paragraph elements*

```
$(".note-output p").empty();
```

- also temporarily remove elements from the window

```
$note.fadeOut("slow");
```

- elements are not removed from the DOM, their style is updated

```
display: none;
```

# jQuery - basics - part 6

---

## events and async

- jQuery uses a standard pattern for events and handling

```
//handle user event for `add` button click
$(".note-input button").on("click", function(e) {
    ...
});
```

- allows us to set up listeners for many user triggered events
- commonly known as **event-driven** or **asynchronous** programming
- main difference with more traditional procedural patterns, is the way we use **callbacks**
  - *allow us to set functions for later execution*
- functions are set as parameters, then executed at the appropriate, required time
- callbacks are not only appropriate for interaction or user events
- use them throughout our programming to schedule functions and execution

```
setTimeout(function() {
    ...
}, 2000);
```

- an issue with **asynchronous** programming
  - *often simply being aware of the execution order or sequence of events*

# Demos

---

- JSFiddle - this - events
- JSFiddle - this - global
- JSFiddle - this - literal
- JSFiddle - this - literal 2
- JSFiddle - this - window
- JSFiddle - Parse JSON
- Travel Notes app
  - *DEMO 1 - travel notes - v0.1*
  - *DEMO 2 - travel notes - v0.2*
  - *DEMO 3 - travel notes - v0.3*
  - *DEMO 4 - travel notes - v0.4*
  - *DEMO 5 - travel notes - v0.5*
  - *DEMO 6 - travel notes - v0.6*
  - *DEMO 7 - travel notes - v0.7*
  - *DEMO 8 - travel notes - v0.8*

## References

---

- [jQuery API](#)
- [jQuery :parent selector](#)
- [JSLint - JavaScript Validator](#)
- [JSONLint - JSON Validator](#)
- [W3 - JS Object](#)
- [W3 - JS Performance](#)