

# Application to 2016 Election Data

```
## Erin's path
path_data = "~/Dropbox/Documents/2019__2020/work/kpop/2016_reweighting_example/data/"
#Ciara's
#path_data = "../data/"
path_data = "/Users/Ciara/Dropbox/kpop/2016_reweighting_example/data/"

vote_contrast <- quote((recode_vote_2016Democrat - recode_vote_2016Republican) /
                       (recode_vote_2016Democrat + recode_vote_2016Republican))

### Function for creating targets from auxiliary information and formula
create_targets <- function(target_design, target_formula) {
  target_mf <- model.frame(target_formula, model.frame(target_design))
  target_mm <- model.matrix(target_formula, target_mf)
  wts <- weights(target_design)
  colSums(target_mm * wts) / sum(wts)
}
```

## Load Data

```
## SURVEY DATA (PEW)
### Load
pew <- readRDS(paste0(path_data, "pew.rds"))

## AUXILIARY INFORMATION (CCES)
### Load
cces <- readRDS(paste0(path_data, "cces.rds"))
### Drop invalid cases
cces <- cces %>%
  filter((CC16_401 == "I definitely voted in the General Election.") &
         !is.na(commonweight_vv_post))

## make recode_educ_white column
cces <- cces %>%
  mutate(recode_educ_white =
    factor(case_when(recode_race == "White" ~ as.character(recode_educ),
                     TRUE ~ "No Split"),
           levels = c(levels(cces$recode_educ), "No Split")),
    commonweight_vv_post = commonweight_vv_post / mean(commonweight_vv_post))

pew <- pew %>%
  mutate(recode_educ_white =
    factor(case_when(recode_race == "White" ~ as.character(recode_educ),
                     TRUE ~ "No Split"),
           levels = c(levels(pew$recode_educ), "No Split"))))

### Actual results
pres <- readRDS(paste0(path_data, "election.rds"))
```

```

natl_margin <- pres %>%
  summarise(margin = (sum(demttotal) - sum(repttotal)) /
    (sum(demttotal) + sum(repttotal))) %>%
  as.numeric()
natl_margin

## [1] 0.02325013

formula_rake_demos_noeduc <- ~recode_age_bucket + recode_female +
  recode_race + recode_region + recode_pid_3way
formula_rake_demos_weduc <- ~recode_age_bucket + recode_female +
  recode_race + recode_region + recode_educ + recode_pid_3way
formula_ps <- ~recode_age_3way + recode_female + recode_race +
  recode_region + recode_educ_3way + recode_pid_3way
formula_retrospective <- ~recode_age_bucket:recode_pid_3way +
  recode_female:recode_pid_3way +
  recode_race_educ_reg:recode_pid_3way

## Find Missing Strata
## Make "strata" variable in CCES and Pew
cces <- bind_cols(cces, cces %>%
  unite("strata", all.vars(formula_ps), remove = FALSE) %>%
  unite("strata_wage", c(all.vars(formula_ps), "recode_age"),
    remove = FALSE) %>%
  select(strata, strata_wage))

pew <- bind_cols(pew, pew %>%
  unite("strata", all.vars(formula_ps), remove = FALSE) %>%
  unite("strata_wage", c(all.vars(formula_ps), "recode_age"),
    remove = FALSE) %>%
  select(strata, strata_wage))

missing_strata <- unique(cces$strata)[!(unique(cces$strata) %in% unique(pew$strata))]

## recode missing age

#####XXXXXXX issue here: how to recode age and whether to recode age buckets
#pew$recode_age[is.na(pew$recode_age)] <- mean(pew$recode_age, na.rm = TRUE)
pew$recode_age[is.na(pew$recode_age)] <- mean(cces$recode_age, na.rm = TRUE)
cces$recode_age[is.na(cces$recode_age)] <- mean(cces$recode_age, na.rm = TRUE)

## For Pew, since there are no design weights, assume SRS
pew_srs <- svydesign(ids = ~1, data = pew)
cces_awt <- svydesign(ids = ~1, weights = ~commonweight_vv_post, data = cces)

#### Population targets
targets_rake_demos_noeduc <- create_targets(cces_awt, formula_rake_demos_noeduc)
targets_rake_demos_weduc <- create_targets(cces_awt, formula_rake_demos_weduc)
targets_retrospective <- create_targets(cces_awt, formula_retrospective)

## Raking on demographics, excluding education
rake_demos_noeduc <- calibrate(design = pew_srs,
  formula = formula_rake_demos_noeduc,
  population = targets_rake_demos_noeduc,

```

```

    calfun = "raking")

rake_demos_noeduc <- svydesign(~1, data = pew, weights = weights(rake_demos_noeduc))

## Raking on demographics, including education
rake_demos_weduc <- calibrate(design = pew_srs,
                             formula = formula_rake_demos_weduc,
                             population = targets_rake_demos_weduc,
                             calfun = "raking")

rake_demos_weduc <- svydesign(~1, data = pew, weights = weights(rake_demos_weduc))

## Post-stratification
targets_ps <- svytable(formula = ~strata,
                      design = subset(cces_awt, !(strata %in% missing_strata)))

post_stratification <- postStratify(design = pew_srs,
                                   strata = ~strata,
                                   population = targets_ps)

post_stratification <- svydesign(~1, data = pew,
                               weights = weights(post_stratification))

## Retrospective weighting scheme
#failed to converge? XX
rake_retrospective <- calibrate(design = pew_srs,
                               formula = formula_retrospective,
                               population = targets_retrospective,
                               calfun = "raking",
                               force = TRUE)

## Warning in grake(mm, ww, calfun, bounds = bounds, population =
## population, : Failed to converge: eps=0.00688873036014645 in 51 iterations
rake_retrospective <- svydesign(~1, data = pew, weights = weights(rake_retrospective))

kpop_data <- rbind(pew %>% select(recode_age,
                                recode_female,
                                recode_race,
                                recode_region,
                                recode_pid_3way,
                                recode_educ,
                                recode_age_bucket),
                  cces %>% select(recode_age,
                                recode_female,
                                recode_race,
                                recode_region,
                                recode_pid_3way,
                                recode_educ,
                                recode_age_bucket)) %>%
  model.matrix(as.formula("~. - 1"), .)

kpop_sampled <- c(rep(1, nrow(pew)), rep(0, nrow(cces)))

```

```

kpop_b.5x <- kbal(allx=kpop_data,
  sampled = kpop_sampled,
  b = 0.5 * ncol(kpop_data),
  fullSVD = TRUE,
  meanfirst = FALSE,
  incrementby = 1,
  population.w = cces$commonweight_vv_post / mean(cces$commonweight_vv_post),
  sampledinpop = FALSE,
  printprogress = FALSE)

kpop_mf_b2x <- kbal(allx=kpop_data,
  sampled = kpop_sampled,
  b = 2 * ncol(kpop_data),
  incrementby = 1,
  fullSVD = TRUE,
  meanfirst = TRUE,
  ebal.convergence = TRUE,
  population.w = cces$commonweight_vv_post / mean(cces$commonweight_vv_post),
  sampledinpop = FALSE,
  printprogress = FALSE)

kpop <- svydesign(~1, data = pew, weights = kpop_b.5x$w[kpop_sampled] )
kpop_mf <- svydesign(~1, data = pew, weights = kpop_mf_b2x$w[kpop_sampled])

margin_summary <- round(cbind(cces = svymean(formula_rake_demos_weduc, cces_awt),
  unweighted = svymean(formula_rake_demos_weduc, pew_srs),
  rake_demos_noeduc = svymean(formula_rake_demos_weduc, rake_demos_noeduc),
  rake_demos_weduc = svymean(formula_rake_demos_weduc, rake_demos_weduc),
  post_stratification = svymean(formula_rake_demos_weduc, post_stratification),
  rake_retrospective = svymean(formula_rake_demos_weduc, rake_retrospective),
  kpop = svymean(formula_rake_demos_weduc, kpop),
  kpop_mf = svymean(formula_rake_demos_weduc, kpop_mf)) * 100, 1) %>%
data.frame() %>%
rownames_to_column() %>%
mutate(variable = case_when(str_detect(rowname, "age") ~ "4-way Age Bucket",
  str_detect(rowname, "female") ~ "Gender",
  str_detect(rowname, "race") ~ "Race/Ethnicity",
  str_detect(rowname, "region") ~ "Region",
  str_detect(rowname, "educ") ~ "Education Level",
  str_detect(rowname, "pid") ~ "Party Identification",
  TRUE ~ "Empty"),
  level =
  gsub("recode_|age_bucket|female|race|region|educ|pid_3way", "", rowname)) %>%
select(level, everything(), -rowname, -variable)

## Total missing strata
sum(cces$commonweight_vv_post[cces$strata %in% missing_strata]) / sum(cces$commonweight_vv_post)

## [1] 0.08405765

round(cbind(cces = svymean(formula_rake_demos_weduc, cces_awt),
  not_missing = svymean(formula_rake_demos_weduc,
    subset(cces_awt, !(strata %in% missing_strata))),
  missing = svymean(formula_rake_demos_weduc,

```

```

subset(cces_awt, (strata %in% missing_strata))) * 100, 1) %>%
data.frame() %>%
rownames_to_column() %>%
mutate(variable = case_when(str_detect(rowname, "age") ~ "4-way Age Bucket",
                             str_detect(rowname, "female") ~ "Gender",
                             str_detect(rowname, "race") ~ "Race/Ethnicity",
                             str_detect(rowname, "region") ~ "Region",
                             str_detect(rowname, "educ") ~ "Education Level",
                             str_detect(rowname, "pid") ~ "Party Identification",
                             TRUE ~ "Empty"),
        level =
        gsub("recode_|age_bucket|female|race|region|educ|pid_3way", "", rowname)) %>%
select(level, everything(), -rowname, -variable)

```

##		level	cces	not_missing	missing
## 1	18 to 35	34.8	37.6	4.0	
## 2	36 to 50	22.6	24.5	2.0	
## 3	51 to 64	28.9	29.7	20.6	
## 4	65+	13.7	8.3	73.4	
## 5	Female	50.8	50.8	51.5	
## 6	Male	49.2	49.2	48.5	
## 7	Black	11.8	11.5	14.9	
## 8	Hispanic	6.5	6.2	10.1	
## 9	Other	6.8	6.5	10.3	
## 10	White	74.9	75.8	64.8	
## 11	Midwest	23.4	23.2	25.5	
## 12	Northeast	19.7	19.3	24.4	
## 13	South	35.5	36.9	19.9	
## 14	West	21.4	20.6	30.2	
## 15	No HS	6.8	6.2	13.2	
## 16	High school graduate	30.6	30.3	32.9	
## 17	Some college	23.0	23.5	17.6	
## 18	2-year	10.6	10.8	8.6	
## 19	4-year	18.7	19.0	15.0	
## 20	Post-grad	10.4	10.1	12.8	
## 21	Dem	38.1	38.5	33.1	
## 22	Ind	32.5	32.5	32.0	
## 23	Rep	29.5	29.0	34.9	

```

margin_summary_educ <- round(cbind(cces = svymean(~recode_educ_white, cces_awt),
                                   unweighted = svymean(~recode_educ_white, pew_srs),
                                   rake_demos_noeduc = svymean(~recode_educ_white, rake_demos_noeduc),
                                   rake_demos_weduc = svymean(~recode_educ_white, rake_demos_weduc),
                                   post_stratification = svymean(~recode_educ_white, post_stratification),
                                   rake_retrospective = svymean(~recode_educ_white, rake_retrospective),
                                   kpop = svymean(~recode_educ_white, kpop),
                                   kpop_mf = svymean(~recode_educ_white, kpop_mf)) * 100, 1) %>%
data.frame() %>%
rownames_to_column() %>%
mutate(variable = case_when(str_detect(rowname, "age") ~ "4-way Age Bucket",
                             str_detect(rowname, "female") ~ "Gender",
                             str_detect(rowname, "race") ~ "Race/Ethnicity",
                             str_detect(rowname, "region") ~ "Region",
                             str_detect(rowname, "educ") ~ "Education Level",

```

```

        str_detect(rowname, "pid") ~ "Party Identification",
        TRUE ~ "Empty"),
    level =
      gsub("recode_age_bucket|female|race|region|educ|pid_3way|educ_3way|_white",
          "", rowname)) %>%
select(level, everything(), -rowname, -variable)

## Warning: funs() is soft deprecated as of dplyr 0.8.0
## Please use a list of either functions or lambdas:
##
##   # Simple named list:
##   list(mean = mean, median = median)
##
##   # Auto named with `tibble::lst()` :
##   tibble::lst(mean, median)
##
##   # Using lambdas
##   list(~ mean(., trim = .2), ~ median(., na.rm = TRUE))
## This warning is displayed once per session.
target_margin <- svycontrast(svymean(~recode_vote_2016, cces_awt, na.rm = TRUE),
                             vote_contrast)[1]

svymean(~recode_vote_2016, rake_demos_noeduc, deff = TRUE)

## Warning in svymean.survey.design2(~recode_vote_2016, rake_demos_noeduc, :
## Sample size greater than population size: are weights correctly scaled?
##
##              mean          SE DEff
## recode_vote_2016Democrat  0.5152342 0.0137716  NA
## recode_vote_2016Other    0.0610503 0.0068547  NA
## recode_vote_2016Republican 0.4237155 0.0135460  NA
comp_df <- data.frame(
  cces = svycontrast(svymean(~recode_vote_2016,
                             cces_awt, na.rm = TRUE),
                     vote_contrast),
  unweighted = svycontrast(svymean(~recode_vote_2016,
                                   pew_srs, na.rm = TRUE),
                           vote_contrast),
  rake_demos_noeduc = svycontrast(svymean(~recode_vote_2016,
                                           rake_demos_noeduc, na.rm = TRUE),
                                  vote_contrast),
  rake_demos_weduc = svycontrast(svymean(~recode_vote_2016,
                                           rake_demos_weduc, na.rm = TRUE),
                                  vote_contrast),
  post_stratification = svycontrast(svymean(~recode_vote_2016,
                                              post_stratification, na.rm = TRUE),
                                     vote_contrast),
  rake_retrospective = svycontrast(svymean(~recode_vote_2016,
                                             rake_retrospective, na.rm = TRUE),
                                    vote_contrast),
  kpop = svycontrast(svymean(~recode_vote_2016,
                              kpop, na.rm = TRUE),
                     vote_contrast),

```

```

kpop_mf = svycontrast(svymean(~recode_vote_2016,
                             kpop_mf, na.rm = TRUE),
                      vote_contrast)) %>%
pivot_longer(cols = everything(),
              names_to = c("source", ".value"),
              names_pattern = "(.*)\\.(.*)") %>%
rename(est = nlcon) %>%
mutate(est = est * 100,
       SE = SE * 100,
       err_target = est - target_margin * 100,
       source = str_replace(source, "_", " "),
       source_name = factor(source, labels = c("Target (CCES)",
                                                "KPop",
                                                "KPop + Mean First",
                                                "Post-Stratification",
                                                "Raking\\nDemographics\\nwithout Education",
                                                "Raking\\nDemographics\\nwith Education",
                                                "Raking\\nRetrospective",
                                                "Pew\\nUnweighted"),
                             ordered = TRUE))


```

comp\_df

```

## # A tibble: 8 x 5
##   source      est    SE err_target source_name
##   <chr>      <dbl> <dbl>      <dbl> <ord>
## 1 cces      2.64 0.740      0      Target (CCES)
## 2 unweighted 5.60 2.26      2.96  "Pew\\nUnweighted"
## 3 rake demos_noed~ 9.75 2.81      7.11  "Raking\\nDemographics\\nwithout E~
## 4 rake demos_weduc 5.29 3.11      2.65  "Raking\\nDemographics\\nwith Educ~
## 5 post stratifica~ 5.03 3.04      2.39  Post-Stratification
## 6 rake retrospect~ 5.17 3.39      2.53  "Raking\\nRetrospective"
## 7 kpop      4.09 3.10      1.45  KPop
## 8 kpop mf    2.47 3.41     -0.168 KPop + Mean First

```



```
ggsave("./plots/weighted_pew_results.pdf", width = 6, height = 4)
```

Note from `survey` package:

The design effect compares the variance of a mean or total to the variance from a study of the same size using simple random sampling without replacement. Note that the design effect will be incorrect if the weights have been rescaled so that they are not reciprocals of sampling probabilities. To obtain an estimate of the design effect comparing to simple random sampling with replacement, which does not have this requirement, use `deff="replace"`. This with-replacement design effect is the square of Kish's "deft".

```
lapply(list(rake_demos_noeduc, rake_demos_weduc, post_stratification, rake_retrospective, kpop, kpop_mf),
  function(x) {
    svymean(~recode_vote_2016, x, deff = "replace")
  })
```

```
## [[1]]
##               mean      SE  DEff
## recode_vote_2016Democrat  0.5152342 0.0137716 1.5741
## recode_vote_2016Other    0.0610503 0.0068547 1.6992
## recode_vote_2016Republican 0.4237155 0.0135460 1.5578
##
## [[2]]
##               mean      SE  DEff
## recode_vote_2016Democrat  0.492440 0.015599 2.0182
## recode_vote_2016Other    0.064585 0.010645 3.8881
## recode_vote_2016Republican 0.442974 0.015397 1.9917
##
## [[3]]
##               mean      SE  DEff
```



```
## recode_vote_2016Democrat 0.4951602 0.0146016 1.7681
## recode_vote_2016Other 0.0570701 0.0064833 1.6192
## recode_vote_2016Republican 0.4477697 0.0147349 1.8202
##
## [[4]]
##               mean           SE   DEff
## recode_vote_2016Democrat 0.4955713 0.0162761 2.1968
## recode_vote_2016Other 0.0575692 0.0077328 2.2847
## recode_vote_2016Republican 0.4468595 0.0165905 2.3084
##
## [[5]]
##               mean           SE   DEff
## recode_vote_2016Democrat 0.4911832 0.0149371 1.8507
## recode_vote_2016Other 0.0562514 0.0062328 1.5170
## recode_vote_2016Republican 0.4525654 0.0149954 1.8815
##
## [[6]]
##               mean           SE   DEff
## recode_vote_2016Democrat 0.482228 0.016914 2.3751
## recode_vote_2016Other 0.058803 0.010303 3.9758
## recode_vote_2016Republican 0.458969 0.016838 2.3668
```

## Weights

Looking at the average weight in margins.

```
load("cleaned data/Full SVD/weights_wPid_full.Rdata")
#optimal choice w pid: no mf = 0.5, mf = 2
weights <- pew %>% select(recode_age_bucket,
                          recode_age_3way,
                          recode_female,
                          recode_race,
                          recode_region,
                          recode_educ,
                          recode_educ_3way,
                          recode_pid_3way,
                          recode_race_educ_reg) %>%
  mutate(rake_demos_noeduc_wt = weights(rake_demos_noeduc)/
          mean(weights(rake_demos_noeduc)),
         rake_demos_weduc_wt = weights(rake_demos_weduc)/
          mean(weights(rake_demos_weduc)),
         post_stratification_wt = weights(post_stratification)/
          mean(weights(post_stratification)),
         rake_retrospective_wt = weights(rake_retrospective)/
          mean(weights(rake_retrospective)),
         k_wt = wts_wPid$wtkbal_b.5x,
         k_mf_wt = wts_wPid$wtkbal_mf_b2x)

#just checking everything is internally consistent
#sum(weights$rake_demos_noeduc_wt != wts_wPid$wt1_pid)

age <- weights %>%
  group_by(recode_age_bucket) %>%
```

```

    summarise(mu_1 = mean(rake_demos_noeduc_wt),
              mu_2 = mean(rake_demos_weduc_wt),
              mu_3 = mean(post_stratification_wt),
              mu_4 = mean(rake_retrospective_wt),
              mu_kpop = mean(k_wt),
              mu_kpop_mf = mean(k_mf_wt)) %>% ungroup()

female <- weights %>%
  group_by(recode_female) %>%
  summarise(mu_1 = mean(rake_demos_noeduc_wt),
            mu_2 = mean(rake_demos_weduc_wt),
            mu_3 = mean(post_stratification_wt),
            mu_4 = mean(rake_retrospective_wt),
            mu_kpop = mean(k_wt),
            mu_kpop_mf = mean(k_mf_wt)) %>% ungroup()

race <- weights %>%
  group_by(recode_race) %>%
  summarise(mu_1 = mean(rake_demos_noeduc_wt),
            mu_2 = mean(rake_demos_weduc_wt),
            mu_3 = mean(post_stratification_wt),
            mu_4 = mean(rake_retrospective_wt),
            mu_kpop = mean(k_wt),
            mu_kpop_mf = mean(k_mf_wt)) %>% ungroup()

region <- weights %>%
  group_by(recode_region) %>%
  summarise(mu_1 = mean(rake_demos_noeduc_wt),
            mu_2 = mean(rake_demos_weduc_wt),
            mu_3 = mean(post_stratification_wt),
            mu_4 = mean(rake_retrospective_wt),
            mu_kpop = mean(k_wt),
            mu_kpop_mf = mean(k_mf_wt)) %>% ungroup()

education <- weights %>%
  group_by(recode_educ) %>%
  summarise(mu_1 = mean(rake_demos_noeduc_wt),
            mu_2 = mean(rake_demos_weduc_wt),
            mu_3 = mean(post_stratification_wt),
            mu_4 = mean(rake_retrospective_wt),
            mu_kpop = mean(k_wt),
            mu_kpop_mf = mean(k_mf_wt)) %>% ungroup()

pid <- weights %>%
  group_by(recode_pid_3way) %>%
  summarise(mu_1 = mean(rake_demos_noeduc_wt),
            mu_2 = mean(rake_demos_weduc_wt),
            mu_3 = mean(post_stratification_wt),
            mu_4 = mean(rake_retrospective_wt),
            mu_kpop = mean(k_wt),
            mu_kpop_mf = mean(k_mf_wt)) %>% ungroup()

```

```
colnames(age) <- c("Variable", colnames(age)[-1])
colnames(female)<- c("Variable", colnames(female)[-1])
colnames(race)<- c("Variable", colnames(race)[-1])
colnames(region) <- c("Variable", colnames(region)[-1])
colnames(education) <- c("Variable", colnames(education)[-1])
colnames(pid) <- c("Variable", colnames(pid)[-1])

weights_summary <- rbind(age, female, race, region, education, pid)
```

Table 1: Marginal distribution, in precentage points, of important demographics under different weighting models.

	Target (CCES)	Unweighted Pew	Raking: Demographics	Raking: Demographics + Education	Post- Stratification	Raking: Retrospective	KPop	KPop Mean First
<b>4-way Age Bucket</b>								
18 to 35	34.8	43.7	34.8	34.8	35.4	34.8	34.4	34.8
36 to 50	22.6	32.6	22.6	22.6	26.7	22.6	23.6	22.6
51 to 64	28.9	21.0	28.9	28.9	29.7	28.9	29.5	28.9
65+	13.7	2.7	13.7	13.7	8.3	13.7	12.5	13.7
<b>Gender</b>								
Female	50.8	47.3	50.8	50.8	50.8	50.8	50.8	50.8
Male	49.2	52.7	49.2	49.2	49.2	49.2	49.2	49.2
<b>Race/Ethnicity</b>								
Black	11.8	8.9	11.8	11.8	11.5	13.4	11.7	11.8
Hispanic	6.5	7.6	6.5	6.5	6.2	6.5	5.9	6.5
Other	6.8	7.1	6.8	6.8	6.5	6.8	6.2	6.8
White	74.9	76.4	74.9	74.9	75.8	73.2	76.3	74.9
<b>Region</b>								
Midwest	23.4	22.3	23.4	23.4	23.2	24.7	23.6	23.4
Northeast	19.7	18.2	19.7	19.7	19.3	19.7	19.5	19.7
South	35.5	37.9	35.5	35.5	36.9	34.8	36.0	35.5
West	21.4	21.6	21.4	21.4	20.6	20.8	20.8	21.4
<b>Education Level</b>								
No HS	6.8	1.8	1.8	6.8	2.4	3.6	1.9	6.8
High school	30.6	19.7	21.5	30.6	28.8	29.4	31.2	30.6
Some college	23.0	16.7	17.7	23.0	24.5	23.0	24.4	23.0
2-year	10.6	11.3	10.6	10.6	9.5	11.7	10.9	10.6
4-year	18.7	28.6	26.2	18.7	22.2	20.2	20.3	18.7
Post-grad	10.4	21.9	22.3	10.4	12.6	12.2	11.3	10.4
<b>Party Identification</b>								
Dem	38.1	34.4	38.1	38.1	38.5	38.1	37.6	38.1
Ind	32.5	35.2	32.5	32.5	32.5	32.5	32.8	32.5
Rep	29.5	30.4	29.5	29.5	29.0	29.5	29.5	29.5

*Note:*

Cells present the percentage of the population represented by each variable level.

Table 2: Marginal distribution of education level for white voters under different weighting models.

	Target (CCES)	Unweighted Pew	Raking: Demographics	Raking: Demographics + Education	Post- Stratification	Raking: Retrospective	KPop	KPop Mean First
<b>Education Level for White Voters</b>								
No HS	4.6	1.1	1.1	4.5	1.8	3.0	1.2	4.8
High school	22.6	14.6	15.5	22.9	23.1	22.6	23.6	21.9
Some college	16.9	11.5	12.1	16.3	19.5	16.9	18.3	17.7
2-year	7.8	8.3	7.0	7.3	6.1	7.8	7.7	7.2
4-year	14.8	23.0	20.7	15.2	17.1	14.8	16.3	14.8
Post-grad	8.3	18.0	18.5	8.8	8.2	8.3	9.1	8.4
<b>Error</b>								
Mean Absolute Error	–	6.6	5.8	0.4	1.6	0.1	1.2	0.5

*Note:*

Cells present the percentage of the population represented by each variable level. Mean absolute error is the absolute error in each cell, relative to the target (CCES), weighted by the education level's proportion among white voters in the target population.

Table 3: Mean weights of important demographics under different weighting models .

	Raking Demographics without Education	Raking Demographics with Education	Post- Stratification	Raking Retrospective	KPop	KPop Mean First
<b>4-way Age Bucket</b>						
18 to 35	0.795	0.795	0.809	0.795	0.787	0.795
36 to 50	0.692	0.692	0.818	0.692	0.722	0.692
51 to 64	1.378	1.378	1.415	1.378	1.406	1.378
65+	5.183	5.183	3.117	5.183	4.732	5.183
<b>Gender</b>						
Female	1.076	1.076	1.075	1.076	1.075	1.076
Male	0.932	0.932	0.933	0.932	0.933	0.932
<b>Race/Ethnicity</b>						
Black	1.326	1.326	1.293	1.515	1.318	1.326
Hispanic	0.857	0.857	0.815	0.857	0.770	0.857
Other	0.955	0.955	0.911	0.955	0.865	0.955
White	0.981	0.981	0.993	0.959	0.999	0.981
<b>Region</b>						
Midwest	1.052	1.052	1.043	1.110	1.061	1.052
Northeast	1.081	1.081	1.057	1.081	1.071	1.081
South	0.935	0.935	0.972	0.916	0.949	0.935
West	0.994	0.994	0.956	0.965	0.966	0.994
<b>Education Level</b>						
No HS	1.000	3.823	1.320	2.030	1.062	3.823
High school	1.091	1.553	1.463	1.492	1.586	1.553
Some college	1.059	1.374	1.467	1.374	1.457	1.374
2-year	0.937	0.936	0.840	1.029	0.963	0.936
4-year	0.915	0.653	0.777	0.707	0.711	0.653
Post-grad	1.017	0.474	0.575	0.556	0.516	0.474
<b>Party Identification</b>						
Dem	1.105	1.105	1.119	1.105	1.093	1.105
Ind	0.922	0.922	0.924	0.922	0.933	0.922
Rep	0.971	0.971	0.954	0.971	0.973	0.971

*Note:*

Cells present the average weight used to reweight the Pew sample to the CCES target population in each variable level.