my_agent_mod — ADK CLI Basic Weather Agent

This project is a weather lookup agent implemented by extending the standard agent scaffold generated by `adk create my_agent_mod` with a custom tool (`get_weather`). When answering user inquiries, the conversational model calls the tool function (Function Calling) to deliver accurate information when asked about the weather of specific cities.

---

1. Directory Structure

```
my_agent_mod/
├── agent.py          # 📄 [Core Code] Implements get_weather tool and weather_agent (root_agent)
├── __init__.py       # 📄 [Package Init] Module export for ADK loader (`from . import agent`)
├── .env              # ⚙️ [Environment] Model name (ADK_MODEL) and API key configuration
├── .gitignore        # ⚙️ [Git Config] Ignore rules for session DB and local cache
├── README-KR.md      # 📄 [Documentation] Korean guide
├── README-EN.md      # 📄 [Documentation] English guide (this file)
├── README.md         # 📄 [Documentation] Default guide
└── .adk/             # ⚡ [Runtime Generated] Data folder automatically created by ADK during local execution
    └── session.db    # ⚡ [Dynamically Generated] Local SQLite database storing conversation sessions
```

Key Files and Roles

- `tools=[get_weather]` ... `weather_agent` 、`root_agent` 。
- `__init__.py` : Exposes the agent module via `from . import agent` so the ADK loader can discover it.
- `.adk/session.db` : Local SQLite database automatically created to record session history across CLI runs.

---

2. Operation Structure

- **Entry Point**: `root_agent` in `agent.py`
- **Role**: Queries weather for cities such as Seoul and Busan and returns a concise single-sentence response; other questions are answered using general knowledge.
- **Tool (`get_weather`)**:

```
def get_weather(city: str) -> dict:
    """Returns current weather for a specified city."""
    data = {"서울": "맑음, 18°C", "부산": "흐림, 20°C"}
    if city in data:
        return {"status": "success", "report": data[city]}
    return {"status": "error", "error_message": f"No data for {city}"}
```

---

3. How to Run

Run `my_agent_mod` from the parent directory (`part03_cli`) using ADK CLI commands:

```
# 1. Navigate to parent directory (if not already there)
cd part03_cli

# 2. Run terminal interactive REPL
adk run my_agent_mod

# 3. Run with in-memory session (no session.db created/used)
adk run --in_memory my_agent_mod

# 4. Run and save session to a file (creates my_agent_mod/s1.session.json upon exit)
adk run --save_session --session_id s1 my_agent_mod

# 5. Resume from a saved session file
adk run --resume my_agent_mod/s1.session.json my_agent_mod

# 6. Launch web UI (open http://localhost:8000 in your browser)
adk web --port 8000

# 7. Launch headless REST / SSE API server
adk api_server --port 8000
```