

A Multiresolution Scheme for More Efficient Simulation on Adaptive Mesh Refinement Blocks?

Brandon Gusto

Dept. of Scientific Computing
Florida State University

March 6, 2019

Introduction

The following project is concerned with the numerical solution of systems of conservation laws of the form

$$\mathbf{U}_t + \mathbf{F}(\mathbf{U})_x = 0$$

where $\mathbf{U} = (\rho, \rho u, E)$ is a vector of conserved quantities and $\mathbf{F}(\mathbf{U})$ is a flux vector. Consider a standard finite-volume discretization, with midpoint rule

$$\frac{\partial \mathbf{U}_i}{\partial t} = -\frac{1}{h} \left(\mathbf{F}_{i+\frac{1}{2}} - \mathbf{F}_{i-\frac{1}{2}} \right)$$

where the i denotes spatial index.

Adaptivity

The interest is in solution-adaptive methods:

- ▶ adaptive mesh refinement (AMR) based on local truncation error (or some other estimator)

Adaptivity

The interest is in solution-adaptive methods:

- ▶ adaptive mesh refinement (AMR) based on local truncation error (or some other estimator)
- ▶ computations typically done on blocks / patches for efficiency

Adaptivity

The interest is in solution-adaptive methods:


- ▶ adaptive mesh refinement (AMR) based on local truncation error (or some other estimator)
- ▶ computations typically done on blocks / patches for efficiency
- ▶ inherent “overresolution” in some regions of the mesh by using blocks

Adaptivity

The interest is in solution-adaptive methods:

- ▶ adaptive mesh refinement (AMR) based on local truncation error (or some other estimator)
- ▶ computations typically done on blocks / patches for efficiency
- ▶ inherent “overresolution” in some regions of the mesh by using blocks
- ▶ can this be addressed by reducing block size? computational tradeoff?


AMR




1

¹Introduction to Block-Structured Adaptive Mesh Refinement (AMR), Ann S. Almgren

AMR






AMR



Filling

The filling factor is the number of cells in a block which were flagged, divided by the total.



a la Harten

- ▶ Besides the AMR concepts, adaptivity was also introduced by Harten in a multiresolution framework. Although in his scheme, the grid was *not* refined in space. Instead, a wavelet transform was performed on the uniform grid, and the fluxes were interpolated in smooth regions.

a la Harten

- ▶ Besides the AMR concepts, adaptivity was also introduced by Harten in a multiresolution framework. Although in his scheme, the grid was *not* refined in space. Instead, a wavelet transform was performed on the uniform grid, and the fluxes were interpolated in smooth regions.
- ▶ “The goal of a multi-scale decomposition of a discrete set of data is a ”rearrangement” of its information content in such a way that the new discrete representation, exactly equivalent to the old one, is more ”manageable” in some respects.” - Arandiga, Donat

a la Harten

- ▶ Besides the AMR concepts, adaptivity was also introduced by Harten in a multiresolution framework. Although in his scheme, the grid was *not* refined in space. Instead, a wavelet transform was performed on the uniform grid, and the fluxes were interpolated in smooth regions.
- ▶ “The goal of a multi-scale decomposition of a discrete set of data is a ”rearrangement” of its information content in such a way that the new discrete representation, exactly equivalent to the old one, is more ”manageable” in some respects.” - Arandiga, Donat
- ▶ Multi-scale ideas behind Multigrid method, subdivision schemes for graphics / CAD

Multiresolution

Define multiple, nested grids

$$\mathbf{G}^l = \left\{ x'_{i+\frac{1}{2}} \right\}_{i=0}^{N_l} = \left\{ x'^{l+1}_{i+\frac{1}{2}} \right\}_{i=0, i \text{ even}}^{N^{l+1}}.$$

Coarsening of average data in cell done via

$$\mathbf{u}'_i = \frac{1}{2} \left(\mathbf{u}'^{l+1}_{2i} + \mathbf{u}'^{l+1}_{2i+1} \right)$$

Decomposition

The prediction from coarse to fine is done by


$$\hat{\mathbf{U}}_{2i+1}^{l+1} = \sum_{j=1-s}^{s-1} \gamma_j \mathbf{U}_{i+j}^l$$

The regularity information is assessed by computing detail coefficients as

$$\mathbf{d}_i^l = \mathbf{U}_{2i+1}^{l+1} - \hat{\mathbf{U}}_{2i+1}^{l+1}.$$

A mask $\{\mathbf{m}\}_i^{N'}$ is created for significant cells.

Decomposition



Fluxes

- ▶ utilize this regularity information to identify sufficiently smooth regions in which to interpolate the flux.

Fluxes

- ▶ utilize this regularity information to identify sufficiently smooth regions in which to interpolate the flux.
- ▶ introduce big buffer zone around cells that were flagged at each level

Fluxes

- ▶ utilize this regularity information to identify sufficiently smooth regions in which to interpolate the flux.
- ▶ introduce big buffer zone around cells that were flagged at each level
- ▶ perform inverse transform and compute or interpolate fluxes