A Multiresolution Scheme for More Efficient Simulation on Adaptive Mesh Refinement Blocks?

Brandon Gusto

Dept. of Scientific Computing Florida State University

March 6, 2019

Introduction

The following project is concerned with the numerical solution of systems of conservation laws of the form

$$\mathbf{U}_t + \mathbf{F}(\mathbf{U})_{\times} = 0$$

where $\mathbf{U} = (\rho, \rho u, E)$ is a vector of conserved quantities and $\mathbf{F}(\mathbf{U})$ is a flux vector. Consider a standard finite-volume discretization, with midpoint rule

$$\frac{\partial \mathbf{U}_{i}}{\partial t} = -\frac{1}{h} \left(\mathbf{F}_{i+\frac{1}{2}} - \mathbf{F}_{i-\frac{1}{2}} \right)$$

where the i denotes spatial index.

Introduction

Adaptivity

The interest is in solution-adaptive methods:


 adaptive mesh refinement (AMR) based on local truncation error (or some other estimator)

- adaptive mesh refinement (AMR) based on local truncation error (or some other estimator)
- computations typically done on blocks / patches for efficiency

- adaptive mesh refinement (AMR) based on local truncation error (or some other estimator)
- computations typically done on blocks / patches for efficiency
- inherent "overresolution" in some regions of the mesh by using blocks

- adaptive mesh refinement (AMR) based on local truncation error (or some other estimator)
- computations typically done on blocks / patches for efficiency
- inherent "overresolution" in some regions of the mesh by using blocks
- can this be addressed by reducing block size? computational tradeoff?


AMR




1

¹Introduction to Block-Structured Adaptive Mesh Refinement (AMR), Ann

AMR





AMR




Filling

The filling factor is the number of cells in a block which were flagged, divided by the total.







☐ Multiresolution

a la Harten

Besides the AMR concepts, a multiresolution approach was also introduced by Harten. Grid is not refined in space. Instead, a wavelet transform is performed on the uniform grid, and the fluxes are interpolated in smooth regions.

a la Harten

- Besides the AMR concepts, a multiresolution approach was also introduced by Harten. Grid is not refined in space. Instead, a wavelet transform is performed on the uniform grid, and the fluxes are interpolated in smooth regions.
- "The goal of a multi-scale decomposition of a discrete set of data is a "rearrangement" of its information content in such a way that the new discrete representation, exactly equivalent to the old one, is more "manageable" in some respects." -Arandiga, Donat

Multiresolution

Define multiple, nested grids

$$\mathbf{G}^{I} = \left\{ x_{i+\frac{1}{2}}^{I} \right\}_{i=0}^{N_{I}} = \left\{ x_{i+\frac{1}{2}}^{I+1} \right\}_{i=0,i \text{ even}}^{N^{I+1}}.$$

Coarsening of avarage data in cell done via

$$\mathbf{U}_{i}^{l} = \frac{1}{2} \left(\mathbf{U}_{2i}^{l+1} + \mathbf{U}_{2i+1}^{l+1} \right)$$

Decomposition

The prediction from coarse to fine is done by


$$\hat{\mathbf{U}}_{2i+1}^{l+1} = \sum_{j=1-s}^{s-1} \gamma_j \mathbf{U}_{i+j}^l$$

The regularity information is assessed by computing detail coefficients as

$$\mathbf{d}_{i}^{l} = \mathbf{U}_{2i+1}^{l+1} - \hat{\mathbf{U}}_{2i+1}^{l+1}.$$

A mask $\{\mathbf{m}\}_{i}^{N'}$ is created for significant cells.

Decomposition



Once the forward wavelet transform has been computed on cell-averaged solution data...

Once the forward wavelet transform has been computed on cell-averaged solution data...

utilize this regularity information to identify sufficiently smooth regions in which to interpolate the flux.

Once the forward wavelet transform has been computed on cell-averaged solution data...


- utilize this regularity information to identify sufficiently smooth regions in which to interpolate the flux.
- introduce sufficiently large buffer region (why?) around flagged cells

Once the forward wavelet transform has been computed on cell-averaged solution data...

- utilize this regularity information to identify sufficiently smooth regions in which to interpolate the flux.
- introduce sufficiently large buffer region (why?) around flagged cells
- perform inverse transform and compute or interpolate fluxes

Convergence

Sine wave advection after one period:




develop performance study for effect of filling factor on time to solution, overheads... with and without wavelet scheme

- develop performance study for effect of filling factor on time to solution, overheads... with and without wavelet scheme
- weakly compressible turbulence (uniform mesh)

- develop performance study for effect of filling factor on time to solution, overheads... with and without wavelet scheme
- weakly compressible turbulence (uniform mesh)
- compressible turbulence (potentially adaptive)

- develop performance study for effect of filling factor on time to solution, overheads... with and without wavelet scheme
- weakly compressible turbulence (uniform mesh)
- compressible turbulence (potentially adaptive)
- turbulent combustion (adaptive)

Turbulence



when two white dwarfs merge, their material violently mixes we model the evolution of small region containing such mixed material fluctuations of burning time scale in plasma may cause detonation