
notes

fangjun

Aug 06, 2022

CONTENTS:

1	Sphinx	3
1.1	Setup	3
1.2	How to include code from a file	4
1.3	Link	4
1.3.1	hello	5
2	git	7
2.1	Commands	7
2.1.1	rev-parse	7
3	docker	9
3.1	Installation	9
3.1.1	macos	9
4	LaTeX	11
4.1	TikZ	11
4.1.1	Basics	11
5	Kaldi	13
5.1	Decoding	13
6	bash	15
6.1	sort	15
6.2	echo	15
6.3	ffmpeg	15
6.3.1	Convert format	15
6.3.2	References	16
7	CUDA	17
7.1	Installation	17
7.1.1	CUDA 10.1.243	17
7.1.2	CUDA 11.0.3	17
7.1.3	CUDA 11.3.1	18
7.1.4	CUDA 11.5.2	18
7.1.5	CUDA 11.6.1	18
8	torch	19
8.1	torch.load and torch.save	19
8.2	torch.gather	19
8.3	DDP	20
8.3.1	Initialization	20

8.4	TorchScript	20
8.4.1	doxygen doc	20
8.4.2	Hello	20
8.4.3	Load in C++	25
8.4.4	ArrayRef	27
8.4.5	ScalarType	29
8.4.6	TypeMeta	30
8.4.7	torch::Device	31
8.4.8	TensorOptions	33
8.4.9	Tensor Creation	34
8.4.10	Tensor	36
8.4.11	intrusive_ptr	40
8.4.12	optional	40
8.4.13	PackedSequence	40
8.4.14	ivalue	42
8.4.15	method	44
8.4.16	type	45
8.5	Logical operations	47
8.6	Note	48
8.7	Quantization	48
8.7.1	Internals	48
8.7.2	torch.quantize_per_tensor	50
8.7.3	quantize_per_tensor_dynamic	51
8.7.4	torch.quantize_per_channel	52
8.7.5	Observer	54
8.7.6	Hello	55
8.7.7	References	56
8.8	android	56
8.8.1	References	56
8.9	onnx	56
8.9.1	Install	56
8.9.2	Hello	57
8.9.3	Multiple models	59
8.9.4	References	61
9	Python	63
9.1	asyncio	63
9.1.1	asyncio.Future	63
9.1.2	iterator	63
9.1.3	yield	63
9.1.4	Hello World	63
9.1.5	References	64
9.1.6	TODOs	64
9.2	argv	65
9.3	TODO	65
9.4	time	65
9.5	Numbers	65
9.5.1	binary representation	65
9.6	str	66
9.6.1	format	66
9.7	enum	67
9.7.1	Hello	67
9.8	socket	69
9.8.1	AddressFamily	69

9.8.2	SocketKind	70
9.8.3	struct sockaddr_in	71
9.8.4	AddressInfo	72
9.8.5	inet_pton	72
9.8.6	inet_ntop	77
9.8.7	Echo Server and Client	81
9.8.8	TODOs	84
10	java	85
10.1	Install	85
10.1.1	formatter	85
10.1.2	JDK	85
10.2	Hello world	86
10.3	Reference	87
11	javascript	89
11.1	Hello world	89
11.1.1	array	89
11.1.2	class	90
11.2	node	90
11.3	TODOs	91
12	HTML	93
12.1	Hello world	93
12.1.1	comments	93
12.1.2	images	93
12.1.3	ordered lists	93
12.1.4	unordered lists	94
12.1.5	links	94
12.2	References	94
13	css	95
13.1	Hello world	95
13.1.1	comment	95
13.1.2	Selector	95
13.2	References	96
14	pybind11	97
14.1	GIL	97
15	Protocol Buffers	99
15.1	Installation	99
15.1.1	C++	99
15.1.2	Install with cmake	107
15.2	Hello	107
15.2.1	hello.proto	107
15.2.2	makefile	108
15.2.3	hello.pb.h	109
15.2.4	hello.pb.cc	130
16	gRPC	151
16.1	Install	151
17	lwn.net	153
17.1	TODOs	153

18	Linker and Loader	155
18.1	References	155
18.2	Questions	156
19	espnet	157
19.1	aishell	157
19.1.1	AM training	157
20	cmake	159
20.1	Tutorials	159
20.2	Install	159
21	huggingface	161
21.1	spaces	161
21.1.1	Install client API	161
21.1.2	gradio	161
22	EECS E6870 Speech Recognition	163
22.1	Notes	163
23	ncnn	165
23.1	Hello	165
23.2	ncnn::Mat	166
24	LLVM	167
24.1	Installation	167
24.2	ninja	168
24.3	Documentation	168
24.4	Intermediate representation	169

Download this website in a single [pdf file](#).

This page describes how this website is setup.

1.1 Setup

1. Install the dependencies in `./docs/requirements.txt`.

```
sphinx==4.3.2
sphinx-autodoc-typehints==1.12.0
sphinx_rtd_theme==1.0.0
sphinxcontrib-bibtex==2.4.1
```

2. Use `sphinx-quickstart` to generate the skeleton. When it prompts:

```
Separate source and build directories(y/n)
```

Answer yes.

3. Edit `docs/source/conf.py` and add the following lines to it:

```
import sphinx_rtd_theme
extensions = [
    'sphinx.ext.autodoc',
    'sphinx.ext.autosummary',
    'sphinx.ext.githubpages',
    'sphinx.ext.mathjax',
    'sphinx.ext.napoleon',
    'sphinx.ext.todo',
    'sphinx.ext.viewcode',
    'sphinxcontrib.bibtex',
]

html_theme = 'sphinx_rtd_theme'

master_doc = 'index'
pygments_style = 'sphinx'
html_theme_path = [sphinx_rtd_theme.get_html_theme_path()]
smartquotes = False
html_show_sourcelink = True

html_context = {
```

(continues on next page)

(continued from previous page)

```
'display_github': True,
'github_user': 'csu-fangjun',
'github_repo': 'notes',
'github_version': 'master',
'conf_py_path': '/docs/source/',
}

html_theme_options = {
    'logo_only': False,
    'display_version': True,
    'prev_next_buttons_location': 'bottom',
    'style_external_links': True,
}
latex_engine = 'xelatex'
```

4. To generate the notes in pdf format, use `make latex`, which generates lots of `tex` files in `./build/latex`. Switch to `build/latex` and run `make`. Assume that you have installed the software to compile `tex` files. It will generate `notes.pdf`.

1.2 How to include code from a file

See <https://www.sphinx-doc.org/en/master/usage/restructuredtext/directives.html#directive-literalinclude>.

1. Show line number: `:linenos:`. By default, line number counts from 0. To add an offset, e.g., 10, to the line number, use `:lineno-start: 10`. Note: It still includes all the contents of the file.
2. To emphasize a line, specified lines, or specified line ranges, use: `:emphasize-lines: 10`, `:emphasize-lines: 10,12,14`, and `:emphasize-lines: 12,15-18`. Note: `emphasize` means to change the background color.
3. Set the language, e.g., `:language: python`.
4. Set the caption, e.g., `:caption: hello world`.
5. To include a function from the python file, use `:pyobject: my_func`.
6. To include specified lines, use `:lines:1,3,5-10,15-`. Note that if using this option, line number counts from 0. Use `:lineno-start: xx` to change the offset for display.

1.3 Link

See <https://sublime-and-sphinx-guide.readthedocs.io/en/latest/references.html> and <https://www.sphinx-doc.org/en/master/usage/restructuredtext/basics.html#hyperlinks>

1.3.1 hello

Here is a link to *hello*.

```
.. _Link to hello:
```

```
hello
```

```
-----
```

```
Here is a link to :ref:`Link to hello`.
```


This page describes commonly used git commands.

2.1 Commands

2.1.1 rev-parse

It is quite common to get the root directory of the repository with the command:

```
git rev-parse --show-toplevel
```

For instance, the above command executed in this repository prints something like as follows:

```
/xxx/notes
```

The following shows its usage in a Python script:

```
#!/usr/bin/env python3

import subprocess

d = (
    subprocess.check_output(["git", "rev-parse", "--show-toplevel"])
    .decode("ascii")
    .strip() # remove the trailing \n
)
print(d) # /path/to/notes
```

It can also be used in bash script:

```
root_dir=$(git rev-parse --show-toplevel)
echo "root_dir ${root_dir}"
```

help git-rev-parse outputs helpful information for git rev-parse. In particular, it explains the differences among HEAD~, HEAD~n, HEAD^, and HEAD^n. The following shows the help information about it:

```
<rev>^[<n>], e.g. HEAD^, v1.5.1^0
  A suffix ^ to a revision parameter means the first parent of that commit object. ^
  ↪<n> means the <n>th parent
```

(continues on next page)

(continued from previous page)

(i.e. `<rev>^` is equivalent to `<rev>^1`). As a special rule, `<rev>^0` means the commit itself and is used when `<rev>` is the object name of a tag object that refers to a commit object.

`<rev>~[<n>]`, e.g. `HEAD~`, `master~3`

A suffix `~` to a revision parameter means the first parent of that commit object. A suffix `~<n>` to a revision parameter means the commit object that is the `<n>`th generation ancestor of the named commit object, following only the first parents. I.e. `<rev>~3` is equivalent to `<rev>^^^` which is equivalent to `<rev>^1^1^1`. See below for an illustration of the usage of this form.



$A = A^0$
 $B = A^1 = A^1_1 = A_{~1}$
 $C = A^2$
 $D = A^{11} = A^{1^1_1} = A_{~2}$
 $E = B^2 = A^{12}$
 $F = B^3 = A^{13}$
 $G = A^{111} = A^{1^1_1^1} = A_{~3}$
 $H = D^2 = B^{12} = A^{112} = A_{~2}^2$
 $I = F^1 = B^{13} = A^{113}$
 $J = F^2 = B^{132} = A^{1132}$

3.1 Installation

3.1.1 macos

Refer to <https://docs.docker.com/desktop/mac/install/>.

4.1 TikZ

4.1.1 Basics

This page describes commonly used git commands.

5.1 Decoding

```
CompactLattice compact_lat;  
decoder.GetLattice(true, &compact_lat);  
  
CompactLattice compact_best_path;  
CompactLatticeShortestPath(compact_lat, &compact_best_path);  
  
Lattice best_path;  
ConvertLattice(compact_best_path, best_path);  
  
std::vector<int32_t> tokens;  
std::vector<int32_t> words;  
LatticeWeight weight;  
GetLinearSymbolSequence(best_path, &tokens, &words, &weight);
```

- decoder/simple-decoder.{h,cc}

6.1 sort

Sort files in the folder `t`. The filename has the pattern `xxx.n.txt`, where `n` is some numerical value. Also, exclude `xxx.100.txt`.

```
find ./t -name "xxx*.txt" ! -name "xxx.100.txt" -print0 | sort -z -t. -k2 -n | xargs -r0
```

6.2 echo

Generate a binary file:

```
echo -n -e '\x30\x31\x32' > a.bin  
hexdump a.bin
```

6.3 ffmeg

```
ffprobe xxx.opus
```

6.3.1 Convert format

- opus to wav

```
ffmpeg -i input.opus output.wav  
ffmpeg -i input.opus -acodec pcm_s16le -ac 1 -ar 16000 output.wav
```

- Extract part of a file

```
# extract 30 seconds starting at offset 1 minute  
ffmpeg -i input.opus -ss 60 -t 30 output.wav  
# or use HH:MM:SS format  
ffmpeg -i input.opus -ss 0:01:00 -t 0:00:30 output.wav
```

6.3.2 References

See <https://gist.github.com/whizkydee/804d7e290f46c73f55a84db8a8936d74>

CUDA

7.1 Installation

7.1.1 CUDA 10.1.243

```
./cuda_10.1.243_418.87.00_linux.run --silent --toolkit --installpath=/ceph-data4/fangjun/  
↳ software/cuda-10.1.243 --no-opengl-libs --no-drm --no-man-page  
  
# Install cuDNN  
cd /ceph-data4/fangjun/software/cuda-10.1.243  
tar xvf /ceph-sh0/fangjun/cudnn/cudnn-10.1-linux-x64-v8.0.4.30.tgz --strip-components=1
```

```
#!/usr/bin/env bash  
  
export CUDA_HOME=/ceph-data4/fangjun/software/cuda-10.1.243  
export PATH=$CUDA_HOME/bin:$PATH  
export LD_LIBRARY_PATH=$CUDA_HOME/lib64:$LD_LIBRARY_PATH  
  
# See /ceph-fj/fangjun/py38/lib/python3.8/site-packages/torch/share/cmake/Caffe2/Modules_  
↳ CUDA_fix/upstream/FindCUDA.cmake  
export CUDA_TOOLKIT_ROOT_DIR=$CUDA_HOME  
export CUDA_TOOLKIT_ROOT=$CUDA_HOME  
export CUDA_BIN_PATH=$CUDA_HOME  
export CUDA_PATH=$CUDA_HOME  
export CUDA_INC_PATH=$CUDA_HOME/targets/x86_64-linux
```

7.1.2 CUDA 11.0.3

```
./cuda_11.0.3_450.51.06_linux.run --silent --toolkit --installpath=/ceph-data4/fangjun/  
↳ software/cuda-11.0.3 --no-opengl-libs --no-drm --no-man-page  
  
# Install cuDNN  
cd /ceph-data4/fangjun/software/cuda-11.0.3  
tar xvf /ceph-sh0/fangjun/cudnn/cudnn-11.0-linux-x64-v8.0.4.30.tgz --strip-components=1
```

7.1.3 CUDA 11.3.1

```
./cuda_11.3.1_465.19.01_linux.run --silent --toolkit --installpath=/ceph-data4/fangjun/  
↪software/cuda-11.3.1 --no-opengl-libs --no-drm --no-man-page  
cd /ceph-data4/fangjun/software/cuda-11.3.1  
tar xvf /ceph-sh0/fangjun/cudnn/cudnn-11.3-linux-x64-v8.2.1.32.tgz --strip-components=1
```

7.1.4 CUDA 11.5.2

```
./cuda_11.5.2_495.29.05_linux.run --silent --toolkit --installpath=/ceph-data4/fangjun/  
↪software/cuda-11.5.2 --no-opengl-libs --no-drm --no-man-page  
cd /ceph-data4/fangjun/software/cuda-11.5.2  
tar xvf /ceph-sh0/fangjun/cudnn/cudnn-linux-x86_64-8.3.2.44_cuda11.5-archive.tar.xz --  
↪strip-components=1
```

7.1.5 CUDA 11.6.1

```
./cuda_11.6.1_510.47.03_linux.run --silent --toolkit --installpath=/ceph-data4/fangjun/  
↪software/cuda-11.6.1 --no-opengl-libs --no-drm --no-man-page  
cd /ceph-data4/fangjun/software/cuda-11.6.1  
tar xvf /ceph-sh0/fangjun/cudnn/cudnn-11.3-linux-x64-v8.2.1.32.tgz --strip-components=1
```


8.1 torch.load and torch.save

Listing 1: ./code/load-and-save.py

```
1  #!/usr/bin/env python3
2
3  import torch
4  import tempfile
5
6
7  def main():
8      a = torch.arange(3)
9      with tempfile.NamedTemporaryFile() as f:
10         torch.save(a, f)
11         f.seek(0)
12         b = torch.load(f)
13         assert torch.all(torch.eq(a, b)), (a, b)
14
15
16 if __name__ == "__main__":
17     main()
```

8.2 torch.gather

Listing 2: ./code/gather.py

```
1  #!/usr/bin/env python3
2
3  import torch
4
5
6  def main():
7      N = 5
8      T = 10
9      H = 20
10     W = 2 * H - 1
11     a = torch.randn(N, T, H, W)
```

(continues on next page)

(continued from previous page)

```
12
13 if False:
14     rows = torch.arange(start=H - 1, end=-1, step=-1).unsqueeze(-1)
15     cols = torch.arange(H)
16     indexes = rows + cols
17
18     indexes = torch.tile(indexes, (N * T, 1))
19 else:
20     rows = torch.arange(start=H - 1, end=-1, step=-1)
21     cols = torch.arange(H)
22     rows = torch.cat([rows] * (N * T)).unsqueeze(-1)
23     indexes = rows + cols
24
25 print(indexes.shape)
26
27 ta = a.reshape(-1, W)
28
29 b = torch.gather(ta, dim=1, index=indexes)
30 b = b.reshape(N, T, H, -1)
31
32 c = a.as_strided((N, T, H, H), (T * H * W, H * W, W - 1, 1), storage_offset=H - 1)
33 assert torch.equal(b, c)
34
35
36 if __name__ == "__main__":
37     torch.manual_seed(20220727)
38     main()
```

8.3 DDP

8.3.1 Initialization

8.4 TorchScript

8.4.1 doxygen doc

See

8.4.2 Hello

See https://pytorch.org/tutorials/beginner/Intro_to_TorchScript_tutorial.html.

torch.jit.script as a decorator

Listing 3: ./code/1-ex.py

```

1 @torch.jit.script
2 def adder(x: int):
3     return x + 1
4
5
6 def test_adder():
7     assert isinstance(adder, torch.jit.ScriptFunction)
8     print(adder.graph)
9     print("-" * 10)
10    print(adder.code)
11    adder.save("adder.pt")
12
13    my_adder = torch.jit.load("adder.pt")
14
15    assert isinstance(my_adder, torch.jit._script.RecursiveScriptModule)
16    assert isinstance(my_adder, torch.jit.ScriptModule)
17    assert not isinstance(my_adder, torch.jit.ScriptFunction)
18    print(my_adder(torch.tensor([3])))
19
20
21 """
22 graph(%x.1 : int):
23     %2 : int = prim::Constant[value=1]() # ./1-ex.py:8:15
24     %3 : int = aten::add(%x.1, %2) # ./1-ex.py:8:11
25     return (%3)
26
27 -----
28 def adder(x: int) -> int:
29     return torch.add(x, 1)
30
31 4
32 """

```

torch.jit.script as a function

Listing 4: ./code/2-ex.py

```

1 def adder(x: int):
2     return x + 2
3
4
5 def test_adder():
6     adder_func = torch.jit.script(adder)
7     assert isinstance(adder_func, torch.jit.ScriptFunction)
8     print(adder_func.graph)
9     print(adder_func(3))
10
11

```

(continues on next page)

(continued from previous page)

```

12 """
13 graph(%x.1 : int):
14   %2 : int = prim::Constant[value=2]() # ./2-ex.py:6:15
15   %3 : int = aten::add(%x.1, %2) # ./2-ex.py:6:11
16   return (%3)
17
18 5
19 """

```

torchscript a module

Listing 5: ./code/3-ex.py

```

1 class MyModel(torch.nn.Module):
2     def __init__(self):
3         super().__init__()
4         self.p = torch.nn.Parameter(torch.tensor([2.0]))
5
6     def forward(self, x: torch.Tensor):
7         return self.p * x
8
9
10 def test_my_model():
11     model = MyModel()
12     scripted_model = torch.jit.script(model)
13     print(scripted_model.graph)
14     print("-" * 10)
15     print(scripted_model.code)
16     print(scripted_model(torch.tensor([10])))
17
18
19 """
20 graph(%self : __torch__.MyModel,
21       %x.1 : Tensor):
22   %p : Tensor = prim::GetAttr[name="p"](%self)
23   %4 : Tensor = aten::mul(%p, %x.1) # ./3-ex.py:12:15
24   return (%4)
25
26 -----
27 def forward(self,
28             x: Tensor) -> Tensor:
29     p = self.p
30     return torch.mul(p, x)
31 """

```

trace a module

Listing 6: ./code/trace/ex0.py

```

1  #!/usr/bin/env python3
2
3  import torch
4
5  import torch.nn as nn
6
7
8  class Foo(nn.Module):
9      def __init__(self):
10         super().__init__()
11         self.relu = nn.ReLU()
12
13     def forward(self, x):
14         return self.relu(x)
15
16
17 def main():
18     f = Foo()
19     m = torch.jit.trace(f, torch.rand(2, 3))
20
21     print(m(torch.rand(2)))
22     print(m(torch.rand(2, 3, 4)))
23
24
25 if __name__ == "__main__":
26     main()

```

Export and ignore methods

1. Use `@torch.jit.export` decorator to export a method.
2. Use `torch.jit.export` function call to export a method.
3. Use `@torch.jit.ignore` decorator to ignore a method.
4. Use `torch.jit.ignore` function call to ignore a method.
5. Use `@torch.jit.unused` or `torch.jit.unused` to ignore a method.

See [Load in C++](#) to load the saved file.

Listing 7: ./code/4-ex.py

```

1  class MyModel(torch.nn.Module):
2      def __init__(self):
3          super().__init__()
4          self.p = torch.nn.Parameter(torch.tensor([2.0]))
5
6      def foobar(self, x: torch.Tensor):
7          return x + 3

```

(continues on next page)

```

8
9     def foo(self, x: torch.Tensor):
10         return self.foobar(x)
11
12     def bar(self, x: torch.Tensor):
13         return self.p - x
14
15     @torch.jit.export
16     def baz(self, x: torch.Tensor):
17         return self.p + x + 2
18
19     def forward(self, x: torch.Tensor):
20         return self.p * x
21
22
23 def test_my_model():
24     MyModel.foo = torch.jit.export(MyModel.foo) # manually export
25
26     # Note: forward is exported by default. We ignore it here manually
27     MyModel.forward = torch.jit.ignore(MyModel.forward)
28
29     model = MyModel()
30     scripted_model = torch.jit.script(model)
31     assert hasattr(scripted_model, "foo")
32     assert hasattr(scripted_model, "baz")
33     assert hasattr(scripted_model, "foobar") # because it is called by `foo`
34     assert not hasattr(scripted_model, "bar")
35
36     scripted_model.save("foo.pt")
37
38     m = torch.jit.load("foo.pt")
39     print(m.foo(torch.tensor([1])))
40     print(m.baz(torch.tensor([1])))
41
42
43 """
44 graph(%self : __torch__.MyModel,
45       %x.1 : Tensor):
46     %p : Tensor = prim::GetAttr[name="p"](%self)
47     %4 : Tensor = aten::mul(%p, %x.1) # ./3-ex.py:12:15
48     return (%4)
49
50 -----
51 def forward(self,
52             x: Tensor) -> Tensor:
53     p = self.p
54     return torch.mul(p, x)
55 """

```

8.4.3 Load in C++

See https://pytorch.org/tutorials/advanced/cpp_export.html.

Load the saved `foo.pt` in C++ from *Export and ignore methods*.

Listing 8: `./code/load-in-cpp/Makefile`

```

1  USE_CXX11_ABI := $(shell python3 -c 'import torch; print(int(torch.compiled_with_cxx11_
   ↪abi()))')
2  TORCH_INSTALL_DIR := $(shell python3 -c 'import os; import torch; print(os.path.
   ↪dirname(torch.__file__))')
3
4  $(info USE_CXX11_ABI $(USE_CXX11_ABI))
5  $(info TORCH_INSTALL_DIR $(TORCH_INSTALL_DIR))
6
7  CXXFLAGS := -I$(TORCH_INSTALL_DIR)/include
8  CXXFLAGS += -I$(TORCH_INSTALL_DIR)/include/torch/csrc/api/include
9  CXXFLAGS += -I$(TORCH_INSTALL_DIR)/include/TH
10 CXXFLAGS += -I$(TORCH_INSTALL_DIR)/include/THC
11 CXXFLAGS += -std=c++14
12 CXXFLAGS += -D_GLIBCXX_USE_CXX11_ABI=$(USE_CXX11_ABI)
13
14 CXXFLAGS += -Wno-unknown-pragmas # disable omp warnings
15
16 LDFLAGS := -L$(TORCH_INSTALL_DIR)/lib
17 LDFLAGS += -lc10 -ltorch -ltorch_cpu
18 # LDFLAGS += -lc10 -ltorch
19 LDFLAGS += -Wl,-rpath,$(TORCH_INSTALL_DIR)/lib
20
21 HAS_CUDA := $(shell python3 -c 'import torch; print("yes" if torch.cuda.is_available()
   ↪else "no")')
22 HAS_CUDA := yes
23 $(info has cuda $(HAS_CUDA))
24
25 ifeq ($(HAS_CUDA),yes)
26 CUDA_HOME := $(shell which nvcc | xargs dirname | xargs dirname)
27 CXXFLAGS += -I$(CUDA_HOME)/include
28 LDFLAGS += -L$(CUDA_HOME)/lib64
29 LDFLAGS += -lcudart -lc10_cuda -ltorch_cuda
30 LDFLAGS += -Wl,-rpath,$(CUDA_HOME)/lib64
31 endif
32
33 .PHONY: clean
34
35 main: main.o
36     $(CXX) -o $@ $< $(LDFLAGS)
37
38 main.o: main.cc
39     $(CXX) $(CXXFLAGS) -c -o $@ $<
40
41 clean:
42     $(RM) main.o main

```

Note: `torch::jit::script::Module` is deprecated, use `torch::jit::Module` instead.

Listing 9: `./code/load-in-cpp/main.cc`

```

1  #include "torch/script.h"
2
3  int main() {
4      // see torch/csrc/jit/module.h
5      torch::jit::Module m = torch::jit::load("../foo.pt");
6      std::cout << "is training: " << m.is_training() << "\n";
7      m.eval();
8      std::cout << "after m.eval(): is training: " << m.is_training() << "\n";
9      torch::Tensor x = torch::tensor({1, 2, 3}, torch::kFloat);
10     torch::Tensor y = m.run_method("baz", x).toTensor();
11     std::cout << y << "\n";
12
13     return 0;
14 }

```

The output of `make` is:

```

USE_CXX11_ABI 0
TORCH_INSTALL_DIR /ceph-fj/fangjun/software/py38/lib/python3.8/site-packages/torch
has cuda yes
g++ -I/ceph-fj/fangjun/software/py38/lib/python3.8/site-packages/torch/include \
    -I/ceph-fj/fangjun/software/py38/lib/python3.8/site-packages/torch/include/torch/
    ↪csrc/api/include \
    -I/ceph-fj/fangjun/software/py38/lib/python3.8/site-packages/torch/include/TH \
    -I/ceph-fj/fangjun/software/py38/lib/python3.8/site-packages/torch/include/THC \
    -std=c++14 \
    -D_GLIBCXX_USE_CXX11_ABI=0 \
    -Wno-unknown-pragmas \
    -I/ceph-sh1/fangjun/software/cuda-10.2.89/include \
    -c -o main.o main.cc
g++ -o main main.o \
    -L/ceph-fj/fangjun/software/py38/lib/python3.8/site-packages/torch/lib \
    -lc10 -ltorch -ltorch_cpu \
    -Wl,-rpath,/ceph-fj/fangjun/software/py38/lib/python3.8/site-packages/torch/lib \
    -L/ceph-sh1/fangjun/software/cuda-10.2.89/lib64 \
    -lcudart -lc10_cuda -ltorch_cuda \
    -Wl,-rpath,/ceph-sh1/fangjun/software/cuda-10.2.89/lib64

```

The output of `./main` is:

```

is training: 1
after m.eval(): is training: 0
5
6
7
[ CPUFloatType{3} ]

```


8.4.4 ArrayRef

See `c10/utils/ArrayRef.h`.

Caution: `IntArrayRef` is an alias to `ArrayRef<int64_t>`.

`ArrayRef<T>` contains only two members: A const data pointer and a size. It is trivially copyable and assignable.

It has similar methods like `std::vector`. It also has two methods to get the front and back: `front()` and `back()`; both return a const reference.

Its method `vec()` converts itself to a `std::vector` by **copying** the underlying data.

Constructors

Data members

Listing 10: `./code/array_ref/main.cc` (Check size)

```
1 struct Foo {  
2     const int32_t *p;  
3     size_t len;  
4 };  
5  
6 static void TestSize() {  
7     // Note: The data pointer in ArrayRef is const!  
8     static_assert(sizeof(torch::ArrayRef<int32_t>) == sizeof(Foo), "");  
9 }
```

Default constructed

Listing 11: ./code/array_ref/main.cc (Default constructor)

```
1 static void TestDefaultConstructor() {
2     torch::ArrayRef<int32_t> a;
3     TORCH_CHECK(a.data() == nullptr);
4     TORCH_CHECK(a.size() == 0);
5     TORCH_CHECK(a.empty() == true);
6
7     TORCH_CHECK(a.begin() == nullptr);
8     TORCH_CHECK(a.end() == nullptr);
9 }
```

From a single element

Listing 12: ./code/array_ref/main.cc (From a single element)

```
1 static void TestFromSingleElement() {
2     int32_t a = 10;
3     torch::ArrayRef<int32_t> b(a);
4     TORCH_CHECK(b[0] == a);
5     TORCH_CHECK(b.data() == &a);
6     TORCH_CHECK(b.size() == 1);
7 }
```

From an initializer list

Listing 13: ./code/array_ref/main.cc (From an initializer list)

```
1 static void TestFromInitializerList() {
2     torch::ArrayRef<int32_t> a = {1, 2, 3};
3     TORCH_CHECK(a.size() == 3);
4     TORCH_CHECK(a[0] == 1);
5     TORCH_CHECK(a[1] == 2);
6     TORCH_CHECK(a[2] == 3);
7 }
```

Other types of constructors

- From two pointers: begin and end
- From a pointer and a length
- From a *std::vector*
- From a container that has `data()` and `size()` methods
- From a C array
- From a *std::array*

8.4.5 ScalarType

See `c10/core/ScalarType.h` and <https://github.com/pytorch/pytorch/blob/master/torch/csrc/api/include/torch/types.h>.

ScalarType is an enum class, i.e., `enum class ScalarType : int8_t { ... }`.

Members

It has the following members:

Listing 14: `./code/scalar-type/members.cc`

```

1  #define AT_FORALL_SCALAR_TYPES_WITH_COMPLEX_EXCEPT_COMPLEX_HALF(_) \
2      _(uint8_t, Byte) \
3      _(int8_t, Char) \
4      _(int16_t, Short) \
5      _(int, Int) \
6      _(int64_t, Long) \
7      _(at::Half, Half) \
8      _(float, Float) \
9      _(double, Double) \
10     _(c10::complex<float>, ComplexFloat) \
11     _(c10::complex<double>, ComplexDouble) \
12     _(bool, Bool) \
13     _(at::BFloat16, BFloat16)

```

Some aliases

Listing 15: `./code/scalar-type/main.cc` (alias)

```

1  static void TestAlias() {
2      static_assert(c10::ScalarType::Int == c10::kInt, "");
3      static_assert(c10::ScalarType::Byte == c10::kByte, "");
4  }

```

Listing 16: `./code/scalar-type/alias.cc`

```

1  // See torch/csrc/api/include/torch/types.h
2  using Dtype = at::ScalarType;
3
4  /// Fixed width dtypes.
5  constexpr auto kUInt8 = at::kByte;
6  constexpr auto kInt8 = at::kChar;
7  constexpr auto kInt16 = at::kShort;
8  constexpr auto kInt32 = at::kInt;
9  constexpr auto kInt64 = at::kLong;
10 constexpr auto kFloat16 = at::kHalf;
11 constexpr auto kFloat32 = at::kFloat;
12 constexpr auto kFloat64 = at::kDouble;
13
14 /// Rust-style short dtypes.
15 constexpr auto kU8 = kUInt8;

```

(continues on next page)

(continued from previous page)

```

16 constexpr auto kI8 = kInt8;
17 constexpr auto kI16 = kInt16;
18 constexpr auto kI32 = kInt32;
19 constexpr auto kI64 = kInt64;
20 constexpr auto kF16 = kFloat16;
21 constexpr auto kF32 = kFloat32;
22 constexpr auto kF64 = kFloat64;

```

ScalarType to CPP type

Listing 17: ./code/scalar-type/main.cc

```

1 static void TestScalarTypeToCppType() {
2     static_assert(
3         std::is_same<
4             int32_t, //
5             c10::impl::ScalarTypeToCppType<c10::ScalarType::Int>::type>::value,
6         "");
7 }

```

CPP type to ScalarType

Listing 18: ./code/scalar-type/main.cc

```

1 static void TestCppTypeToScalarType() {
2     static_assert(
3         c10::CppTypeToScalarType<float>::value == c10::ScalarType::Float, "");
4 }

```

Note: It is `c10::impl::ScalarTypeToCppType`, but it is `c10::CppTypeToScalarType`.

8.4.6 TypeMeta

See

- <https://github.com/pytorch/pytorch/blob/master/c10/util/typeid.h>
- <https://github.com/pytorch/pytorch/blob/master/c10/core/ScalarTypeToTypeMeta.h>

`struct TypeMeta` contains only a single `int16_t` data member:

Listing 19: ./code/type-meta/main.cc (Check size)

```

1 static void TestSize() {
2     static_assert(sizeof(caffe2::TypeMeta) == sizeof(int16_t), "");
3 }

```

Constructors

Listing 20: ./code/type-meta/main.cc (Make)

```

1 static void TestConstructor() {
2     caffe2::TypeMeta t = caffe2::TypeMeta::Make<int32_t>();
3     TORCH_CHECK(t.Match<int32_t>());
4
5     TORCH_CHECK(t.isScalarType());
6
7     TORCH_CHECK(t.isScalarType(torch::kInt));
8     TORCH_CHECK(t.isScalarType(torch::kFloat) == false);
9
10    TORCH_CHECK(t.name() == "int");
11 }

```

Operations with ScalarType

Listing 21: ./code/type-meta/main.cc (Operations with ScalarType)

```

1 static void TestFromScalarType() {
2     caffe2::TypeMeta t = caffe2::TypeMeta::fromScalarType(torch::kDouble);
3
4     TORCH_CHECK(t.isScalarType(torch::kDouble));
5     TORCH_CHECK(t.name() == "double");
6
7     TORCH_CHECK(t.toScalarType() == torch::kDouble);
8     TORCH_CHECK(t == torch::kDouble);
9     TORCH_CHECK(t != torch::kFloat);
10    TORCH_CHECK(torch::kInt != t);

```

8.4.7 torch::Device

See

- <https://github.com/pytorch/pytorch/blob/master/c10/core/DeviceType.h>
- <https://github.com/pytorch/pytorch/blob/master/c10/core/Device.h>

DeviceType

`torch::DeviceType` is defined as enum class `Device: int8_t {...}`. The most commonly used types are `torch::DeviceType::CPU` and `torch::DeviceType::CUDA`, which are aliased to `torch::kCPU` and `torch::kCUDA`.

Listing 22: ./code/device/main.cc

```

1 void TestDeviceType() {
2     torch::DeviceType d = torch::kCPU;
3     std::ostringstream os;
4     os << d;

```

(continues on next page)

(continued from previous page)

```
5 TORCH_CHECK(os.str() == "cpu");
6
7 TORCH_CHECK(DeviceTypeName(d /*,lower_case=false*/ ) == "CPU");
8 TORCH_CHECK(DeviceTypeName(d, /*lower_case*/ true) == "cpu");
```

Device

A `torch::Device` class has two members: a `torch::DeviceType` and an `int8_t index`.

Listing 23: `./code/device/main.cc` (Constructors)

```
1 void TestDeviceConstructorCPU() {
2     torch::Device d(torch::kCPU);
3     TORCH_CHECK(d.is_cpu() == true);
4     TORCH_CHECK(d.is_cuda() == false);
5     TORCH_CHECK(d.type() == torch::kCPU);
6     TORCH_CHECK(d.has_index() == false);
7     TORCH_CHECK(d.index() == -1);
8     TORCH_CHECK(d.str() == "cpu");
9 }
10
11 void TestDeviceConstructorCUDA() {
12     torch::Device d(torch::kCUDA, 3);
13     TORCH_CHECK(d.is_cpu() == false);
14     TORCH_CHECK(d.is_cuda() == true);
15     TORCH_CHECK(d.type() == torch::kCUDA);
16     TORCH_CHECK(d.has_index() == true);
17     TORCH_CHECK(d.index() == 3);
18     TORCH_CHECK(d.str() == "cuda:3");
19
20     d.set_index(2);
21     TORCH_CHECK(d.index() == 2);
22     TORCH_CHECK(d.str() == "cuda:2");
23
24     d = torch::Device("cpu");
25     TORCH_CHECK(d.is_cpu() == true);
26
27     d = torch::Device("CPU");
28     TORCH_CHECK(d.is_cpu() == true);
29
30     d = torch::Device("cuda:1");
31     TORCH_CHECK(d.is_cuda() == true);
32     TORCH_CHECK(d.index() == 1);
33
34     d = torch::Device("CUDA:1");
35     TORCH_CHECK(d.is_cuda() == true);
36     TORCH_CHECK(d.index() == 1);
37 }
```

8.4.8 TensorOptions

See <https://github.com/pytorch/pytorch/blob/master/c10/core/TensorOptions.h>

Constructors (not recommended)

Listing 24: ./code/tensor-options/main.cc (Not recommended constructors)

```

1 void TestConstructor() {
2     // not recommended
3     torch::TensorOptions opt1(torch::kCPU);
4     torch::TensorOptions opt2(torch::Device(torch::kCPU));
5     torch::TensorOptions opt3(torch::Device({torch::kCUDA, 1}));
6     torch::TensorOptions opt4("cpu");
7     // torch::TensorOptions opt5("CPU") // error;
8     torch::TensorOptions opt6("cuda:1");
9     // torch::TensorOptions opt7("CUDA:1"); // error
10
11     // not recommended, from a scalar type (implicit)
12     torch::TensorOptions opt8(torch::kInt32);
13 }
```

Constructors (Recommended)

Listing 25: ./code/tensor-options/main.cc (Recommended constructors)

```

1 void TestConstructor2() {
2     // recommended
3     torch::TensorOptions opt1 = torch::dtype(torch::kFloat);
4     torch::TensorOptions opt2 = torch::dtype(caffe2::TypeMeta::Make<float>());
5     torch::TensorOptions opt3 = torch::device(torch::kCPU);
6     torch::TensorOptions opt4 = torch::device({torch::kCUDA, 1});
7     // Note: torch::device() returns a TensorOptions
8     // while torch::Device() is the constructor of a class
9
10    torch::TensorOptions opt5 = torch::requires_grad(true);
11    std::cout << opt5 << "\n";
12    // TensorOptions(dtype=float (default), device=cpu (default), layout=Strided
13    // (default), requires_grad=true, pinned_memory=false (default),
14    // memory_format=(nullopt))
15
16    torch::TensorOptions opt6 = torch::dtype<float>();
17    std::cout << torch::toString(opt6) << "\n";
18    // TensorOptions(dtype=float, device=cpu (default), layout=Strided (default),
19    // requires_grad=false (default), pinned_memory=false (default),
20    // memory_format=(nullopt))
21
22    std::cout << "default:" << torch::TensorOptions() << "\n";
23    // default:TensorOptions(dtype=float (default), device=cpu (default),
24    // layout=Strided (default), requires_grad=false (default),
```

(continues on next page)

(continued from previous page)

```

25 // pinned_memory=false (default), memory_format=(nullopt))
26 }

```

Methods

Listing 26: ./code/tensor-options/main.cc (Methods)

```

1 void TestMethods() {
2     torch::TensorOptions opts = torch::dtype<float>();
3     TORCH_CHECK(opts.device() == torch::Device(torch::kCPU));
4     // It has not device_type!
5     TORCH_CHECK(opts.device() == torch::kCPU);
6     TORCH_CHECK(opts.device().type() == torch::kCPU);
7     TORCH_CHECK(opts.requires_grad() == false);
8
9     torch::TensorOptions opts2 =
10         opts.device("cuda:2").dtype(torch::kInt).requires_grad(false);
11
12     TORCH_CHECK(opts2.dtype() == caffe2::TypeMeta::Make<int32_t>());
13     TORCH_CHECK(opts2.dtype() == torch::kInt32);
14     TORCH_CHECK(opts2.requires_grad() == false);
15 }

```

8.4.9 Tensor Creation

See

TensorDataContainer

Note: data is **copied** to the returned tensor!

See

- <https://github.com/pytorch/pytorch/blob/master/torch/csrc/api/include/torch/detail/TensorDataContainer.h>
- https://github.com/pytorch/pytorch/blob/master/tools/autograd/templates/variable_factories.h
- <https://github.com/pytorch/pytorch/blob/master/aten/src/ATen/Utils.cpp>

Support the following data types:

- From a `std::vector<T>`
- From a scalar
- From an initializer list
- From an `ArrayRef<T>`.

From std::vector

Listing 27: ./code/tensor-creation/main.cc

```

1 static void FromStdVecotr() {
2     torch::Tensor t1 = torch::tensor(std::vector<int32_t>{1, 2, 3});
3     TORCH_CHECK(t1.scalar_type() == torch::kLong);
4     t1 = t1.to(torch::kInt);
5     const int32_t *p1 = t1.data_ptr<int32_t>();
6     TORCH_CHECK(p1[0] == 1);
7     TORCH_CHECK(p1[1] == 2);
8     TORCH_CHECK(p1[2] == 3);
9
10    torch::Tensor t2 = torch::tensor(std::vector<float>{1, 2, 3});
11    TORCH_CHECK(t2.scalar_type() == torch::kFloat);
12
13    torch::Tensor t3 =
14        torch::tensor(std::vector<double>{1, 2, 3}, torch::kDouble);
15    TORCH_CHECK(t3.scalar_type() == torch::kDouble);
16
17    torch::Tensor t4 =
18        torch::tensor(std::vector<double>{1, 2, 3},
19                      torch::dtype(torch::kDouble).device("cuda:0"));
20    TORCH_CHECK(t4.is_cuda());
21 }

```

From scalar

Listing 28: ./code/tensor-creation/main.cc

```

1 static void FromScalar() {
2     torch::Tensor t = torch::tensor(3);
3     TORCH_CHECK(t.item<int64_t>() == 3);
4
5     torch::Tensor t2 = torch::tensor(0.5);
6     TORCH_CHECK(t2.scalar_type() == torch::kFloat);
7 }

```

From initializer list

Listing 29: ./code/tensor-creation/main.cc

```

1 static void FromInitializerList() {
2     torch::Tensor t1 = torch::tensor({1, 2, 3});
3     torch::Tensor t2 = torch::tensor(std::vector<int32_t>{1, 2, 3});
4     TORCH_CHECK(torch::allclose(t1, t2));
5
6     torch::Tensor t3 = torch::tensor({{1, 2, 3}, {4, 5, 6}});
7     TORCH_CHECK(t3.dim() == 2);
8 }

```

(continues on next page)

(continued from previous page)

```

9  torch::Tensor t4 = torch::tensor({1, 2, 3});
10 torch::Tensor t5 = torch::tensor({4, 5, 6});
11 TORCH_CHECK(torch::allclose(t3[0], t4));
12 TORCH_CHECK(torch::allclose(t3[1], t5));
13 }

```

From ArrayRef

Listing 30: ./code/tensor-creation/main.cc

```

1  static void FromArrayRef() {
2      int32_t i[] = {1, 2, 3};
3      torch::ArrayRef<int32_t> a(i);
4      torch::Tensor t = torch::tensor(a);
5      // Data is copied to t
6
7      TORCH_CHECK(t[0].item<int64_t>(), 1);
8      TORCH_CHECK(t[1].item<int64_t>(), 2);
9      TORCH_CHECK(t[2].item<int64_t>(), 3);
10 }

```

8.4.10 Tensor

See

- <https://github.com/pytorch/pytorch/blob/master/aten/src/ATen/core/TensorBase.h>
- <https://github.com/pytorch/pytorch/blob/master/aten/src/ATen/templates/TensorBody.h>
- <https://github.com/pytorch/pytorch/blob/master/c10/core/TensorImpl.h>

Common methods

Listing 31: ./code/tensor/main.cc (Not recommended constructors)

```

1  static void TestCommonMethods() {
2      torch::Tensor t = torch::rand({2, 3, 4});
3
4      TORCH_CHECK(t.dim() == 3); // 3-d tensor
5      TORCH_CHECK(t.ndimension() == t.dim()); // same
6      TORCH_CHECK(t.numel() == 2 * 3 * 4);
7      TORCH_CHECK(t.is_contiguous() == true);
8      TORCH_CHECK(t.contiguous().is_contiguous() == true);
9
10     t.fill_(10); // fill all entries to 10
11     t.zero(); // zero out all entries
12
13     t = t.to(torch::kInt);
14     TORCH_CHECK(t.is_floating_point() == false);
15     TORCH_CHECK(t.is_signed() == true);

```

(continues on next page)

(continued from previous page)

```

16 TORCH_CHECK(t.size(0) == 2);
17 TORCH_CHECK(t.size(1) == 3);
18 TORCH_CHECK(t.size(2) == 4);
19 TORCH_CHECK(t.sizes() == torch::ArrayRef<int64_t>({2, 3, 4}));
20
21 t = t.contiguous();
22 TORCH_CHECK(t.stride(0) == 3 * 4);
23 TORCH_CHECK(t.stride(1) == 4);
24 TORCH_CHECK(t.stride(2) == 1);
25 TORCH_CHECK(t.strides() == torch::ArrayRef<int64_t>({12, 4, 1}));
26
27 TORCH_CHECK(t.defined() == true);
28 {
29     torch::Tensor a;
30     TORCH_CHECK(a.defined() == false);
31     a = t;
32     TORCH_CHECK(a.defined() == true);
33     a.reset();
34     TORCH_CHECK(a.defined() == false);
35 }
36
37 t = t.to(torch::kShort);
38 TORCH_CHECK(t.itemsize() == sizeof(int16_t));
39 TORCH_CHECK(t.nbytes() == t.numel() * t.itemsize());
40 TORCH_CHECK(t.itemsize() == t.element_size()); // same
41
42 TORCH_CHECK(t.scalar_type() == torch::kShort);
43 TORCH_CHECK(t.dtype() == caffe2::TypeMeta::Make<int16_t>());
44 TORCH_CHECK(t.dtype().toScalarType() == torch::kShort);
45
46 TORCH_CHECK(t.device() == torch::Device("cpu"));
47 TORCH_CHECK(t.device() == torch::Device(torch::kCPU));
48
49 // Note: t.device() return an instance of torch::Device
50 // t.get_device() returns the device index.
51 TORCH_CHECK(t.get_device() == t.device().index());
52
53 TORCH_CHECK(t.is_cpu() == true);
54 TORCH_CHECK(t.is_cuda() == false);
55
56 t = t.to(torch::kInt);
57 int32_t *p = t.data_ptr<int32_t>();
58 p[0] = 100;
59
60 torch::TensorAccessor<int32_t, 3> acc = t.accessor<int32_t, 3>();
61 TORCH_CHECK(acc[0][0][0] == p[0]);
62 p[12] = -2;
63 TORCH_CHECK(acc[1][0][0] == -2);
64
65 acc[1][1][2] = 3;
66 TORCH_CHECK(*(p + 12 + 4 + 2) == 3);
67

```

(continues on next page)

(continued from previous page)

```

68
69 t = t.to(torch::kFloat);
70 t.set_requires_grad(true);
71 TORCH_CHECK(t.requires_grad() == true);
72
73 t.set_requires_grad(false);
74 TORCH_CHECK(t.requires_grad() == false);
75
76 t = t.cuda();
77 TORCH_CHECK(t.device().type() == torch::kCUDA);
78 t = t.cpu();
79
80 torch::TensorOptions opts = t.options();
81 TORCH_CHECK(opts.device() == t.device());
82 }

```

slice

Listing 32: torch::slice

```

1 static void TestSlice() {
2     auto t = torch::tensor({1, 2, 3, 4, 5}, torch::kInt);
3     torch::TensorAccessor<int32_t, 1> acc = t.accessor<int32_t, 1>();
4
5     // t2 = t[1:3]
6     torch::Tensor t2 = t.slice(/*dim*/ 0, /*start*/ 1,
7                               /*end, exclusive*/ 3); // memory is shared
8     torch::TensorAccessor<int32_t, 1> acc2 = t2.accessor<int32_t, 1>();
9     TORCH_CHECK(acc2[0] == 2);
10    TORCH_CHECK(acc2[1] == 3);
11
12    acc2[0] = 10; // also changes t since the memory is shared
13    TORCH_CHECK(acc[1] == 10);
14 }

```

topk

Listing 33: torch::topk

```

1 // https://pytorch.org/docs/stable/generated/torch.topk.html
2 static void TestTopK() {
3     auto t = torch::tensor({1, 0, 3, -1}, torch::kInt).to(torch::kFloat);
4     torch::Tensor values, indexes;
5     std::tie(values, indexes) =
6         t.topk(/*k*/ 2, /*dim*/ 0, /*largest*/ true, /*sorted*/ true);
7     auto values_acc = values.accessor<float, 1>();
8     auto indexes_acc = indexes.accessor<int64_t, 1>(); // Note: it is int64_t
9
10    TORCH_CHECK(values.numel() == 2); // k in topk is 2

```

(continues on next page)

(continued from previous page)

```
11  TORCH_CHECK(values_acc[0] == 3); // the largest value is 3, at t[2]
12  TORCH_CHECK(values_acc[1] == 1); // the second largest value is 1, at t[0]
13  //
14  TORCH_CHECK(indexes_acc[0] == 2); // the largest value is t[2]
15  TORCH_CHECK(indexes_acc[1] == 0); // the second largest value is t[0]
16  }
```

floor_divide

Listing 34: torch::floor_divide

```
1  static void TestFloorDivide() {
2      auto t = torch::tensor({1, 0, 3, 5, 9}, torch::kInt);
3      auto p = torch::floor_divide(t, 2);
4      auto acc = p.accessor<int32_t, 1>();
5      TORCH_CHECK(acc[0] == 1 / 2);
6      TORCH_CHECK(acc[1] == 0 / 2);
7      TORCH_CHECK(acc[2] == 3 / 2);
8      TORCH_CHECK(acc[3] == 5 / 2);
9      TORCH_CHECK(acc[4] == 9 / 2);
10 }
```

div

Listing 35: torch::div

```

1 // https://pytorch.org/docs/stable/generated/torch.div.html
2 static void TestDiv() {
3     auto t = torch::tensor({1, 0, 3, 5, 9}, torch::kInt);
4     // the rounding mode is supported in torch >= 1.8.0
5     auto p = torch::div(t, 2, /*rounding_mode*/ "trunc");
6     auto acc = p.accessor<int32_t, 1>();
7     TORCH_CHECK(acc[0] == 1 / 2);
8     TORCH_CHECK(acc[1] == 0 / 2);
9     TORCH_CHECK(acc[2] == 3 / 2);
10    TORCH_CHECK(acc[3] == 5 / 2);
11    TORCH_CHECK(acc[4] == 9 / 2);
12 }

```

remainder

Listing 36: torch::remainder

```

1 static void TestRemainder() {
2     auto t = torch::tensor({1, 3, 8}, torch::kInt);
3     auto p = torch::remainder(t, 3);
4     auto acc = p.accessor<int32_t, 1>();
5     TORCH_CHECK(acc[0] == 1);
6     TORCH_CHECK(acc[1] == 0);
7     TORCH_CHECK(acc[2] == 2);
8 }

```

empty

Listing 37: torch::empty

```

1 static void TestEmpty() {
2     auto t = torch::empty({3}, torch::kInt);
3     TORCH_CHECK(t.scalar_type() == torch::kInt);
4     TORCH_CHECK(t.numel() == 3);
5 }

```

8.4.11 intrusive_ptr

8.4.12 optional

8.4.13 PackedSequence

See

- <https://github.com/pytorch/pytorch/blob/master/torch/csrc/api/include/torch/nn/Utils/rnn.h>
- <https://github.com/pytorch/pytorch/blob/master/torch/nn/Utils/rnn.py>

pack_padded_sequence

Listing 38: ./code/packed-sequence/main.cc

```

1 static void TestPadPackedSequence() {
2     torch::Tensor t = torch::tensor({
3         {{10, 20, 30}, {0, 0, 0}, {0, 0, 0}},
4         {{1, 2, 3}, {4, 5, 6}, {7, 8, 9}},
5         {{-1, 2, 3}, {-4, 5, 6}, {0, 0, 0}},
6     });
7     torch::Tensor lengths = torch::tensor({1, 3, 2});
8     torch::nn::utils::rnn::PackedSequence packed_seq =
9         torch::nn::utils::rnn::pack_padded_sequence(
10             t, lengths, /*batch_first*/ true, /*enforce_sorted*/ false);
11     std::cout << "data: " << packed_seq.data() << "\n";
12     std::cout << "batch_sizes: " << packed_seq.batch_sizes() << "\n";
13     std::cout << "sorted_indices: " << packed_seq.sorted_indices() << "\n";
14     std::cout << "unsorted_indices: " << packed_seq.unsorted_indices() << "\n";
15 }
16 /*
17 data:   1   2   3
18  -1   2   3
19  10  20  30
20   4   5   6
21  -4   5   6
22   7   8   9
23 [ CPULongType{6,3} ]
24 batch_sizes:  3
25   2
26   1
27 [ CPULongType{3} ]
28 sorted_indices: 1
29   2
30   0
31 [ CPULongType{3} ]
32 unsorted_indices: 2
33   0
34   1
35 [ CPULongType{3} ]
36 */

```

The output is

Listing 39: ./code/packed-sequence/main.cc

```

1 }
2 /*
3 data:   1   2   3
4  -1   2   3
5  10  20  30
6   4   5   6
7  -4   5   6
8   7   8   9

```

(continues on next page)

(continued from previous page)

```

9  [ CPULongType{6,3} ]
10 batch_sizes: 3
11 2
12 1
13 [ CPULongType{3} ]
14 sorted_indices: 1
15 2

```

8.4.14 ivalue

Listing 40: ./code/ivalue/main.cc

```

1  #include "torch/script.h"
2
3  static void TestVectorOfTensor() {
4      torch::jit::Module m("m");
5      m.define(R"(
6          def forward(self, x, y):
7              return [x, y]
8      )");
9      auto x = torch::tensor({1, 2, 3});
10     auto y = torch::tensor({4, 5, 6});
11     auto i = m.run_method("forward", x, y);
12
13     assert(i.tagKind() == "GenericList");
14
15     torch::ArrayRef<torch::IValue> tensor_list = i.toListRef();
16     TORCH_CHECK(torch::allclose(x, tensor_list[0].toTensor()));
17     TORCH_CHECK(torch::allclose(y, tensor_list[1].toTensor()));
18
19     torch::List<torch::IValue> k = i.toList();
20
21     torch::List<torch::Tensor> o =
22         c10::impl::toTypedList<torch::Tensor>(std::move(k));
23
24     TORCH_CHECK(torch::allclose(o[0], x));
25     TORCH_CHECK(torch::allclose(o[1], y));
26
27     std::vector<torch::Tensor> p = o.vec();
28     TORCH_CHECK(torch::allclose(p[0], x));
29     TORCH_CHECK(torch::allclose(p[1], y));
30 }
31
32 static void TestVectorOfTensor2() {
33     torch::jit::Module m("m");
34     m.define(R"(
35         def forward(self, x):
36             return [[x], [x,x]]
37     )");
38     auto x = torch::tensor({1, 2, 3});

```

(continues on next page)

(continued from previous page)

```

39  auto i = m.run_method("forward", x);
40  TORCH_CHECK(i.tagKind() == "GenericList");
41
42  torch::List<torch::IValue> list = i.toList();
43  torch::Tensor a = list.get(0).toListRef()[0].toTensor();
44  TORCH_CHECK(torch::allclose(a, x));
45
46  std::vector<torch::Tensor> b =
47      c10::impl::toTypedList<torch::Tensor>(list.get(1).toList()).vec();
48  TORCH_CHECK(torch::allclose(b[0], x));
49  TORCH_CHECK(torch::allclose(b[1], x));
50 }
51
52 static void TestVectorOfTensor3() {
53     torch::jit::Module m("m");
54     m.define(R"(
55         def forward(self, x: List[torch.Tensor]):
56             return x[0] + x[1]
57     )");
58
59     std::vector<torch::Tensor> v;
60     v.push_back(torch::tensor({1, 2}));
61     v.push_back(torch::tensor({3, 4}));
62     c10::List<torch::Tensor> ilist(v);
63
64     c10::impl::GenericList generic_list = c10::impl::toList(ilist);
65
66     c10::List<torch::Tensor> l2 =
67         c10::impl::toTypedList<torch::Tensor>(generic_list);
68
69     TORCH_CHECK(torch::allclose(l2[0], v[0]));
70     TORCH_CHECK(torch::allclose(l2[1], v[1]));
71
72     auto r = m.run_method("forward", generic_list);
73     TORCH_CHECK(torch::allclose(r.toTensor(), v[0] + v[1]));
74
75     // Note: We can pass a vector directly
76     r = m.run_method("forward", v);
77     TORCH_CHECK(torch::allclose(r.toTensor(), v[0] + v[1]));
78
79     r = m.run_method("forward", ilist); // also OK
80     TORCH_CHECK(torch::allclose(r.toTensor(), v[0] + v[1]));
81 }
82
83 static void TestVectorOfTensor4() {
84     torch::jit::Module m("m");
85     m.define(R"(
86         def forward(self, x: Tuple[List[torch.Tensor]]):
87             return x[0][0] + x[0][1]
88     )");
89
90     std::vector<torch::Tensor> v;

```

(continues on next page)

(continued from previous page)

```

91 v.push_back(torch::tensor({1, 2}));
92 v.push_back(torch::tensor({3, 4}));
93 auto t = torch::ivar::Tuple::create(v);
94
95 auto r = m.run_method("forward", t);
96 TORCH_CHECK(torch::allclose(r.toTensor(), v[0] + v[1]));
97 }
98
99 static void TestVectorOfTensor5() {
100     torch::jit::Module m("m");
101     m.define(R"(
102         def forward(self, x: Tuple[List[List[torch.Tensor]], List[torch.Tensor]]):
103             return x[0][0][0] + x[0][0][1] + x[1][0] + x[1][1]
104     )");
105
106     std::vector<torch::Tensor> v;
107     v.push_back(torch::tensor({1, 2}));
108     v.push_back(torch::tensor({3, 4}));
109
110     std::vector<std::vector<torch::Tensor>> vv;
111     vv.push_back(v);
112     vv.push_back(v);
113
114     auto t = torch::ivar::Tuple::create(vv, v);
115
116     auto r = m.run_method("forward", t);
117     TORCH_CHECK(torch::allclose(r.toTensor(), v[0] + v[1] + v[0] + v[1]));
118 }
119
120 int main() {
121     TestVectorOfTensor();
122     TestVectorOfTensor2();
123     TestVectorOfTensor3();
124     TestVectorOfTensor4();
125     TestVectorOfTensor5();
126     return 0;
127 }

```

8.4.15 method

See:

- <https://github.com/pytorch/pytorch/blob/master/torch/csrc/api/include/torch/imethod.h>

Listing 41: ./code/method/main.cc

```

1 #include "torch/script.h"
2
3 static void TestHello() {
4     torch::jit::Module m("m");
5     m.define(R"(

```

(continues on next page)

(continued from previous page)

```

6     def forward(self, x: torch.Tensor, y: torch.Tensor):
7         return x + y
8     )");
9
10    torch::jit::Method method = m.get_method("forward");
11    TORCH_CHECK(method.name() == "forward");
12
13    const std::vector<std::string> &names = method.getArgumentNames();
14    TORCH_CHECK(names.size() == 2);
15    TORCH_CHECK(names[0] == "x");
16    TORCH_CHECK(names[1] == "y");
17
18    std::vector<torch::IValue> args;
19    auto x = torch::tensor({1, 2});
20    auto y = torch::tensor({1, 2});
21    args.emplace_back(x);
22    args.emplace_back(y);
23    auto z = method(args).toTensor();
24
25    TORCH_CHECK(torch::equal(z, x + y));
26
27    std::shared_ptr<torch::jit::Graph> g = method.graph();
28    // see graph/main.cc
29 }
30
31 int main() {
32     TestHello();
33     return 0;
34 }

```

8.4.16 type

See: - https://github.com/pytorch/pytorch/blob/master/aten/src/ATen/core/jit_type_base.h - https://github.com/pytorch/pytorch/blob/master/aten/src/ATen/core/jit_type.h - https://github.com/pytorch/pytorch/blob/master/aten/src/ATen/core/jit_type_base.h

`torch::Type` contains a member `torch::TypeKind`. `torch::SharedType` is a subclass of `torch::Type` and `std::enabled_shared_from_this<torch::SharedType>`.

```

// https://github.com/pytorch/pytorch/blob/master/aten/src/ATen/core/jit_type_base.h#L637
using TypePtr = SingletonOrSharedTypePtr<Type>;

```

Listing 42: ./code/type/main.cc

```

1 #include "torch/script.h"
2
3 static void TestTypeKind() {
4     // https://github.com/pytorch/pytorch/blob/master/aten/src/ATen/core/jit_type_base.h
5     torch::TypeKind k = torch::TypeKind::AnyType;
6     TORCH_CHECK(torch::typeKindToString(k) == std::string("AnyType"));
7
8     // NamedType is not a member of TypeKind

```

(continues on next page)

(continued from previous page)

```

9 }
10
11 static void TestNumberType() {
12     // torch::NumberType::get() returns a static object!
13     // so p and q are actually the same
14     torch::NumberTypePtr p = torch::NumberType::get();
15     torch::NumberTypePtr q = torch::NumberType::get();
16
17     TORCH_CHECK(p.get() == q.get());
18
19     TORCH_CHECK(p->str() == "Scalar");
20     TORCH_CHECK(p->kind() == torch::NumberType::Kind);
21     TORCH_CHECK(p->kind() == torch::TypeKind::NumberType);
22 }
23
24 static void TestIntType() {
25     torch::IntTypePtr p = torch::IntType::get();
26     TORCH_CHECK(p->str() == "int");
27     TORCH_CHECK(p->kind() == torch::TypeKind::IntType);
28     TORCH_CHECK(p->kind() == torch::IntType::Kind);
29     TORCH_CHECK(p->isSubtypeOf(torch::NumberType::get()) == true);
30 }
31
32 static void TestFloatType() {
33     torch::FloatTypePtr p = torch::FloatType::get();
34     TORCH_CHECK(p->str() == "float");
35     TORCH_CHECK(p->kind() == torch::TypeKind::FloatType);
36     TORCH_CHECK(p->kind() == torch::FloatType::Kind);
37     TORCH_CHECK(p->isSubtypeOf(torch::NumberType::get()) == true);
38     TORCH_CHECK(p->isSubtypeOf(torch::IntType::get()) == false);
39 }
40
41 static void TestBoolType() {
42     torch::BoolTypePtr p = torch::BoolType::get();
43     TORCH_CHECK(p->str() == "bool");
44     TORCH_CHECK(p->kind() == torch::TypeKind::BoolType);
45     TORCH_CHECK(p->kind() == torch::BoolType::Kind);
46     TORCH_CHECK(p->isSubtypeOf(torch::NumberType::get()) == true);
47     TORCH_CHECK(p->isSubtypeOf(torch::IntType::get()) == false);
48 }
49
50 static void TestNamedType() {
51     // torch::Type is an abstract class!
52     //
53     // torch::NamedType is an abstract class!
54     //
55     // torch::NamedType t(torch::TypeKind::AnyType, "foo.bar"); // error
56     // TORCH_CHECK(t.name()->qualifiedName() == "foo.bar");
57 }
58
59 static void TestAnyType() {
60     torch::AnyTypePtr p = torch::AnyType::get();

```

(continues on next page)

(continued from previous page)

```

61 TORCH_CHECK(p->Kind == torch::TypeKind::AnyType);
62 TORCH_CHECK(p->kind() == torch::TypeKind::AnyType);
63 TORCH_CHECK(p->str() == "Any");
64 TORCH_CHECK(p->requires_grad() == false);
65
66 TORCH_CHECK(p == torch::AnyType::get());
67
68 // available in newer versions of PyTorch
69 // TORCH_CHECK(p->equals(torch::AnyType::get()));
70
71 TORCH_CHECK(torch::toString(p) == "Any");
72 }
73
74 int main() {
75     TestTypeKind();
76     TestNumberType();
77     TestIntType();
78     TestFloatType();
79     TestNamedType();
80     TestAnyType();
81     return 0;
82 }

```

8.5 Logical operations

Listing 43: ./code/logical-op.py

```

1  #!/usr/bin/env python3
2
3  import torch
4
5  a = torch.tensor([float("inf")])
6  b = torch.tensor([float("nan")])
7  assert torch.isinf(a).item() is True
8  assert torch.isnan(a).item() is False
9
10 assert torch.isinf(b).item() is False
11 assert torch.isnan(b).item() is True
12
13 assert torch.logical_or(torch.isinf(a), torch.isnan(b)).item() is True
14
15 assert a.isinf().item() is True
16 assert a.isnan().item() is False
17
18 assert b.isinf().item() is False
19 assert b.isnan().item() is True

```

8.6 Note

To clip gradient, use:

```
tot_norm = torch.nn.utils.clip_grad_norm_(model.parameters(), max_norm=5, norm_type=2.0)
if torch.logical_or(tot_norm.isnan(), tot_norm.isinf()):
    # skip this update
    continue
else:
    optimizer.step()
```

8.7 Quantization

8.7.1 Internals

<https://github.com/pytorch/pytorch/blob/master/aten/src/ATen/core/QuantizerBase.h> defines the base class Quantizer.

<https://github.com/pytorch/pytorch/blob/master/aten/src/ATen/quantized/Quantizer.h> defines the subclasses of Quantizer, such as

- PerTensorAffineQuantizer - qscheme is kPerTensorAffine.

QScheme

See <https://github.com/pytorch/pytorch/blob/master/c10/core/QScheme.h>

Listing 44: ./code/qscheme/main.cc

```
1  #include "torch/script.h"
2
3  static void TestQScheme() {
4      TORCH_CHECK(torch::toString(torch::kPerTensorAffine) == "per_tensor_affine");
5
6      TORCH_CHECK(torch::toString(torch::kPerChannelAffine) ==
7                  "per_channel_affine");
8
9      TORCH_CHECK(torch::toString(torch::kPerTensorSymmetric) ==
10                 "per_tensor_symmetric");
11
12     TORCH_CHECK(torch::toString(torch::kPerChannelSymmetric) ==
13                 "per_channel_symmetric");
14
15     TORCH_CHECK(torch::toString(torch::kPerChannelAffineFloatQParams) ==
16                 "per_channel_affine_float_qparams");
17 }
18
19 int main() {
20     TestQScheme();
21     return 0;
22 }
```

PerTensorAffineQuantizer

It has 4 important methods:

- `QScheme qscheme() const`, always returns `kPerTensorAffine`.
- `double scale() const`
- `int64_t zero_point() const`
- `ScalarType scalar_type() const`

It uses `quantize_tensor_per_tensor_affine_cpu` when `FBGEMM` is available.

Otherwise, it uses <https://github.com/pytorch/pytorch/blob/master/aten/src/ATen/native/quantized/cpu/kernels/QuantizedOpKernels.cpp>

- For arm, it uses `quantize_tensor_arm`. It is a template with many specializations.
- For x86, it uses `quantize_val`
 - If `FBGEMM` is available, it uses `quantize_val`
 - Otherwise, it uses <https://github.com/pytorch/pytorch/blob/master/aten/src/ATen/native/quantized/AffineQuantizerBase.cpp>

```
template <typename T>
T quantize_val(double scale, int64_t zero_point, float value) {
    // std::nearbyint results in nearest integer value according to the current
    // rounding mode and the default rounding mode is rounds to even in half-way
    // cases in most popular processor architectures like x86 and ARM. This is
    // typically faster than an alternatives like std::round that rounds half-way
    // cases away from zero, and can be consistent with SIMD implementations for
    // example in x86 using _mm512_cvtps_epi32 or mm512_round_ps with
    // _MM_FROUND_CUR_DIRECTION option that also follow the current rounding mode.
    int64_t qvalue;
    constexpr int64_t qmin = std::numeric_limits<typename T::underlying>::min();
    constexpr int64_t qmax = std::numeric_limits<typename T::underlying>::max();
    float inv_scale = 1.0f / static_cast<float>(scale);
    qvalue = static_cast<int64_t>(zero_point + Round(value * inv_scale));
    qvalue = std::max<int64_t>(qvalue, qmin);
    qvalue = std::min<int64_t>(qvalue, qmax);
    return static_cast<T>(qvalue);
}
```

`dequantize_val` is defined as:

```
template <typename T>
TORCH_API float dequantize_val(double scale, int64_t zero_point, T value) {
    return static_cast<float>(scale) * (value.val_ - static_cast<int32_t>(zero_point));
}
```

8.7.2 torch.quantize_per_tensor

See https://pytorch.org/docs/stable/generated/torch.quantize_per_tensor.html

```
def test_quantize_per_tensor():
    scale = 0.1
    zero_point = 1
    a = torch.tensor([10.0, 2.0], dtype=torch.float32)
    q = torch.quantize_per_tensor(
        input=a,
        scale=scale,
        zero_point=zero_point,
        dtype=torch.qint8,
    )
    assert isinstance(q, torch.Tensor)
    assert q.is_quantized is True

    assert q.q_scale() == scale
    assert q.q_zero_point() == zero_point
    assert str(q.qscheme()) == "torch.per_tensor_affine"
    assert q.dtype == torch.qint8

    c = q.int_repr()
    assert c[0] == a[0] / scale + zero_point
    assert c[1] == a[1] / scale + zero_point
    assert torch.all(torch.eq(c, torch.tensor([101, 21], dtype=torch.int8)))
    d = q.dequantize()
    assert d.dtype == torch.float32
    assert torch.all(torch.eq(d, a))

    f = torch.dequantize(q)
    assert torch.all(torch.eq(f, a))
    # print(q)
    """
    tensor([10., 2.], size=(2,), dtype=torch.qint8,
           quantization_scheme=torch.per_tensor_affine, scale=0.1, zero_point=1)
    """
    assert q[0].item() == 10 # q[0].item() will dequantize() to a float
    assert q[1].item() == 2
    print(type(q[0].item()))
    q[0] = 2.5 # Note: it will quantize 2.5 and store it in q
    print(q.int_repr())
    """
    tensor([26, 21], dtype=torch.int8)
    """
```


Compress ration

```
def test_size():
    r = torch.rand(100, 100, dtype=torch.float32)
    q = torch.quantize_per_tensor(r, scale=0.1, zero_point=0, dtype=torch.qint8)
    torch.save(r, "float32.pt")
    torch.save(q, "int8.pt")
    float_size = os.path.getsize("float32.pt")
    int8_size = os.path.getsize("int8.pt")
    print("float_size:", float_size)
    print("int8_size:", int8_size)
    print(f"ratio: {float_size}/{int8_size}: {float_size/int8_size:.3f}")
    os.remove("float32.pt")
    os.remove("int8.pt")
    """
    float_size: 40747
    int8_size: 10795
    ratio: 40747/10795: 3.775
    """
```

8.7.3 quantize_per_tensor_dynamic

Listing 45: ./code/quantize_per_tensor_dynamic/main.cc

```
1 // #include "ATen/native/quantized/cpu/QuantUtils.h" // for the latest pytorch
2
3 #include "ATen/native/quantized/cpu/quant_utils.h" // for torch 1.10
4 #include "ATen/ops/quantize_per_tensor_dynamic.h" // needs torch>=1.11
5 #include "torch/script.h"
6
7 // See
8 // https://github.com/pytorch/pytorch/blob/master/aten/src/ATen/native/quantized/cpu/
9 // QuantUtils.h#L59
10 static void TestChooseQuantizationParams() {
11     quant_utils::TensorQuantizationParams p;
12     p = quant_utils::ChooseQuantizationParams(-1 /*min*/, 2 /*max*/,
13                                              -128 /*qmin*/, 127 /*qmax*/);
14     std::cout << "zero_point: " << p.zero_point << "\n";
15     std::cout << "scale: " << p.scale << "\n";
16     /**
17      * scale = (max - min) / (qmax - qmin) = 3 / 255 = 0.0117647
18      * zero_point_min = qmin - min/scale = -128 - (-1)/scale = -43
19      * zero_point_max = qmax - max/scale = 127 - 2/scale = -43
20      *
21      * min_error = abs(qmin) - abs(min/scale) = 128 - 1/scale = 43
22      * max_error = abs(qmax) - abs(max/scale) = 127 - 2/scale = -43
23      *
24      * zero_point = (min_error < max_error) ? zero_point_min : zero_point_max
25      */
26 }
```

(continues on next page)

(continued from previous page)

```

27 // See
28 // https://github.com/pytorch/pytorch/blob/master/aten/src/ATen/native/quantized/QTensor.
   ↪ cpp#L14
29 // and
30 static void TestQuantizePerTensorDynamic() {
31     torch::Tensor r = torch::tensor({-1, 0, 2}, torch::kFloat32);
32     torch::Tensor q = torch::quantize_per_tensor_dynamic(r, torch::kQInt8, false);
33     std::cout << "q: " << q << "\n";
34     #if 0
35     q: -1
36         0
37         2
38     [ QuantizedCPUQInt8Type{3}, qscheme: per_tensor_affine, scale: 0.0117647, zero_point: -
   ↪ 43 ]
39     #endif
40     std::cout << "q.int_repr(): " << q.int_repr() << "\n";
41     #if 0
42     q.int_repr(): -128
43         -43
44         127
45     [ CPUCharType{3} ]
46     #endif
47 }
48
49 int main() {
50     TestChooseQuantizationParams();
51     TestQuantizePerTensorDynamic();
52     return 0;
53 }

```

8.7.4 torch.quantize_per_channel

See https://pytorch.org/docs/stable/generated/torch.quantize_per_channel.html#torch.quantize_per_channel `_k`

```

def test_quantize_per_channel_2d():
    # (N, C)
    a = torch.tensor(
        [
            [1, 2, 3],
            [4, 5, 6],
        ],
        dtype=torch.float32,
    )
    assert a.shape == (2, 3)
    scales = torch.tensor([0.125, 0.25, 0.5])

    # It will be converted to torch.int64 internally
    zero_points = torch.tensor([10, 20, 30], dtype=torch.int32)
    q = torch.quantize_per_channel(
        input=a,
        scales=scales,

```

(continues on next page)

(continued from previous page)

```

        zero_points=zero_points,
        axis=1,
        dtype=torch.qint8,
    )
    assert q.dtype == torch.qint8

    assert q.q_per_channel_scales().dtype == torch.float64
    assert torch.all(torch.eq(q.q_per_channel_scales(), scales))

    assert q.q_per_channel_zero_points().dtype == torch.int64
    assert torch.all(torch.eq(q.q_per_channel_zero_points(), zero_points))

    assert str(q.qscheme()) == "torch.per_channel_affine"

    assert q.q_per_channel_axis() == 1

    i = q.int_repr()
    expected_i = torch.tensor([[18, 28, 36], [42, 40, 42]], dtype=torch.int8)
    assert i.dtype == torch.int8
    assert torch.all(torch.eq(i, expected_i))

    assert i[0][0].item() == a[0][0].item() / scales[0] + zero_points[0]
    assert i[0][1].item() == a[0][1].item() / scales[1] + zero_points[1]
    assert i[0][2].item() == a[0][2].item() / scales[2] + zero_points[2]

    assert i[1][0].item() == a[1][0].item() / scales[0] + zero_points[0]
    assert i[1][1].item() == a[1][1].item() / scales[1] + zero_points[1]
    assert i[1][2].item() == a[1][2].item() / scales[2] + zero_points[2]

    d = q.dequantize()
    assert torch.all(torch.eq(d, a))

    f = torch.dequantize(q)
    assert torch.all(torch.eq(f, a))

    # print(q)
    """
    tensor([[1., 2., 3.],
           [4., 5., 6.]], size=(2, 3), dtype=torch.qint8,
           quantization_scheme=torch.per_channel_affine,
           scale=tensor([0.1250, 0.2500, 0.5000], dtype=torch.float64),
           zero_point=tensor([10, 20, 30]), axis=1)
    """

```

8.7.5 Observer

Listing 46: ./code/observer/ex0.py

```

1  #!/usr/bin/env python3
2
3  import torch
4  from torch.aot.quantization.observer import _with_args, MinMaxObserver
5
6
7  class Foo:
8      def __init__(self, a=1, b=2):
9          self.a = a
10         self.b = b
11
12
13  def test_with_args():
14      Foo.with_args = classmethod(_with_args)
15      foo_builder = Foo.with_args(a=3).with_args(b=4).with_args(a=10)
16      f = foo_builder()
17      assert f.a == 10 # the last a=10 replaces the first a=3
18      assert f.b == 4
19
20      f2 = foo_builder()
21      assert id(f) != id(f2)
22
23
24  def test_min_max_observer():
25      ob = MinMaxObserver(dtype=torch.qint8)
26      print(ob) # MinMaxObserver(min_val=-inf, max_val=-inf)
27
28      ob(torch.tensor([1, 2, 3]))
29      print(ob) # MinMaxObserver(min_val=1.0, max_val=3.0)
30
31      ob(torch.tensor([-1, 30]))
32      print(ob) # MinMaxObserver(min_val=-1.0, max_val=30.0)
33      scale, zero_point = ob.calculate_qparams()
34      print("scale", scale) # scale tensor([0.1216])
35      print("zero_point", zero_point) # zero_point tensor([-120], dtype=torch.int32)
36
37
38  def main():
39      test_with_args()
40      test_min_max_observer()
41
42
43  if __name__ == "__main__":
44      main()

```

8.7.6 Hello

Listing 47: ./code/ex1.py

```

1  #!/usr/bin/env python3
2
3  import torch
4  import torch.nn as nn
5
6
7  class Model(torch.nn.Module):
8      def __init__(self):
9          super().__init__()
10         self.fc = nn.Linear(1, 1)
11
12     def forward(self, x):
13         x = self.fc(x)
14         return x
15
16
17 def main():
18     m = Model()
19     model_int8 = torch.quantization.quantize_dynamic(
20         model=m,
21         qconfig_spec={torch.nn.Linear},
22         dtype=torch.qint8,
23     )
24     print(model_int8)
25     print(model_int8.fc)
26     assert model_int8.fc.weight().is_quantized
27     assert model_int8.fc.weight().dtype == torch.qint8
28
29     assert model_int8.fc.bias().is_quantized is False
30     assert model_int8.fc.bias().dtype == torch.float32
31     assert isinstance(model_int8.fc, torch.nn.quantized.dynamic.Linear)
32     print(type(model_int8.fc))
33
34     x = torch.tensor([[1.0]], dtype=torch.float32)
35     y = m(x)
36     print(x, y)  # tensor([[1.]]) tensor([[ -1.2900]], grad_fn=<AddmmBackward0>)
37
38     qy = model_int8(x)
39     print(qy)  # tensor([[ -1.2931]])
40
41
42 if __name__ == "__main__":
43     torch.manual_seed(20220723)
44     main()

```

8.7.7 References

The main implementation is in

<https://github.com/pytorch/pytorch/tree/master/aten/src/ATen/native/quantized>

- Introducing Quantized Tensor
<https://github.com/pytorch/pytorch/wiki/Introducing-Quantized-Tensor>
- Model Quantization for PyTorch (Proposal) #18318
<https://github.com/pytorch/pytorch/issues/18318>
- torch_quantization_design_proposal
https://github.com/pytorch/pytorch/wiki/torch_quantization_design_proposal

Links

- https://github.com/pytorch/pytorch/blob/master/test/quantization/core/test_quantized_tensor.py
- https://github.com/pytorch/pytorch/blob/master/test/quantization/core/experimental/test_quantized_tensor.py
- https://github.com/pytorch/pytorch/blob/master/aten/src/ATen/test/quantized_test.cpp
- <https://github.com/pytorch/pytorch/blob/master/aten/src/ATen/native/quantized/README.md>
- <https://pytorch.org/blog/introduction-to-quantization-on-pytorch/>
- <https://pytorch.org/docs/stable/quantization.html>
- Deep Dive on PyTorch Quantization - Chris Gottbrath
YouTube: <https://www.youtube.com/watch?v=c3MT2qV5f9w>

8.8 android

8.8.1 References

- <https://zhuanlan.zhihu.com/p/54665674>
- Pytorch model to Caffe & ncnn
<https://github.com/starimeL/PytorchConverter>

8.9 onnx

8.9.1 Install

```
pip install onnx onnxruntime
pip install netron # for visualization
# Or go to https://netron.app/
```

API references

- <https://github.com/onnx/onnx/blob/main/docs/PythonAPIOverview.md>
- https://onnxruntime.ai/docs/api/python/api_summary.html#inferencesession

8.9.2 Hello

Listing 48: ./code/hello/ex0.py

```

1  #!/usr/bin/env python3
2
3  import torch
4  import torch.nn as nn
5
6
7  class Foo(nn.Module):
8      def __init__(self, i):
9          super().__init__()
10         self.relu = nn.ReLU()
11         self.i = 1
12
13     def forward(self, x):
14         if x.sum().item() > 0:
15             return self.relu(x + 1)
16         else:
17             return self.relu(x + 2)
18
19
20 def main():
21     f = Foo(1)
22     f.eval() # f.train(False)
23     f = torch.jit.script(f)
24
25     x = torch.rand(2, 3, 4)
26     # [N, T, C]
27     torch.onnx.export(
28         f,
29         x,
30         "f.onnx",
31         verbose=False,
32         input_names=["x"],
33         output_names=["y"],
34         dynamic_axes={"x": {0: "batch_size", 1: "T"}, "y": [0, 1]},
35         # dynamic_axes={"x": [0, 1], "y": [0, 1]},
36     )
37
38
39 if __name__ == "__main__":
40     main()

```

Listing 49: ./code/hello/ex0-1.py

```
1  #!/usr/bin/env python3
2
3  import onnx
4
5
6  def main():
7      model = onnx.load("f.onnx")
8      # print(model)
9      # Check that the model is well formed
10     onnx.checker.check_model(model)
11     # Print a human readable representation of the graph
12     print(onnx.helper.printable_graph(model.graph))
13     onnx.save(model, "f2.onnx")
14
15
16 if __name__ == "__main__":
17     main()
```

Listing 50: ./code/hello/ex0-2.py

```
1  #!/usr/bin/env python3
2
3  import onnxruntime as ort
4  import numpy as np
5
6
7  def main():
8      # https://github.com/microsoft/onnxruntime/issues/10113
9      options = ort.SessionOptions()
10     options.inter_op_num_threads = 1
11     options.intra_op_num_threads = 1
12
13     ort_session = ort.InferenceSession("f.onnx", sess_options=options)
14
15     x = np.arange(24).reshape(2, 3, 4).astype(np.float32)
16     ortvalue = ort.OrtValue.ortvalue_from_numpy(x)
17     assert ortvalue.device_name() == "cpu"
18     assert list(ortvalue.shape()) == list(x.shape)
19     assert ortvalue.data_type() == "tensor(float)"
20     assert ortvalue.is_tensor() is True
21
22     results = ort_session.run(["y"], {"x": ortvalue})
23     print(results)
24
25     ort_inputs = {ort_session.get_inputs()[0].name: x}
26     results = ort_session.run(["y"], ort_inputs)
27     print(results)
28
29     results = ort_session.run(["y"], {"x": x})
30     print(results)
```

(continues on next page)

(continued from previous page)

```

31
32 # https://onnxruntime.ai/docs/api/python/api_summary.html#onnxruntime.NodeArg
33 inputs = ort_session.get_inputs()
34 assert isinstance(inputs, list)
35 assert len(inputs) == 1
36 assert isinstance(inputs[0], ort.NodeArg)
37 print(inputs[0].name, inputs[0].type, inputs[0].shape)
38 assert inputs[0].name == "x"
39 assert inputs[0].type == "tensor(float)"
40 assert inputs[0].shape == ["batch_size", "T", 4]
41
42 outputs = ort_session.get_outputs()
43 assert isinstance(outputs, list)
44 assert isinstance(outputs[0], ort.NodeArg)
45 assert len(outputs) == 1
46 assert outputs[0].name == "y"
47 assert outputs[0].type == "tensor(float)"
48 assert outputs[0].shape == ["y_dynamic_axes_1", "y_dynamic_axes_2", 4]
49
50
51 if __name__ == "__main__":
52     main()

```

8.9.3 Multiple models

Listing 51: ./code/multiple-models/ex.py

```

1  #!/usr/bin/env python3
2
3  import torch
4  import torch.nn as nn
5  import onnx
6  import onnxruntime as ort
7  import numpy as np
8  import os
9
10
11 class Foo(nn.Module):
12     def forward(self, x):
13         return x + 1
14
15
16 class Bar(nn.Module):
17     def forward(self, x):
18         return x - 1
19
20
21 def export_to_onnx():
22     x = torch.rand(2, 3, dtype=torch.float32)
23     f = Foo()

```

(continues on next page)

(continued from previous page)

```

24 torch.onnx.export(
25     f,
26     x,
27     "f.onnx",
28     verbose=False,
29     input_names=["x1"],
30     output_names=["y1"],
31     dynamic_axes={
32         "x1": {0: "N", 1: "T"},
33         "y1": {0: "N", 1: "T"},
34     },
35 )
36
37 x = torch.rand(1, dtype=torch.float32)
38 b = Bar()
39 torch.onnx.export(
40     b,
41     x,
42     "b.onnx",
43     verbose=False,
44     input_names=["x2"],
45     output_names=["y2"],
46     dynamic_axes={
47         "x2": {0: "N"},
48         "y2": {0: "N"},
49     },
50 )
51
52
53 def merge_models():
54     f = onnx.load("f.onnx")
55     f = onnx.compose.add_prefix(f, prefix="f/")
56     b = onnx.load("b.onnx")
57     combined_model = onnx.compose.merge_models(f, b, io_map={})
58     onnx.save(combined_model, "all.onnx")
59
60
61 def test_merged_model():
62     # https://github.com/microsoft/onnxruntime/issues/10113
63     options = ort.SessionOptions()
64     options.inter_op_num_threads = 1
65     options.intra_op_num_threads = 1
66
67     all_model = onnx.load("all.onnx")
68
69     extractor = onnx.utils.Extractor(all_model)
70
71     f = extractor.extract_model(input_names=["f/x1"], output_names=["f/y1"])
72     f_session = ort.InferenceSession(f.SerializeToString(), sess_options=options)
73     f_inputs = f_session.get_inputs()
74     f_out = f_session.run(["f/y1"], {"f/x1": np.array([[1, 3]], dtype=np.float32)})
75     print(f_out[0]) # [[2. 4.]]

```

(continues on next page)

(continued from previous page)

```
76
77     b = extractor.extract_model(input_names=["x2"], output_names=["y2"])
78     b_session = ort.InferenceSession(b.SerializeToString(), sess_options=options)
79     b_inputs = b_session.get_inputs()
80     b_out = b_session.run(["y2"], {"x2": np.array([1, 3], dtype=np.float32)})
81     print(b_out[0]) # [0. 2.]
82
83
84 def main():
85     export_to_onnx()
86     merge_models()
87     test_merged_model()
88     os.remove("f.onnx")
89     os.remove("b.onnx")
90     os.remove("all.onnx")
91
92
93 if __name__ == "__main__":
94     main()
```

We can first merge multiple models into one and then extract them.

8.9.4 References

- (OPTIONAL) EXPORTING A MODEL FROM PYTORCH TO ONNX AND RUNNING IT USING ONNX RUNTIME
https://pytorch.org/tutorials/advanced/super_resolution_with_onnxruntime.html
- Dynamic dummy input when exporting a PyTorch model? #654
<https://github.com/onnx/onnx/issues/654>
- onnxruntime latest version segment fault #10113
<https://github.com/microsoft/onnxruntime/issues/10113>

9.1 asyncio

9.1.1 asyncio.Future

9.1.2 iterator

See <https://peps.python.org/pep-0234/>

9.1.3 yield

9.1.4 Hello World

Exercise 1

Listing 1: ./code/hello_world/ex1.py

```
1 import asyncio
2
3
4 async def hello():
5     print("hello world")
6
7
8 asyncio.run(hello())
```

Exercise 2

Listing 2: ./code/hello_world/ex2.py

```
1 import asyncio
2 import time
3
4
5 loop = asyncio.get_event_loop()
6
7
```

(continues on next page)

(continued from previous page)

```
8 @asyncio.coroutine
9 def hello():
10     print(f"hello {time.strftime('%X')}")
11     yield from asyncio.sleep(1)
12     print(f"world {time.strftime('%X')}")
13
14
15 if __name__ == "__main__":
16     loop.run_until_complete(hello())
```

9.1.5 References

- PEP 234 – Iterators
<https://peps.python.org/pep-0234/>
- Why does defining `__getitem__` on a class make it iterable in python?
<https://localcoder.org/why-does-defining-getitem-on-a-class-make-it-iterable-in-python>
- PEP 255 – Simple Generators
<https://peps.python.org/pep-0255/>
- Curious Course on Coroutines and Concurrency
https://www.youtube.com/watch?v=Z_OAllhXziw&ab_channel=DavidBeazley
By David Beazley.
- Generator Tricks for Systems Programmers
<https://www.dabeaz.com/generators2/>
- Generators: The Final Frontier
<https://www.youtube.com/watch?v=5-qadlG7tWo&ab_channel=DavidBeazley>
By David Beazley.

9.1.6 TODOs

`asyncio.to_thread()` runs the function in an executor, where the default executor is a threadpool executor, which invokes `loop.run_in_executor()` indirectly.

How to set the executor of a loop? Maybe something related to `set_default_executor`?

If we want to schedule a callback to run in the loop from the C++ code, we can use `loop.call_soon_safe()` method.

9.2 argv

From the doc <https://docs.python.org/3/library/sys.html>:

The `list` of command line arguments passed to a Python script. `argv[0]` **is** the script name (it **is** operating system dependent whether this **is** a full pathname **or not**). If the command was executed using the `-c` command line option to the interpreter, `argv[0]` **is set** to the string `'-c'`. If no script name was passed to the Python interpreter, `argv[0]` **is** the empty string.

Note that `argv` is at least of size 1, though `argv[0]` may be an empty string.

```
import sys
print(sys.argv)
```

9.3 TODO

Python with zeroMQ (c extension)

9.4 time

```
import time
print(f'Started at {time.strftime("%X")}')
# do something
print(f'Finished at {time.strftime("%X")}')
```

9.5 Numbers

9.5.1 binary representation

Listing 3: `./code/numbers/representations.py`

```
1 print(bin(1)) # 0b1
2 print(bin(3)) # 0b11
3 print(bin(255)) # 0b11111111
4 print(bin(256)) # 0b100000000
5 assert isinstance(bin(1), str)
6 assert int("11", base=2) == 3
7 assert int("0b11", base=0) == 3
8 assert hex(2) == "0x2"
9 assert hex(10) == "0xa"
10
11 assert oct(10) == "0o12"
12 assert int("12", base=8) == 10
13 assert int("0o12", base=0) == 10
```

(continues on next page)

(continued from previous page)

```
14
15 assert 1_000 == 1000
16 assert 1_000_000 == 1000000
```

9.6 str

9.6.1 format

See <https://docs.python.org/3/library/string.html#formatspec> and <https://peps.python.org/pep-3101/>

Listing 4: ./code/str/format.py

```
1 a = 1
2 b = 2
3 c = 3
4 assert "{}".format(a) == "1"
5 assert "{}".format(b) == "2"
6 assert "{0} {1} {foo}".format(a, b, foo=c) == "1 2 3"
7
8 # 1 - the first positional argument (counting from 0)
9 # foo - it is a keyword argument
10 # 0 - the zeros positional
11 assert "{1} {foo} {0}".format(a, b, foo=c) == "2 3 1"
12
13 assert "{0} {1} {0} {0}".format(a, b) == "1 2 1 1"
14
15 assert "skip braces {0} {}".format(a) == "skip braces 1 {}"
16 print("{}") # {}
17 try:
18     print("{} {}".format(a))
19 except IndexError as e:
20     assert str(e) == "Replacement index 1 out of range for positional args tuple"
21
22 assert "{0:2}".format(a) == " 1"
23 assert "{0:02}".format(a) == "01"
24 assert "{0:03}".format(a) == "001"
25 assert "{0:1}".format(-1) == "-1"
26 assert "{0:2}".format(-1) == "-1"
27 assert "{0:3}".format(-1) == "-1"
28 assert "{0:03}".format(-1) == "-01"
29
30 assert "{0:.2f}".format(0.5) == "0.50"
31 assert "{0:.3f}".format(0.5) == "0.500"
```


9.7 enum

9.7.1 Hello

See <https://docs.python.org/3.11/howto/enum.html>

Enum

Note:

- It is iterable, i.e., supports `__iter__`
- name and value
- alias and `@unique`.
- `__members__`.
- `str` and `repr`.
- `auto`

Listing 5: `./code/hello/ex1.py`

```

1  from enum import Enum
2
3
4  class Color(Enum):
5      RED = 1
6      GREEN = 2
7      BLUE = 3
8      # BLUE = 4 # TypeError: Attempted to reuse key: 'BLUE'
9      ALIAS_FOR_RED = 1 # Use @unique to disallow this
10     MAX_COLOR = 4 # Note the naming convention
11
12
13  assert isinstance(Color.RED, Color)
14
15  assert str(Color(1)) == "Color.RED"
16  assert str(repr(Color(1))) == "<Color.RED: 1>"
17
18  assert Color.RED.name == "RED"
19  assert Color.BLUE.value == 3
20
21  print(list(Color))
22  print(type(list(Color)[0]))
23  for c in Color:
24      print(c, type(c))
25
26  """
27  [<Color.RED: 1>, <Color.GREEN: 2>, <Color.BLUE: 3>, <Color.MAX_COLOR: 4>]
28  <enum 'Color'>
29  Color.RED <enum 'Color'>
30  Color.GREEN <enum 'Color'>
31  Color.BLUE <enum 'Color'>

```

(continues on next page)

(continued from previous page)

```
32 Color.MAX_COLOR <enum 'Color'>
33 """
34
35 assert Color(1) == Color.RED
36 assert Color["RED"] == Color.RED
37 assert Color["ALIAS_FOR_RED"] == Color.RED
38
39 print(Color.__members__)
40 """
41 {'RED': <Color.RED: 1>, 'GREEN': <Color.GREEN: 2>, 'BLUE': <Color.BLUE: 3>, 'ALIAS_FOR_RED':
42  ↳<Color.RED: 1>, 'MAX_COLOR': <Color.MAX_COLOR: 4>}
```

Flag

Listing 6: ./code/hello/ex2.py

```
1 from enum import Flag
2
3
4 class Weekday(Flag):
5     MONDAY = 1 << 0
6     TUESDAY = 1 << 1
7     WEDNESDAY = 1 << 2
8     THURSDAY = 1 << 3
9     FRIDAY = 1 << 4
10    SATURDAY = 1 << 5
11    SUNDAY = 1 << 6
12
13
14 assert Weekday.MONDAY.value == 1
15 assert Weekday.TUESDAY.value == 2
16 assert Weekday.WEDNESDAY.value == 4
17 assert Weekday.THURSDAY.value == 8
18 assert Weekday.FRIDAY.value == 16
19 assert Weekday.SATURDAY.value == 32
20 assert Weekday.SUNDAY.value == 64
21
22 weekend = Weekday.SATURDAY | Weekday.SUNDAY
23 print(weekend) # Weekday.SUNDAY|SATURDAY
24 print(repr(weekend)) # <Weekday.SUNDAY|SATURDAY: 96>
25 assert Weekday.SATURDAY in weekend
26 assert Weekday.SUNDAY in weekend
27 assert Weekday.MONDAY not in weekend
```

auto

Listing 7: ./code/hello/ex3.py

```
1 from enum import Enum, Flag, auto
2
3
4 class Weekday(Flag):
5     MONDAY = auto() # start from 1
6     TUESDAY = auto()
7     WEDNESDAY = auto()
8     THURSDAY = auto()
9     FRIDAY = auto()
10    SATURDAY = 128
11    SUNDAY = auto()
12
13
14 assert Weekday.MONDAY.value == 1
15 assert Weekday.TUESDAY.value == 2
16 assert Weekday.WEDNESDAY.value == 4
17 assert Weekday.THURSDAY.value == 8
18 assert Weekday.FRIDAY.value == 16
19 assert Weekday.SATURDAY.value == 128
20 assert Weekday.SUNDAY.value == 256
21
22
23 class Color(Enum):
24     RED = auto() # start from 1
25     GREEN = auto()
26     BLUE = auto()
27     YELLOW = 10
28     WHITE = auto()
29
30
31 assert Color.RED.value == 1
32 assert Color.GREEN.value == 2
33 assert Color.BLUE.value == 3
34 assert Color.YELLOW.value == 10
35 assert Color.WHITE.value == 11
```

9.8 socket

9.8.1 AddressFamily

It is an IntEnum and all of its members are exported to socket.

Listing 8: ./code/address-family.py

```
1 import socket
2
3 print(list(socket.AddressFamily))
```

(continues on next page)

(continued from previous page)

```

4  """
5  [<AddressFamily.AF_UNSPEC: 0>, <AddressFamily.AF_UNIX: 1>,
6  <AddressFamily.AF_INET: 2>, <AddressFamily.AF_AX25: 3>,
7  <AddressFamily.AF_IPX: 4>, <AddressFamily.AF_APPLETALK: 5>,
8  <AddressFamily.AF_NETROM: 6>, <AddressFamily.AF_BRIDGE: 7>,
9  <AddressFamily.AF_ATMPVC: 8>, <AddressFamily.AF_X25: 9>,
10 <AddressFamily.AF_INET6: 10>, <AddressFamily.AF_ROSE: 11>,
11 <AddressFamily.AF_NETBEUI: 13>, <AddressFamily.AF_SECURITY: 14>,
12 <AddressFamily.AF_KEY: 15>, <AddressFamily.AF_NETLINK: 16>,
13 <AddressFamily.AF_PACKET: 17>, <AddressFamily.AF_ASH: 18>,
14 <AddressFamily.AF_ECONET: 19>, <AddressFamily.AF_ATMSVC: 20>,
15 <AddressFamily.AF_RDS: 21>, <AddressFamily.AF_SNA: 22>,
16 <AddressFamily.AF_IRDA: 23>, <AddressFamily.AF_PPPOX: 24>,
17 <AddressFamily.AF_WANPIPE: 25>, <AddressFamily.AF_LLC: 26>,
18 <AddressFamily.AF_CAN: 29>, <AddressFamily.AF_TIPC: 30>,
19 <AddressFamily.AF_BLUETOOTH: 31>, <AddressFamily.AF_ALG: 38>,
20 <AddressFamily.AF_VSOCK: 40>, <AddressFamily.AF_QIPCRTR: 42>]
21 """
22
23 assert socket.AF_UNIX == socket.AddressFamily.AF_UNIX
24 assert socket.AF_INET == socket.AddressFamily.AF_INET

```

9.8.2 SocketKind

It is an `IntEnum` and all of its members are exported to `socket`.

Listing 9: `./code/socket-kind.py`

```

1  import socket
2
3  print(list(socket.SocketKind))
4  """
5  [<SocketKind.SOCK_STREAM: 1>, <SocketKind.SOCK_DGRAM: 2>,
6  <SocketKind.SOCK_RAW: 3>, <SocketKind.SOCK_RDM: 4>,
7  <SocketKind.SOCK_SEQPACKET: 5>, <SocketKind.SOCK_NONBLOCK: 2048>,
8  <SocketKind.SOCK_CLOEXEC: 524288>]
9  """
10
11 assert socket.SOCK_STREAM == socket.SocketKind.SOCK_STREAM
12 assert socket.SOCK_DGRAM == socket.SocketKind.SOCK_DGRAM

```

9.8.3 struct sockaddr_in

See also

- https://www.gta.ufrj.br/ensino/eel878/sockets/sockaddr_inman.html
- <https://man7.org/linux/man-pages/man7/ip.7.html>

Listing 10: ./code/sockaddr_in.h

```

1 // https://github.com/lattera/glibc/blob/master/bits/sockaddr.h
2 /* POSIX.1g specifies this type name for the `sa_family' member. */
3 typedef unsigned short int sa_family_t;
4
5 #define __SOCKADDR_COMMON(sa_prefix) sa_family_t sa_prefix##family
6
7 // https://github.com/lattera/glibc/blob/master/bits/socket.h
8
9 struct sockaddr {
10     __SOCKADDR_COMMON(sa_); /* Common data: address family and length. */
11     char sa_data[14]; /* Address data. */
12 };
13
14 // https://github.com/lattera/glibc/blob/master/inet/netinet/in.h
15 struct sockaddr_in {
16     __SOCKADDR_COMMON(sin_);
17     in_port_t sin_port; /* Port number. */
18     struct in_addr sin_addr; /* Internet address. */
19
20     /* Pad to size of `struct sockaddr'. */
21     unsigned char sin_zero[sizeof(struct sockaddr) - __SOCKADDR_COMMON_SIZE -
22                               sizeof(in_port_t) - sizeof(struct in_addr)];
23 };
24
25 typedef uint32_t in_addr_t;
26 struct in_addr {
27     in_addr_t s_addr;
28 };
29
30 /* Address to accept any incoming messages. */
31 #define INADDR_ANY ((in_addr_t)0x00000000)
32 /* Address to send to all hosts. */
33 #define INADDR_BROADCAST ((in_addr_t)0xffffffff)
34 /* Address indicating an error return. */
35 #define INADDR_NONE ((in_addr_t)0xffffffff)
36
37 /* Network number for local host loopback. */
38 #define IN_LOOPBACKNET 127
39 /* Address to loopback in software to local host. */
40 #ifndef INADDR_LOOPBACK
41 #define INADDR_LOOPBACK ((in_addr_t)0x7f000001) /* Inet 127.0.0.1. */
42 #endif

```

9.8.4 AddressInfo

Listing 11: ./code/address-info.py

```

1 import socket
2
3 print(list(socket.AddressInfo))
4 """
5 [<AddressInfo.AI_PASSIVE: 1>, <AddressInfo.AI_CANONNAME: 2>,
6 <AddressInfo.AI_NUMERICHOST: 4>, <AddressInfo.AI_V4MAPPED: 8>,
7 <AddressInfo.AI_ALL: 16>, <AddressInfo.AI_ADDRCONFIG: 32>,
8 <AddressInfo.AI_NUMERICSERV: 1024>]
9 """
10 assert socket.AI_PASSIVE == socket.AddressInfo.AI_PASSIVE

```

9.8.5 inet_pton

https://man7.org/linux/man-pages/man3/inet_pton.3.html

Representation format to network address.

The resulting network address is in network order, i.e., big endian.

Listing 12: ./code/inet_pton.c

```

1 #include <arpa/inet.h>
2 #include <stdio.h>
3
4 int main() {
5     struct in_addr addr;
6     int res = inet_pton(AF_INET, "192.168.1.2", &addr);
7     printf("%08x\n", addr.s_addr);
8     printf("192: %x\n", 192);
9     printf("168: %x\n", 168);
10    printf("1: %x\n", 1);
11    printf("2: %x\n", 2);
12    return 0;
13 }
14 #if 0
15 ./inet_pton
16 0201a8c0
17 192: c0
18 168: a8
19 1: 1
20 2: 2
21 #endif

```

Its implementation can be found at https://github.com/bminor/glibc/blob/master/resolv/inet_pton.c

Listing 13: ./code/inet_pton_impl.c

```

1 // See https://github.com/bminor/glibc/blob/master/resolv/inet_pton.c
2 //

```

(continues on next page)

(continued from previous page)

```

3  /* Copyright (C) 1996-2022 Free Software Foundation, Inc.
4     This file is part of the GNU C Library.
5
6     The GNU C Library is free software; you can redistribute it and/or
7     modify it under the terms of the GNU Lesser General Public
8     License as published by the Free Software Foundation; either
9     version 2.1 of the License, or (at your option) any later version.
10
11    The GNU C Library is distributed in the hope that it will be useful,
12    but WITHOUT ANY WARRANTY; without even the implied warranty of
13    MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE.  See the GNU
14    Lesser General Public License for more details.
15
16    You should have received a copy of the GNU Lesser General Public
17    License along with the GNU C Library; if not, see
18    <https://www.gnu.org/licenses/>.  */
19
20  /*
21   * Copyright (c) 1996,1999 by Internet Software Consortium.
22   *
23   * Permission to use, copy, modify, and distribute this software for any
24   * purpose with or without fee is hereby granted, provided that the above
25   * copyright notice and this permission notice appear in all copies.
26   *
27   * THE SOFTWARE IS PROVIDED "AS IS" AND INTERNET SOFTWARE CONSORTIUM DISCLAIMS
28   * ALL WARRANTIES WITH REGARD TO THIS SOFTWARE INCLUDING ALL IMPLIED WARRANTIES
29   * OF MERCHANTABILITY AND FITNESS.  IN NO EVENT SHALL INTERNET SOFTWARE
30   * CONSORTIUM BE LIABLE FOR ANY SPECIAL, DIRECT, INDIRECT, OR CONSEQUENTIAL
31   * DAMAGES OR ANY DAMAGES WHATSOEVER RESULTING FROM LOSS OF USE, DATA OR
32   * PROFITS, WHETHER IN AN ACTION OF CONTRACT, NEGLIGENCE OR OTHER TORTIOUS
33   * ACTION, ARISING OUT OF OR IN CONNECTION WITH THE USE OR PERFORMANCE OF THIS
34   * SOFTWARE.
35   */
36
37  #include <arpa/inet.h>
38  #include <arpa/nameser.h>
39  #include <ctype.h>
40  #include <errno.h>
41  #include <netinet/in.h>
42  #include <resolv/resolv-internal.h>
43  #include <string.h>
44  #include <sys/socket.h>
45  #include <sys/types.h>
46
47  static int inet_pton4 (const char *src, const char *src_end, u_char *dst);
48  static int inet_pton6 (const char *src, const char *src_end, u_char *dst);
49
50  int
51  __inet_pton_length (int af, const char *src, size_t srclen, void *dst)
52  {
53      switch (af)
54      {

```

(continues on next page)

(continued from previous page)

```

55     case AF_INET:
56         return inet_pton4 (src, src + srclen, dst);
57     case AF_INET6:
58         return inet_pton6 (src, src + srclen, dst);
59     default:
60         __set_errno (EAFNOSUPPORT);
61         return -1;
62     }
63 }
64 libc_hidden_def (__inet_pton_length)
65
66 /* Like __inet_pton_length, but use strlen (SRC) as the length of
67 SRC. */
68 int
69 __inet_pton (int af, const char *src, void *dst)
70 {
71     return __inet_pton_length (af, src, strlen (src), dst);
72 }
73 libc_hidden_def (__inet_pton)
74 weak_alias (__inet_pton, inet_pton)
75 libc_hidden_weak (inet_pton)
76
77 /* Like inet_aton but without all the hexadecimal, octal and shorthand
78 (and trailing garbage is not ignored). Return 1 if SRC is a valid
79 dotted quad, else 0. This function does not touch DST unless it's
80 returning 1.
81 Author: Paul Vixie, 1996. */
82 static int
83 inet_pton4 (const char *src, const char *end, unsigned char *dst)
84 {
85     int saw_digit, octets, ch;
86     unsigned char tmp[NS_INADDRSZ], *tp;
87
88     saw_digit = 0;
89     octets = 0;
90     *(tp = tmp) = 0;
91     while (src < end)
92     {
93         ch = *src++;
94         if (ch >= '0' && ch <= '9')
95         {
96             unsigned int new = *tp * 10 + (ch - '0');
97
98             if (saw_digit && *tp == 0)
99                 return 0;
100             if (new > 255)
101                 return 0;
102             *tp = new;
103             if (! saw_digit)
104             {
105                 if (++octets > 4)
106                     return 0;

```

(continues on next page)

(continued from previous page)

```

107         saw_digit = 1;
108     }
109 }
110 else if (ch == '.' && saw_digit)
111 {
112     if (octets == 4)
113         return 0;
114     *++tp = 0;
115     saw_digit = 0;
116 }
117 else
118     return 0;
119 }
120 if (octets < 4)
121     return 0;
122 memcpy (dst, tmp, NS_INADDRSZ);
123 return 1;
124 }
125
126 /* Return the value of CH as a hexademical digit, or -1 if it is a
127 different type of character. */
128 static int
129 hex_digit_value (char ch)
130 {
131     if ('0' <= ch && ch <= '9')
132         return ch - '0';
133     if ('a' <= ch && ch <= 'f')
134         return ch - 'a' + 10;
135     if ('A' <= ch && ch <= 'F')
136         return ch - 'A' + 10;
137     return -1;
138 }
139
140 /* Convert presentation-level IPv6 address to network order binary
141 form. Return 1 if SRC is a valid [RFC1884 2.2] address, else 0.
142 This function does not touch DST unless it's returning 1.
143 Author: Paul Vixie, 1996. Inspired by Mark Andrews. */
144 static int
145 inet_pton6 (const char *src, const char *src_endp, unsigned char *dst)
146 {
147     unsigned char tmp[NS_IN6ADDRSZ], *tp, *endp, *colonp;
148     const char *curtok;
149     int ch;
150     size_t xdigits_seen;      /* Number of hex digits since colon. */
151     unsigned int val;
152
153     tp = memset (tmp, '\0', NS_IN6ADDRSZ);
154     endp = tp + NS_IN6ADDRSZ;
155     colonp = NULL;
156
157     /* Leading :: requires some special handling. */
158     if (src == src_endp)

```

(continues on next page)

(continued from previous page)

```

159     return 0;
160     if (*src == ':')
161     {
162         ++src;
163         if (src == src_endp || *src != ':')
164             return 0;
165     }
166
167     curtok = src;
168     xdigits_seen = 0;
169     val = 0;
170     while (src < src_endp)
171     {
172         ch = *src++;
173         int digit = hex_digit_value (ch);
174         if (digit >= 0)
175         {
176             if (xdigits_seen == 4)
177                 return 0;
178             val <= 4;
179             val |= digit;
180             if (val > 0xffff)
181                 return 0;
182             ++xdigits_seen;
183             continue;
184         }
185         if (ch == ':')
186         {
187             curtok = src;
188             if (xdigits_seen == 0)
189             {
190                 if (colonp)
191                     return 0;
192                 colonp = tp;
193                 continue;
194             }
195             else if (src == src_endp)
196                 return 0;
197             if (tp + NS_INT16SZ > endp)
198                 return 0;
199             *tp++ = (unsigned char) (val >> 8) & 0xff;
200             *tp++ = (unsigned char) val & 0xff;
201             xdigits_seen = 0;
202             val = 0;
203             continue;
204         }
205         if (ch == '.' && ((tp + NS_INADDRSZ) <= endp)
206             && inet_pton4 (curtok, src_endp, tp) > 0)
207         {
208             tp += NS_INADDRSZ;
209             xdigits_seen = 0;
210             break; /* '\0' was seen by inet_pton4. */

```

(continues on next page)

(continued from previous page)

```

211     }
212     return 0;
213 }
214 if (xdigits_seen > 0)
215 {
216     if (tp + NS_INT16SZ > endp)
217         return 0;
218     *tp++ = (unsigned char) (val >> 8) & 0xff;
219     *tp++ = (unsigned char) val & 0xff;
220 }
221 if (colonp != NULL)
222 {
223     /* Replace :: with zeros. */
224     if (tp == endp)
225         /* :: would expand to a zero-width field. */
226         return 0;
227     size_t n = tp - colonp;
228     memmove (endp - n, colonp, n);
229     memset (colonp, 0, endp - n - colonp);
230     tp = endp;
231 }
232 if (tp != endp)
233     return 0;
234 memcpy (dst, tmp, NS_IN6ADDRSZ);
235 return 1;
236 }

```

9.8.6 inet_ntop

Network address to representation format.

See https://man7.org/linux/man-pages/man3/inet_ntop.3.html

Listing 14: ./code/inet_ntop.c

```

1  #include <arpa/inet.h>
2  #include <stdio.h>
3
4  int main() {
5      struct in_addr addr;
6      uint8_t *p = (uint8_t *)&addr.s_addr;
7      p[0] = 192;
8      p[1] = 168;
9      p[2] = 1;
10     p[3] = 2;
11     char buf[INET_ADDRSTRLEN];
12     const char *ret = inet_ntop(AF_INET, &addr.s_addr, buf, sizeof(buf));
13     printf("%s\n", buf);
14     printf("%p, %p\n", buf, ret);
15     return 0;
16 }

```

(continues on next page)

(continued from previous page)

```

17 #if 0
18 192.168.1.2
19 0x7ffc808b5e80, 0x7ffc808b5e80
20 #endif

```

Its implementation can be found at https://github.com/bminor/glibc/blob/master/resolv/inet_ntop.c

Listing 15: ./code/inet_ntop_impl.c

```

1 // https://github.com/bminor/glibc/blob/master/resolv/inet_ntop.c
2 /*
3  * Copyright (c) 1996-1999 by Internet Software Consortium.
4  *
5  * Permission to use, copy, modify, and distribute this software for any
6  * purpose with or without fee is hereby granted, provided that the above
7  * copyright notice and this permission notice appear in all copies.
8  *
9  * THE SOFTWARE IS PROVIDED "AS IS" AND INTERNET SOFTWARE CONSORTIUM DISCLAIMS
10 * ALL WARRANTIES WITH REGARD TO THIS SOFTWARE INCLUDING ALL IMPLIED WARRANTIES
11 * OF MERCHANTABILITY AND FITNESS. IN NO EVENT SHALL INTERNET SOFTWARE
12 * CONSORTIUM BE LIABLE FOR ANY SPECIAL, DIRECT, INDIRECT, OR CONSEQUENTIAL
13 * DAMAGES OR ANY DAMAGES WHATSOEVER RESULTING FROM LOSS OF USE, DATA OR
14 * PROFITS, WHETHER IN AN ACTION OF CONTRACT, NEGLIGENCE OR OTHER TORTIOUS
15 * ACTION, ARISING OUT OF OR IN CONNECTION WITH THE USE OR PERFORMANCE OF THIS
16 * SOFTWARE.
17 */
18
19 #include <sys/param.h>
20 #include <sys/types.h>
21 #include <sys/socket.h>
22
23 #include <netinet/in.h>
24 #include <arpa/inet.h>
25 #include <arpa/nameser.h>
26
27 #include <errno.h>
28 #include <stdio.h>
29 #include <string.h>
30
31 #ifdef SPRINTF_CHAR
32 # define SPRINTF(x) strlen(sprintf/**/x)
33 #else
34 # define SPRINTF(x) ((size_t)sprintf x)
35 #endif
36
37 /*
38  * WARNING: Don't even consider trying to compile this on a system where
39  * sizeof(int) < 4.  sizeof(int) > 4 is fine; all the world's not a VAX.
40  */
41
42 static const char *inet_ntop4 (const u_char *src, char *dst, socklen_t size);
43 static const char *inet_ntop6 (const u_char *src, char *dst, socklen_t size);

```

(continues on next page)

(continued from previous page)

```

44
45 /* char *
46  * inet_ntop(af, src, dst, size)
47  *      convert a network format address to presentation format.
48  * return:
49  *      pointer to presentation format address ('dst'), or NULL (see errno).
50  * author:
51  *      Paul Vixie, 1996.
52  */
53 const char *
54 inet_ntop (int af, const void *src, char *dst, socklen_t size)
55 {
56     switch (af) {
57     case AF_INET:
58         return (inet_ntop4(src, dst, size));
59     case AF_INET6:
60         return (inet_ntop6(src, dst, size));
61     default:
62         __set_errno (EAFNOSUPPORT);
63         return (NULL);
64     }
65     /* NOTREACHED */
66 }
67 libc_hidden_def (inet_ntop)
68
69 /* const char *
70  * inet_ntop4(src, dst, size)
71  *      format an IPv4 address
72  * return:
73  *      'dst' (as a const)
74  * notes:
75  *      (1) uses no statics
76  *      (2) takes a u_char* not an in_addr as input
77  * author:
78  *      Paul Vixie, 1996.
79  */
80 static const char *
81 inet_ntop4 (const u_char *src, char *dst, socklen_t size)
82 {
83     static const char fmt[] = "%u.%u.%u.%u";
84     char tmp[sizeof "255.255.255.255"];
85
86     if (SPRINTF((tmp, fmt, src[0], src[1], src[2], src[3])) >= size) {
87         __set_errno (ENOSPC);
88         return (NULL);
89     }
90     return strcpy(dst, tmp);
91 }
92
93 /* const char *
94  * inet_ntop6(src, dst, size)
95  *      convert IPv6 binary address into presentation (printable) format

```

(continues on next page)

(continued from previous page)

```

96  * author:
97  *      Paul Vixie, 1996.
98  */
99  static const char *
100 inet_ntop6 (const u_char *src, char *dst, socklen_t size)
101 {
102     /*
103      * Note that int32_t and int16_t need only be "at least" large enough
104      * to contain a value of the specified size.  On some systems, like
105      * Crays, there is no such thing as an integer variable with 16 bits.
106      * Keep this in mind if you think this function should have been coded
107      * to use pointer overlays.  All the world's not a VAX.
108      */
109     char tmp[sizeof "ffff:ffff:ffff:ffff:ffff:ffff:255.255.255.255"], *tp;
110     struct { int base, len; } best, cur;
111     u_int words[NS_IN6ADDRSZ / NS_INT16SZ];
112     int i;
113
114     /*
115      * Preprocess:
116      *      Copy the input (bytewise) array into a wordwise array.
117      *      Find the longest run of 0x00's in src[] for :: shorthanding.
118      */
119     memset(words, '\\0', sizeof words);
120     for (i = 0; i < NS_IN6ADDRSZ; i += 2)
121         words[i / 2] = (src[i] << 8) | src[i + 1];
122     best.base = -1;
123     cur.base = -1;
124     best.len = 0;
125     cur.len = 0;
126     for (i = 0; i < (NS_IN6ADDRSZ / NS_INT16SZ); i++) {
127         if (words[i] == 0) {
128             if (cur.base == -1)
129                 cur.base = i, cur.len = 1;
130             else
131                 cur.len++;
132         } else {
133             if (cur.base != -1) {
134                 if (best.base == -1 || cur.len > best.len)
135                     best = cur;
136                 cur.base = -1;
137             }
138         }
139     }
140     if (cur.base != -1) {
141         if (best.base == -1 || cur.len > best.len)
142             best = cur;
143     }
144     if (best.base != -1 && best.len < 2)
145         best.base = -1;
146
147     /*

```

(continues on next page)

(continued from previous page)

```

148     * Format the result.
149     */
150     tp = tmp;
151     for (i = 0; i < (NS_IN6ADDRSZ / NS_INT16SZ); i++) {
152         /* Are we inside the best run of 0x00's? */
153         if (best.base != -1 && i >= best.base &&
154             i < (best.base + best.len)) {
155             if (i == best.base)
156                 *tp++ = ':';
157             continue;
158         }
159         /* Are we following an initial run of 0x00s or any real hex? */
160         if (i != 0)
161             *tp++ = ':';
162         /* Is this address an encapsulated IPv4? */
163         if (i == 6 && best.base == 0 &&
164             (best.len == 6 || (best.len == 5 && words[5] == 0xffff))) {
165             if (!inet_ntop4(src+12, tp, sizeof tmp - (tp - tmp)))
166                 return (NULL);
167             tp += strlen(tp);
168             break;
169         }
170         tp += SPRINTF((tp, "%x", words[i]));
171     }
172     /* Was it a trailing run of 0x00's? */
173     if (best.base != -1 && (best.base + best.len) ==
174         (NS_IN6ADDRSZ / NS_INT16SZ))
175         *tp++ = ':';
176     *tp++ = '\0';
177
178     /*
179     * Check for overflow, copy, and we're done.
180     */
181     if ((socklen_t)(tp - tmp) > size) {
182         __set_errno (ENOSPC);
183         return (NULL);
184     }
185     return strcpy(dst, tmp);
186 }

```

9.8.7 Echo Server and Client

Server

Listing 16: ./code/echo-hello/server.py

```

1  #!/usr/bin/env python3
2  import socket
3  import threading
4

```

(continues on next page)

(continued from previous page)

```
5 # nc localhost 6006
6
7
8 def run_server():
9     sock = socket.socket(family=socket.AF_INET, type=socket.SOCK_STREAM)
10    sock.setsockopt(socket.SOL_SOCKET, socket.SO_REUSEADDR, 1)
11    sock.bind("", 6006)
12    # sock.setblocking(False) # It returns socket.BlockingIOError
13    sock.listen(2) # backlog is 2
14    while True:
15        client_sock, addr = sock.accept()
16        assert isinstance(client_sock, socket.socket)
17        assert isinstance(addr, tuple)
18        assert isinstance(addr[0], str)
19        assert isinstance(addr[1], int)
20        print("Connected from", addr) # Connected from ('127.0.0.1', 54266)
21        threading.Thread(target=handle_client, args=(client_sock,)).start()
22
23
24 def handle_client(sock: socket.socket):
25     while True:
26         data = sock.recv(1024)
27         if not data:
28             break
29         sock.sendall(data.decode("utf-8").upper().encode())
30     print("Disconnected from", sock.getpeername())
31     sock.close()
32
33
34 if __name__ == "__main__":
35     run_server()
```

To test the server, use `nc localhost 6006` or use the following client.

Client

Listing 17: ./code/echo-hello/client.py

```

1 def main():
2     sock = socket.socket(socket.AF_INET, socket.SOCK_STREAM)
3     sock.connect(("localhost", 6006))
4     for i in range(5):
5         sock.send("hello".encode())
6         b = sock.recv(1024)
7         print(b.decode())
8         time.sleep(0.5)

```

Server2

With `concurrent.futures.ThreadPoolExecutor`.

Listing 18: ./code/echo-hello/server2.py

```

1  #!/usr/bin/env python3
2  import socket
3  import threading
4  from concurrent.futures import ThreadPoolExecutor
5
6  # nc localhost 6006
7  pool = ThreadPoolExecutor(max_workers=3)
8
9
10 def run_server():
11     sock = socket.socket(family=socket.AF_INET, type=socket.SOCK_STREAM)
12     sock.setsockopt(socket.SOL_SOCKET, socket.SO_REUSEADDR, 1)
13     sock.bind("", 6006)
14     # sock.setblocking(False) # It returns socket.BlockingIOError
15     sock.listen(2) # backlog is 2
16     while True:
17         client_sock, addr = sock.accept()
18         assert isinstance(client_sock, socket.socket)
19         assert isinstance(addr, tuple)
20         assert isinstance(addr[0], str)
21         assert isinstance(addr[1], int)
22         print("Connected from", addr) # Connected from ('127.0.0.1', 54266)
23         pool.submit(handle_client, client_sock)
24
25
26 def handle_client(sock: socket.socket):
27     while True:
28         data = sock.recv(1024)
29         if not data:
30             break
31         sock.sendall(data.decode("utf-8").upper().encode())
32     print("Disconnected from", sock.getpeername())
33     sock.close()
34
35

```

(continues on next page)

(continued from previous page)

```
36 if __name__ == "__main__":  
37     run_server()
```

9.8.8 TODOs

- Beej's Guide to Network Programming Using Internet Sockets
<https://www.gta.ufrj.br/ensino/eel878/sockets/index.html>
- LWN.net Weekly Edition Archives
<https://lwn.net/Archives/>

10.1 Install

10.1.1 formatter

Install <https://github.com/google/google-java-format>

```
wget https://github.com/google/google-java-format/releases/download/v1.15.0/google-java-format-1.15.0-all-deps.jar
```

Create a script with filename `google-java-format`:

```
#!/usr/bin/env bash

java -jar /ceph-sh0/fangjun/download/google-java-format-1.15.0-all-deps.jar $@
```

`chmod +x google-java-format` and add the path to `PATH`.

10.1.2 JDK

Go to <https://www.oracle.com/java/technologies/downloads/#java17> and download

```
wget https://download.oracle.com/java/17/latest/jdk-17_linux-x64_bin.tar.gz
mkdir /ceph-fj/fangjun/software/
tar xvf jdk-17_linux-x64_bin.tar.gz -C /ceph-fj/fangjun/software
```

And then set the following environment variables:

```
export JAVA_HOME=/ceph-fj/fangjun/software/jdk-17.0.3
export PATH=$JAVA_HOME/bin:$JAVA_HOME
```

10.2 Hello world

Listing 1: Hello.java

```
// Usage 1:
// java Hello.java
// Usage 2:
// javac Hello.java
// java Hello
//
// Note:
// - "javac Hello.java" generates a file "Hello.class"
// - "java Hello" takes as input "Hello.class" and executes it
//
class Hello {
    public static void main(String[] args) {
        System.out.println("hello world");
    }
} // There is no ';' here
```

Listing 2: EqualTest.java

```
class EqualTest {
    public int i;

    public EqualTest(int a) {
        this.i = a;
    }

    public boolean equals(Object anObject) {
        if (this == anObject) {
            return true;
        }
        if (anObject instanceof EqualTest) {
            return this.i == ((EqualTest) anObject).i;
        }
        return false;
    }

    public static void main(String[] args) {
        EqualTest e1 = new EqualTest(10);
        EqualTest e2 = new EqualTest(10);

        System.out.println(e1 == e2); // false, compare the reference
        System.out.println(e1 != e2); // true
        System.out.println(e1.equals(e2)); // true, compare the contained value
    }
}
```

10.3 Reference

- <https://docs.oracle.com/javase/tutorial/>
- <https://docs.oracle.com/en/java/javase/17/docs/api/index.html>
- <https://github.com/openjdk/jdk.git>

Clone it and you can find the source code in `src/java.base/share/classes/java/lang/System.java` for `java.lang.System`.

JAVASCRIPT

11.1 Hello world

```
console.log('hello world')
console.log(eval('3 + 5'))
```

To write multi-line javascript, use shift + Enter for a new line.

```
(function(){
  "use strict";
  /* Start of your code */
  function greetMe(yourName) {
    alert('Hello ' + yourName);
  }

  greetMe('World');
  /* End of your code */
})();
```

It is case sensitive. Statements are separated by ;. Comments are the same as in C/C++.

11.1.1 array

Listing 1: ./code/hello_world/array.js

```
1 let a = [ 1, 2, 3 ];
2 function sum(arr) {
3   let s = 0;
4   for (let x of arr) {
5     s += x;
6   }
7   return s;
8 }
9 // Sum of the array [1,2,3] is 6
10 console.log('Sum of the array [' + a + '] is ' + sum(a));
11
12 function sum2(arr) {
13   let s = 0;
14   for (let i = 0; i != arr.length; ++i) {
```

(continues on next page)

(continued from previous page)

```
15     s += arr[i];
16   }
17   return s;
18 }
19 console.log(sum2(a)); // 6
```

Note that there are two ways to iterate an array:

- `for(let x of array)`
- `for(let i = 0; i != array.length; ++i) { ... }`

To run the above code, use:

```
node array.js
```

11.1.2 class

Listing 2: `./code/hello_world/class.js`

```
1 class Point {
2   constructor(x, y) {
3     this.x = x;
4     this.y = y;
5   }
6
7   distance() { return Math.sqrt(this.x * this.x + this.y * this.y); }
8 }
9
10 let p = new Point(1, 1);
11 console.log(p.distance()); // 1.4142135623730951
```

It defines a `Point` class with two fields `x`, `y`. `Point` has two methods: a constructor and a method `distance()`.

Note that class names are by convention capitalized.

11.2 node

Go to <https://nodejs.org/en/download/> to download pre-built binaries:

```
wget https://nodejs.org/dist/v16.15.1/node-v16.15.1-linux-x64.tar.xz
tar xvf node-v16.15.1-linux-x64.tar.xz
```

and then add `/path/to/node-v16.15.1-linux-x64/bin/` to `PATH`.

11.3 TODOs

1. This page https://developer.mozilla.org/en-US/docs/Learn/Getting_started_with_the_web/Installing_basic_software lists some tools to minify code:
 - WebPack: <https://webpack.js.org/>
 - Grunt: <https://gruntjs.com/>
 - Gulp: <https://gulpjs.com/>
2. Color picker tool: https://developer.mozilla.org/en-US/docs/Web/CSS/CSS_Colors/Color_picker_tool
3. Google font: <https://fonts.google.com/> and https://developers.google.com/fonts/docs/getting_started

12.1 Hello world

Listing 1: hello_world.html

```
<!DOCTYPE html>
<html>
  <head>
    <meta charset="utf-8">
    <title>Hello World</title>
  </head>
  <body>
    <p>Hello world</p>
  </body>
</html>
```

12.1.1 comments

```
<!-- this is a comment -->
```

12.1.2 images

```
</img>
</img>
</img>
```

12.1.3 ordered lists

```
<p> The following points </p>

<ol>
  <li> First </li>
  <li> Second </li>
</ol>
```

12.1.4 unordered lists

```
<p> The following points </p>

<ul>
  <li> foo </li>
  <li> bar </li>
</ul>
```

12.1.5 links

```
<a href="https://www.google.com">some text</a>
```

12.2 References

- Structuring the web with HTML
<https://developer.mozilla.org/en-US/docs/Learn/HTML>

13.1 Hello world

13.1.1 comment

```
/* this is a comment */
```

```
p { color: red; }
```

Then, in some html file, use:

```
<link href="abc/foo.css" rel="stylesheet">
```

13.1.2 Selector

- tag name or element name: e.g., `p` selects `<p>`; `h1` selects `<h1>`.
- ID: e.g., `#my-id` selects `` or `<p id="my-id">`
- class: e.g., `.my-class` selects `` and `<p class="my-class">`
- attribute: e.g., `img[src]` selects `` but not ``

See https://developer.mozilla.org/en-US/docs/Learn/Getting_started_with_the_web/CSS_basics#different_types_of_selectors and https://developer.mozilla.org/en-US/docs/Learn/CSS/Building_blocks/Selectors for more.

Example with multiple rules:

Listing 1: Example with multiple rules

```
p {  
  color: red;  
  width: 500px;  
  border: 1px solid black;  
}
```

Example with multiple selectors:

Listing 2: Example with multiple selectors

```
p, li, h1 { color: red; }
```

13.2 References

- CSS basics

https://developer.mozilla.org/en-US/docs/Learn/Getting_started_with_the_web/CSS_basics

14.1 GIL

PROTOCOL BUFFERS

15.1 Installation

15.1.1 C++

See <https://github.com/protocolbuffers/protobuf/blob/main/src/README.md>.

```
make protocol-buffers
cd protocol-buffers
wget https://github.com/protocolbuffers/protobuf/releases/download/v3.20.1/protobuf-all-
↪3.20.1.tar.gz
tar xvf protobuf-all-3.20.1.tar.gz
cd protobuf-all-3.20.1
./configure --prefix=$HOME/software/protobuf-3.20.1
make -j 20
make -j 10 check
make install 2>&1 | tee my-log.txt
cd $HOME/software/protobuf-3.20.1
tree . > tree-log.txt
```

```
$ export PKG_CONFIG_PATH=$HOME/software/protobuf-3.20.1:$PKG_CONFIG_PATH

$ pkg-config --cflags protobuf
-I/root/fangjun/software/protobuf-3.20.1/include

$ pkg-config --libs protobuf
-L/root/fangjun/software/protobuf-3.20.1/lib -lprotobuf

$ pkg-config --cflags --libs protobuf
-I/root/fangjun/software/protobuf-3.20.1/include -L/root/fangjun/software/protobuf-3.20.
↪1/lib -lprotobuf

$ pkg-config --libs-only-L protobuf
-L/root/fangjun/software/protobuf-3.20.1/lib

$ pkg-config --libs-only-l protobuf
-lprotobuf
```

```
$ export PATH=$HOME/software/protobuf-3.20.1/bin:$PATH
$ protoc --version
libprotoc 3.20.1
```

Listing 1: ./code/my-log.txt (Installation logs)

```
1 Making install in .
2 make[1]: Entering directory '/ceph-fj/fangjun/open-source-2/protocol-buffers/protobuf-3.
  ↳ 20.1'
3 make[2]: Entering directory '/ceph-fj/fangjun/open-source-2/protocol-buffers/protobuf-3.
  ↳ 20.1'
4 make[2]: Nothing to be done for 'install-exec-am'.
5 /bin/mkdir -p '/root/fangjun/software/protobuf-3.20.1/lib/pkgconfig'
6 /usr/bin/install -c -m 644 protobuf.pc protobuf-lite.pc '/root/fangjun/software/
  ↳ protobuf-3.20.1/lib/pkgconfig'
7 make[2]: Leaving directory '/ceph-fj/fangjun/open-source-2/protocol-buffers/protobuf-3.
  ↳ 20.1'
8 make[1]: Leaving directory '/ceph-fj/fangjun/open-source-2/protocol-buffers/protobuf-3.
  ↳ 20.1'
9 Making install in src
10 make[1]: Entering directory '/ceph-fj/fangjun/open-source-2/protocol-buffers/protobuf-3.
  ↳ 20.1/src'
11 make[2]: Entering directory '/ceph-fj/fangjun/open-source-2/protocol-buffers/protobuf-3.
  ↳ 20.1/src'
12 /bin/mkdir -p '/root/fangjun/software/protobuf-3.20.1/lib'
13 /bin/bash ../libtool --mode=install /usr/bin/install -c libprotobuf-lite.la
  ↳ libprotobuf.la libprotoc.la '/root/fangjun/software/protobuf-3.20.1/lib'
14 libtool: install: /usr/bin/install -c .libs/libprotobuf-lite.so.31.0.1 /root/fangjun/
  ↳ software/protobuf-3.20.1/lib/libprotobuf-lite.so.31.0.1
15 libtool: install: (cd /root/fangjun/software/protobuf-3.20.1/lib && { ln -s -f
  ↳ libprotobuf-lite.so.31.0.1 libprotobuf-lite.so.31 || { rm -f libprotobuf-lite.so.31 &&
  ↳ ln -s libprotobuf-lite.so.31.0.1 libprotobuf-lite.so.31; }; })
16 libtool: install: (cd /root/fangjun/software/protobuf-3.20.1/lib && { ln -s -f
  ↳ libprotobuf-lite.so.31.0.1 libprotobuf-lite.so || { rm -f libprotobuf-lite.so && ln -s
  ↳ libprotobuf-lite.so.31.0.1 libprotobuf-lite.so; }; })
17 libtool: install: /usr/bin/install -c .libs/libprotobuf-lite.lai /root/fangjun/software/
  ↳ protobuf-3.20.1/lib/libprotobuf-lite.la
18 libtool: install: /usr/bin/install -c .libs/libprotobuf.so.31.0.1 /root/fangjun/software/
  ↳ protobuf-3.20.1/lib/libprotobuf.so.31.0.1
19 libtool: install: (cd /root/fangjun/software/protobuf-3.20.1/lib && { ln -s -f
  ↳ libprotobuf.so.31.0.1 libprotobuf.so.31 || { rm -f libprotobuf.so.31 && ln -s
  ↳ libprotobuf.so.31.0.1 libprotobuf.so.31; }; })
20 libtool: install: (cd /root/fangjun/software/protobuf-3.20.1/lib && { ln -s -f
  ↳ libprotobuf.so.31.0.1 libprotobuf.so || { rm -f libprotobuf.so && ln -s libprotobuf.so.
  ↳ 31.0.1 libprotobuf.so; }; })
21 libtool: install: /usr/bin/install -c .libs/libprotobuf.lai /root/fangjun/software/
  ↳ protobuf-3.20.1/lib/libprotobuf.la
22 libtool: warning: relinking 'libprotoc.la'
23 libtool: install: (cd /root/fangjun/open-source-2/protocol-buffers/protobuf-3.20.1/src; /
  ↳ bin/bash "/root/fangjun/open-source-2/protocol-buffers/protobuf-3.20.1/libtool" --
  ↳ silent --tag CXX --mode=relink g++ -pthread -DHAVE_PTHREAD=1 -DHAVE_ZLIB=1 -Wall -Wno-
  ↳ sign-compare -O2 -g -std=c++11 -DDEBUG -version-info 31:1:0 -export-dynamic -no-
  ↳ undefined -Wl,--version-script=../libprotoc.map -o libprotoc.la -rpath /root/fangjun/
  ↳ software/protobuf-3.20.1/lib google/protobuf/compiler/code_generator.lo google/
  ↳ protobuf/compiler/command_line_interface.lo google/protobuf/compiler/cpp/cpp_enum.lo
  ↳ google/protobuf/compiler/cpp/cpp_enum_field.lo google/protobuf/compiler/cpp/cpp_
  ↳ extension.lo google/protobuf/compiler/cpp/cpp_field.lo google/protobuf/compiler/cpp/
  ↳ cpp_file.lo google/protobuf/compiler/cpp/cpp_generator.lo google/protobuf/compiler/cpp/
  ↳ cpp_helpers.lo google/protobuf/compiler/cpp/cpp_map_field.lo google/protobuf/compiler/
  ↳ cpp/cpp_message.lo google/protobuf/compiler/cpp/cpp_message_field.lo google/protobuf/
  ↳ (continues on next page)
```

(continued from previous page)

```

24 libtool: install: /usr/bin/install -c .libs/libprotoc.so.31.0.1T /root/fangjun/software/
↳protobuf-3.20.1/lib/libprotoc.so.31.0.1
25 libtool: install: (cd /root/fangjun/software/protobuf-3.20.1/lib && { ln -s -f libprotoc.
↳so.31.0.1 libprotoc.so.31 || { rm -f libprotoc.so.31 && ln -s libprotoc.so.31.0.1
↳libprotoc.so.31; }; })
26 libtool: install: (cd /root/fangjun/software/protobuf-3.20.1/lib && { ln -s -f libprotoc.
↳so.31.0.1 libprotoc.so || { rm -f libprotoc.so && ln -s libprotoc.so.31.0.1 libprotoc.
↳so; }; })
27 libtool: install: /usr/bin/install -c .libs/libprotoc.lai /root/fangjun/software/
↳protobuf-3.20.1/lib/libprotoc.la
28 libtool: install: /usr/bin/install -c .libs/libprotobuf-lite.a /root/fangjun/software/
↳protobuf-3.20.1/lib/libprotobuf-lite.a
29 libtool: install: chmod 644 /root/fangjun/software/protobuf-3.20.1/lib/libprotobuf-lite.a
30 libtool: install: ranlib /root/fangjun/software/protobuf-3.20.1/lib/libprotobuf-lite.a
31 libtool: install: /usr/bin/install -c .libs/libprotobuf.a /root/fangjun/software/
↳protobuf-3.20.1/lib/libprotobuf.a
32 libtool: install: chmod 644 /root/fangjun/software/protobuf-3.20.1/lib/libprotobuf.a
33 libtool: install: ranlib /root/fangjun/software/protobuf-3.20.1/lib/libprotobuf.a
34 libtool: install: /usr/bin/install -c .libs/libprotoc.a /root/fangjun/software/protobuf-
↳3.20.1/lib/libprotoc.a
35 libtool: install: chmod 644 /root/fangjun/software/protobuf-3.20.1/lib/libprotoc.a
36 libtool: install: ranlib /root/fangjun/software/protobuf-3.20.1/lib/libprotoc.a
37 libtool: finish: PATH="/ceph-fj/fangjun/software/py38/bin:/ceph-fj/fangjun/software/jdk-
↳17.0.3/bin:/ceph-fj/fangjun/software/cmake/bin:/ceph-fj/fangjun/software/texlive2021-
↳20210325/bin/x86_64-linux:/ceph-sh1/fangjun/software/cuda-10.2.89/bin:/ceph-fj/fangjun/
↳software/bin:/ceph-sh1/fangjun/software/bin:/ceph-sh1/fangjun/software/nvim-linux64/
↳bin:/ceph-fj/fangjun/software/py38/bin:/ceph-fj/fangjun/software/cmake/bin:/ceph-fj/
↳fangjun/software/texlive2021-20210325/bin/x86_64-linux:/ceph-sh1/fangjun/software/cuda-
↳10.2.89/bin:/ceph-sh1/fangjun/software/nvim-linux64/bin:/usr/local/sbin:/usr/local/
↳bin:/usr/sbin:/usr/bin:/sbin:/bin:/usr/games:/sbin" ldconfig -n /root/fangjun/software/
↳protobuf-3.20.1/lib
38 -----
39 Libraries have been installed in:
40   /root/fangjun/software/protobuf-3.20.1/lib
41
42 If you ever happen to want to link against installed libraries
43 in a given directory, LIBDIR, you must either use libtool, and
44 specify the full pathname of the library, or use the '-LLIBDIR'
45 flag during linking and do at least one of the following:
46   - add LIBDIR to the 'LD_LIBRARY_PATH' environment variable
47     during execution
48   - add LIBDIR to the 'LD_RUN_PATH' environment variable
49     during linking
50   - use the '-Wl,-rpath -Wl,LIBDIR' linker flag
51   - have your system administrator add LIBDIR to '/etc/ld.so.conf'
52
53 See any operating system documentation about shared libraries for
54 more information, such as the ld(1) and ld.so(8) manual pages.
55 -----
56 /bin/mkdir -p '/root/fangjun/software/protobuf-3.20.1/bin'
57 /bin/bash ../libtool --mode=install /usr/bin/install -c protoc '/root/fangjun/
↳software/protobuf-3.20.1/bin'

```

(continues on next page)

(continued from previous page)

```

58 libtool: install: /usr/bin/install -c .libs/protoc /root/fangjun/software/protobuf-3.20.
    ↪ 1/bin/protoc
59 /bin/mkdir -p '/root/fangjun/software/protobuf-3.20.1/include'
60 /bin/mkdir -p '/root/fangjun/software/protobuf-3.20.1/include/google/protobuf'
61 /usr/bin/install -c -m 644 google/protobuf/any.proto google/protobuf/api.proto google/
    ↪ protobuf/descriptor.proto google/protobuf/duration.proto google/protobuf/empty.proto
    ↪ google/protobuf/field_mask.proto google/protobuf/source_context.proto google/protobuf/
    ↪ struct.proto google/protobuf/timestamp.proto google/protobuf/type.proto google/
    ↪ protobuf/wrappers.proto '/root/fangjun/software/protobuf-3.20.1/include/google/protobuf
    ↪ '
62 /bin/mkdir -p '/root/fangjun/software/protobuf-3.20.1/include/google/protobuf/compiler'
63 /usr/bin/install -c -m 644 google/protobuf/compiler/plugin.proto '/root/fangjun/
    ↪ software/protobuf-3.20.1/include/google/protobuf/compiler'
64 /bin/mkdir -p '/root/fangjun/software/protobuf-3.20.1/include'
65 /bin/mkdir -p '/root/fangjun/software/protobuf-3.20.1/include/google/protobuf'
66 /usr/bin/install -c -m 644 google/protobuf/any.h google/protobuf/any.pb.h google/
    ↪ protobuf/api.pb.h google/protobuf/arena.h google/protobuf/arena_impl.h google/protobuf/
    ↪ arenastring.h google/protobuf/arenaz_sampler.h google/protobuf/descriptor.h google/
    ↪ protobuf/descriptor.pb.h google/protobuf/descriptor_database.h google/protobuf/
    ↪ duration.pb.h google/protobuf/dynamic_message.h google/protobuf/empty.pb.h google/
    ↪ protobuf/explicitly_constructed.h google/protobuf/extension_set.h google/protobuf/
    ↪ extension_set_inl.h google/protobuf/field_access_listener.h google/protobuf/field_mask.
    ↪ pb.h google/protobuf/generated_enum_reflection.h google/protobuf/generated_enum_util.h
    ↪ google/protobuf/generated_message_bases.h google/protobuf/generated_message_reflection.
    ↪ h google/protobuf/generated_message_tctable_decl.h google/protobuf/generated_message_
    ↪ tctable_impl.h google/protobuf/generated_message_util.h google/protobuf/has_bits.h
    ↪ google/protobuf/implicit_weak_message.h google/protobuf/inlined_string_field.h google/
    ↪ protobuf/map.h google/protobuf/map_entry.h google/protobuf/map_entry_lite.h google/
    ↪ protobuf/map_field.h google/protobuf/map_field_inl.h google/protobuf/map_field_lite.h
    ↪ google/protobuf/map_type_handler.h google/protobuf/message.h google/protobuf/message_
    ↪ lite.h google/protobuf/metadata.h google/protobuf/metadata_lite.h google/protobuf/
    ↪ parse_context.h '/root/fangjun/software/protobuf-3.20.1/include/google/protobuf'
67 /bin/mkdir -p '/root/fangjun/software/protobuf-3.20.1/include/google/protobuf/compiler/
    ↪ js'
68 /usr/bin/install -c -m 644 google/protobuf/compiler/js/js_generator.h '/root/fangjun/
    ↪ software/protobuf-3.20.1/include/google/protobuf/compiler/js'
69 /bin/mkdir -p '/root/fangjun/software/protobuf-3.20.1/include/google/protobuf/compiler/
    ↪ cpp'
70 /usr/bin/install -c -m 644 google/protobuf/compiler/cpp/cpp_file.h google/protobuf/
    ↪ compiler/cpp/cpp_generator.h google/protobuf/compiler/cpp/cpp_helpers.h google/
    ↪ protobuf/compiler/cpp/cpp_names.h '/root/fangjun/software/protobuf-3.20.1/include/
    ↪ google/protobuf/compiler/cpp'
71 /bin/mkdir -p '/root/fangjun/software/protobuf-3.20.1/include/google/protobuf/compiler/
    ↪ ruby'
72 /usr/bin/install -c -m 644 google/protobuf/compiler/ruby/ruby_generator.h '/root/
    ↪ fangjun/software/protobuf-3.20.1/include/google/protobuf/compiler/ruby'
73 /bin/mkdir -p '/root/fangjun/software/protobuf-3.20.1/include/google/protobuf/compiler/
    ↪ python'
74 /usr/bin/install -c -m 644 google/protobuf/compiler/python/python_generator.h google/
    ↪ protobuf/compiler/python/python_pyi_generator.h '/root/fangjun/software/protobuf-3.20.
    ↪ 1/include/google/protobuf/compiler/python'
75 /bin/mkdir -p '/root/fangjun/software/protobuf-3.20.1/include/google/protobuf/util'

```

(continues on next page)

(continued from previous page)

```

76 /usr/bin/install -c -m 644 google/protobuf/util/delimited_message_util.h google/
↳ protobuf/util/field_comparator.h google/protobuf/util/field_mask_util.h google/
↳ protobuf/util/json_util.h google/protobuf/util/message_differencer.h google/protobuf/
↳ util/time_util.h google/protobuf/util/type_resolver.h google/protobuf/util/type_
77 ↳ resolver_util.h '/root/fangjun/software/protobuf-3.20.1/include/google/protobuf/util'
78 /usr/bin/install -c -m 644 google/protobuf/io/coded_stream.h google/protobuf/io/gzip_
↳ stream.h google/protobuf/io/io_win32.h google/protobuf/io/printer.h google/protobuf/io/
↳ strtod.h google/protobuf/io/tokenizer.h google/protobuf/io/zero_copy_stream.h google/
↳ protobuf/io/zero_copy_stream_impl.h google/protobuf/io/zero_copy_stream_impl_lite.h '/'
79 ↳ root/fangjun/software/protobuf-3.20.1/include/google/protobuf/io'
↳ /bin/mkdir -p '/root/fangjun/software/protobuf-3.20.1/include/google/protobuf/compiler/
↳ csharp'
80 /usr/bin/install -c -m 644 google/protobuf/compiler/csharp/csharp_doc_comment.h google/
↳ protobuf/compiler/csharp/csharp_generator.h google/protobuf/compiler/csharp/csharp_
↳ names.h google/protobuf/compiler/csharp/csharp_options.h '/root/fangjun/software/
↳ protobuf-3.20.1/include/google/protobuf/compiler/csharp'
81 ↳ /bin/mkdir -p '/root/fangjun/software/protobuf-3.20.1/include/google/protobuf/compiler/
↳ php'
82 /usr/bin/install -c -m 644 google/protobuf/compiler/php/php_generator.h '/root/fangjun/
↳ software/protobuf-3.20.1/include/google/protobuf/compiler/php'
83 ↳ /bin/mkdir -p '/root/fangjun/software/protobuf-3.20.1/include/google/protobuf/stubs'
84 /usr/bin/install -c -m 644 google/protobuf/stubs/bytestream.h google/protobuf/stubs/
↳ callback.h google/protobuf/stubs/casts.h google/protobuf/stubs/common.h google/
↳ protobuf/stubs/hash.h google/protobuf/stubs/logging.h google/protobuf/stubs/macros.h
↳ google/protobuf/stubs/map_util.h google/protobuf/stubs/mutex.h google/protobuf/stubs/
↳ once.h google/protobuf/stubs/platform_macros.h google/protobuf/stubs/port.h google/
↳ protobuf/stubs/status.h google/protobuf/stubs/stl_util.h google/protobuf/stubs/
↳ stringpiece.h google/protobuf/stubs/strutil.h google/protobuf/stubs/template_util.h '/'
85 ↳ root/fangjun/software/protobuf-3.20.1/include/google/protobuf/stubs'
↳ /bin/mkdir -p '/root/fangjun/software/protobuf-3.20.1/include/google/protobuf/compiler/
↳ java'
86 /usr/bin/install -c -m 644 google/protobuf/compiler/java/java_generator.h google/
↳ protobuf/compiler/java/java_kotlin_generator.h google/protobuf/compiler/java/java_
↳ names.h '/root/fangjun/software/protobuf-3.20.1/include/google/protobuf/compiler/java'
87 ↳ /bin/mkdir -p '/root/fangjun/software/protobuf-3.20.1/include/google/protobuf'
88 /usr/bin/install -c -m 644 google/protobuf/port.h google/protobuf/port_def.inc google/
↳ protobuf/port_undef.inc google/protobuf/reflection.h google/protobuf/reflection_ops.h
↳ google/protobuf/repeated_field.h google/protobuf/repeated_ptr_field.h google/protobuf/
↳ service.h google/protobuf/source_context.pb.h google/protobuf/struct.pb.h google/
↳ protobuf/text_format.h google/protobuf/timestamp.pb.h google/protobuf/type.pb.h google/
↳ protobuf/unknown_field_set.h google/protobuf/wire_format.h google/protobuf/wire_format_
↳ lite.h google/protobuf/wrappers.pb.h '/root/fangjun/software/protobuf-3.20.1/include/
↳ google/protobuf'
89 ↳ /bin/mkdir -p '/root/fangjun/software/protobuf-3.20.1/include/google/protobuf/compiler/
↳ objectivec'
90 /usr/bin/install -c -m 644 google/protobuf/compiler/objectivec/objectivec_generator.h
↳ google/protobuf/compiler/objectivec/objectivec_helpers.h '/root/fangjun/software/
↳ protobuf-3.20.1/include/google/protobuf/compiler/objectivec'
91 ↳ /bin/mkdir -p '/root/fangjun/software/protobuf-3.20.1/include/google/protobuf/compiler'
92 /usr/bin/install -c -m 644 google/protobuf/compiler/code_generator.h google/protobuf/
↳ compiler/command_line_interface.h google/protobuf/compiler/importer.h google/protobuf/
↳ compiler/parser.h google/protobuf/compiler/plugin.h google/protobuf/compiler/plugin.pb
↳ h '/root/fangjun/software/protobuf-3.20.1/include/google/protobuf/compiler'

```

(continued from previous page)

```

93 make[2]: Leaving directory '/ceph-fj/fangjun/open-source-2/protocol-buffers/protobuf-3.
    ↳20.1/src'
94 make[1]: Leaving directory '/ceph-fj/fangjun/open-source-2/protocol-buffers/protobuf-3.
    ↳20.1/src'

```

Listing 2: ./code/tree-log.txt (Installed files)

```

1  .
2  |-- bin
3  |   |-- protoc
4  |-- include
5  |   |-- google
6  |       |-- protobuf
7  |           |-- any.h
8  |           |-- any.pb.h
9  |           |-- any.proto
10 |           |-- api.pb.h
11 |           |-- api.proto
12 |           |-- arena.h
13 |           |-- arena_impl.h
14 |           |-- arenastring.h
15 |           |-- arenaz_sampler.h
16 |           |-- compiler
17 |               |-- code_generator.h
18 |               |-- command_line_interface.h
19 |               |-- cpp
20 |                   |-- cpp_file.h
21 |                   |-- cpp_generator.h
22 |                   |-- cpp_helpers.h
23 |                   |-- cpp_names.h
24 |               |-- csharp
25 |                   |-- csharp_doc_comment.h
26 |                   |-- csharp_generator.h
27 |                   |-- csharp_names.h
28 |                   |-- csharp_options.h
29 |               |-- importer.h
30 |               |-- java
31 |                   |-- java_generator.h
32 |                   |-- java_kotlin_generator.h
33 |                   |-- java_names.h
34 |               |-- js
35 |                   |-- js_generator.h
36 |               |-- objectivec
37 |                   |-- objectivec_generator.h
38 |                   |-- objectivec_helpers.h
39 |               |-- parser.h
40 |               |-- php
41 |                   |-- php_generator.h
42 |               |-- plugin.h
43 |               |-- plugin.pb.h
44 |               |-- plugin.proto
45 |               |-- python

```

(continues on next page)

(continued from previous page)

```

46 |         | | | -- python_generator.h
47 |         | | | -- python_pyi_generator.h
48 |         | | | -- ruby
49 |         | | | -- ruby_generator.h
50 |         | -- descriptor.h
51 |         | -- descriptor.pb.h
52 |         | -- descriptor.proto
53 |         | -- descriptor_database.h
54 |         | -- duration.pb.h
55 |         | -- duration.proto
56 |         | -- dynamic_message.h
57 |         | -- empty.pb.h
58 |         | -- empty.proto
59 |         | -- explicitly_constructed.h
60 |         | -- extension_set.h
61 |         | -- extension_set_inl.h
62 |         | -- field_access_listener.h
63 |         | -- field_mask.pb.h
64 |         | -- field_mask.proto
65 |         | -- generated_enum_reflection.h
66 |         | -- generated_enum_util.h
67 |         | -- generated_message_bases.h
68 |         | -- generated_message_reflection.h
69 |         | -- generated_message_tctable_decl.h
70 |         | -- generated_message_tctable_impl.h
71 |         | -- generated_message_util.h
72 |         | -- has_bits.h
73 |         | -- implicit_weak_message.h
74 |         | -- inlined_string_field.h
75 |         | -- io
76 |         | | -- coded_stream.h
77 |         | | -- gzip_stream.h
78 |         | | -- io_win32.h
79 |         | | -- printer.h
80 |         | | -- strtod.h
81 |         | | -- tokenizer.h
82 |         | | -- zero_copy_stream.h
83 |         | | -- zero_copy_stream_impl.h
84 |         | | -- zero_copy_stream_impl_lite.h
85 |         | -- map.h
86 |         | -- map_entry.h
87 |         | -- map_entry_lite.h
88 |         | -- map_field.h
89 |         | -- map_field_inl.h
90 |         | -- map_field_lite.h
91 |         | -- map_type_handler.h
92 |         | -- message.h
93 |         | -- message_lite.h
94 |         | -- metadata.h
95 |         | -- metadata_lite.h
96 |         | -- parse_context.h
97 |         | -- port.h

```

(continues on next page)

(continued from previous page)

```

98 |         |-- port_def.inc
99 |         |-- port_undef.inc
100 |        |-- reflection.h
101 |        |-- reflection_ops.h
102 |        |-- repeated_field.h
103 |        |-- repeated_ptr_field.h
104 |        |-- service.h
105 |        |-- source_context.pb.h
106 |        |-- source_context.proto
107 |        |-- struct.pb.h
108 |        |-- struct.proto
109 |        |-- stubs
110 |        |   |-- bytestream.h
111 |        |   |-- callback.h
112 |        |   |-- casts.h
113 |        |   |-- common.h
114 |        |   |-- hash.h
115 |        |   |-- logging.h
116 |        |   |-- macros.h
117 |        |   |-- map_util.h
118 |        |   |-- mutex.h
119 |        |   |-- once.h
120 |        |   |-- platform_macros.h
121 |        |   |-- port.h
122 |        |   |-- status.h
123 |        |   |-- stl_util.h
124 |        |   |-- stringpiece.h
125 |        |   |-- strutil.h
126 |        |   `-- template_util.h
127 |        |-- text_format.h
128 |        |-- timestamp.pb.h
129 |        |-- timestamp.proto
130 |        |-- type.pb.h
131 |        |-- type.proto
132 |        |-- unknown_field_set.h
133 |        |-- util
134 |        |   |-- delimited_message_util.h
135 |        |   |-- field_comparator.h
136 |        |   |-- field_mask_util.h
137 |        |   |-- json_util.h
138 |        |   |-- message_differencer.h
139 |        |   |-- time_util.h
140 |        |   |-- type_resolver.h
141 |        |   `-- type_resolver_util.h
142 |        |-- wire_format.h
143 |        |-- wire_format_lite.h
144 |        |-- wrappers.pb.h
145 |        `-- wrappers.proto
146 |-- lib
147 |   |-- libprotobuf-lite.a
148 |   |-- libprotobuf-lite.la
149 |   |-- libprotobuf-lite.so -> libprotobuf-lite.so.31.0.1

```

(continues on next page)

(continued from previous page)

```

150 | |-- libprotobuf-lite.so.31 -> libprotobuf-lite.so.31.0.1
151 | |-- libprotobuf-lite.so.31.0.1
152 | |-- libprotobuf.a
153 | |-- libprotobuf.la
154 | |-- libprotobuf.so -> libprotobuf.so.31.0.1
155 | |-- libprotobuf.so.31 -> libprotobuf.so.31.0.1
156 | |-- libprotobuf.so.31.0.1
157 | |-- libprotoc.a
158 | |-- libprotoc.la
159 | |-- libprotoc.so -> libprotoc.so.31.0.1
160 | |-- libprotoc.so.31 -> libprotoc.so.31.0.1
161 | |-- libprotoc.so.31.0.1
162 | `-- pkgconfig
163 |     |-- protobuf-lite.pc
164 |     `-- protobuf.pc
165 |-- tree-log.txt
166
167 18 directories, 146 files

```

15.1.2 Install with cmake

```

make protocol-buffers
cd protocol-buffers
wget https://github.com/protocolbuffers/protobuf/releases/download/v3.20.1/protobuf-all-
↪3.20.1.tar.gz
tar xvf protobuf-all-3.20.1.tar.gz
cd protobuf-all-3.20.1
mkdir my-build
cd my-build
cmake -Dprotobuf_BUILD_SHARED_LIBS=ON -DCMAKE_INSTALL_PREFIX=/ceph-fj/fangjun/software/
↪protobuf-3.20.1-cmake/ ../cmake 2>&1 | tee cmake-configure-shared-lib.log
make -j10 2>&1 | tee make-shared.log
make install 2>&1 | tee make-shared-install.log

cd $HOME/software/protobuf-3.20.1-cmake
tree . > tree-cmake-log.txt

```

15.2 Hello

15.2.1 hello.proto

See

- <https://developers.google.com/protocol-buffers/docs/cpptutorial>
- <https://developers.google.com/protocol-buffers/docs/pythontutorial>

Listing 3: ./code/hello.proto

```
1 syntax = "proto2";
2
3 package tutorial;
4
5 // available types:
6 // bool, int32, float, double, string
7 message Person {
8     optional string name = 1;
9     optional int32 id = 2;
10    optional string email = 3;
11
12    enum PhoneType {
13        MOBILE = 0;
14        HOME = 1;
15        WORK = 2;
16    }
17
18    message PhoneNumber {
19        optional string number = 1;
20        optional PhoneType type = 2 [ default = HOME ];
21    }
22
23    repeated PhoneNumber phones = 4;
24 }
25
26 message AddressBook { repeated Person people = 1; }
```

15.2.2 makefile

Listing 4: ./code/Makefile

```

1 .PHONY: all clean
2
3 all: hello.pb.cc hello.pb.h hello_pb2.py
4
5 hello.pb.cc hello.pb.h: hello.proto
6     protoc -I=./ --cpp_out=./ ./hello.proto
7
8 hello_pb2.py: hello.proto
9     protoc -I=./ --python_out=./ ./hello.proto
10
11 clean:
12     $(RM) hello.pb.cc hello.pb.h hello_pb2.py

```

15.2.3 hello.pb.h

Listing 5: ./code/hello.pb.h

```

1  // Generated by the protocol buffer compiler.  DO NOT EDIT!
2  // source: hello.proto
3
4  #ifndef GOOGLE_PROTOBUF_INCLUDED_hello_2eproto
5  #define GOOGLE_PROTOBUF_INCLUDED_hello_2eproto
6
7  #include <limits>
8  #include <string>
9
10 #include <google/protobuf/port_def.inc>
11 #if PROTOBUF_VERSION < 3020000
12 #error This file was generated by a newer version of protoc which is
13 #error incompatible with your Protocol Buffer headers. Please update
14 #error your headers.
15 #endif
16 #if 3020001 < PROTOBUF_MIN_PROTOC_VERSION
17 #error This file was generated by an older version of protoc which is
18 #error incompatible with your Protocol Buffer headers. Please
19 #error regenerate this file with a newer version of protoc.
20 #endif
21
22 #include <google/protobuf/port_undef.inc>
23 #include <google/protobuf/io/coded_stream.h>
24 #include <google/protobuf/arena.h>
25 #include <google/protobuf/arenastring.h>
26 #include <google/protobuf/generated_message_util.h>
27 #include <google/protobuf/metadata_lite.h>
28 #include <google/protobuf/generated_message_reflection.h>
29 #include <google/protobuf/message.h>
30 #include <google/protobuf/repeated_field.h> // IWYU pragma: export
31 #include <google/protobuf/extension_set.h> // IWYU pragma: export
32 #include <google/protobuf/generated_enum_reflection.h>

```

(continues on next page)

(continued from previous page)

```

33 #include <google/protobuf/unknown_field_set.h>
34 // @@protoc_insertion_point(includes)
35 #include <google/protobuf/port_def.inc>
36 #define PROTOBUF_INTERNAL_EXPORT_hello_2eproto
37 PROTOBUF_NAMESPACE_OPEN
38 namespace internal {
39 class AnyMetadata;
40 } // namespace internal
41 PROTOBUF_NAMESPACE_CLOSE
42
43 // Internal implementation detail -- do not use these members.
44 struct TableStruct_hello_2eproto {
45     static const uint32_t offsets[];
46 };
47 extern const ::PROTOBUF_NAMESPACE_ID::internal::DescriptorTable descriptor_table_hello_
48 ↪ 2eproto;
49 namespace tutorial {
50 class AddressBook;
51 struct AddressBookDefaultTypeInternal;
52 extern AddressBookDefaultTypeInternal _AddressBook_default_instance_;
53 class Person;
54 struct PersonDefaultTypeInternal;
55 extern PersonDefaultTypeInternal _Person_default_instance_;
56 class Person_PhoneNumber;
57 struct Person_PhoneNumberDefaultTypeInternal;
58 extern Person_PhoneNumberDefaultTypeInternal _Person_PhoneNumber_default_instance_;
59 } // namespace tutorial
60 PROTOBUF_NAMESPACE_OPEN
61 template<> ::tutorial::AddressBook* Arena::CreateMaybeMessage<::tutorial::AddressBook>
62 ↪ (Arena*);
63 template<> ::tutorial::Person* Arena::CreateMaybeMessage<::tutorial::Person>(Arena*);
64 template<> ::tutorial::Person_PhoneNumber* Arena::CreateMaybeMessage<::tutorial::Person_
65 ↪ PhoneNumber>(Arena*);
66 PROTOBUF_NAMESPACE_CLOSE
67 namespace tutorial {
68
69 enum Person_PhoneType : int {
70     Person_PhoneType_MOBILE = 0,
71     Person_PhoneType_HOME = 1,
72     Person_PhoneType_WORK = 2
73 };
74 bool Person_PhoneType_IsValid(int value);
75 constexpr Person_PhoneType Person_PhoneType_PhoneType_MIN = Person_PhoneType_MOBILE;
76 constexpr Person_PhoneType Person_PhoneType_PhoneType_MAX = Person_PhoneType_WORK;
77 constexpr int Person_PhoneType_PhoneType_ARRAYSIZE = Person_PhoneType_PhoneType_MAX + 1;
78
79 const ::PROTOBUF_NAMESPACE_ID::EnumDescriptor* Person_PhoneType_descriptor();
80 template<typename T>
81 inline const std::string& Person_PhoneType_Name(T enum_t_value) {
82     static_assert(::std::is_same<T, Person_PhoneType>::value ||
83         ::std::is_integral<T>::value,
84         "Incorrect type passed to function Person_PhoneType_Name.");

```

(continues on next page)

(continued from previous page)

```

82  return ::PROTOBUF_NAMESPACE_ID::internal::NameOfEnum(
83      Person_PhoneType_descriptor(), enum_t_value);
84  }
85  inline bool Person_PhoneType_Parse(
86      ::PROTOBUF_NAMESPACE_ID::ConstStringParam name, Person_PhoneType* value) {
87      return ::PROTOBUF_NAMESPACE_ID::internal::ParseNamedEnum<Person_PhoneType>(
88          Person_PhoneType_descriptor(), name, value);
89  }
90  // =====
91
92  class Person_PhoneNumber final :
93      public ::PROTOBUF_NAMESPACE_ID::Message /* @@protoc_insertion_point(class_
94      ↪ definition:tutorial.Person.PhoneNumber) */ {
95  public:
96      inline Person_PhoneNumber() : Person_PhoneNumber(nullptr) {}
97      ~Person_PhoneNumber() override;
98      explicit PROTOBUF_CONSTEXPR Person_PhoneNumber(::PROTOBUF_NAMESPACE_
99      ↪ ID::internal::ConstantInitialized);
100
101      Person_PhoneNumber(const Person_PhoneNumber& from);
102      Person_PhoneNumber(Person_PhoneNumber&& from) noexcept
103          : Person_PhoneNumber() {
104          *this = ::std::move(from);
105      }
106
107      inline Person_PhoneNumber& operator=(const Person_PhoneNumber& from) {
108          CopyFrom(from);
109          return *this;
110      }
111
112      inline Person_PhoneNumber& operator=(Person_PhoneNumber&& from) noexcept {
113          if (this == &from) return *this;
114          if (GetOwningArena() == from.GetOwningArena()
115              #ifdef PROTOBUF_FORCE_COPY_IN_MOVE
116                  && GetOwningArena() != nullptr
117              #endif // !PROTOBUF_FORCE_COPY_IN_MOVE
118          ) {
119              InternalSwap(&from);
120          } else {
121              CopyFrom(from);
122          }
123          return *this;
124      }
125
126      inline const ::PROTOBUF_NAMESPACE_ID::UnknownFieldSet& unknown_fields() const {
127          return _internal_metadata_.unknown_fields<::PROTOBUF_NAMESPACE_ID::UnknownFieldSet>
128          ↪ (::PROTOBUF_NAMESPACE_ID::UnknownFieldSet::default_instance);
129      }
130
131      inline ::PROTOBUF_NAMESPACE_ID::UnknownFieldSet* mutable_unknown_fields() {
132          return _internal_metadata_.mutable_unknown_fields<::PROTOBUF_NAMESPACE_
133          ↪ ID::UnknownFieldSet>();
134      }

```

(continues on next page)

(continued from previous page)

```

130 static const ::PROTOBUF_NAMESPACE_ID::Descriptor* descriptor() {
131     return GetDescriptor();
132 }
133 static const ::PROTOBUF_NAMESPACE_ID::Descriptor* GetDescriptor() {
134     return default_instance().GetMetadata().descriptor;
135 }
136 static const ::PROTOBUF_NAMESPACE_ID::Reflection* GetReflection() {
137     return default_instance().GetMetadata().reflection;
138 }
139 static const Person_PhoneNumber& default_instance() {
140     return *internal_default_instance();
141 }
142 static inline const Person_PhoneNumber* internal_default_instance() {
143     return reinterpret_cast<const Person_PhoneNumber*>(
144         &_Person_PhoneNumber_default_instance_);
145 }
146 static constexpr int kIndexInFileMessages =
147     0;
148
149 friend void swap(Person_PhoneNumber& a, Person_PhoneNumber& b) {
150     a.Swap(&b);
151 }
152 inline void Swap(Person_PhoneNumber* other) {
153     if (other == this) return;
154 #ifdef PROTOBUF_FORCE_COPY_IN_SWAP
155     if (GetOwningArena() != nullptr &&
156         GetOwningArena() == other->GetOwningArena()) {
157     #else // PROTOBUF_FORCE_COPY_IN_SWAP
158     if (GetOwningArena() == other->GetOwningArena()) {
159 #endif // !PROTOBUF_FORCE_COPY_IN_SWAP
160         InternalSwap(other);
161     } else {
162         ::PROTOBUF_NAMESPACE_ID::internal::GenericSwap(this, other);
163     }
164 }
165 void UnsafeArenaSwap(Person_PhoneNumber* other) {
166     if (other == this) return;
167     GOOGLE_DCHECK(GetOwningArena() == other->GetOwningArena());
168     InternalSwap(other);
169 }
170
171 // implements Message -----
172
173 Person_PhoneNumber* New(::PROTOBUF_NAMESPACE_ID::Arena* arena = nullptr) const final {
174     return CreateMaybeMessage<Person_PhoneNumber>(arena);
175 }
176 using ::PROTOBUF_NAMESPACE_ID::Message::CopyFrom;
177 void CopyFrom(const Person_PhoneNumber& from);
178 using ::PROTOBUF_NAMESPACE_ID::Message::MergeFrom;
179 void MergeFrom(const Person_PhoneNumber& from);
180 private:
181 static void MergeImpl(::PROTOBUF_NAMESPACE_ID::Message* to, const ::PROTOBUF_NAMESPACE_
↪ ID::Message& from);

```

(continues on next page)

(continued from previous page)

```

182 public:
183   PROTOBUF_ATTRIBUTE_REINITIALIZES void Clear() final;
184   bool IsInitialized() const final;
185
186   size_t ByteSizeLong() const final;
187   const char* _InternalParse(const char* ptr, ::PROTOBUF_NAMESPACE_
↪ ID::internal::ParseContext* ctx) final;
188   uint8_t* _InternalSerialize(
189     uint8_t* target, ::PROTOBUF_NAMESPACE_ID::io::EpsCopyOutputStream* stream) const_
↪ final;
190   int GetCachedSize() const final { return _cached_size_.Get(); }
191
192 private:
193   void SharedCtor();
194   void SharedDtor();
195   void SetCachedSize(int size) const final;
196   void InternalSwap(Person_PhoneNumber* other);
197
198 private:
199   friend class ::PROTOBUF_NAMESPACE_ID::internal::AnyMetadata;
200   static ::PROTOBUF_NAMESPACE_ID::StringPiece FullMessageName() {
201     return "tutorial.Person.PhoneNumber";
202   }
203 protected:
204   explicit Person_PhoneNumber(::PROTOBUF_NAMESPACE_ID::Arena* arena,
205     bool is_message_owned = false);
206 public:
207
208   static const ClassData _class_data_;
209   const ::PROTOBUF_NAMESPACE_ID::Message::ClassData* GetClassData() const final;
210
211   ::PROTOBUF_NAMESPACE_ID::Metadata GetMetadata() const final;
212
213   // nested types -----
214
215   // accessors -----
216
217   enum : int {
218     kNumberFieldName = 1,
219     kTypeFieldName = 2,
220   };
221   // optional string number = 1;
222   bool has_number() const;
223 private:
224   bool _internal_has_number() const;
225 public:
226   void clear_number();
227   const std::string& number() const;
228   template <typename ArgT0 = const std::string&, typename... ArgT>
229   void set_number(ArgT0&& arg0, ArgT... args);
230   std::string* mutable_number();
231   PROTOBUF_NODISCARD std::string* release_number();

```

(continues on next page)

(continued from previous page)

```

232 void set_allocated_number(std::string* number);
233 private:
234 const std::string& _internal_number() const;
235 inline PROTOBUF_ALWAYS_INLINE void _internal_set_number(const std::string& value);
236 std::string* _internal_mutable_number();
237 public:
238
239 // optional .tutorial.Person.PhoneType type = 2 [default = HOME];
240 bool has_type() const;
241 private:
242 bool _internal_has_type() const;
243 public:
244 void clear_type();
245 ::tutorial::Person_PhoneType type() const;
246 void set_type(::tutorial::Person_PhoneType value);
247 private:
248 ::tutorial::Person_PhoneType _internal_type() const;
249 void _internal_set_type(::tutorial::Person_PhoneType value);
250 public:
251
252 // @@protoc_insertion_point(class_scope:tutorial.Person.PhoneNumber)
253 private:
254 class _Internal;
255
256 template <typename T> friend class ::PROTOBUF_NAMESPACE_ID::Arena::InternalHelper;
257 typedef void InternalArenaConstructable_;
258 typedef void DestructorSkippable_;
259 ::PROTOBUF_NAMESPACE_ID::internal::HasBits<1> _has_bits_;
260 mutable ::PROTOBUF_NAMESPACE_ID::internal::CachedSize _cached_size_;
261 ::PROTOBUF_NAMESPACE_ID::internal::ArenaStringPtr number_;
262 int type_;
263 friend struct ::TableStruct_hello_2eproto;
264 };
265 // -----
266
267 class Person final :
268     public ::PROTOBUF_NAMESPACE_ID::Message /* @@protoc_insertion_point(class_
↳ definition:tutorial.Person) */ {
269 public:
270     inline Person() : Person(nullptr) {}
271     ~Person() override;
272     explicit PROTOBUF_CONSTEXPR Person(::PROTOBUF_NAMESPACE_
↳ ID::internal::ConstantInitialized);
273
274     Person(const Person& from);
275     Person(Person&& from) noexcept
276         : Person() {
277         *this = ::std::move(from);
278     }
279
280     inline Person& operator=(const Person& from) {
281         CopyFrom(from);

```

(continues on next page)

(continued from previous page)

```

282     return *this;
283 }
284 inline Person& operator=(Person&& from) noexcept {
285     if (this == &from) return *this;
286     if (GetOwningArena() == from.GetOwningArena()
287 #ifdef PROTOBUF_FORCE_COPY_IN_MOVE
288         && GetOwningArena() != nullptr
289 #endif // !PROTOBUF_FORCE_COPY_IN_MOVE
290     ) {
291         InternalSwap(&from);
292     } else {
293         CopyFrom(from);
294     }
295     return *this;
296 }
297
298 inline const ::PROTOBUF_NAMESPACE_ID::UnknownFieldSet& unknown_fields() const {
299     return _internal_metadata_.unknown_fields<::PROTOBUF_NAMESPACE_ID::UnknownFieldSet>
300     ↪ (::PROTOBUF_NAMESPACE_ID::UnknownFieldSet::default_instance);
301 }
302 inline ::PROTOBUF_NAMESPACE_ID::UnknownFieldSet* mutable_unknown_fields() {
303     return _internal_metadata_.mutable_unknown_fields<::PROTOBUF_NAMESPACE_
304     ↪ ID::UnknownFieldSet>();
305 }
306
307 static const ::PROTOBUF_NAMESPACE_ID::Descriptor* descriptor() {
308     return GetDescriptor();
309 }
310 static const ::PROTOBUF_NAMESPACE_ID::Descriptor* GetDescriptor() {
311     return default_instance().GetMetadata().descriptor;
312 }
313 static const ::PROTOBUF_NAMESPACE_ID::Reflection* GetReflection() {
314     return default_instance().GetMetadata().reflection;
315 }
316 static const Person& default_instance() {
317     return *internal_default_instance();
318 }
319 static inline const Person* internal_default_instance() {
320     return reinterpret_cast<const Person*>(
321         &_Person_default_instance_);
322 }
323 static constexpr int kIndexInFileMessages =
324     1;
325
326 friend void swap(Person& a, Person& b) {
327     a.Swap(&b);
328 }
329 inline void Swap(Person* other) {
330     if (other == this) return;
331 #ifdef PROTOBUF_FORCE_COPY_IN_SWAP
332     if (GetOwningArena() != nullptr &&
333         GetOwningArena() == other->GetOwningArena()) {

```

(continues on next page)

(continued from previous page)

```

332     #else // PROTOBUF_FORCE_COPY_IN_SWAP
333         if (GetOwningArena() == other->GetOwningArena()) {
334     #endif // !PROTOBUF_FORCE_COPY_IN_SWAP
335         InternalSwap(other);
336     } else {
337         ::PROTOBUF_NAMESPACE_ID::internal::GenericSwap(this, other);
338     }
339 }
340 void UnsafeArenaSwap(Person* other) {
341     if (other == this) return;
342     GOOGLE_DCHECK(GetOwningArena() == other->GetOwningArena());
343     InternalSwap(other);
344 }
345
346 // implements Message -----
347
348 Person* New(::PROTOBUF_NAMESPACE_ID::Arena* arena = nullptr) const final {
349     return CreateMaybeMessage<Person>(arena);
350 }
351 using ::PROTOBUF_NAMESPACE_ID::Message::CopyFrom;
352 void CopyFrom(const Person& from);
353 using ::PROTOBUF_NAMESPACE_ID::Message::MergeFrom;
354 void MergeFrom(const Person& from);
355 private:
356 static void MergeImpl(::PROTOBUF_NAMESPACE_ID::Message* to, const ::PROTOBUF_NAMESPACE_ID::Message& from);
357 public:
358 PROTOBUF_ATTRIBUTE_REINITIALIZES void Clear() final;
359 bool IsInitialized() const final;
360
361 size_t ByteSizeLong() const final;
362 const char* _InternalParse(const char* ptr, ::PROTOBUF_NAMESPACE_ID::internal::ParseContext* ctx) final;
363 uint8_t* _InternalSerialize(
364     uint8_t* target, ::PROTOBUF_NAMESPACE_ID::io::EpsCopyOutputStream* stream) const final;
365 int GetCachedSize() const final { return _cached_size_.Get(); }
366
367 private:
368 void SharedCtor();
369 void SharedDtor();
370 void SetCachedSize(int size) const final;
371 void InternalSwap(Person* other);
372
373 private:
374 friend class ::PROTOBUF_NAMESPACE_ID::internal::AnyMetadata;
375 static ::PROTOBUF_NAMESPACE_ID::StringPiece FullMessageName() {
376     return "tutorial.Person";
377 }
378 protected:
379 explicit Person(::PROTOBUF_NAMESPACE_ID::Arena* arena,
380                 bool is_message_owned = false);

```

(continues on next page)

(continued from previous page)

```

381 public:
382
383 static const ClassData _class_data_;
384 const ::PROTOBUF_NAMESPACE_ID::Message::ClassData*GetClassData() const final;
385
386 ::PROTOBUF_NAMESPACE_ID::Metadata GetMetadata() const final;
387
388 // nested types -----
389
390 typedef Person_PhoneNumber PhoneNumber;
391
392 typedef Person_PhoneType PhoneType;
393 static constexpr PhoneType MOBILE =
394     Person_PhoneType_MOBILE;
395 static constexpr PhoneType HOME =
396     Person_PhoneType_HOME;
397 static constexpr PhoneType WORK =
398     Person_PhoneType_WORK;
399 static inline bool PhoneType_IsValid(int value) {
400     return Person_PhoneType_IsValid(value);
401 }
402 static constexpr PhoneType PhoneType_MIN =
403     Person_PhoneType_PhoneType_MIN;
404 static constexpr PhoneType PhoneType_MAX =
405     Person_PhoneType_PhoneType_MAX;
406 static constexpr int PhoneType_ARRAYSIZE =
407     Person_PhoneType_PhoneType_ARRAYSIZE;
408 static inline const ::PROTOBUF_NAMESPACE_ID::EnumDescriptor*
409 PhoneType_descriptor() {
410     return Person_PhoneType_descriptor();
411 }
412 template<typename T>
413 static inline const std::string& PhoneType_Name(T enum_t_value) {
414     static_assert(::std::is_same<T, PhoneType>::value ||
415         ::std::is_integral<T>::value,
416         "Incorrect type passed to function PhoneType_Name.");
417     return Person_PhoneType_Name(enum_t_value);
418 }
419 static inline bool PhoneType_Parse(::PROTOBUF_NAMESPACE_ID::ConstStringParam name,
420     PhoneType* value) {
421     return Person_PhoneType_Parse(name, value);
422 }
423
424 // accessors -----
425
426 enum : int {
427     kPhonesFieldNumber = 4,
428     kNameFieldNumber = 1,
429     kEmailFieldNumber = 3,
430     kIdFieldNumber = 2,
431 };
432 // repeated .tutorial.Person.PhoneNumber phones = 4;

```

(continues on next page)

(continued from previous page)

```

433 int phones_size() const;
434 private:
435 int _internal_phones_size() const;
436 public:
437 void clear_phones();
438 ::tutorial::Person_PhoneNumber* mutable_phones(int index);
439 ::PROTOBUF_NAMESPACE_ID::RepeatedPtrField< ::tutorial::Person_PhoneNumber >*
440     mutable_phones();
441 private:
442 const ::tutorial::Person_PhoneNumber& _internal_phones(int index) const;
443 ::tutorial::Person_PhoneNumber* _internal_add_phones();
444 public:
445 const ::tutorial::Person_PhoneNumber& phones(int index) const;
446 ::tutorial::Person_PhoneNumber* add_phones();
447 const ::PROTOBUF_NAMESPACE_ID::RepeatedPtrField< ::tutorial::Person_PhoneNumber >&
448     phones() const;
449
450 // optional string name = 1;
451 bool has_name() const;
452 private:
453 bool _internal_has_name() const;
454 public:
455 void clear_name();
456 const std::string& name() const;
457 template <typename ArgT0 = const std::string&, typename... ArgT>
458 void set_name(ArgT0&& arg0, ArgT... args);
459 std::string* mutable_name();
460 PROTOBUF_NODISCARD std::string* release_name();
461 void set_allocated_name(std::string* name);
462 private:
463 const std::string& _internal_name() const;
464 inline PROTOBUF_ALWAYS_INLINE void _internal_set_name(const std::string& value);
465 std::string* _internal_mutable_name();
466 public:
467
468 // optional string email = 3;
469 bool has_email() const;
470 private:
471 bool _internal_has_email() const;
472 public:
473 void clear_email();
474 const std::string& email() const;
475 template <typename ArgT0 = const std::string&, typename... ArgT>
476 void set_email(ArgT0&& arg0, ArgT... args);
477 std::string* mutable_email();
478 PROTOBUF_NODISCARD std::string* release_email();
479 void set_allocated_email(std::string* email);
480 private:
481 const std::string& _internal_email() const;
482 inline PROTOBUF_ALWAYS_INLINE void _internal_set_email(const std::string& value);
483 std::string* _internal_mutable_email();
484 public:

```

(continues on next page)

(continued from previous page)

```

485
486 // optional int32 id = 2;
487 bool has_id() const;
488 private:
489 bool _internal_has_id() const;
490 public:
491 void clear_id();
492 int32_t id() const;
493 void set_id(int32_t value);
494 private:
495 int32_t _internal_id() const;
496 void _internal_set_id(int32_t value);
497 public:
498
499 // @@protoc_insertion_point(class_scope:tutorial.Person)
500 private:
501 class _Internal;
502
503 template <typename T> friend class ::PROTOBUF_NAMESPACE_ID::Arena::InternalHelper;
504 typedef void InternalArenaConstructable_;
505 typedef void DestructorSkippable_;
506 ::PROTOBUF_NAMESPACE_ID::internal::HasBits<1> _has_bits_;
507 mutable ::PROTOBUF_NAMESPACE_ID::internal::CachedSize _cached_size_;
508 ::PROTOBUF_NAMESPACE_ID::RepeatedPtrField< ::tutorial::Person_PhoneNumber > phones_;
509 ::PROTOBUF_NAMESPACE_ID::internal::ArenaStringPtr name_;
510 ::PROTOBUF_NAMESPACE_ID::internal::ArenaStringPtr email_;
511 int32_t id_;
512 friend struct ::TableStruct_hello_2eproto;
513 };
514 // -----
515
516 class AddressBook final :
517     public ::PROTOBUF_NAMESPACE_ID::Message /* @@protoc_insertion_point(class_
↳ definition:tutorial.AddressBook) */ {
518 public:
519     inline AddressBook() : AddressBook(nullptr) {}
520     ~AddressBook() override;
521     explicit PROTOBUF_CONSTEXPR AddressBook(::PROTOBUF_NAMESPACE_ID::
↳ ID::internal::ConstantInitialized);
522
523     AddressBook(const AddressBook& from);
524     AddressBook(AddressBook&& from) noexcept
525         : AddressBook() {
526         *this = ::std::move(from);
527     }
528
529     inline AddressBook& operator=(const AddressBook& from) {
530         CopyFrom(from);
531         return *this;
532     }
533     inline AddressBook& operator=(AddressBook&& from) noexcept {
534         if (this == &from) return *this;

```

(continues on next page)

(continued from previous page)

```

535     if (GetOwningArena() == from.GetOwningArena()
536     #ifdef PROTOBUF_FORCE_COPY_IN_MOVE
537         && GetOwningArena() != nullptr
538     #endif // !PROTOBUF_FORCE_COPY_IN_MOVE
539         ) {
540         InternalSwap(&from);
541     } else {
542         CopyFrom(from);
543     }
544     return *this;
545 }
546
547 inline const ::PROTOBUF_NAMESPACE_ID::UnknownFieldSet& unknown_fields() const {
548     return _internal_metadata_.unknown_fields<::PROTOBUF_NAMESPACE_ID::UnknownFieldSet>
549     ↪ (::PROTOBUF_NAMESPACE_ID::UnknownFieldSet::default_instance());
550 }
551 inline ::PROTOBUF_NAMESPACE_ID::UnknownFieldSet* mutable_unknown_fields() {
552     return _internal_metadata_.mutable_unknown_fields<::PROTOBUF_NAMESPACE_
553     ↪ ID::UnknownFieldSet>();
554 }
555
556 static const ::PROTOBUF_NAMESPACE_ID::Descriptor* descriptor() {
557     return GetDescriptor();
558 }
559 static const ::PROTOBUF_NAMESPACE_ID::Descriptor* GetDescriptor() {
560     return default_instance().GetMetadata().descriptor;
561 }
562 static const ::PROTOBUF_NAMESPACE_ID::Reflection* GetReflection() {
563     return default_instance().GetMetadata().reflection;
564 }
565 static const AddressBook& default_instance() {
566     return *internal_default_instance();
567 }
568 static inline const AddressBook* internal_default_instance() {
569     return reinterpret_cast<const AddressBook*>(
570         &_AddressBook_default_instance_);
571 }
572 static constexpr int kIndexInFileMessages =
573     2;
574
575 friend void swap(AddressBook& a, AddressBook& b) {
576     a.Swap(&b);
577 }
578 inline void Swap(AddressBook* other) {
579     if (other == this) return;
580 #ifdef PROTOBUF_FORCE_COPY_IN_SWAP
581     if (GetOwningArena() != nullptr &&
582         GetOwningArena() == other->GetOwningArena()) {
583     #else // PROTOBUF_FORCE_COPY_IN_SWAP
584     if (GetOwningArena() == other->GetOwningArena()) {
585     #endif // !PROTOBUF_FORCE_COPY_IN_SWAP
586         InternalSwap(other);

```

(continues on next page)

(continued from previous page)

```

585     } else {
586         ::PROTOBUF_NAMESPACE_ID::internal::GenericSwap(this, other);
587     }
588 }
589 void UnsafeArenaSwap(AddressBook* other) {
590     if (other == this) return;
591     GOOGLE_DCHECK(GetOwningArena() == other->GetOwningArena());
592     InternalSwap(other);
593 }
594
595 // implements Message -----
596
597 AddressBook* New(::PROTOBUF_NAMESPACE_ID::Arena* arena = nullptr) const final {
598     return CreateMaybeMessage<AddressBook>(arena);
599 }
600 using ::PROTOBUF_NAMESPACE_ID::Message::CopyFrom;
601 void CopyFrom(const AddressBook& from);
602 using ::PROTOBUF_NAMESPACE_ID::Message::MergeFrom;
603 void MergeFrom(const AddressBook& from);
604 private:
605 static void MergeImpl(::PROTOBUF_NAMESPACE_ID::Message* to, const ::PROTOBUF_NAMESPACE_ID::Message& from);
606 public:
607 PROTOBUF_ATTRIBUTE_REINITIALIZES void Clear() final;
608 bool IsInitialized() const final;
609
610 size_t ByteSizeLong() const final;
611 const char* _InternalParse(const char* ptr, ::PROTOBUF_NAMESPACE_ID::internal::ParseContext* ctx) final;
612 uint8_t* _InternalSerialize(
613     uint8_t* target, ::PROTOBUF_NAMESPACE_ID::io::EpsCopyOutputStream* stream) const final;
614 int GetCachedSize() const final { return _cached_size_.Get(); }
615
616 private:
617 void SharedCtor();
618 void SharedDtor();
619 void SetCachedSize(int size) const final;
620 void InternalSwap(AddressBook* other);
621
622 private:
623 friend class ::PROTOBUF_NAMESPACE_ID::internal::AnyMetadata;
624 static ::PROTOBUF_NAMESPACE_ID::StringPiece FullMessageName() {
625     return "tutorial.AddressBook";
626 }
627 protected:
628 explicit AddressBook(::PROTOBUF_NAMESPACE_ID::Arena* arena,
629                     bool is_message_owned = false);
630 public:
631
632 static const ClassData _class_data_;
633 const ::PROTOBUF_NAMESPACE_ID::Message::ClassData* GetClassData() const final;

```

(continues on next page)

(continued from previous page)

```

634
635 ::PROTOBUF_NAMESPACE_ID::Metadata GetMetadata() const final;
636
637 // nested types -----
638
639 // accessors -----
640
641 enum : int {
642     kPeopleFieldName = 1,
643 };
644 // repeated .tutorial.Person people = 1;
645 int people_size() const;
646 private:
647 int _internal_people_size() const;
648 public:
649 void clear_people();
650 ::tutorial::Person* mutable_people(int index);
651 ::PROTOBUF_NAMESPACE_ID::RepeatedPtrField< ::tutorial::Person >*
652     mutable_people();
653 private:
654 const ::tutorial::Person& _internal_people(int index) const;
655 ::tutorial::Person* _internal_add_people();
656 public:
657 const ::tutorial::Person& people(int index) const;
658 ::tutorial::Person* add_people();
659 const ::PROTOBUF_NAMESPACE_ID::RepeatedPtrField< ::tutorial::Person >&
660     people() const;
661
662 // @@protoc_insertion_point(class_scope:tutorial.AddressBook)
663 private:
664 class _Internal;
665
666 template <typename T> friend class ::PROTOBUF_NAMESPACE_ID::Arena::InternalHelper;
667 typedef void InternalArenaConstructable_;
668 typedef void DestructorSkippable_;
669 ::PROTOBUF_NAMESPACE_ID::RepeatedPtrField< ::tutorial::Person > people_;
670 mutable ::PROTOBUF_NAMESPACE_ID::internal::CachedSize _cached_size_;
671 friend struct ::TableStruct_hello_2eproto;
672 };
673 // =====
674
675 // =====
676
677 #ifdef __GNUC__
678     #pragma GCC diagnostic push
679     #pragma GCC diagnostic ignored "-Wstrict-aliasing"
680 #endif // __GNUC__
681 // Person_PhoneNumber
682
683
684 // optional string number = 1;
685 inline bool Person_PhoneNumber::_internal_has_number() const {

```

(continues on next page)

(continued from previous page)

```

686     bool value = (_has_bits_[0] & 0x00000001u) != 0;
687     return value;
688 }
689 inline bool Person_PhoneNumber::has_number() const {
690     return _internal_has_number();
691 }
692 inline void Person_PhoneNumber::clear_number() {
693     number_.ClearToEmpty();
694     _has_bits_[0] &= ~0x00000001u;
695 }
696 inline const std::string& Person_PhoneNumber::number() const {
697     // @@protoc_insertion_point(field_get:tutorial.Person.PhoneNumber.number)
698     return _internal_number();
699 }
700 template <typename ArgT0, typename... ArgT>
701 inline PROTOBUF_ALWAYS_INLINE
702 void Person_PhoneNumber::set_number(ArgT0&& arg0, ArgT... args) {
703     _has_bits_[0] |= 0x00000001u;
704     number_.Set(static_cast<ArgT0 &&>(arg0), args..., GetArenaForAllocation());
705     // @@protoc_insertion_point(field_set:tutorial.Person.PhoneNumber.number)
706 }
707 inline std::string* Person_PhoneNumber::mutable_number() {
708     std::string* _s = _internal_mutable_number();
709     // @@protoc_insertion_point(field_mutable:tutorial.Person.PhoneNumber.number)
710     return _s;
711 }
712 inline const std::string& Person_PhoneNumber::_internal_number() const {
713     return number_.Get();
714 }
715 inline void Person_PhoneNumber::_internal_set_number(const std::string& value) {
716     _has_bits_[0] |= 0x00000001u;
717     number_.Set(value, GetArenaForAllocation());
718 }
719 inline std::string* Person_PhoneNumber::_internal_mutable_number() {
720     _has_bits_[0] |= 0x00000001u;
721     return number_.Mutable(GetArenaForAllocation());
722 }
723 inline std::string* Person_PhoneNumber::release_number() {
724     // @@protoc_insertion_point(field_release:tutorial.Person.PhoneNumber.number)
725     if (!_internal_has_number()) {
726         return nullptr;
727     }
728     _has_bits_[0] &= ~0x00000001u;
729     auto* p = number_.Release();
730 #ifdef PROTOBUF_FORCE_COPY_DEFAULT_STRING
731     if (number_.IsDefault()) {
732         number_.Set("", GetArenaForAllocation());
733     }
734 #endif // PROTOBUF_FORCE_COPY_DEFAULT_STRING
735     return p;
736 }
737 inline void Person_PhoneNumber::set_allocated_number(std::string* number) {

```

(continues on next page)

(continued from previous page)

```

738     if (number != nullptr) {
739         _has_bits_[0] |= 0x000000001u;
740     } else {
741         _has_bits_[0] &= ~0x000000001u;
742     }
743     number_.SetAllocated(number, GetArenaForAllocation());
744 #ifdef PROTOBUF_FORCE_COPY_DEFAULT_STRING
745     if (number_.IsDefault()) {
746         number_.Set("", GetArenaForAllocation());
747     }
748 #endif // PROTOBUF_FORCE_COPY_DEFAULT_STRING
749     // @@protoc_insertion_point(field_set_allocated:tutorial.Person.PhoneNumber.number)
750 }
751
752 // optional .tutorial.Person.PhoneType type = 2 [default = HOME];
753 inline bool Person_PhoneNumber::_internal_has_type() const {
754     bool value = (_has_bits_[0] & 0x000000002u) != 0;
755     return value;
756 }
757 inline bool Person_PhoneNumber::has_type() const {
758     return _internal_has_type();
759 }
760 inline void Person_PhoneNumber::clear_type() {
761     type_ = 1;
762     _has_bits_[0] &= ~0x000000002u;
763 }
764 inline ::tutorial::Person_PhoneType Person_PhoneNumber::_internal_type() const {
765     return static_cast< ::tutorial::Person_PhoneType >(type_);
766 }
767 inline ::tutorial::Person_PhoneType Person_PhoneNumber::type() const {
768     // @@protoc_insertion_point(field_get:tutorial.Person.PhoneNumber.type)
769     return _internal_type();
770 }
771 inline void Person_PhoneNumber::_internal_set_type(::tutorial::Person_PhoneType value) {
772     assert(::tutorial::Person_PhoneType_IsValid(value));
773     _has_bits_[0] |= 0x000000002u;
774     type_ = value;
775 }
776 inline void Person_PhoneNumber::set_type(::tutorial::Person_PhoneType value) {
777     _internal_set_type(value);
778     // @@protoc_insertion_point(field_set:tutorial.Person.PhoneNumber.type)
779 }
780
781 // -----
782
783 // Person
784
785 // optional string name = 1;
786 inline bool Person::_internal_has_name() const {
787     bool value = (_has_bits_[0] & 0x000000001u) != 0;
788     return value;
789 }

```

(continues on next page)

(continued from previous page)

```

790 inline bool Person::has_name() const {
791     return _internal_has_name();
792 }
793 inline void Person::clear_name() {
794     name_.ClearToEmpty();
795     _has_bits_[0] &= ~0x00000001u;
796 }
797 inline const std::string& Person::name() const {
798     // @@protoc_insertion_point(field_get:tutorial.Person.name)
799     return _internal_name();
800 }
801 template <typename ArgT0, typename... ArgT>
802 inline PROTOBUF_ALWAYS_INLINE
803 void Person::set_name(ArgT0&& arg0, ArgT... args) {
804     _has_bits_[0] |= 0x00000001u;
805     name_.Set(static_cast<ArgT0 &&>(arg0), args..., GetArenaForAllocation());
806     // @@protoc_insertion_point(field_set:tutorial.Person.name)
807 }
808 inline std::string* Person::mutable_name() {
809     std::string* _s = _internal_mutable_name();
810     // @@protoc_insertion_point(field_mutable:tutorial.Person.name)
811     return _s;
812 }
813 inline const std::string& Person::_internal_name() const {
814     return name_.Get();
815 }
816 inline void Person::_internal_set_name(const std::string& value) {
817     _has_bits_[0] |= 0x00000001u;
818     name_.Set(value, GetArenaForAllocation());
819 }
820 inline std::string* Person::_internal_mutable_name() {
821     _has_bits_[0] |= 0x00000001u;
822     return name_.Mutable(GetArenaForAllocation());
823 }
824 inline std::string* Person::release_name() {
825     // @@protoc_insertion_point(field_release:tutorial.Person.name)
826     if (!_internal_has_name()) {
827         return nullptr;
828     }
829     _has_bits_[0] &= ~0x00000001u;
830     auto* p = name_.Release();
831 #ifdef PROTOBUF_FORCE_COPY_DEFAULT_STRING
832     if (name_.IsDefault()) {
833         name_.Set("", GetArenaForAllocation());
834     }
835 #endif // PROTOBUF_FORCE_COPY_DEFAULT_STRING
836     return p;
837 }
838 inline void Person::set_allocated_name(std::string* name) {
839     if (name != nullptr) {
840         _has_bits_[0] |= 0x00000001u;
841     } else {

```

(continues on next page)

(continued from previous page)

```

842     _has_bits_[0] &= ~0x00000001u;
843 }
844 name_.SetAllocated(name, GetArenaForAllocation());
845 #ifdef PROTOBUF_FORCE_COPY_DEFAULT_STRING
846 if (name_.IsDefault()) {
847     name_.Set("", GetArenaForAllocation());
848 }
849 #endif // PROTOBUF_FORCE_COPY_DEFAULT_STRING
850 // @@protoc_insertion_point(field_set_allocated:tutorial.Person.name)
851 }
852
853 // optional int32 id = 2;
854 inline bool Person::_internal_has_id() const {
855     bool value = (_has_bits_[0] & 0x00000004u) != 0;
856     return value;
857 }
858 inline bool Person::has_id() const {
859     return _internal_has_id();
860 }
861 inline void Person::clear_id() {
862     id_ = 0;
863     _has_bits_[0] &= ~0x00000004u;
864 }
865 inline int32_t Person::_internal_id() const {
866     return id_;
867 }
868 inline int32_t Person::id() const {
869     // @@protoc_insertion_point(field_get:tutorial.Person.id)
870     return _internal_id();
871 }
872 inline void Person::_internal_set_id(int32_t value) {
873     _has_bits_[0] |= 0x00000004u;
874     id_ = value;
875 }
876 inline void Person::set_id(int32_t value) {
877     _internal_set_id(value);
878     // @@protoc_insertion_point(field_set:tutorial.Person.id)
879 }
880
881 // optional string email = 3;
882 inline bool Person::_internal_has_email() const {
883     bool value = (_has_bits_[0] & 0x00000002u) != 0;
884     return value;
885 }
886 inline bool Person::has_email() const {
887     return _internal_has_email();
888 }
889 inline void Person::clear_email() {
890     email_.ClearToEmpty();
891     _has_bits_[0] &= ~0x00000002u;
892 }
893 inline const std::string& Person::email() const {

```

(continues on next page)

(continued from previous page)

```

894 // @@protoc_insertion_point(field_get:tutorial.Person.email)
895 return _internal_email();
896 }
897 template <typename ArgT0, typename... ArgT>
898 inline PROTOBUF_ALWAYS_INLINE
899 void Person::set_email(ArgT0&& arg0, ArgT... args) {
900   _has_bits_[0] |= 0x000000002u;
901   email_.Set(static_cast<ArgT0 &&>(arg0), args..., GetArenaForAllocation());
902   // @@protoc_insertion_point(field_set:tutorial.Person.email)
903 }
904 inline std::string* Person::mutable_email() {
905   std::string* _s = _internal_mutable_email();
906   // @@protoc_insertion_point(field_mutable:tutorial.Person.email)
907   return _s;
908 }
909 inline const std::string& Person::_internal_email() const {
910   return email_.Get();
911 }
912 inline void Person::_internal_set_email(const std::string& value) {
913   _has_bits_[0] |= 0x000000002u;
914   email_.Set(value, GetArenaForAllocation());
915 }
916 inline std::string* Person::_internal_mutable_email() {
917   _has_bits_[0] |= 0x000000002u;
918   return email_.Mutable(GetArenaForAllocation());
919 }
920 inline std::string* Person::release_email() {
921   // @@protoc_insertion_point(field_release:tutorial.Person.email)
922   if (!_internal_has_email()) {
923     return nullptr;
924   }
925   _has_bits_[0] &= ~0x000000002u;
926   auto* p = email_.Release();
927   #ifdef PROTOBUF_FORCE_COPY_DEFAULT_STRING
928   if (email_.IsDefault()) {
929     email_.Set("", GetArenaForAllocation());
930   }
931   #endif // PROTOBUF_FORCE_COPY_DEFAULT_STRING
932   return p;
933 }
934 inline void Person::set_allocated_email(std::string* email) {
935   if (email != nullptr) {
936     _has_bits_[0] |= 0x000000002u;
937   } else {
938     _has_bits_[0] &= ~0x000000002u;
939   }
940   email_.SetAllocated(email, GetArenaForAllocation());
941   #ifdef PROTOBUF_FORCE_COPY_DEFAULT_STRING
942   if (email_.IsDefault()) {
943     email_.Set("", GetArenaForAllocation());
944   }
945   #endif // PROTOBUF_FORCE_COPY_DEFAULT_STRING

```

(continues on next page)

(continued from previous page)

```

946 // @@protoc_insertion_point(field_set_allocated:tutorial.Person.email)
947 }
948
949 // repeated .tutorial.Person.PhoneNumber phones = 4;
950 inline int Person::_internal_phones_size() const {
951     return phones_.size();
952 }
953 inline int Person::phones_size() const {
954     return _internal_phones_size();
955 }
956 inline void Person::clear_phones() {
957     phones_.Clear();
958 }
959 inline ::tutorial::Person_PhoneNumber* Person::mutable_phones(int index) {
960     // @@protoc_insertion_point(field_mutable:tutorial.Person.phones)
961     return phones_.Mutable(index);
962 }
963 inline ::PROTOBUF_NAMESPACE_ID::RepeatedPtrField< ::tutorial::Person_PhoneNumber >*
964 Person::mutable_phones() {
965     // @@protoc_insertion_point(field_mutable_list:tutorial.Person.phones)
966     return &phones_;
967 }
968 inline const ::tutorial::Person_PhoneNumber& Person::_internal_phones(int index) const {
969     return phones_.Get(index);
970 }
971 inline const ::tutorial::Person_PhoneNumber& Person::phones(int index) const {
972     // @@protoc_insertion_point(field_get:tutorial.Person.phones)
973     return _internal_phones(index);
974 }
975 inline ::tutorial::Person_PhoneNumber* Person::_internal_add_phones() {
976     return phones_.Add();
977 }
978 inline ::tutorial::Person_PhoneNumber* Person::add_phones() {
979     ::tutorial::Person_PhoneNumber* _add = _internal_add_phones();
980     // @@protoc_insertion_point(field_add:tutorial.Person.phones)
981     return _add;
982 }
983 inline const ::PROTOBUF_NAMESPACE_ID::RepeatedPtrField< ::tutorial::Person_PhoneNumber >&
984 Person::phones() const {
985     // @@protoc_insertion_point(field_list:tutorial.Person.phones)
986     return phones_;
987 }
988
989 // -----
990
991 // AddressBook
992
993 // repeated .tutorial.Person people = 1;
994 inline int AddressBook::_internal_people_size() const {
995     return people_.size();
996 }
997 inline int AddressBook::people_size() const {

```

(continues on next page)

(continued from previous page)

```

998     return _internal_people_size();
999 }
1000 inline void AddressBook::clear_people() {
1001     people_.Clear();
1002 }
1003 inline ::tutorial::Person* AddressBook::mutable_people(int index) {
1004     // @@protoc_insertion_point(field_mutable:tutorial.AddressBook.people)
1005     return people_.Mutable(index);
1006 }
1007 inline ::PROTOBUF_NAMESPACE_ID::RepeatedPtrField< ::tutorial::Person >*
1008 AddressBook::mutable_people() {
1009     // @@protoc_insertion_point(field_mutable_list:tutorial.AddressBook.people)
1010     return &people_;
1011 }
1012 inline const ::tutorial::Person& AddressBook::_internal_people(int index) const {
1013     return people_.Get(index);
1014 }
1015 inline const ::tutorial::Person& AddressBook::people(int index) const {
1016     // @@protoc_insertion_point(field_get:tutorial.AddressBook.people)
1017     return _internal_people(index);
1018 }
1019 inline ::tutorial::Person* AddressBook::_internal_add_people() {
1020     return people_.Add();
1021 }
1022 inline ::tutorial::Person* AddressBook::add_people() {
1023     ::tutorial::Person* _add = _internal_add_people();
1024     // @@protoc_insertion_point(field_add:tutorial.AddressBook.people)
1025     return _add;
1026 }
1027 inline const ::PROTOBUF_NAMESPACE_ID::RepeatedPtrField< ::tutorial::Person >&
1028 AddressBook::people() const {
1029     // @@protoc_insertion_point(field_list:tutorial.AddressBook.people)
1030     return people_;
1031 }
1032
1033 #ifdef __GNUC__
1034     #pragma GCC diagnostic pop
1035 #endif // __GNUC__
1036 // -----
1037
1038 // -----
1039
1040 // @@protoc_insertion_point(namespace_scope)
1041
1042 } // namespace tutorial
1043
1044 PROTOBUF_NAMESPACE_OPEN
1045
1046 template <> struct is_proto_enum< ::tutorial::Person_PhoneType> : ::std::true_type {};
1047 template <>
1048 inline const EnumDescriptor* GetEnumDescriptor< ::tutorial::Person_PhoneType>() {
1049

```

(continues on next page)

(continued from previous page)

```

1050     return ::tutorial::Person_PhoneType_descriptor();
1051 }
1052
1053 PROTOBUF_NAMESPACE_CLOSE
1054
1055 // @@protoc_insertion_point(global_scope)
1056
1057 #include <google/protobuf/port_undef.inc>
1058 #endif // GOOGLE_PROTOBUF_INCLUDED_GOOGLE_PROTOBUF_INCLUDED_hello_2eproto

```

15.2.4 hello.pb.cc

Listing 6: ./code/hello.pb.cc

```

1  // Generated by the protocol buffer compiler.  DO NOT EDIT!
2  // source: hello.proto
3
4  #include "hello.pb.h"
5
6  #include <algorithm>
7
8  #include <google/protobuf/io/coded_stream.h>
9  #include <google/protobuf/extension_set.h>
10 #include <google/protobuf/wire_format_lite.h>
11 #include <google/protobuf/descriptor.h>
12 #include <google/protobuf/generated_message_reflection.h>
13 #include <google/protobuf/reflection_ops.h>
14 #include <google/protobuf/wire_format.h>
15 // @@protoc_insertion_point(includes)
16 #include <google/protobuf/port_def.inc>
17
18 PROTOBUF_PRAGMA_INIT_SEG
19
20 namespace _pb = ::PROTOBUF_NAMESPACE_ID;
21 namespace _pbi = _pb::internal;
22
23 namespace tutorial {
24   PROTOBUF_CONSTEXPR Person_PhoneNumber::Person_PhoneNumber(
25     : _pbi::ConstantInitialized)
26     : number_(&:_pbi::fixed_address_empty_string, : _pbi::ConstantInitialized{})
27     , type_(1)
28   {}
29   struct Person_PhoneNumberDefaultTypeInternal {
30     PROTOBUF_CONSTEXPR Person_PhoneNumberDefaultTypeInternal()
31       : _instance(: _pbi::ConstantInitialized{}) {}
32     ~Person_PhoneNumberDefaultTypeInternal() {}
33     union {
34       Person_PhoneNumber _instance;
35     };
36   };

```

(continues on next page)

(continued from previous page)

```

37 PROTOBUF_ATTRIBUTE_NO_DESTROY PROTOBUF_CONSTINIT PROTOBUF_ATTRIBUTE_INIT_PRIORITY1
   ↪ Person_PhoneNumberDefaultTypeInternal _Person_PhoneNumber_default_instance_;
38 PROTOBUF_CONSTEXPR Person::Person(
39     ::_pbi::ConstantInitialized)
40     : phones_()
41     , name_(&::_pbi::fixed_address_empty_string, ::_pbi::ConstantInitialized{})
42     , email_(&::_pbi::fixed_address_empty_string, ::_pbi::ConstantInitialized{})
43     , id_(0){}
44 struct PersonDefaultTypeInternal {
45     PROTOBUF_CONSTEXPR PersonDefaultTypeInternal()
46         : _instance(::_pbi::ConstantInitialized{}) {}
47     ~PersonDefaultTypeInternal() {}
48     union {
49         Person _instance;
50     };
51 };
52 PROTOBUF_ATTRIBUTE_NO_DESTROY PROTOBUF_CONSTINIT PROTOBUF_ATTRIBUTE_INIT_PRIORITY1
   ↪ PersonDefaultTypeInternal _Person_default_instance_;
53 PROTOBUF_CONSTEXPR AddressBook::AddressBook(
54     ::_pbi::ConstantInitialized)
55     : people_(){}
56 struct AddressBookDefaultTypeInternal {
57     PROTOBUF_CONSTEXPR AddressBookDefaultTypeInternal()
58         : _instance(::_pbi::ConstantInitialized{}) {}
59     ~AddressBookDefaultTypeInternal() {}
60     union {
61         AddressBook _instance;
62     };
63 };
64 PROTOBUF_ATTRIBUTE_NO_DESTROY PROTOBUF_CONSTINIT PROTOBUF_ATTRIBUTE_INIT_PRIORITY1
   ↪ AddressBookDefaultTypeInternal _AddressBook_default_instance_;
65 } // namespace tutorial
66 static ::_pb::Metadata file_level_metadata_hello_2eproto[3];
67 static const ::_pb::EnumDescriptor* file_level_enum_descriptors_hello_2eproto[1];
68 static constexpr ::_pb::ServiceDescriptor const** file_level_service_descriptors_hello_
   ↪ 2eproto = nullptr;
69
70 const uint32_t TableStruct_hello_2eproto::offsets[] PROTOBUF_SECTION_VARIABLE(protodesc_
   ↪ cold) = {
71     PROTOBUF_FIELD_OFFSET(::tutorial::Person_PhoneNumber, _has_bits_),
72     PROTOBUF_FIELD_OFFSET(::tutorial::Person_PhoneNumber, _internal_metadata_),
73     ~0u, // no _extensions_
74     ~0u, // no _oneof_case_
75     ~0u, // no _weak_field_map_
76     ~0u, // no _inlined_string_donated_
77     PROTOBUF_FIELD_OFFSET(::tutorial::Person_PhoneNumber, number_),
78     PROTOBUF_FIELD_OFFSET(::tutorial::Person_PhoneNumber, type_),
79     0,
80     1,
81     PROTOBUF_FIELD_OFFSET(::tutorial::Person, _has_bits_),
82     PROTOBUF_FIELD_OFFSET(::tutorial::Person, _internal_metadata_),
83     ~0u, // no _extensions_

```

(continues on next page)

(continued from previous page)

```

84 ~0u, // no _oneof_case_
85 ~0u, // no _weak_field_map_
86 ~0u, // no _inlined_string_donated_
87 PROTOBUF_FIELD_OFFSET(::tutorial::Person, name_),
88 PROTOBUF_FIELD_OFFSET(::tutorial::Person, id_),
89 PROTOBUF_FIELD_OFFSET(::tutorial::Person, email_),
90 PROTOBUF_FIELD_OFFSET(::tutorial::Person, phones_),
91 0,
92 2,
93 1,
94 ~0u,
95 ~0u, // no _has_bits_
96 PROTOBUF_FIELD_OFFSET(::tutorial::AddressBook, _internal_metadata_),
97 ~0u, // no _extensions_
98 ~0u, // no _oneof_case_
99 ~0u, // no _weak_field_map_
100 ~0u, // no _inlined_string_donated_
101 PROTOBUF_FIELD_OFFSET(::tutorial::AddressBook, people_),
102 };
103 static const ::_pbi::MigrationSchema schemas[] PROTOBUF_SECTION_VARIABLE(protodesc_cold) = {
104     ↪= {
105         { 0, 8, -1, sizeof(::tutorial::Person_PhoneNumber)},
106         { 10, 20, -1, sizeof(::tutorial::Person)},
107         { 24, -1, -1, sizeof(::tutorial::AddressBook)},
108     };
109 static const ::_pb::Message* const file_default_instances[] = {
110     &::tutorial::Person_PhoneNumber_default_instance._instance,
111     &::tutorial::Person_default_instance._instance,
112     &::tutorial::AddressBook_default_instance._instance,
113 };
114
115 const char descriptor_table_protodef_hello_2eproto[] PROTOBUF_SECTION_VARIABLE(protodesc_
116 ↪cold) =
117     "\n\013hello.proto\022\010tutorial\"333\001\n\006Person\022\014\n\004na"
118     "me\030\001 \001(\t\022\n\n\002id\030\002 \001(\005\022\r\n\005email\030\003 \001(\t\022\022\n\006p"
119     "hones\030\004 \003(\0132\034.tutorial.Person.PhoneNumbe"
120     "r\032M\n\013PhoneNumber\022\016\n\006number\030\001 \001(\t\022.\n\004type"
121     "\030\002 \001(\0162\032.tutorial.Person.PhoneType:\004HOME"
122     "\"+\n\tPhoneType\022\n\n\006MOBILE\020\000\022\010\n\004HOME\020\001\022\010\n\004W"
123     "ORK\020\002\"/\n\013AddressBook\022 \n\006people\030\001 \003(\0132\020.t"
124     "utorial.Person"
125 ;
126 static ::_pbi::once_flag descriptor_table_hello_2eproto_once;
127 const ::_pbi::DescriptorTable descriptor_table_hello_2eproto = {
128     false, false, 294, descriptor_table_protodef_hello_2eproto,
129     "hello.proto",
130     &descriptor_table_hello_2eproto_once, nullptr, 0, 3,
131     schemas, file_default_instances, TableStruct_hello_2eproto::offsets,
132     file_level_metadata_hello_2eproto, file_level_enum_descriptors_hello_2eproto,
133     file_level_service_descriptors_hello_2eproto,

```

(continues on next page)

(continued from previous page)

```

133 };
134 PROTOBUF_ATTRIBUTE_WEAK const ::_pbi::DescriptorTable* descriptor_table_hello_2eproto_
    ↪getter() {
135     return &descriptor_table_hello_2eproto;
136 }
137
138 // Force running AddDescriptors() at dynamic initialization time.
139 PROTOBUF_ATTRIBUTE_INIT_PRIORITY2 static ::_pbi::AddDescriptorsRunner dynamic_init_dummy_
    ↪hello_2eproto(&descriptor_table_hello_2eproto);
140 namespace tutorial {
141 const ::PROTOBUF_NAMESPACE_ID::EnumDescriptor* Person_PhoneType_descriptor() {
142     ::PROTOBUF_NAMESPACE_ID::internal::AssignDescriptors(&descriptor_table_hello_2eproto);
143     return file_level_enum_descriptors_hello_2eproto[0];
144 }
145 bool Person_PhoneType_IsValid(int value) {
146     switch (value) {
147         case 0:
148         case 1:
149         case 2:
150             return true;
151         default:
152             return false;
153     }
154 }
155
156 #if (__cplusplus < 201703) && (!defined(_MSC_VER) || (_MSC_VER >= 1900 && _MSC_VER <
    ↪1912))
157 constexpr Person_PhoneType Person::MOBILE;
158 constexpr Person_PhoneType Person::HOME;
159 constexpr Person_PhoneType Person::WORK;
160 constexpr Person_PhoneType Person::PhoneType_MIN;
161 constexpr Person_PhoneType Person::PhoneType_MAX;
162 constexpr int Person::PhoneType_ARRAYSIZE;
163 #endif // (__cplusplus < 201703) && (!defined(_MSC_VER) || (_MSC_VER >= 1900 && _MSC_
    ↪VER < 1912))
164
165 // =====
166
167 class Person_PhoneNumber::_Internal {
168 public:
169     using HasBits = decltype(std::declval<Person_PhoneNumber>()._has_bits_);
170     static void set_has_number(HasBits* has_bits) {
171         (*has_bits)[0] |= 1u;
172     }
173     static void set_has_type(HasBits* has_bits) {
174         (*has_bits)[0] |= 2u;
175     }
176 };
177
178 Person_PhoneNumber::Person_PhoneNumber(::PROTOBUF_NAMESPACE_ID::Arena* arena,
179     bool is_message_owned)
180     : ::PROTOBUF_NAMESPACE_ID::Message(arena, is_message_owned) {

```

(continues on next page)

(continued from previous page)

```

181     SharedCtor();
182     // @@protoc_insertion_point(arena_constructor:tutorial.Person.PhoneNumber)
183 }
184 Person_PhoneNumber::Person_PhoneNumber(const Person_PhoneNumber& from)
185 : ::PROTOBUF_NAMESPACE_ID::Message(),
186   _has_bits_(from._has_bits_) {
187   _internal_metadata_.MergeFrom<::PROTOBUF_NAMESPACE_ID::UnknownFieldSet>(from._internal_
188   ↪_metadata_);
189   number_.InitDefault();
190   #ifdef PROTOBUF_FORCE_COPY_DEFAULT_STRING
191     number_.Set("", GetArenaForAllocation());
192   #endif // PROTOBUF_FORCE_COPY_DEFAULT_STRING
193   if (from._internal_has_number()) {
194     number_.Set(from._internal_number(),
195       GetArenaForAllocation());
196   }
197   type_ = from.type_;
198   // @@protoc_insertion_point(copy_constructor:tutorial.Person.PhoneNumber)
199 }
200 inline void Person_PhoneNumber::SharedCtor() {
201   number_.InitDefault();
202   #ifdef PROTOBUF_FORCE_COPY_DEFAULT_STRING
203     number_.Set("", GetArenaForAllocation());
204   #endif // PROTOBUF_FORCE_COPY_DEFAULT_STRING
205   type_ = 1;
206 }
207
208 Person_PhoneNumber::~Person_PhoneNumber() {
209   // @@protoc_insertion_point(destructor:tutorial.Person.PhoneNumber)
210   if (auto *arena = _internal_metadata_.DeleteReturnArena<::PROTOBUF_NAMESPACE_
211   ↪ID::UnknownFieldSet>()) {
212     (void)arena;
213     return;
214   }
215   SharedDtor();
216 }
217 inline void Person_PhoneNumber::SharedDtor() {
218   GOOGLE_DCHECK(GetArenaForAllocation() == nullptr);
219   number_.Destroy();
220 }
221
222 void Person_PhoneNumber::SetCachedSize(int size) const {
223   _cached_size_.Set(size);
224 }
225
226 void Person_PhoneNumber::Clear() {
227   // @@protoc_insertion_point(message_clear_start:tutorial.Person.PhoneNumber)
228   uint32_t cached_has_bits = 0;
229   // Prevent compiler warnings about cached_has_bits being unused
230   (void) cached_has_bits;

```

(continues on next page)

(continued from previous page)

```

231
232 cached_has_bits = _has_bits_[0];
233 if (cached_has_bits & 0x00000003u) {
234     if (cached_has_bits & 0x00000001u) {
235         number_.ClearNonDefaultToEmpty();
236     }
237     type_ = 1;
238 }
239 _has_bits_.Clear();
240 _internal_metadata_.Clear<:PROTOBUF_NAMESPACE_ID::UnknownFieldSet>();
241 }
242
243 const char* Person_PhoneNumber::_InternalParse(const char* ptr, ::_pbi::ParseContext*
↪ ctx) {
244 #define CHK_(x) if (PROTOBUF_PREDICT_FALSE(!(x))) goto failure
245 _Internal::HasBits has_bits{};
246 while (!ctx->Done(&ptr)) {
247     uint32_t tag;
248     ptr = ::_pbi::ReadTag(ptr, &tag);
249     switch (tag >> 3) {
250         // optional string number = 1;
251         case 1:
252             if (PROTOBUF_PREDICT_TRUE(static_cast<uint8_t>(tag) == 10)) {
253                 auto str = _internal_mutable_number();
254                 ptr = ::_pbi::InlineGreedyStringParser(str, ptr, ctx);
255                 CHK_(ptr);
256                 #ifndef NDEBUG
257                 ::_pbi::VerifyUTF8(str, "tutorial.Person.PhoneNumber.number");
258                 #endif // !NDEBUG
259             } else
260                 goto handle_unusual;
261             continue;
262         // optional .tutorial.Person.PhoneType type = 2 [default = HOME];
263         case 2:
264             if (PROTOBUF_PREDICT_TRUE(static_cast<uint8_t>(tag) == 16)) {
265                 uint64_t val = ::PROTOBUF_NAMESPACE_ID::internal::ReadVarint64(&ptr);
266                 CHK_(ptr);
267                 if (PROTOBUF_PREDICT_TRUE(::tutorial::Person_PhoneType_IsValid(val))) {
268                     _internal_set_type(static_cast<:tutorial::Person_PhoneType>(val));
269                 } else {
270                     ::PROTOBUF_NAMESPACE_ID::internal::WriteVarint(2, val, mutable_unknown_
↪ fields());
271                 }
272             } else
273                 goto handle_unusual;
274             continue;
275         default:
276             goto handle_unusual;
277     } // switch
278 handle_unusual:
279     if ((tag == 0) || ((tag & 7) == 4)) {
280         CHK_(ptr);

```

(continues on next page)

(continued from previous page)

```

281     ctx->SetLastTag(tag);
282     goto message_done;
283 }
284 ptr = UnknownFieldParse(
285     tag,
286     _internal_metadata_.mutable_unknown_fields<:PROTOBUF_NAMESPACE_
↪ ID::UnknownFieldSet>(),
287     ptr, ctx);
288     CHK_(ptr != nullptr);
289 } // while
290 message_done:
291     _has_bits_.Or(has_bits);
292     return ptr;
293 failure:
294     ptr = nullptr;
295     goto message_done;
296 #undef CHK_
297 }
298
299 uint8_t* Person_PhoneNumber::_InternalSerialize(
300     uint8_t* target, ::PROTOBUF_NAMESPACE_ID::io::EpsCopyOutputStream* stream) const {
301     // @@protoc_insertion_point(serialize_to_array_start:tutorial.Person.PhoneNumber)
302     uint32_t cached_has_bits = 0;
303     (void) cached_has_bits;
304
305     cached_has_bits = _has_bits_[0];
306     // optional string number = 1;
307     if (cached_has_bits & 0x00000001u) {
308         ::PROTOBUF_NAMESPACE_ID::internal::WireFormat::VerifyUTF8StringNamedField(
309             this->_internal_number().data(), static_cast<int>(this->_internal_number().
↪ length()),
310             ::PROTOBUF_NAMESPACE_ID::internal::WireFormat::SERIALIZE,
311             "tutorial.Person.PhoneNumber.number");
312         target = stream->WriteStringMaybeAliased(
313             1, this->_internal_number(), target);
314     }
315
316     // optional .tutorial.Person.PhoneType type = 2 [default = HOME];
317     if (cached_has_bits & 0x00000002u) {
318         target = stream->EnsureSpace(target);
319         target = ::_pbi::WireFormatLite::WriteEnumToArray(
320             2, this->_internal_type(), target);
321     }
322
323     if (PROTOBUF_PREDICT_FALSE(_internal_metadata_.have_unknown_fields())) {
324         target = ::_pbi::WireFormat::InternalSerializeUnknownFieldsToArray(
325             _internal_metadata_.unknown_fields<:PROTOBUF_NAMESPACE_ID::UnknownFieldSet>
↪ (::PROTOBUF_NAMESPACE_ID::UnknownFieldSet::default_instance), target, stream);
326     }
327     // @@protoc_insertion_point(serialize_to_array_end:tutorial.Person.PhoneNumber)
328     return target;
329 }

```

(continues on next page)

(continued from previous page)

```

330
331 size_t Person_PhoneNumber::ByteSizeLong() const {
332 // @@protoc_insertion_point(message_byte_size_start:tutorial.Person.PhoneNumber)
333     size_t total_size = 0;
334
335     uint32_t cached_has_bits = 0;
336     // Prevent compiler warnings about cached_has_bits being unused
337     (void) cached_has_bits;
338
339     cached_has_bits = _has_bits_[0];
340     if (cached_has_bits & 0x00000003u) {
341         // optional string number = 1;
342         if (cached_has_bits & 0x00000001u) {
343             total_size += 1 +
344                 ::PROTOBUF_NAMESPACE_ID::internal::WireFormatLite::StringSize(
345                 this->_internal_number());
346         }
347
348         // optional .tutorial.Person.PhoneType type = 2 [default = HOME];
349         if (cached_has_bits & 0x00000002u) {
350             total_size += 1 +
351                 ::_pbi::WireFormatLite::EnumSize(this->_internal_type());
352         }
353     }
354
355     return MaybeComputeUnknownFieldsSize(total_size, &_cached_size_);
356 }
357
358 const ::PROTOBUF_NAMESPACE_ID::Message::ClassData Person_PhoneNumber::_class_data_ = {
359     ::PROTOBUF_NAMESPACE_ID::Message::CopyWithSizeCheck,
360     Person_PhoneNumber::MergeImpl
361 };
362 const ::PROTOBUF_NAMESPACE_ID::Message::ClassData*Person_PhoneNumber::GetClassData() {
363     ↪ const { return &_class_data_; }
364
365 void Person_PhoneNumber::MergeImpl(::PROTOBUF_NAMESPACE_ID::Message* to,
366     const ::PROTOBUF_NAMESPACE_ID::Message& from) {
367     static_cast<Person_PhoneNumber *>(to)->MergeFrom(
368         static_cast<const Person_PhoneNumber &>(from));
369 }
370
371 void Person_PhoneNumber::MergeFrom(const Person_PhoneNumber& from) {
372 // @@protoc_insertion_point(class_specific_merge_from_start:tutorial.Person.PhoneNumber)
373     GOOGLE_DCHECK_NE(&from, this);
374     uint32_t cached_has_bits = 0;
375     (void) cached_has_bits;
376
377     cached_has_bits = from._has_bits_[0];
378     if (cached_has_bits & 0x00000003u) {
379         if (cached_has_bits & 0x00000001u) {
380             _internal_set_number(from._internal_number());

```

(continues on next page)

(continued from previous page)

```

381     }
382     if (cached_has_bits & 0x00000002u) {
383         type_ = from.type_;
384     }
385     _has_bits_[0] |= cached_has_bits;
386 }
387 _internal_metadata_.MergeFrom<::PROTOBUF_NAMESPACE_ID::UnknownFieldSet>(from._internal_
↪ metadata_);
388 }
389
390 void Person_PhoneNumber::CopyFrom(const Person_PhoneNumber& from) {
391     // @@protoc_insertion_point(class_specific_copy_from_start:tutorial.Person.PhoneNumber)
392     if (&from == this) return;
393     Clear();
394     MergeFrom(from);
395 }
396
397 bool Person_PhoneNumber::IsInitialized() const {
398     return true;
399 }
400
401 void Person_PhoneNumber::InternalSwap(Person_PhoneNumber* other) {
402     using std::swap;
403     auto* lhs_arena = GetArenaForAllocation();
404     auto* rhs_arena = other->GetArenaForAllocation();
405     _internal_metadata_.InternalSwap(&other->_internal_metadata_);
406     swap(_has_bits_[0], other->_has_bits_[0]);
407     ::PROTOBUF_NAMESPACE_ID::internal::ArenaStringPtr::InternalSwap(
408         &number_, lhs_arena,
409         &other->number_, rhs_arena
410     );
411     swap(type_, other->type_);
412 }
413
414 ::PROTOBUF_NAMESPACE_ID::Metadata Person_PhoneNumber::GetMetadata() const {
415     return ::_pbi::AssignDescriptors(
416         &descriptor_table_hello_2eproto_getter, &descriptor_table_hello_2eproto_once,
417         file_level_metadata_hello_2eproto[0]);
418 }
419
420 // =====
421
422 class Person::_Internal {
423 public:
424     using HasBits = decltype(std::declval<Person>()._has_bits_);
425     static void set_has_name(HasBits* has_bits) {
426         (*has_bits)[0] |= 1u;
427     }
428     static void set_has_id(HasBits* has_bits) {
429         (*has_bits)[0] |= 4u;
430     }
431     static void set_has_email(HasBits* has_bits) {

```

(continues on next page)

(continued from previous page)

```

432     (*has_bits)[0] |= 2u;
433 }
434 };
435
436 Person::Person(::PROTOBUF_NAMESPACE_ID::Arena* arena,
437               bool is_message_owned)
438   : ::PROTOBUF_NAMESPACE_ID::Message(arena, is_message_owned),
439   phones_(arena) {
440   SharedCtor();
441   // @@protoc_insertion_point(arena_constructor:tutorial.Person)
442 }
443 Person::Person(const Person& from)
444   : ::PROTOBUF_NAMESPACE_ID::Message(),
445   _has_bits_(from._has_bits_),
446   phones_(from.phones_) {
447   _internal_metadata_.MergeFrom<::PROTOBUF_NAMESPACE_ID::UnknownFieldSet>(from._internal_
↳ metadata_);
448   name_.InitDefault();
449   #ifdef PROTOBUF_FORCE_COPY_DEFAULT_STRING
450     name_.Set("", GetArenaForAllocation());
451   #endif // PROTOBUF_FORCE_COPY_DEFAULT_STRING
452   if (from._internal_has_name()) {
453     name_.Set(from._internal_name(),
454              GetArenaForAllocation());
455   }
456   email_.InitDefault();
457   #ifdef PROTOBUF_FORCE_COPY_DEFAULT_STRING
458     email_.Set("", GetArenaForAllocation());
459   #endif // PROTOBUF_FORCE_COPY_DEFAULT_STRING
460   if (from._internal_has_email()) {
461     email_.Set(from._internal_email(),
462               GetArenaForAllocation());
463   }
464   id_ = from.id_;
465   // @@protoc_insertion_point(copy_constructor:tutorial.Person)
466 }
467
468 inline void Person::SharedCtor() {
469   name_.InitDefault();
470   #ifdef PROTOBUF_FORCE_COPY_DEFAULT_STRING
471     name_.Set("", GetArenaForAllocation());
472   #endif // PROTOBUF_FORCE_COPY_DEFAULT_STRING
473   email_.InitDefault();
474   #ifdef PROTOBUF_FORCE_COPY_DEFAULT_STRING
475     email_.Set("", GetArenaForAllocation());
476   #endif // PROTOBUF_FORCE_COPY_DEFAULT_STRING
477   id_ = 0;
478 }
479
480 Person::~Person() {
481   // @@protoc_insertion_point(destructor:tutorial.Person)
482   if (auto *arena = _internal_metadata_.DeleteReturnArena<::PROTOBUF_NAMESPACE_
↳ ID::UnknownFieldSet>()) {

```

(continues on next page)

(continued from previous page)

```

483     (void)arena;
484     return;
485 }
486 SharedDtor();
487 }
488
489 inline void Person::SharedDtor() {
490     GOOGLE_DCHECK(GetArenaForAllocation() == nullptr);
491     name_.Destroy();
492     email_.Destroy();
493 }
494
495 void Person::SetCachedSize(int size) const {
496     _cached_size_.Set(size);
497 }
498
499 void Person::Clear() {
500     // @@protoc_insertion_point(message_clear_start:tutorial.Person)
501     uint32_t cached_has_bits = 0;
502     // Prevent compiler warnings about cached_has_bits being unused
503     (void) cached_has_bits;
504
505     phones_.Clear();
506     cached_has_bits = _has_bits_[0];
507     if (cached_has_bits & 0x000000003u) {
508         if (cached_has_bits & 0x000000001u) {
509             name_.ClearNonDefaultToEmpty();
510         }
511         if (cached_has_bits & 0x000000002u) {
512             email_.ClearNonDefaultToEmpty();
513         }
514     }
515     id_ = 0;
516     _has_bits_.Clear();
517     _internal_metadata_.Clear<::PROTOBUF_NAMESPACE_ID::UnknownFieldSet>();
518 }
519
520 const char* Person::_InternalParse(const char* ptr, ::_pbi::ParseContext* ctx) {
521     #define CHK_(x) if (PROTOBUF_PREDICT_FALSE(!(x))) goto failure
522     _Internal::HasBits has_bits{};
523     while (!ctx->Done(&ptr)) {
524         uint32_t tag;
525         ptr = ::_pbi::ReadTag(ptr, &tag);
526         switch (tag >> 3) {
527             // optional string name = 1;
528             case 1:
529                 if (PROTOBUF_PREDICT_TRUE(static_cast<uint8_t>(tag) == 10)) {
530                     auto str = _internal_mutable_name();
531                     ptr = ::_pbi::InlineGreedyStringParser(str, ptr, ctx);
532                     CHK_(ptr);
533                     #ifndef NDEBUG
534                     ::_pbi::VerifyUTF8(str, "tutorial.Person.name");
535                     #endif
536                 }
537             default:
538                 goto failure;
539         }
540     }
541     #undef CHK_
542     return ptr;
543 }

```

(continues on next page)

(continued from previous page)

```

535     #endif // !NDEBUG
536   } else
537     goto handle_unusual;
538   continue;
539   // optional int32 id = 2;
540   case 2:
541     if (PROTOBUF_PREDICT_TRUE(static_cast<uint8_t>(tag) == 16)) {
542       _Internal::set_has_id(&has_bits);
543       id = ::PROTOBUF_NAMESPACE_ID::internal::ReadVarint32(&ptr);
544       CHK_(ptr);
545     } else
546       goto handle_unusual;
547     continue;
548   // optional string email = 3;
549   case 3:
550     if (PROTOBUF_PREDICT_TRUE(static_cast<uint8_t>(tag) == 26)) {
551       auto str = _internal_mutable_email();
552       ptr = ::_pbi::InlineGreedyStringParser(str, ptr, ctx);
553       CHK_(ptr);
554       #ifndef NDEBUG
555       ::_pbi::VerifyUTF8(str, "tutorial.Person.email");
556       #endif // !NDEBUG
557     } else
558       goto handle_unusual;
559     continue;
560   // repeated .tutorial.Person.PhoneNumber phones = 4;
561   case 4:
562     if (PROTOBUF_PREDICT_TRUE(static_cast<uint8_t>(tag) == 34)) {
563       ptr -= 1;
564       do {
565         ptr += 1;
566         ptr = ctx->ParseMessage(_internal_add_phones(), ptr);
567         CHK_(ptr);
568         if (!ctx->DataAvailable(ptr)) break;
569       } while (::PROTOBUF_NAMESPACE_ID::internal::ExpectTag<34>(ptr));
570     } else
571       goto handle_unusual;
572     continue;
573   default:
574     goto handle_unusual;
575 } // switch
576 handle_unusual:
577 if ((tag == 0) || ((tag & 7) == 4)) {
578   CHK_(ptr);
579   ctx->SetLastTag(tag);
580   goto message_done;
581 }
582 ptr = UnknownFieldParse(
583   tag,
584   _internal_metadata_.mutable_unknown_fields<::PROTOBUF_NAMESPACE_
↵ ID::UnknownFieldSet>(),
585   ptr, ctx);

```

(continues on next page)

(continued from previous page)

```

586     CHK_(ptr != nullptr);
587 } // while
588 message_done:
589     _has_bits_.Or(has_bits);
590     return ptr;
591 failure:
592     ptr = nullptr;
593     goto message_done;
594 #undef CHK_
595 }
596
597 uint8_t* Person::_InternalSerialize(
598     uint8_t* target, ::PROTOBUF_NAMESPACE_ID::io::EpsCopyOutputStream* stream) const {
599     // @@protoc_insertion_point(serialize_to_array_start:tutorial.Person)
600     uint32_t cached_has_bits = 0;
601     (void) cached_has_bits;
602
603     cached_has_bits = _has_bits_[0];
604     // optional string name = 1;
605     if (cached_has_bits & 0x000000001u) {
606         ::PROTOBUF_NAMESPACE_ID::internal::WireFormat::VerifyUTF8StringNamedField(
607             this->_internal_name().data(), static_cast<int>(this->_internal_name().length()),
608             ::PROTOBUF_NAMESPACE_ID::internal::WireFormat::SERIALIZE,
609             "tutorial.Person.name");
610         target = stream->WriteStringMaybeAliased(
611             1, this->_internal_name(), target);
612     }
613
614     // optional int32 id = 2;
615     if (cached_has_bits & 0x000000004u) {
616         target = stream->EnsureSpace(target);
617         target = ::_pbi::WireFormatLite::WriteInt32ToArray(2, this->_internal_id(), target);
618     }
619
620     // optional string email = 3;
621     if (cached_has_bits & 0x000000002u) {
622         ::PROTOBUF_NAMESPACE_ID::internal::WireFormat::VerifyUTF8StringNamedField(
623             this->_internal_email().data(), static_cast<int>(this->_internal_email().length()),
624             ::PROTOBUF_NAMESPACE_ID::internal::WireFormat::SERIALIZE,
625             "tutorial.Person.email");
626         target = stream->WriteStringMaybeAliased(
627             3, this->_internal_email(), target);
628     }
629
630     // repeated .tutorial.Person.PhoneNumber phones = 4;
631     for (unsigned i = 0,
632         n = static_cast<unsigned>(this->_internal_phones_size()); i < n; i++) {
633         const auto& repfield = this->_internal_phones(i);
634         target = ::PROTOBUF_NAMESPACE_ID::internal::WireFormatLite::
635             InternalWriteMessage(4, repfield, repfield.GetCachedSize(), target, stream);
636     }
637

```

(continues on next page)

(continued from previous page)

```

638     if (PROTOBUF_PREDICT_FALSE(_internal_metadata_.have_unknown_fields())) {
639         target = ::_pbi::WireFormat::InternalSerializeUnknownFieldsToArray(
640             _internal_metadata_.unknown_fields<::PROTOBUF_NAMESPACE_ID::UnknownFieldSet>
641             ↪ (::PROTOBUF_NAMESPACE_ID::UnknownFieldSet::default_instance), target, stream);
642     }
643     // @@protoc_insertion_point(serialize_to_array_end:tutorial.Person)
644     return target;
645 }
646
647 size_t Person::ByteSizeLong() const {
648     // @@protoc_insertion_point(message_byte_size_start:tutorial.Person)
649     size_t total_size = 0;
650
651     uint32_t cached_has_bits = 0;
652     // Prevent compiler warnings about cached_has_bits being unused
653     (void) cached_has_bits;
654
655     // repeated .tutorial.Person.PhoneNumber phones = 4;
656     total_size += 1UL * this->_internal_phones_size();
657     for (const auto& msg : this->phones_) {
658         total_size +=
659             ::PROTOBUF_NAMESPACE_ID::internal::WireFormatLite::MessageSize(msg);
660     }
661
662     cached_has_bits = _has_bits_[0];
663     if (cached_has_bits & 0x000000007u) {
664         // optional string name = 1;
665         if (cached_has_bits & 0x000000001u) {
666             total_size += 1 +
667                 ::PROTOBUF_NAMESPACE_ID::internal::WireFormatLite::StringSize(
668                     this->_internal_name());
669         }
670
671         // optional string email = 3;
672         if (cached_has_bits & 0x000000002u) {
673             total_size += 1 +
674                 ::PROTOBUF_NAMESPACE_ID::internal::WireFormatLite::StringSize(
675                     this->_internal_email());
676         }
677
678         // optional int32 id = 2;
679         if (cached_has_bits & 0x000000004u) {
680             total_size += ::_pbi::WireFormatLite::Int32SizePlusOne(this->_internal_id());
681         }
682     }
683     return MaybeComputeUnknownFieldsSize(total_size, &_cached_size_);
684 }
685
686 const ::PROTOBUF_NAMESPACE_ID::Message::ClassData Person::_class_data_ = {
687     ::PROTOBUF_NAMESPACE_ID::Message::CopyWithSizeCheck,
688     Person::MergeImpl

```

(continues on next page)

(continued from previous page)

```

689 };
690 const ::PROTOBUF_NAMESPACE_ID::Message::ClassData*Person::GetClassData() const { return &
↳_class_data_; }
691
692 void Person::MergeImpl(::PROTOBUF_NAMESPACE_ID::Message* to,
693                       const ::PROTOBUF_NAMESPACE_ID::Message& from) {
694     static_cast<Person*>(to)->MergeFrom(
695         static_cast<const Person&>(from));
696 }
697
698
699 void Person::MergeFrom(const Person& from) {
700     // @@protoc_insertion_point(class_specific_merge_from_start:tutorial.Person)
701     GOOGLE_DCHECK_NE(&from, this);
702     uint32_t cached_has_bits = 0;
703     (void) cached_has_bits;
704
705     phones_.MergeFrom(from.phones_);
706     cached_has_bits = from._has_bits_[0];
707     if (cached_has_bits & 0x00000007u) {
708         if (cached_has_bits & 0x00000001u) {
709             _internal_set_name(from._internal_name());
710         }
711         if (cached_has_bits & 0x00000002u) {
712             _internal_set_email(from._internal_email());
713         }
714         if (cached_has_bits & 0x00000004u) {
715             id_ = from.id_;
716         }
717         _has_bits_[0] |= cached_has_bits;
718     }
719     _internal_metadata_.MergeFrom<::PROTOBUF_NAMESPACE_ID::UnknownFieldSet>(from._internal_
↳metadata_);
720 }
721
722 void Person::CopyFrom(const Person& from) {
723     // @@protoc_insertion_point(class_specific_copy_from_start:tutorial.Person)
724     if (&from == this) return;
725     Clear();
726     MergeFrom(from);
727 }
728
729 bool Person::IsInitialized() const {
730     return true;
731 }
732
733 void Person::InternalSwap(Person* other) {
734     using std::swap;
735     auto* lhs_arena = GetArenaForAllocation();
736     auto* rhs_arena = other->GetArenaForAllocation();
737     _internal_metadata_.InternalSwap(&other->_internal_metadata_);
738     swap(_has_bits_[0], other->_has_bits_[0]);

```

(continues on next page)

(continued from previous page)

```

739 phones_.InternalSwap(&other->phones_);
740 ::PROTOBUF_NAMESPACE_ID::internal::ArenaStringPtr::InternalSwap(
741     &name_, lhs_arena,
742     &other->name_, rhs_arena
743 );
744 ::PROTOBUF_NAMESPACE_ID::internal::ArenaStringPtr::InternalSwap(
745     &email_, lhs_arena,
746     &other->email_, rhs_arena
747 );
748 swap(id_, other->id_);
749 }
750
751 ::PROTOBUF_NAMESPACE_ID::Metadata Person::GetMetadata() const {
752     return ::_pbi::AssignDescriptors(
753         &descriptor_table_hello_2eproto_getter, &descriptor_table_hello_2eproto_once,
754         file_level_metadata_hello_2eproto[1]);
755 }
756
757 // =====
758
759 class AddressBook::_Internal {
760 public:
761 };
762
763 AddressBook::AddressBook(::PROTOBUF_NAMESPACE_ID::Arena* arena,
764                          bool is_message_owned)
765   : ::PROTOBUF_NAMESPACE_ID::Message(arena, is_message_owned),
766   people_(arena) {
767   SharedCtor();
768   // @@protoc_insertion_point(arena_constructor:tutorial.AddressBook)
769 }
770 AddressBook::AddressBook(const AddressBook& from)
771   : ::PROTOBUF_NAMESPACE_ID::Message(),
772   people_(from.people_) {
773   _internal_metadata_.MergeFrom<::PROTOBUF_NAMESPACE_ID::UnknownFieldSet>(from._internal_
774 ↪ metadata_);
775   // @@protoc_insertion_point(copy_constructor:tutorial.AddressBook)
776 }
777
778 inline void AddressBook::SharedCtor() {
779 }
780
781 AddressBook::~AddressBook() {
782   // @@protoc_insertion_point(destructor:tutorial.AddressBook)
783   if (auto *arena = _internal_metadata_.DeleteReturnArena<::PROTOBUF_NAMESPACE_
784 ↪ ID::UnknownFieldSet>()) {
785     (void)arena;
786     return;
787   }
788   SharedDtor();
789 }

```

(continues on next page)

(continued from previous page)

```

789 inline void AddressBook::SharedDtor() {
790     GOOGLE_DCHECK(GetArenaForAllocation() == nullptr);
791 }
792
793 void AddressBook::SetCachedSize(int size) const {
794     _cached_size_.Set(size);
795 }
796
797 void AddressBook::Clear() {
798     // @@protoc_insertion_point(message_clear_start:tutorial.AddressBook)
799     uint32_t cached_has_bits = 0;
800     // Prevent compiler warnings about cached_has_bits being unused
801     (void) cached_has_bits;
802
803     people_.Clear();
804     _internal_metadata_.Clear<:PROTOBUF_NAMESPACE_ID::UnknownFieldSet>();
805 }
806
807 const char* AddressBook::_InternalParse(const char* ptr, ::_pbi::ParseContext* ctx) {
808     #define CHK_(x) if (PROTOBUF_PREDICT_FALSE(!(x))) goto failure
809     while (!ctx->Done(&ptr)) {
810         uint32_t tag;
811         ptr = ::_pbi::ReadTag(ptr, &tag);
812         switch (tag >> 3) {
813             // repeated .tutorial.Person people = 1;
814             case 1:
815                 if (PROTOBUF_PREDICT_TRUE(static_cast<uint8_t>(tag) == 10)) {
816                     ptr -= 1;
817                     do {
818                         ptr += 1;
819                         ptr = ctx->ParseMessage(_internal_add_people(), ptr);
820                         CHK_(ptr);
821                         if (!ctx->DataAvailable(ptr)) break;
822                     } while (::PROTOBUF_NAMESPACE_ID::internal::ExpectTag<10>(ptr));
823                 } else
824                     goto handle_unusual;
825                 continue;
826             default:
827                 goto handle_unusual;
828         } // switch
829     handle_unusual:
830         if ((tag == 0) || ((tag & 7) == 4)) {
831             CHK_(ptr);
832             ctx->SetLastTag(tag);
833             goto message_done;
834         }
835         ptr = UnknownFieldParse(
836             tag,
837             _internal_metadata_.mutable_unknown_fields<:PROTOBUF_NAMESPACE_
838             ID::UnknownFieldSet>(),
839             ptr, ctx);
840         CHK_(ptr != nullptr);

```

(continues on next page)

(continued from previous page)

```

840     } // while
841 message_done:
842     return ptr;
843 failure:
844     ptr = nullptr;
845     goto message_done;
846 #undef CHK_
847 }
848
849 uint8_t* AddressBook::_InternalSerialize(
850     uint8_t* target, ::PROTOBUF_NAMESPACE_ID::io::EpsCopyOutputStream* stream) const {
851     // @@protoc_insertion_point(serialize_to_array_start:tutorial.AddressBook)
852     uint32_t cached_has_bits = 0;
853     (void) cached_has_bits;
854
855     // repeated .tutorial.Person people = 1;
856     for (unsigned i = 0,
857          n = static_cast<unsigned>(this->_internal_people_size()); i < n; i++) {
858         const auto& repfield = this->_internal_people(i);
859         target = ::PROTOBUF_NAMESPACE_ID::internal::WireFormatLite::
860             InternalWriteMessage(1, repfield, repfield.GetCachedSize(), target, stream);
861     }
862
863     if (PROTOBUF_PREDICT_FALSE(_internal_metadata_.have_unknown_fields())) {
864         target = ::_pbi::WireFormat::InternalSerializeUnknownFieldsToArray(
865             _internal_metadata_.unknown_fields<::PROTOBUF_NAMESPACE_ID::UnknownFieldSet>
866             ↪ (::PROTOBUF_NAMESPACE_ID::UnknownFieldSet::default_instance), target, stream);
867     }
868     // @@protoc_insertion_point(serialize_to_array_end:tutorial.AddressBook)
869     return target;
870 }
871
872 size_t AddressBook::ByteSizeLong() const {
873     // @@protoc_insertion_point(message_byte_size_start:tutorial.AddressBook)
874     size_t total_size = 0;
875
876     uint32_t cached_has_bits = 0;
877     // Prevent compiler warnings about cached_has_bits being unused
878     (void) cached_has_bits;
879
880     // repeated .tutorial.Person people = 1;
881     total_size += 1UL * this->_internal_people_size();
882     for (const auto& msg : this->people_) {
883         total_size +=
884             ::PROTOBUF_NAMESPACE_ID::internal::WireFormatLite::MessageSize(msg);
885     }
886
887     return MaybeComputeUnknownFieldsSize(total_size, &_cached_size_);
888 }
889
890 const ::PROTOBUF_NAMESPACE_ID::Message::ClassData AddressBook::_class_data_ = {
891     ::PROTOBUF_NAMESPACE_ID::Message::CopyWithSizeCheck,

```

(continues on next page)

(continued from previous page)

```

891     AddressBook::MergeImpl
892 };
893 const ::PROTOBUF_NAMESPACE_ID::Message::ClassData*AddressBook::GetClassData() const {
894     ↪return &_class_data_; }
895
896 void AddressBook::MergeImpl(::PROTOBUF_NAMESPACE_ID::Message* to,
897                             const ::PROTOBUF_NAMESPACE_ID::Message& from) {
898     static_cast<AddressBook*>(to)->MergeFrom(
899         static_cast<const AddressBook&>(from));
900 }
901
902 void AddressBook::MergeFrom(const AddressBook& from) {
903     // @@protoc_insertion_point(class_specific_merge_from_start:tutorial.AddressBook)
904     GOOGLE_DCHECK_NE(&from, this);
905     uint32_t cached_has_bits = 0;
906     (void) cached_has_bits;
907
908     people_.MergeFrom(from.people_);
909     _internal_metadata_.MergeFrom<::PROTOBUF_NAMESPACE_ID::UnknownFieldSet>(from._internal_
910     ↪metadata_);
911 }
912
913 void AddressBook::CopyFrom(const AddressBook& from) {
914     // @@protoc_insertion_point(class_specific_copy_from_start:tutorial.AddressBook)
915     if (&from == this) return;
916     Clear();
917     MergeFrom(from);
918 }
919
920 bool AddressBook::IsInitialized() const {
921     return true;
922 }
923
924 void AddressBook::InternalSwap(AddressBook* other) {
925     using std::swap;
926     _internal_metadata_.InternalSwap(&other->_internal_metadata_);
927     people_.InternalSwap(&other->people_);
928 }
929
930 ::PROTOBUF_NAMESPACE_ID::Metadata AddressBook::GetMetadata() const {
931     return ::_pbi::AssignDescriptors(
932         &descriptor_table_hello_2eproto_getter, &descriptor_table_hello_2eproto_once,
933         file_level_metadata_hello_2eproto[2]);
934 }
935
936 // @@protoc_insertion_point(namespace_scope)
937 } // namespace tutorial
938 PROTOBUF_NAMESPACE_OPEN
939 template<> PROTOBUF_NOINLINE ::tutorial::Person_PhoneNumber*
940 Arena::CreateMaybeMessage< ::tutorial::Person_PhoneNumber >(Arena* arena) {
941     return Arena::CreateMessageInternal< ::tutorial::Person_PhoneNumber >(arena);

```

(continues on next page)

(continued from previous page)

```
941 }
942 template<> PROTOBUF_NOINLINE ::tutorial::Person*
943 Arena::CreateMaybeMessage< ::tutorial::Person >(Arena* arena) {
944     return Arena::CreateMessageInternal< ::tutorial::Person >(arena);
945 }
946 template<> PROTOBUF_NOINLINE ::tutorial::AddressBook*
947 Arena::CreateMaybeMessage< ::tutorial::AddressBook >(Arena* arena) {
948     return Arena::CreateMessageInternal< ::tutorial::AddressBook >(arena);
949 }
950 PROTOBUF_NAMESPACE_CLOSE
951
952 // @@protoc_insertion_point(global_scope)
953 #include <google/protobuf/port_undef.inc>
```


16.1 Install

See <https://grpc.io/docs/languages/cpp/quickstart/>

```
git clone --recurse-submodules -b v1.46.3 --depth 1 --shallow-submodules https://github.
↳ com/grpc/grpc
mkdir build
cd build
cmake -Dgrpc_INSTALL=ON -Dgrpc_BUILD_TESTS=OFF -DCMAKE_INSTALL_PREFIX=/ceph-fj/fangjun/
↳ software/grpc-1.46.3 .. 2>&1 | tee cmake-configure-1.log
make -j20 2>&1 | tee make-1.log
make install 2>&1 | tee make-2.log
```


17.1 TODOs

- Striking gold in binutils
<https://lwn.net/Articles/274859/>
- A ToC of the 20 part linker essay
<https://lwn.net/Articles/276782/>

There are other resources for linkers and loaders, see

- Executables linking and loading reading
<http://research.tedneward.com/reading/software/linking-loading/index.html>
- Optimizing real-world applications with GCC Link Time Optimization
<https://pdfs.semanticscholar.org/6adf/872e3533f40a607f39cdeaf264585efde9af.pdf>
by Honza Hubicka, whose scholar page is <https://scholar.google.cz/citations?user=vhXJ0JEAAAAJ&hl=en>

LINKER AND LOADER

18.1 References

- A ToC of the 20 part linker essay
<https://lwn.net/Articles/276782/>, which is written by Ian Lance Taylor
 1. Introduction, personal history, first half of what's-a-linker
 2. What's-a-linker: Dynamic linking, linker data types, linker operation
 3. Address spaces, Object file formats
 4. Shared Libraries
 5. More Shared Libraries -- specifically, linker implementation; ELF Symbols
- <https://www.ucw.cz/~hubicka/>, author of the gold linker
- Rod Evans: Surfing With a Linker Alien <http://www.linker-aliens.org/blogs/rie/>
 1. Hello there
- Michael Walker's Weblog <http://www.linker-aliens.org/blogs/msw/>
 1. Hello World
 2. How to build a Shared Library
 3. Library Bindings - let's be a little bit more precise shall we

Note: It shows the usage of LD_DEBUG, pldd, ldd, pgrep elfdump.

- Solaris Linking Blogs (Combined Index) <http://www.linker-aliens.org/blogs/>
- LD_LIBRARY_PATH - just say no
http://www.linker-aliens.org/blogs/rie/entry/tt_ld_library_path_tt/
- <https://github.com/berkus/odin/blob/master/tools/sjofn/sjofn.c>
An ELF linker. Read its source code!

18.2 Questions

1. How to view PLT?
2. How to view the relocation information? How many types of relocation are there?
3. What PIC code and non-PIC code look like?
4. What is lazy binding and how to use LD_BIND_NOW?
5. What is PLT and GOT?

19.1 aishell

19.1.1 AM training

The first one was added on 2019-02-01.

`asr_train.py` is in `espnet/bin/asr_train.py`, which invokes `espnet.asr.pytorch_backend.asr.train`.

The model is from `espnet.nets.pytorch_backend.e2e_asr.E2E`.

The encoder type *vggblstm*, 3 layers, hidden dim, 1024, proj dim 1024, subsampling 1_2_2_1_1.

Command is:

```
asr_train.py \  
  --config conf/train.yaml \  
  --preprocess-conf \  
  --ngpu 1 \  
  --backend pytorch \  
  --outdir exp/xxx \  
  --debugmode 1 \  
  --dict data/lang_char/train_sp_units.txt \  
  --minibatches 0 \  
  --verbose 0 \  
  --resume \  
  --train-json xxx/data.json \  
  --valid-json yyy/data.json
```


CMAKE

20.1 Tutorials

- <https://cmake.org/cmake/help/latest/guide/tutorial/index.html>

20.2 Install

Go to <https://github.com/Kitware/CMake/releases> for download.

```
wget https://github.com/Kitware/CMake/releases/download/v3.10.3/cmake-3.10.3-Linux-x86_
↪64.sh
chmod +x ./cmake-3.10.3-Linux-x86_64.sh
./cmake-3.10.3-Linux-x86_64.sh --help
mkdir /path/to/software/cmake-3.10.3
./cmake-3.10.3-Linux-x86_64.sh --prefix=/path/to/software/cmake-3.10.3 --skip-license
export PATH=/path/to/software/cmake-3.10.3/bin:$PATH
```


HUGGINGFACE

21.1 spaces

21.1.1 Install client API

```
pip install huggingface_hub
```

```
(py38) kuangfangjun:t$ python3
Python 3.8.0 (default, Oct 28 2019, 16:14:01)
[GCC 8.3.0] on linux
Type "help", "copyright", "credits" or "license" for more information.
>>> from huggingface_hub import hf_hub_download
>>> hf_hub_download(repo_id="google/pegasus-xsum", filename="config.json")
Downloading: 100%|-----| 1.39k/1.39k [00:00<00:00, 1.12MB/s]
'/root/fangjun/.cache/huggingface/hub/models--google--pegasus-xsum/snapshots/
a0aa5531c00f59a32a167b75130805098b046f9c/config.json'
>>>
```

21.1.2 gradio

- <https://huggingface.co/spaces/alphacep/asr>
- <https://huggingface.co/spaces/jonatasgrosman/asr>
- <https://github.com/gradio-app/gradio/issues/1359>
- <https://huggingface.co/spaces/Gradio-Blocks/neon-tts-plugin-coqui/blob/main/app.py>, css styles

EECS E6870 SPEECH RECOGNITION

22.1 Notes

- <https://www.ee.columbia.edu/~stanchen/spring16/e6870/outline.html>
 - username: speech
 - password: pythonrules

23.1 Hello

```
git clone https://github.com/tencent/ncnn
cd ncnn
git checkout 7b4e77671a4457a414b60cee5425758212e725cf
mkdir build
cd build
cmake -DCMAKE_PREFIX_PATH=/ceph-fj/fangjun/software/protobuf-3.20.1-cmake ..
```

We have to make the following changes:

Listing 1: ./code/hello/7b4e77.diff

```
1 diff --git a/tools/CMakeLists.txt b/tools/CMakeLists.txt
2 index 0b710050..e1a5b3d0 100644
3 --- a/tools/CMakeLists.txt
4 +++ b/tools/CMakeLists.txt
5 @@ -8,6 +8,7 @@ include_directories(${CMAKE_CURRENT_BINARY_DIR})
6     protobuf_generate_cpp(CAFFE_PROTO_SRCS CAFFE_PROTO_HDRS caffe.proto)
7
8     add_executable(caffe2ncnn caffe2ncnn.cpp ${CAFFE_PROTO_SRCS} ${CAFFE_PROTO_HDRS})
9 +include_directories(${Protobuf_INCLUDE_DIR})
10
11     target_link_libraries(caffe2ncnn ${PROTOBUF_LIBRARIES})
12
13 diff --git a/tools/caffe2ncnn.cpp b/tools/caffe2ncnn.cpp
14 index 0eff756a..229cc653 100644
15 --- a/tools/caffe2ncnn.cpp
16 +++ b/tools/caffe2ncnn.cpp
17 @@ -193,7 +193,7 @@ static bool read_proto_from_binary(const char* filepath,
18     google::protobuf::Message
19     google::protobuf::io::InputStream input(&fs);
20     google::protobuf::io::CodedInputStream codedstr(&input);
21
22 -    codedstr.SetTotalBytesLimit(INT_MAX, INT_MAX / 2);
23 +    codedstr.SetTotalBytesLimit(INT_MAX);
24
25     bool success = message->ParseFromCodedStream(&codedstr);
```

23.2 ncnn::Mat

- Use CHW format
- Support reference counting, like a smart pointer.

24.1 Installation

Refer to <https://llvm.org/docs/GettingStarted.html#requirements>

<https://llvm.org/docs/GettingStarted.html#getting-a-modern-host-c-toolchain> describes how to install GCC from source.

Use of a user provided GCC:

```
mkdir build
cd build
CC=$HOME/toolchains/bin/gcc CXX=$HOME/toolchains/bin/g++ \
  cmake .. -DCMAKE_CXX_LINK_FLAGS="-Wl,-rpath,$HOME/toolchains/lib64 -L$HOME/toolchains/
  ↳ lib64"
```

Useful tools that can be found in *build/bin*:

```
$ llvm-config --cxxflags
-I/ceph-fj/fangjun/open-source-2/llvm-project/llvm/include -I/ceph-fj/fangjun/open-
↳ source-2/llvm-project/build/include -std=c++14 -fno-exceptions -fno-rtti -D_GNU_
↳ SOURCE -D__STDC_CONSTANT_MACROS -D__STDC_FORMAT_MACROS -D__STDC_LIMIT_MACROS

$ llvm-config --libdir
/ceph-fj/fangjun/open-source-2/llvm-project/build/lib

$ llvm-config --cflags
-I/ceph-fj/fangjun/open-source-2/llvm-project/llvm/include -I/ceph-fj/fangjun/open-
↳ source-2/llvm-project/build/include -D_GNU_SOURCE -D__STDC_CONSTANT_MACROS -D__STDC_
↳ FORMAT_MACROS -D__STDC_LIMIT_MACROS

$ llvm-config --ldflags
-L/ceph-fj/fangjun/open-source-2/llvm-project/build/lib

$ llvm-config --src-root
/ceph-fj/fangjun/open-source-2/llvm-project/llvm

$ llvm-config --obj-root
/ceph-fj/fangjun/open-source-2/llvm-project/build

$ llvm-config --version
15.0.0git
```

(continues on next page)

(continued from previous page)

```
$ llvm-config --bindir  
/ceph-fj/fangjun/open-source-2/llvm-project/build/bin
```

24.2 ninja

```
pip install ninja
```

```
ninja
```

will look for the file *\$PWD/build.ninja*

```
ninja --help  
ninja -C build -j 20  
ninja -t targets  
ninja -t clean  
ninja -t cleandead  
  
ninja -v # be verbose while compiling files  
  
# suppose hello is a target  
ninja -v hello  
ninja -v -t clean hello  
  
ninja -n -v hello # dry run
```

24.3 Documentation

- Coding standard
<https://llvm.org/docs/CodingStandards.html>
- LLVM Developer Policy
<https://llvm.org/docs/DeveloperPolicy.html>
- doxygen doc
<https://llvm.org/doxygen/>
- <http://www.aosabook.org/en/llvm.html>

24.4 Intermediate representation

```
clang --help
```

```
-emit-llvm  Use the LLVM representation for assembler and object files  
-S          Only run preprocess and compilation steps
```

- `clang -S -emit-llvm ex.c` generates a text file `ex.ll`.
- `clang -c -emit-llvm ex.c` generates a binary file `ex.bc`.
- `llvm-dis ex.bc` generates a file `ex.ll`, which is identical with the file generated using `clang -S -emit-llvm ex.c`.`
- `llvm-as ex.ll` generates a file `ex.bc`, which is identical with the file generated using `clang -c -emit-llvm ex.c`.
- `llc ex.ll` generates the assembly file `ex.s`
- `lli ex.ll` can run this file. Use `echo $?` to see the return value.

See https://llvm.org/devmtg/2019-04/slides/Tutorial-Bridgers-LLVM_IR_tutorial.pdf.