
notes

fangjun

May 08, 2022

CONTENTS:

1	Sphinx	3
1.1	Setup	3
2	git	5
2.1	Commands	5
2.1.1	rev-parse	5
3	docker	7
3.1	Installation	7
3.1.1	macos	7
4	LaTeX	9
4.1	TikZ	9
4.1.1	Basics	9
5	Kaldi	11
5.1	Decoding	11
6	Python	13
6.1	asyncio	13
6.1.1	Hello World	13
6.1.2	References	13
6.2	argv	13
7	bash	15
7.1	sort	15
7.2	echo	15
8	CUDA	17
8.1	Installation	17
8.1.1	CUDA 10.1.243	17
8.1.2	CUDA 11.0.3	17
8.1.3	CUDA 11.3.1	18
8.1.4	CUDA 11.5.2	18
8.1.5	CUDA 11.6.1	18
9	torch	19
9.1	DDP	19
9.1.1	Initialization	19
10	java	21

10.1	Install	21
10.1.1	formatter	21
10.1.2	JDK	21
10.2	Hello world	22
10.3	Reference	23
11	javascript	25
11.1	Hello world	25
11.2	TODOs	25
12	HTML	27
12.1	Hello world	27
12.1.1	comments	27
12.1.2	images	27
12.1.3	ordered lists	27
12.1.4	unordered lists	28
12.1.5	links	28
12.2	References	28
13	css	29
13.1	Hello world	29
13.1.1	Selector	29
13.2	References	29

Download this website in a single [pdf file](#).

This page describes how this website is setup.

1.1 Setup

1. Install the dependencies in `./docs/requirements.txt`.

```
sphinx==4.3.2
sphinx-autodoc-typehints==1.12.0
sphinx_rtd_theme==1.0.0
sphinxcontrib-bibtex==2.4.1
```

2. Use `sphinx-quickstart` to generate the skeleton. When it prompts:

```
Separate source and build directories(y/n)
```

Answer yes.

3. Edit `docs/source/conf.py` and add the following lines to it:

```
import sphinx_rtd_theme
extensions = [
    'sphinx.ext.autodoc',
    'sphinx.ext.autosummary',
    'sphinx.ext.githubpages',
    'sphinx.ext.mathjax',
    'sphinx.ext.napoleon',
    'sphinx.ext.todo',
    'sphinx.ext.viewcode',
    'sphinxcontrib.bibtex',
]

html_theme = 'sphinx_rtd_theme'

master_doc = 'index'
pygments_style = 'sphinx'
html_theme_path = [sphinx_rtd_theme.get_html_theme_path()]
smartquotes = False
html_show_sourcelink = True

html_context = {
```

(continues on next page)

(continued from previous page)

```
'display_github': True,
'github_user': 'csu-fangjun',
'github_repo': 'notes',
'github_version': 'master',
'conf_py_path': '/docs/source/',
}

html_theme_options = {
    'logo_only': False,
    'display_version': True,
    'prev_next_buttons_location': 'bottom',
    'style_external_links': True,
}
latex_engine = 'xelatex'
```

4. To generate the notes in pdf format, use `make latex`, which generates lots of `tex` files in `./build/latex`. Switch to `build/latex` and run `make`. Assume that you have installed the software to compile `tex` files. It will generate `notes.pdf`.

This page describes commonly used git commands.

2.1 Commands

2.1.1 rev-parse

It is quite common to get the root directory of the repository with the command:

```
git rev-parse --show-toplevel
```

For instance, the above command executed in this repository prints something like as follows:

```
/xxx/notes
```

The following shows its usage in a Python script:

```
#!/usr/bin/env python3

import subprocess

d = (
    subprocess.check_output(["git", "rev-parse", "--show-toplevel"])
    .decode("ascii")
    .strip() # remove the trailing \n
)
print(d) # /path/to/notes
```

It can also be used in bash script:

```
root_dir=$(git rev-parse --show-toplevel)
echo "root_dir ${root_dir}"
```

help git-rev-parse outputs helpful information for git rev-parse. In particular, it explains the differences among HEAD~, HEAD~n, HEAD^, and HEAD^n. The following shows the help information about it:

```
<rev>^[<n>], e.g. HEAD^, v1.5.1^0
  A suffix ^ to a revision parameter means the first parent of that commit object. ^
  ↪<n> means the <n>th parent
```


(continues on next page)

(continued from previous page)

(i.e. `<rev>^` is equivalent to `<rev>^1`). As a special rule, `<rev>^0` means the commit itself and is used when `<rev>` is the object name of a tag object that refers to a commit object.

`<rev>~[<n>]`, e.g. `HEAD~`, `master~3`

A suffix `~` to a revision parameter means the first parent of that commit object. A suffix `~<n>` to a revision parameter means the commit object that is the `<n>`th generation ancestor of the named commit object, following only the first parents. I.e. `<rev>~3` is equivalent to `<rev>^^^` which is equivalent to `<rev>^1^1^1`. See below for an illustration of the usage of this form.



$A = A^0$
 $B = A^1 = A^1_1 = A_{\sim 1}$
 $C = A^2$
 $D = A^{11} = A^{1^1_1} = A_{\sim 2}$
 $E = B^2 = A^{12}$
 $F = B^3 = A^{13}$
 $G = A^{111} = A^{1^1_1^1} = A_{\sim 3}$
 $H = D^2 = B^{12} = A^{112} = A_{\sim 2}^2$
 $I = F^1 = B^{13} = A^{113}$
 $J = F^2 = B^{132} = A^{1132}$

3.1 Installation

3.1.1 macos

Refer to <https://docs.docker.com/desktop/mac/install/>.

4.1 TikZ

4.1.1 Basics

This page describes commonly used git commands.

5.1 Decoding

```
CompactLattice compact_lat;  
decoder.GetLattice(true, &compact_lat);  
  
CompactLattice compact_best_path;  
CompactLatticeShortestPath(compact_lat, &compact_best_path);  
  
Lattice best_path;  
ConvertLattice(compact_best_path, best_path);  
  
std::vector<int32_t> tokens;  
std::vector<int32_t> words;  
LatticeWeight weight;  
GetLinearSymbolSequence(best_path, &tokens, &words, &weight);
```

- `decoder/simple-decoder.{h,cc}`

6.1 asyncio

6.1.1 Hello World

6.1.2 References

- PEP 234 – Iterators
<https://peps.python.org/pep-0234/>
- Why does defining `__getitem__` on a class make it iterable in python?
<https://localcoder.org/why-does-defining-getitem-on-a-class-make-it-iterable-in-python>
- PEP 255 – Simple Generators
<https://peps.python.org/pep-0255/>
- Curious Course on Coroutines and Concurrency
https://www.youtube.com/watch?v=Z_OAlhXziw&ab_channel=DavidBeazley
By David Beazley.
- Generator Tricks for Systems Programmers
<https://www.dabeaz.com/generators2/>
- Generators: The Final Frontier
<https://www.youtube.com/watch?v=5-qadlG7tWo&ab_channel=DavidBeazley>
By David Beazley.

6.2 argv

From the doc <https://docs.python.org/3/library/sys.html>:

The `list` of command line arguments passed to a Python script. `argv[0]` **is** the script name (it **is** operating system dependent whether this **is** a full pathname **or not**). If the command was executed using the `-c` command line option to the interpreter, `argv[0]` **is set** to the string `'-c'`. If no script name was passed to the Python interpreter, `argv[0]` **is** the empty string.

Note that `argv` is at least of size 1, though `argv[0]` may be an empty string.

```
import sys
print(sys.argv)
```

7.1 sort

Sort files in the folder `t`. The filename has the pattern `xxx.n.txt`, where `n` is some numerical value. Also, exclude `xxx.100.txt`.

```
find ./t -name "xxx*.txt" ! -name "xxx.100.txt" -print0 | sort -z -t. -k2 -n | xargs -r0
```

7.2 echo

Generate a binary file:

```
echo -n -e '\x30\x31\x32' > a.bin  
hexdump a.bin
```


CUDA

8.1 Installation

8.1.1 CUDA 10.1.243

```
./cuda_10.1.243_418.87.00_linux.run --silent --toolkit --installpath=/ceph-data4/fangjun/  
↪software/cuda-10.1.243 --no-opengl-libs --no-drm --no-man-page  
  
# Install cuDNN  
cd /ceph-data4/fangjun/software/cuda-10.1.243  
tar xvf /ceph-sh0/fangjun/cudnn/cudnn-10.1-linux-x64-v8.0.4.30.tgz --strip-components=1
```

```
#!/usr/bin/env bash  
  
export CUDA_HOME=/ceph-data4/fangjun/software/cuda-10.1.243  
export PATH=$CUDA_HOME/bin:$PATH  
export LD_LIBRARY_PATH=$CUDA_HOME/lib64:$LD_LIBRARY_PATH  
  
# See /ceph-fj/fangjun/py38/lib/python3.8/site-packages/torch/share/cmake/Caffe2/Modules_  
↪CUDA_fix/upstream/FindCUDA.cmake  
export CUDA_TOOLKIT_ROOT_DIR=$CUDA_HOME  
export CUDA_TOOLKIT_ROOT=$CUDA_HOME  
export CUDA_BIN_PATH=$CUDA_HOME  
export CUDA_PATH=$CUDA_HOME  
export CUDA_INC_PATH=$CUDA_HOME/targets/x86_64-linux
```

8.1.2 CUDA 11.0.3

```
./cuda_11.0.3_450.51.06_linux.run --silent --toolkit --installpath=/ceph-data4/fangjun/  
↪software/cuda-11.0.3 --no-opengl-libs --no-drm --no-man-page  
  
# Install cuDNN  
cd /ceph-data4/fangjun/software/cuda-11.0.3  
tar xvf /ceph-sh0/fangjun/cudnn/cudnn-11.0-linux-x64-v8.0.4.30.tgz --strip-components=1
```

8.1.3 CUDA 11.3.1

```
./cuda_11.3.1_465.19.01_linux.run --silent --toolkit --installpath=/ceph-data4/fangjun/  
↪software/cuda-11.3.1 --no-opengl-libs --no-drm --no-man-page  
cd /ceph-data4/fangjun/software/cuda-11.3.1  
tar xvf /ceph-sh0/fangjun/cudnn/cudnn-11.3-linux-x64-v8.2.1.32.tgz --strip-components=1
```

8.1.4 CUDA 11.5.2

```
./cuda_11.5.2_495.29.05_linux.run --silent --toolkit --installpath=/ceph-data4/fangjun/  
↪software/cuda-11.5.2 --no-opengl-libs --no-drm --no-man-page  
cd /ceph-data4/fangjun/software/cuda-11.5.2  
tar xvf /ceph-sh0/fangjun/cudnn/cudnn-linux-x86_64-8.3.2.44_cuda11.5-archive.tar.xz --  
↪strip-components=1
```

8.1.5 CUDA 11.6.1

```
./cuda_11.6.1_510.47.03_linux.run --silent --toolkit --installpath=/ceph-data4/fangjun/  
↪software/cuda-11.6.1 --no-opengl-libs --no-drm --no-man-page  
cd /ceph-data4/fangjun/software/cuda-11.6.1  
tar xvf /ceph-sh0/fangjun/cudnn/cudnn-11.3-linux-x64-v8.2.1.32.tgz --strip-components=1
```

This page describes commonly used git commands.

9.1 DDP

9.1.1 Initialization

10.1 Install

10.1.1 formatter

Install <https://github.com/google/google-java-format>

```
wget https://github.com/google/google-java-format/releases/download/v1.15.0/google-java-  
format-1.15.0-all-deps.jar
```

Create a script with filename `google-java-format`:

```
#!/usr/bin/env bash  
  
java -jar /ceph-sh0/fangjun/download/google-java-format-1.15.0-all-deps.jar $@
```

`chmod +x google-java-format` and add the path to `PATH`.

10.1.2 JDK

Go to <https://www.oracle.com/java/technologies/downloads/#java17> and download

```
wget https://download.oracle.com/java/17/latest/jdk-17_linux-x64_bin.tar.gz  
mkdir /ceph-fj/fangjun/software/  
tar xvf jdk-17_linux-x64_bin.tar.gz -C /ceph-fj/fangjun/software
```

And then set the following environment variables:

```
export JAVA_HOME=/ceph-fj/fangjun/software/jdk-17.0.3  
export PATH=$JAVA_HOME/bin:$JAVA_HOME
```

10.2 Hello world

Listing 1: Hello.java

```
// Usage 1:
// java Hello.java
// Usage 2:
// javac Hello.java
// java Hello
//
// Note:
// - "javac Hello.java" generates a file "Hello.class"
// - "java Hello" takes as input "Hello.class" and executes it
//
class Hello {
    public static void main(String[] args) {
        System.out.println("hello world");
    }
} // There is no ';' here
```

Listing 2: EqualTest.java

```
class EqualTest {
    public int i;

    public EqualTest(int a) {
        this.i = a;
    }

    public boolean equals(Object anObject) {
        if (this == anObject) {
            return true;
        }
        if (anObject instanceof EqualTest) {
            return this.i == ((EqualTest) anObject).i;
        }
        return false;
    }

    public static void main(String[] args) {
        EqualTest e1 = new EqualTest(10);
        EqualTest e2 = new EqualTest(10);

        System.out.println(e1 == e2); // false, compare the reference
        System.out.println(e1 != e2); // true
        System.out.println(e1.equals(e2)); // true, compare the contained value
    }
}
```

10.3 Reference

- <https://docs.oracle.com/javase/tutorial/>
- <https://docs.oracle.com/en/java/javase/17/docs/api/index.html>
- <https://github.com/openjdk/jdk.git>

Clone it and you can find the source code in `src/java.base/share/classes/java/lang/System.java` for `java.lang.System`.

JAVASCRIPT

11.1 Hello world

```
console.log('hello world')  
console.log(eval('3 + 5'))
```

To write multi-line javascript, use shift + Enter for a new line.

```
(function(){  
    "use strict";  
    /* Start of your code */  
    function greetMe(yourName) {  
        alert('Hello ' + yourName);  
    }  
  
    greetMe('World');  
    /* End of your code */  
})();
```

It is case sensitive. Statements are separated by ;. Comments are the same as in C/C++.

11.2 TODOs

1. This page https://developer.mozilla.org/en-US/docs/Learn/Getting_started_with_the_web/Installing_basic_software lists some tools to minify code:
 - WebPack: <https://webpack.js.org/>
 - Grunt: <https://gruntjs.com/>
 - Gulp: <https://gulpjs.com/>
2. Color picker tool: https://developer.mozilla.org/en-US/docs/Web/CSS/CSS_Colors/Color_picker_tool
3. Google font: <https://fonts.google.com/> and https://developers.google.com/fonts/docs/getting_started

12.1 Hello world

Listing 1: hello_world.html

```
<!DOCTYPE html>
<html>
  <head>
    <meta charset="utf-8">
    <title>Hello World</title>
  </head>
  <body>
    <p>Hello world</p>
  </body>
</html>
```

12.1.1 comments

```
<!-- this is a comment -->
```

12.1.2 images

```
</img>
</img>
</img>
```

12.1.3 ordered lists

```
<p> The following points </p>

<ol>
  <li> First </li>
  <li> Second </li>
</ol>
```

12.1.4 unordered lists

```
<p> The following points </p>

<ul>
  <li> foo </li>
  <li> bar </li>
</ul>
```

12.1.5 links

```
<a href="https://www.google.com">some text</a>
```

12.2 References

- Structuring the web with HTML
<https://developer.mozilla.org/en-US/docs/Learn/HTML>

13.1 Hello world

```
p { color: red; }
```

Then, in some html file, use:

```
<link href="abc/foo.css" rel="stylesheet">
```

13.1.1 Selector

- tag name or element name: e.g., `p` selects `<p>`; `h1` selects `<h1>`.
- ID: e.g., `#my-id` selects `` or `<p id="my-id">`
- class: e.g., `.my-class`

Example with multiple rules:

Example with multiple selectors:

13.2 References

- CSS basics
https://developer.mozilla.org/en-US/docs/Learn/Getting_started_with_the_web/CSS_basics