

---

**notes**

**fangjun**

**May 16, 2022**



## CONTENTS:

<b>1</b>	<b>Sphinx</b>	<b>3</b>
1.1	Setup . . . . .	3
1.2	How to include code from a file . . . . .	4
1.3	Link . . . . .	4
1.3.1	hello . . . . .	5
<b>2</b>	<b>git</b>	<b>7</b>
2.1	Commands . . . . .	7
2.1.1	rev-parse . . . . .	7
<b>3</b>	<b>docker</b>	<b>9</b>
3.1	Installation . . . . .	9
3.1.1	macos . . . . .	9
<b>4</b>	<b>LaTeX</b>	<b>11</b>
4.1	TikZ . . . . .	11
4.1.1	Basics . . . . .	11
<b>5</b>	<b>Kaldi</b>	<b>13</b>
5.1	Decoding . . . . .	13
<b>6</b>	<b>bash</b>	<b>15</b>
6.1	sort . . . . .	15
6.2	echo . . . . .	15
<b>7</b>	<b>CUDA</b>	<b>17</b>
7.1	Installation . . . . .	17
7.1.1	CUDA 10.1.243 . . . . .	17
7.1.2	CUDA 11.0.3 . . . . .	17
7.1.3	CUDA 11.3.1 . . . . .	18
7.1.4	CUDA 11.5.2 . . . . .	18
7.1.5	CUDA 11.6.1 . . . . .	18
<b>8</b>	<b>torch</b>	<b>19</b>
8.1	DDP . . . . .	19
8.1.1	Initialization . . . . .	19
8.2	TorchScript . . . . .	19
8.2.1	Hello . . . . .	19
8.2.2	Load in C++ . . . . .	22
<b>9</b>	<b>Python</b>	<b>25</b>

9.1	asyncio . . . . .	25
9.1.1	Hello World . . . . .	25
9.1.2	References . . . . .	25
9.2	argv . . . . .	25
<b>10</b>	<b>java</b>	<b>27</b>
10.1	Install . . . . .	27
10.1.1	formatter . . . . .	27
10.1.2	JDK . . . . .	27
10.2	Hello world . . . . .	28
10.3	Reference . . . . .	29
<b>11</b>	<b>javascript</b>	<b>31</b>
11.1	Hello world . . . . .	31
11.2	TODOs . . . . .	31
<b>12</b>	<b>HTML</b>	<b>33</b>
12.1	Hello world . . . . .	33
12.1.1	comments . . . . .	33
12.1.2	images . . . . .	33
12.1.3	ordered lists . . . . .	33
12.1.4	unordered lists . . . . .	34
12.1.5	links . . . . .	34
12.2	References . . . . .	34
<b>13</b>	<b>css</b>	<b>35</b>
13.1	Hello world . . . . .	35
13.1.1	comment . . . . .	35
13.1.2	Selector . . . . .	35
13.2	References . . . . .	36

Download this website in a single [pdf file](#).



This page describes how this website is setup.

## 1.1 Setup

1. Install the dependencies in `./docs/requirements.txt`.

```
sphinx==4.3.2
sphinx-autodoc-typehints==1.12.0
sphinx_rtd_theme==1.0.0
sphinxcontrib-bibtex==2.4.1
```

2. Use `sphinx-quickstart` to generate the skeleton. When it prompts:

```
Separate source and build directories(y/n)
```

Answer yes.

3. Edit `docs/source/conf.py` and add the following lines to it:

```
import sphinx_rtd_theme
extensions = [
    'sphinx.ext.autodoc',
    'sphinx.ext.autosummary',
    'sphinx.ext.githubpages',
    'sphinx.ext.mathjax',
    'sphinx.ext.napoleon',
    'sphinx.ext.todo',
    'sphinx.ext.viewcode',
    'sphinxcontrib.bibtex',
]

html_theme = 'sphinx_rtd_theme'

master_doc = 'index'
pygments_style = 'sphinx'
html_theme_path = [sphinx_rtd_theme.get_html_theme_path()]
smartquotes = False
html_show_sourcelink = True

html_context = {
```

(continues on next page)

(continued from previous page)

```
'display_github': True,
'github_user': 'csu-fangjun',
'github_repo': 'notes',
'github_version': 'master',
'conf_py_path': '/docs/source/',
}

html_theme_options = {
    'logo_only': False,
    'display_version': True,
    'prev_next_buttons_location': 'bottom',
    'style_external_links': True,
}
latex_engine = 'xelatex'
```

4. To generate the notes in pdf format, use `make latex`, which generates lots of `tex` files in `./build/latex`. Switch to `build/latex` and run `make`. Assume that you have installed the software to compile `tex` files. It will generate `notes.pdf`.

## 1.2 How to include code from a file

See <https://www.sphinx-doc.org/en/master/usage/restructuredtext/directives.html#directive-literalinclude>.

1. Show line number: `:linenos:`. By default, line number counts from 0. To add an offset, e.g., 10, to the line number, use `:lineno-start: 10`. Note: It still includes all the contents of the file.
2. To emphasize a line, specified lines, or specified line ranges, use: `:emphasize-lines: 10`, `:emphasize-lines: 10,12,14`, and `:emphasize-lines: 12,15-18`. Note: `emphasize` means to change the background color.
3. Set the language, e.g., `:language: python`.
4. Set the caption, e.g., `:caption: hello world`.
5. To include a function from the python file, use `:pyobject: my_func`.
6. To include specified lines, use `:lines:1,3,5-10,15-`. Note that if using this option, line number counts from 0. Use `:lineno-start: xx` to change the offset for display.

## 1.3 Link

See <https://sublime-and-sphinx-guide.readthedocs.io/en/latest/references.html> and <https://www.sphinx-doc.org/en/master/usage/restructuredtext/basics.html#hyperlinks>



### 1.3.1 hello

Here is a link to *hello*.

```
.. _Link to hello:
```

```
hello
```

```
-----
```

```
Here is a link to :ref:`Link to hello`.
```



This page describes commonly used git commands.

## 2.1 Commands

### 2.1.1 rev-parse

It is quite common to get the root directory of the repository with the command:

```
git rev-parse --show-toplevel
```

For instance, the above command executed in this repository prints something like as follows:

```
/xxx/notes
```

The following shows its usage in a Python script:

```
#!/usr/bin/env python3

import subprocess

d = (
    subprocess.check_output(["git", "rev-parse", "--show-toplevel"])
    .decode("ascii")
    .strip() # remove the trailing \n
)
print(d) # /path/to/notes
```

It can also be used in bash script:

```
root_dir=$(git rev-parse --show-toplevel)
echo "root_dir ${root_dir}"
```

help git-rev-parse outputs helpful information for git rev-parse. In particular, it explains the differences among HEAD~, HEAD~n, HEAD^, and HEAD^n. The following shows the help information about it:

```
<rev>^[<n>], e.g. HEAD^, v1.5.1^0
  A suffix ^ to a revision parameter means the first parent of that commit object. ^
  ↪<n> means the <n>th parent
```


(continues on next page)

(continued from previous page)

(i.e. `<rev>^` is equivalent to `<rev>^1`). As a special rule, `<rev>^0` means the commit itself and is used when `<rev>` is the object name of a tag object that refers to a commit object.

`<rev>~[<n>]`, e.g. `HEAD~`, `master~3`

A suffix `~` to a revision parameter means the first parent of that commit object. A suffix `~<n>` to a revision parameter means the commit object that is the `<n>`th generation ancestor of the named commit object, following only the first parents. I.e. `<rev>~3` is equivalent to `<rev>^^^` which is equivalent to `<rev>^1^1^1`. See below for an illustration of the usage of this form.



$A = A^0$   
 $B = A^1 = A^1_1 = A_{~1}$   
 $C = A^2$   
 $D = A^{11} = A^{1^1}_1 = A_{~2}$   
 $E = B^2 = A^{12}$   
 $F = B^3 = A^{13}$   
 $G = A^{111} = A^{1^1^1}_1 = A_{~3}$   
 $H = D^2 = B^{12} = A^{112} = A_{~2}^2$   
 $I = F^1 = B^{13}$   
 $J = F^2 = B^{13^2} = A^{13^2}$

## 3.1 Installation

### 3.1.1 macos

Refer to <https://docs.docker.com/desktop/mac/install/>.



## **4.1 TikZ**

### **4.1.1 Basics**





This page describes commonly used git commands.

## 5.1 Decoding

```
CompactLattice compact_lat;  
decoder.GetLattice(true, &compact_lat);  
  
CompactLattice compact_best_path;  
CompactLatticeShortestPath(compact_lat, &compact_best_path);  
  
Lattice best_path;  
ConvertLattice(compact_best_path, best_path);  
  
std::vector<int32_t> tokens;  
std::vector<int32_t> words;  
LatticeWeight weight;  
GetLinearSymbolSequence(best_path, &tokens, &words, &weight);
```

- `decoder/simple-decoder.{h,cc}`



## BASH

### 6.1 sort

Sort files in the folder `t`. The filename has the patten `xxx.n.txt`, where `n` is some numerical value. Also, exclude `xxx.100.txt`.

```
find ./t -name "xxx*.txt" ! -name "xxx.100.txt" -print0 | sort -z -t. -k2 -n | xargs -r0
```

### 6.2 echo

Generate a binary file:

```
echo -n -e '\x30\x31\x32' > a.bin  
hexdump a.bin
```



## CUDA

### 7.1 Installation

#### 7.1.1 CUDA 10.1.243

```
./cuda_10.1.243_418.87.00_linux.run --silent --toolkit --installpath=/ceph-data4/fangjun/  
↪software/cuda-10.1.243 --no-opengl-libs --no-drm --no-man-page  
  
# Install cuDNN  
cd /ceph-data4/fangjun/software/cuda-10.1.243  
tar xvf /ceph-sh0/fangjun/cudnn/cudnn-10.1-linux-x64-v8.0.4.30.tgz --strip-components=1
```

```
#!/usr/bin/env bash  
  
export CUDA_HOME=/ceph-data4/fangjun/software/cuda-10.1.243  
export PATH=$CUDA_HOME/bin:$PATH  
export LD_LIBRARY_PATH=$CUDA_HOME/lib64:$LD_LIBRARY_PATH  
  
# See /ceph-fj/fangjun/py38/lib/python3.8/site-packages/torch/share/cmake/Caffe2/Modules_  
↪CUDA_fix/upstream/FindCUDA.cmake  
export CUDA_TOOLKIT_ROOT_DIR=$CUDA_HOME  
export CUDA_TOOLKIT_ROOT=$CUDA_HOME  
export CUDA_BIN_PATH=$CUDA_HOME  
export CUDA_PATH=$CUDA_HOME  
export CUDA_INC_PATH=$CUDA_HOME/targets/x86_64-linux
```

#### 7.1.2 CUDA 11.0.3

```
./cuda_11.0.3_450.51.06_linux.run --silent --toolkit --installpath=/ceph-data4/fangjun/  
↪software/cuda-11.0.3 --no-opengl-libs --no-drm --no-man-page  
  
# Install cuDNN  
cd /ceph-data4/fangjun/software/cuda-11.0.3  
tar xvf /ceph-sh0/fangjun/cudnn/cudnn-11.0-linux-x64-v8.0.4.30.tgz --strip-components=1
```

### 7.1.3 CUDA 11.3.1

```
./cuda_11.3.1_465.19.01_linux.run --silent --toolkit --installpath=/ceph-data4/fangjun/  
↪ software/cuda-11.3.1 --no-opengl-libs --no-drm --no-man-page  
cd /ceph-data4/fangjun/software/cuda-11.3.1  
tar xvf /ceph-sh0/fangjun/cudnn/cudnn-11.3-linux-x64-v8.2.1.32.tgz --strip-components=1
```

### 7.1.4 CUDA 11.5.2

```
./cuda_11.5.2_495.29.05_linux.run --silent --toolkit --installpath=/ceph-data4/fangjun/  
↪ software/cuda-11.5.2 --no-opengl-libs --no-drm --no-man-page  
cd /ceph-data4/fangjun/software/cuda-11.5.2  
tar xvf /ceph-sh0/fangjun/cudnn/cudnn-linux-x86_64-8.3.2.44_cuda11.5-archive.tar.xz --  
↪ strip-components=1
```

### 7.1.5 CUDA 11.6.1

```
./cuda_11.6.1_510.47.03_linux.run --silent --toolkit --installpath=/ceph-data4/fangjun/  
↪ software/cuda-11.6.1 --no-opengl-libs --no-drm --no-man-page  
cd /ceph-data4/fangjun/software/cuda-11.6.1  
tar xvf /ceph-sh0/fangjun/cudnn/cudnn-11.3-linux-x64-v8.2.1.32.tgz --strip-components=1
```

This page describes commonly used git commands.

## 8.1 DDP

### 8.1.1 Initialization

## 8.2 TorchScript

### 8.2.1 Hello

`torch.jit.script` as a decorator

Listing 1: `./code/1-ex.py`

```
1 @torch.jit.script
2 def adder(x: int):
3     return x + 1
4
5
6 def test_adder():
7     assert isinstance(adder, torch.jit.ScriptFunction)
8     print(adder.graph)
9     print("-" * 10)
10    print(adder.code)
11    adder.save("adder.pt")
12
13    my_adder = torch.jit.load("adder.pt")
14
15    assert isinstance(my_adder, torch.jit._script.RecursiveScriptModule)
16    assert isinstance(my_adder, torch.jit.ScriptModule)
17    assert not isinstance(my_adder, torch.jit.ScriptFunction)
18    print(my_adder(torch.tensor([3])))
19
20
21 """
22 graph(%x.1 : int):
23     %2 : int = prim::Constant[value=1]() # ./1-ex.py:8:15
```

(continues on next page)

(continued from previous page)

```

24     %3 : int = aten::add(%x.1, %2) # ./1-ex.py:8:11
25     return (%3)
26
27     -----
28     def adder(x: int) -> int:
29         return torch.add(x, 1)
30
31     4
32     """

```

### torch.jit.script as a function

Listing 2: ./code/2-ex.py

```

1  def adder(x: int):
2      return x + 2
3
4
5  def test_adder():
6      adder_func = torch.jit.script(adder)
7      assert isinstance(adder_func, torch.jit.ScriptFunction)
8      print(adder_func.graph)
9      print(adder_func(3))
10
11
12     """
13     graph(%x.1 : int):
14         %2 : int = prim::Constant[value=2]() # ./2-ex.py:6:15
15         %3 : int = aten::add(%x.1, %2) # ./2-ex.py:6:11
16         return (%3)
17
18     5
19     """

```

### torchscript a module

Listing 3: ./code/3-ex.py

```

1  class MyModel(torch.nn.Module):
2      def __init__(self):
3          super().__init__()
4          self.p = torch.nn.Parameter(torch.tensor([2.0]))
5
6      def forward(self, x: torch.Tensor):
7          return self.p * x
8
9
10 def test_my_model():
11     model = MyModel()

```

(continues on next page)



(continued from previous page)

```

12 scripted_model = torch.jit.script(model)
13 print(scripted_model.graph)
14 print("-" * 10)
15 print(scripted_model.code)
16 print(scripted_model(torch.tensor([10])))
17
18
19 """
20 graph(%self : __torch__.MyModel,
21       %x.1 : Tensor):
22   %p : Tensor = prim::GetAttr[name="p"](%self)
23   %4 : Tensor = aten::mul(%p, %x.1) # ./3-ex.py:12:15
24   return (%4)
25
26 -----
27 def forward(self,
28             x: Tensor) -> Tensor:
29     p = self.p
30     return torch.mul(p, x)
31 """

```

## Export and ignore methods

1. Use `@torch.jit.export` decorator to export a method.
2. Use `torch.jit.export` function call to export a method.
3. Use `@torch.jit.ignore` decorator to ignore a method.
4. Use `torch.jit.ignore` function call to ignore a method.
5. Use `@torch.jit.unused` or `torch.jit.unused` to ignore a method.

See [Load in C++](#) to load the saved file.

Listing 4: `./code/4-ex.py`

```

1 class MyModel(torch.nn.Module):
2     def __init__(self):
3         super().__init__()
4         self.p = torch.nn.Parameter(torch.tensor([2.0]))
5
6     def foobar(self, x: torch.Tensor):
7         return x + 3
8
9     def foo(self, x: torch.Tensor):
10        return self.foobar(x)
11
12    def bar(self, x: torch.Tensor):
13        return self.p - x
14
15    @torch.jit.export
16    def baz(self, x: torch.Tensor):

```

(continues on next page)

(continued from previous page)

```

17         return self.p + x + 2
18
19     def forward(self, x: torch.Tensor):
20         return self.p * x
21
22
23 def test_my_model():
24     MyModel.foo = torch.jit.export(MyModel.foo) # manually export
25
26     # Note: forward is exported by default. We ignore it here manually
27     MyModel.forward = torch.jit.ignore(MyModel.forward)
28
29     model = MyModel()
30     scripted_model = torch.jit.script(model)
31     assert hasattr(scripted_model, "foo")
32     assert hasattr(scripted_model, "baz")
33     assert hasattr(scripted_model, "foobar") # because it is called by `foo`
34     assert not hasattr(scripted_model, "bar")
35
36     scripted_model.save("foo.pt")
37
38     m = torch.jit.load("foo.pt")
39     print(m.foo(torch.tensor([1])))
40     print(m.baz(torch.tensor([1])))
41
42
43 """
44 graph(%self : __torch__.MyModel,
45       %x.1 : Tensor):
46     %p : Tensor = prim::GetAttr[name="p"](%self)
47     %4 : Tensor = aten::mul(%p, %x.1) # ./3-ex.py:12:15
48     return (%4)
49
50 -----
51 def forward(self,
52       x: Tensor) -> Tensor:
53     p = self.p
54     return torch.mul(p, x)
55 """

```

## 8.2.2 Load in C++

Load the saved `foo.pt` in C++ from *Export and ignore methods*.

Listing 5: `./code/load-in-cpp/Makefile`

```

1  USE_CXX11_ABI := $(shell python3 -c 'import torch; print(int(torch.compiled_with_cxx11_
   ↪abi()))')
2  TORCH_INSTALL_DIR := $(shell python3 -c 'import os; import torch; print(os.path.
   ↪dirname(torch.__file__))')
3

```

(continues on next page)

(continued from previous page)

```

4 $(info USE_CXX11_ABI $(USE_CXX11_ABI))
5 $(info TORCH_INSTALL_DIR $(TORCH_INSTALL_DIR))
6
7 CXXFLAGS := -I$(TORCH_INSTALL_DIR)/include
8 CXXFLAGS += -I$(TORCH_INSTALL_DIR)/include/torch/csrc/api/include
9 CXXFLAGS += -I$(TORCH_INSTALL_DIR)/include/TH
10 CXXFLAGS += -I$(TORCH_INSTALL_DIR)/include/THC
11 CXXFLAGS += -std=c++14
12 CXXFLAGS += -D_GLIBCXX_USE_CXX11_ABI=$(USE_CXX11_ABI)
13
14 CXXFLAGS += -Wno-unknown-pragmas # disable omp warnings
15
16 LDFLAGS := -L$(TORCH_INSTALL_DIR)/lib
17 LDFLAGS += -lc10 -ltorch -ltorch_cpu
18 # LDFLAGS += -lc10 -ltorch
19 LDFLAGS += -Wl,-rpath,$(TORCH_INSTALL_DIR)/lib
20
21 HAS_CUDA := $(shell python3 -c 'import torch; print("yes" if torch.cuda.is_available()
↪ else "no")')
22 $(info has cuda $(HAS_CUDA))
23
24 ifeq ($(HAS_CUDA),yes)
25 CUDA_HOME := $(shell which nvcc | xargs dirname | xargs dirname)
26 CXXFLAGS += -I$(CUDA_HOME)/include
27 LDFLAGS += -L$(CUDA_HOME)/lib64
28 LDFLAGS += -lcudart -lc10_cuda -ltorch_cuda
29 LDFLAGS += -Wl,-rpath,$(CUDA_HOME)/lib64
30 endif
31
32 .PHONY: clean
33
34 main: main.o
35     $(CXX) -o $@ $< $(LDFLAGS)
36
37 main.o: main.cc
38     $(CXX) $(CXXFLAGS) -c -o $@ $<
39
40 clean:
41     $(RM) main.o main

```

Listing 6: ./code/load-in-cpp/main.cc

```

1 #include "torch/script.h"
2
3 int main() {
4     // see torch/csrc/jit/module.h
5     torch::jit::Module m = torch::jit::load("../foo.pt");
6     std::cout << "is training: " << m.is_training() << "\n";
7     m.eval();
8     std::cout << "after m.eval(): is training: " << m.is_training() << "\n";
9     torch::Tensor x = torch::tensor({1, 2, 3}, torch::kFloat);
10    torch::Tensor y = m.run_method("baz", x).toTensor();

```

(continues on next page)

(continued from previous page)

```

11     std::cout << y << "\n";
12
13     return 0;
14 }

```

The output of make is:

```

USE_CXX11_ABI 0
TORCH_INSTALL_DIR /ceph-fj/fangjun/software/py38/lib/python3.8/site-packages/torch
has cuda yes
g++ -I/ceph-fj/fangjun/software/py38/lib/python3.8/site-packages/torch/include \
    -I/ceph-fj/fangjun/software/py38/lib/python3.8/site-packages/torch/include/torch/
    ↪csrc/api/include \
    -I/ceph-fj/fangjun/software/py38/lib/python3.8/site-packages/torch/include/TH \
    -I/ceph-fj/fangjun/software/py38/lib/python3.8/site-packages/torch/include/THC \
    -std=c++14 \
    -D_GLIBCXX_USE_CXX11_ABI=0 \
    -Wno-unknown-pragmas \
    -I/ceph-sh1/fangjun/software/cuda-10.2.89/include \
    -c -o main.o main.cc
g++ -o main main.o \
    -L/ceph-fj/fangjun/software/py38/lib/python3.8/site-packages/torch/lib \
    -lc10 -ltorch -ltorch_cpu \
    -Wl,-rpath,/ceph-fj/fangjun/software/py38/lib/python3.8/site-packages/torch/lib \
    -L/ceph-sh1/fangjun/software/cuda-10.2.89/lib64 \
    -lcudart -lc10_cuda -ltorch_cuda \
    -Wl,-rpath,/ceph-sh1/fangjun/software/cuda-10.2.89/lib64

```

The output of ./main is:

```

is training: 1
after m.eval(): is training: 0
5
6
7
[ CPUFloatType{3} ]

```

## 9.1 asyncio

### 9.1.1 Hello World

### 9.1.2 References

- PEP 234 – Iterators  
<https://peps.python.org/pep-0234/>
- Why does defining `__getitem__` on a class make it iterable in python?  
<https://localcoder.org/why-does-defining-getitem-on-a-class-make-it-iterable-in-python>
- PEP 255 – Simple Generators  
<https://peps.python.org/pep-0255/>
- Curious Course on Coroutines and Concurrency  
[https://www.youtube.com/watch?v=Z\\_OAlhXziw&ab\\_channel=DavidBeazley](https://www.youtube.com/watch?v=Z_OAlhXziw&ab_channel=DavidBeazley)  
By David Beazley.
- Generator Tricks for Systems Programmers  
<https://www.dabeaz.com/generators2/>
- Generators: The Final Frontier  
<[https://www.youtube.com/watch?v=5-qadlG7tWo&ab\\_channel=DavidBeazley](https://www.youtube.com/watch?v=5-qadlG7tWo&ab_channel=DavidBeazley)>  
By David Beazley.

## 9.2 argv

From the doc <https://docs.python.org/3/library/sys.html>:

The `list` of command line arguments passed to a Python script. `argv[0]` **is** the script name (it **is** operating system dependent whether this **is** a full pathname **or not**). If the command was executed using the `-c` command line option to the interpreter, `argv[0]` **is set** to the string `'-c'`. If no script name was passed to the Python interpreter, `argv[0]` **is** the empty string.

Note that `argv` is at least of size 1, though `argv[0]` may be an empty string.

```
import sys
print(sys.argv)
```

## 10.1 Install

### 10.1.1 formatter

Install <https://github.com/google/google-java-format>

```
wget https://github.com/google/google-java-format/releases/download/v1.15.0/google-java-format-1.15.0-all-deps.jar
```

Create a script with filename `google-java-format`:

```
#!/usr/bin/env bash

java -jar /ceph-sh0/fangjun/download/google-java-format-1.15.0-all-deps.jar $@
```

`chmod +x google-java-format` and add the path to `PATH`.

### 10.1.2 JDK

Go to <https://www.oracle.com/java/technologies/downloads/#java17> and download

```
wget https://download.oracle.com/java/17/latest/jdk-17_linux-x64_bin.tar.gz
mkdir /ceph-fj/fangjun/software/
tar xvf jdk-17_linux-x64_bin.tar.gz -C /ceph-fj/fangjun/software
```

And then set the following environment variables:

```
export JAVA_HOME=/ceph-fj/fangjun/software/jdk-17.0.3
export PATH=$JAVA_HOME/bin:$JAVA_HOME
```

## 10.2 Hello world

Listing 1: Hello.java

```
// Usage 1:
//  java Hello.java
// Usage 2:
//  javac Hello.java
//  java Hello
//
// Note:
//  - "javac Hello.java" generates a file "Hello.class"
//  - "java Hello" takes as input "Hello.class" and executes it
//
class Hello {
    public static void main(String[] args) {
        System.out.println("hello world");
    }
} // There is no ';' here
```

Listing 2: EqualTest.java

```
class EqualTest {
    public int i;

    public EqualTest(int a) {
        this.i = a;
    }

    public boolean equals(Object anObject) {
        if (this == anObject) {
            return true;
        }
        if (anObject instanceof EqualTest) {
            return this.i == ((EqualTest) anObject).i;
        }
        return false;
    }

    public static void main(String[] args) {
        EqualTest e1 = new EqualTest(10);
        EqualTest e2 = new EqualTest(10);

        System.out.println(e1 == e2); // false, compare the reference
        System.out.println(e1 != e2); // true
        System.out.println(e1.equals(e2)); // true, compare the contained value
    }
}
```



## 10.3 Reference

- <https://docs.oracle.com/javase/tutorial/>
- <https://docs.oracle.com/en/java/javase/17/docs/api/index.html>
- <https://github.com/openjdk/jdk.git>

Clone it and you can find the source code in `src/java.base/share/classes/java/lang/System.java` for `java.lang.System`.



## JAVASCRIPT

### 11.1 Hello world

```
console.log('hello world')  
console.log(eval('3 + 5'))
```

To write multi-line javascript, use shift + Enter for a new line.

```
(function(){  
    "use strict";  
    /* Start of your code */  
    function greetMe(yourName) {  
        alert('Hello ' + yourName);  
    }  
  
    greetMe('World');  
    /* End of your code */  
})();
```

It is case sensitive. Statements are separated by ;. Comments are the same as in C/C++.

### 11.2 TODOs

1. This page [https://developer.mozilla.org/en-US/docs/Learn/Getting\\_started\\_with\\_the\\_web/Installing\\_basic\\_software](https://developer.mozilla.org/en-US/docs/Learn/Getting_started_with_the_web/Installing_basic_software) lists some tools to minify code:
  - WebPack: <https://webpack.js.org/>
  - Grunt: <https://gruntjs.com/>
  - Gulp: <https://gulpjs.com/>
2. Color picker tool: [https://developer.mozilla.org/en-US/docs/Web/CSS/CSS\\_Colors/Color\\_picker\\_tool](https://developer.mozilla.org/en-US/docs/Web/CSS/CSS_Colors/Color_picker_tool)
3. Google font: <https://fonts.google.com/> and [https://developers.google.com/fonts/docs/getting\\_started](https://developers.google.com/fonts/docs/getting_started)



## 12.1 Hello world

Listing 1: hello\_world.html

```
<!DOCTYPE html>
<html>
  <head>
    <meta charset="utf-8">
    <title>Hello World</title>
  </head>
  <body>
    <p>Hello world</p>
  </body>
</html>
```

### 12.1.1 comments

```
<!-- this is a comment -->
```

### 12.1.2 images

```
</img>
</img>
</img>
```

### 12.1.3 ordered lists

```
<p> The following points </p>

<ol>
  <li> First </li>
  <li> Second </li>
</ol>
```

### 12.1.4 unordered lists

```
<p> The following points </p>

<ul>
  <li> foo </li>
  <li> bar </li>
</ul>
```

### 12.1.5 links

```
<a href="https://www.google.com">some text</a>
```

## 12.2 References

- Structuring the web with HTML  
<https://developer.mozilla.org/en-US/docs/Learn/HTML>

## 13.1 Hello world

### 13.1.1 comment

```
/* this is a comment */
```

```
p { color: red; }
```

Then, in some html file, use:

```
<link href="abc/foo.css" rel="stylesheet">
```

### 13.1.2 Selector

- tag name or element name: e.g., p selects <p>; h1 selects <h1>.
- ID:, e.g., #my-id selects <a id="my-id"> or <p id="my-id">
- class: e.g., .my-class selects <a class="my-class"> and <p class="my-class">
- attribute: e.g., img[src] selects  but not <img>

See [https://developer.mozilla.org/en-US/docs/Learn/Getting\\_started\\_with\\_the\\_web/CSS\\_basics#different\\_types\\_of\\_selectors](https://developer.mozilla.org/en-US/docs/Learn/Getting_started_with_the_web/CSS_basics#different_types_of_selectors) and [https://developer.mozilla.org/en-US/docs/Learn/CSS/Building\\_blocks/Selectors](https://developer.mozilla.org/en-US/docs/Learn/CSS/Building_blocks/Selectors) for more.

Example with multiple rules:

Listing 1: Example with multiple rules

```
p {  
  color: red;  
  width: 500px;  
  border: 1px solid black;  
}
```

Example with multiple selectors:

## 13.2 References

- CSS basics

[https://developer.mozilla.org/en-US/docs/Learn/Getting\\_started\\_with\\_the\\_web/CSS\\_basics](https://developer.mozilla.org/en-US/docs/Learn/Getting_started_with_the_web/CSS_basics)