

Towards Unobtrusive Obstacle Detection and Notification for VR

Peter Wozniak

University Offenburg

Offenburg, Germany

peter.wozniak@hs-offenburg.de

Nicolas Javahiraly

ICube - University of Strasbourg

CRONENBOURG, France

n.javahiraly@unistra.fr

Antonio Capobianco

ICube - University of Strasbourg

HAGUENAU, France

a.capobianco@unistra.fr

Dan Curticapean

University Offenburg

Offenburg, Germany

dan.curticapean@hs-offenburg.de




Figure 1: The four metaphors: Placeholder (tree); Arrow; Rubber Band; Color Indicator.

ABSTRACT

We present results of a preliminary study on our planned system for the detection of obstacles in the physical environment by means of an RGB-D sensor and their unobtrusive signalling using metaphors within the virtual environment (VE).

CCS CONCEPTS

- Human-centered computing → Empirical studies in HCI; User studies; Laboratory experiments; Interaction techniques;
- Computing methodologies → Virtual reality; 3D imaging;

KEYWORDS

Virtual Reality, Notifications, Interaction metaphor, Collision Avoidance, 3D Interaction, Walking Workspace, Range Imaging, RGB-D

ACM Reference Format:

Peter Wozniak, Antonio Capobianco, Nicolas Javahiraly, and Dan Curticapean. 2018. Towards Unobtrusive Obstacle Detection and Notification for VR. In *VRST 2018: 24th ACM Symposium on Virtual Reality Software and Technology (VRST '18), November 28-December 1, 2018, Tokyo, Japan*. ACM, New York, NY, USA, 2 pages. <https://doi.org/10.1145/3281505.3283391>

Permission to make digital or hard copies of part or all of this work for personal or classroom use is granted without fee provided that copies are not made or distributed for profit or commercial advantage and that copies bear this notice and the full citation on the first page. Copyrights for third-party components of this work must be honored. For all other uses, contact the owner/author(s).

VRST '18, November 28-December 1, 2018, Tokyo, Japan

© 2018 Copyright held by the owner/author(s).

ACM ISBN 978-1-4503-6086-9/18/11.

<https://doi.org/10.1145/3281505.3283391>

1 INTRODUCTION

VR systems with 6DOF tracking allow natural locomotion interfaces. These systems require a defined free-of-obstacles area and use visual cues to warn immersed users [5]. While static objects can be easily avoided, this is not so easy with objects that dynamically change their position (e.g. pets). Our work aims at detecting obstacles by an RGB-D sensor and signaling them in the VE. Prior to working on the detection of moving obstacles, it was necessary to evaluate which visual metaphors are suitable to provide a spatial understanding of the obstacles and to enable users to avoid them efficiently. Therefore, only stationary obstacles were used in this study.

2 RELATED WORK

Walking interfaces offer advantages in navigation of VE systems over other types of locomotion [6, 9, 12]. Real walking is a natural form of locomotion, resulting in higher presence than other types of locomotion [11] and reducing the probability of the occurrence of simulator sickness [1, 6]. Real walking locomotion interfaces are based on the acquisition of the user pose and are limited to tracked space, thus raising the problem that users may leave tracked space. Peck et. al. introduced "deterrents" that appeared when the users were close to the edge of tracked space. They used bars as visual cues and that the users were instructed to avoid [5]. The standard technique today is to display a visual cue when the user threatens to leave the previously defined empty and thus obstacle-free area. Scavarelli's et al. compared different collision-avoidance methods between co-located VR users, but didn't use real obstacles [7]. The Magic Barrier Tape by Cirio et al. is a hybrid collision-avoidance and navigation method. A tape represents the walking area and




Figure 2: Room setup diagram

allows further navigation in VE [2, 3]. Simeone used a depth sensor to detect people, but did not provide a spatial visual representation within the VE [8]. Similar to Nescher et al. [4], Sra et al. used a depth sensor to 3D reconstruct the physical environment and detect the walkable area. Because this process needed to be performed in advance, the authors outlined the need for additional collision-avoidance methods and the lack of detection of moving obstacles. It was also pointed out that these methods should be evaluated in terms of how much they influence the feeling of presence [10].

3 EXPERIMENTAL PROTOCOL

The space for the experiment consisted of an area of 7.8x5.7 meters (tracking area 5x5 meters). To use the room size effectively and due to the maximum cable length of the HTC Vive of 5m (headset) + 1m (breakout box) the computer was positioned relatively centrally (see Figure 2). A Microsoft Kinect v2 was used to detect obstacles placed within a designated area. Four visual metaphors were introduced to signal obstacles in VE (Figure 1). The **Placeholder** metaphor displays any virtual object. We chose a tree as an unobtrusive representation. The **Arrow** metaphor is based on the principle of a compass pointing towards an obstacle. The **Rubber Band** metaphor floats around the virtual center of the body and deforms when close to an obstacle. It is inspired by the Magic Barrier Tape but offers no navigation [2]. The **Color Indicator** metaphor is a color-coded semitransparent fade-in tape. It first appears green at the position of an obstacle and turns orange and subsequently red when the distance decreases further.

20 participants (13 male, 7 female) aging from 21 to 57 (mean : 34.16, sd : 8.38) took part in the study. Invisible to the participants, two obstacles were placed in the room and detected by our system before the subject had to walk across the tracked area and to solve a simple task in VE. We paid attention for each metaphor if a user collided with an obstacle and determined the spatial understanding by asking participants to indicate the suspected location of the obstacles. Everybody was asked to give their subjective assessment, using a likert scale-based questionnaire.

4 RESULTS AND FUTURE WORK

Our results indicate that the metaphor has a significant influence on spatial comprehension ($\chi^2(3) = 39.88$, $p < 0.001$), presence ($\chi^2(3) = 13.237$, $p = 0.0041$) and subjective preference ($\chi^2(3) = 29.28$, $p < 0.001$). Pairwise comparisons show that Placeholder gets higher ratings than the other techniques for these 3 criteria (with all p-values < 0.05). The Placeholder metaphor is the most efficient and leads to a higher spatial understanding. Subjective evaluation indicate a strong preference of the subjects for this metaphor. Not only was it ranked as the preferred technique. It was also perceived as the most intuitive. It is not surprising that it is the technique with the lowest impact on presence. These results suggest that the subjective ratings of participants may be biased such that users rate the sense of presence higher than the ability of a metaphor to ensure security by attracting the user's attention. We plan to complete this first experiment with a follow-up study that will include the possibility of capturing moving objects in the environment and assessing the metaphor's ability to attract the attention of users when needed.

REFERENCES

- [1] S. S. Chance, F. Gaunet, A. C. Beall, and J. M. Loomis. 1998. Locomotion Mode Affects the Updating of Objects Encountered During Travel: The Contribution of Vestibular and Proprioceptive Inputs to Path Integration. *Presence* 7, 2 (April 1998), 168–178. <https://doi.org/10.1162/105474698565659>
- [2] Gabriel Cirio, Maud Marchal, Tony Regia-Corte, and Anatole Lécuyer. 2009. The Magic Barrier Tape: A Novel Metaphor for Infinite Navigation in Virtual Worlds with a Restricted Walking Workspace. In *Proceedings of the 16th ACM Symposium on Virtual Reality Software and Technology (VRST '09)*. ACM, New York, NY, USA, 155–162. <https://doi.org/10.1145/1643928.1643965>
- [3] G. Cirio, P. Vangorp, E. Chapoulie, M. Marchal, A. Lécuyer, and G. Drettakis. 2012. Walking in a Cube: Novel Metaphors for Safely Navigating Large Virtual Environments in Restricted Real Workspaces. *IEEE Transactions on Visualization and Computer Graphics* 18, 4 (April 2012), 546–554. <https://doi.org/10.1109/TVCG.2012.60>
- [4] T. Nescher, M. Zank, and A. Kunz. 2016. Simultaneous mapping and redirected walking for ad hoc free walking in virtual environments. In *2016 IEEE Virtual Reality (VR)*, 239–240. <https://doi.org/10.1109/VR.2016.7504742>
- [5] T. C. Peck, H. Fuchs, and M. C. Whitton. 2012. The Design and Evaluation of a Large-Scale Real-Walking Locomotion Interface. *IEEE Transactions on Visualization and Computer Graphics* 18, 7 (July 2012), 1053–1067. <https://doi.org/10.1109/TVCG.2011.289>
- [6] Roy A. Ruddle and Simon Lessels. 2009. The Benefits of Using a Walking Interface to Navigate Virtual Environments. *ACM Trans. Comput.-Hum. Interact.* 16, 1, Article 5 (April 2009), 18 pages. <https://doi.org/10.1145/1502800.1502805>
- [7] Anthony Scavarelli and Robert J. Teather. 2017. VR Collide! Comparing Collision-Avoidance Methods Between Co-located Virtual Reality Users. In *Proceedings of the 2017 CHI Conference Extended Abstracts on Human Factors in Computing Systems (CHI EA '17)*. ACM, New York, NY, USA, 2915–2921. <https://doi.org/10.1145/3027063.3053180>
- [8] A. L. Simeone. 2016. The VR motion tracker: visualising movement of non-participants in desktop virtual reality experiences. In *2016 IEEE 2nd Workshop on Everyday Virtual Reality (WEVR)*, Vol. 00, 1–4. <https://doi.org/10.1109/WEVR.2016.7859535>
- [9] Mel Slater, Martin Usoh, and Anthony Steed. 1995. Taking Steps: The Influence of a Walking Technique on Presence in Virtual Reality. *ACM Trans. Comput.-Hum. Interact.* 2, 3 (Sept. 1995), 201–219. <https://doi.org/10.1145/210079.210084>
- [10] Mischa Sra, Sergio Garrido-Jurado, Chris Schmandt, and Pattie Maes. 2016. Procedurally Generated Virtual Reality from 3D Reconstructed Physical Space. In *Proceedings of the 22Nd ACM Conference on Virtual Reality Software and Technology (VRST '16)*. ACM, New York, NY, USA, 191–200. <https://doi.org/10.1145/2993369.2993372>
- [11] Martin Usoh, Kevin Arthur, Mary C. Whitton, Rui Bastos, Anthony Steed, Mel Slater, and Frederick P. Brooks, Jr. 1999. Walking > Walking-in-place > Flying, in Virtual Environments. In *Proceedings of the 26th Annual Conference on Computer Graphics and Interactive Techniques (SIGGRAPH '99)*. ACM Press/Addison-Wesley Publishing Co., New York, NY, USA, 359–364. <https://doi.org/10.1145/311535.311589>
- [12] David Waller, Jack M. Loomis, and Daniel B. M. Haun. 2004. Body-based senses enhance knowledge of directions in large-scale environments. *Psychonomic Bulletin & Review* 11, 1 (01 Feb 2004), 157–163. <https://doi.org/10.3758/BF03206476>