
Using GIS landscape analysis tools with high-resolution multibeam bathymetry and ROV mapping to model rockfish distribution and abundance on the Del Monte shale beds, Monterey Bay, California.

A Capstone Project Earth Systems Science Policy California State University, Monterey Bay

Ву



Erica Summers-Morris

5 May 2004

Appendix - Predicting rockfish distribution from multibeam bathymetry data

TABLE OF CONTENTS

TABLE OF FIGURES AND TABLES	3
ABSTRACT	4
Introduction	4
METHODS	8
General Approach	8
Site description	8
Multibeam bathymetry	9
ROV Video Analysis	10
GIS Analysis	11
Depth	11
Slope	12
Rugosity	12
Topographic Position Index (TPI)	12
Habitat Suitability Models	13
Stock Estimates	13
RESULTS	13
ROV Video Analysis	13
GIS Analysis	14
Slope	14
Rugosity	14
Topographic Position Index (TPI)	15
Habitat Suitability Models	15
Model Evaluation	16
Model 1: Distance to TPI ₅₀ Peaks	16
Model 2: Distance to TPI ₅₀ Peaks + Depth	17
Model 3: Distance to Preferred: TPI ₅₀ Peaks + Slope + Rugosity	17
Model 4: Distance to Preferred: TPI ₅₀ Peaks + Slope + Rugosity + Depth	18
Stock Estimates	18
DISCUSSION	19
CONCLUSION	22
LIST OF REFERENCES	24

Appendix - Predicting rockfish distribution from multibeam bathymetry data

TABLE OF FIGURES AND TABLES

FIGURE 1. Shaded-relief grayscale image of multibeam bathymetry for the Del Monte shale beds study	y
site, Monterey Bay, CA.	
FIGURE 2. ROV tracklines for Fall 2002 and Spring 2003 surveys	28
FIGURE 3. Depth zones in 10m increments used in the generation of habitat suitability models	29
Figure 4. Habitat suitability model analysis mask	
FIGURE 5. Schematic depiction of TPI calculation.	31
FIGURE 6. Rockfish distribution and abundance calculated from analysis of ROV video data	
FIGURE 7. Slope analysis of multibeam survey area with distribution and abundance of rockfish obser	
during Spring 2003 ROV survey.	
FIGURE 8. Rugosity analysis of multibeam survey area with distribution and abundance of rockfish	
observed during Spring 2003 ROV survey.	34
FIGURE 9. TPI ₅₀ analysis of multibeam survey area with distribution and abundance of rockfish observ	ved
during Spring 2003 ROV survey.	
FIGURE 10. Model 1: Distance to TPI ₅₀ Peaks	36
FIGURE 11. Model 2 – Deep: Distance to Preferred – TPI ₅₀ Peaks + Depth	37
FIGURE 12. Model 2 – Shallow: Distance to Optimal – TPI ₅₀ Peaks + Depth	
FIGURE 13. Model 3: Distance to Optimal – TPI ₅₀ Peaks + Slope + Rugosity	
FIGURE 14. Model 4 – Deep: Distance to Optimal – TPI ₅₀ Peaks + Slope + Rugosity + Depth	40
FIGURE 15. Model 4 – Shallow: Distance to Optimal – TPI ₅₀ Peaks + Slope + Rugosity +Depth	41
FIGURE 16. Efficiency comparison	
TABLE 1. Counts and percentages of rockfish for slope, rugosity, TPI ₅₀ and depth	44
TABLE 2. Counts and percentages of rockfish for "Distance to Preferred" grids: slope, rugosity, and	
TPI_{50}	45
TABLE 3. Reclassification tables used to rank "Distance to Preferred" grids and depth	46
TABLE 4. Model evaluation tables	
TABLE 5. Density calculations for habitat suitability models	
TABLE 6. Efficiency table calculations	49
APPENDIX 1. Evaluation of TPI analysis at various scales	50
APPENDIX 2. Proportion table for adjusted stock estimates	
APPENDIX 3. Stock estimates for habitat suitability models	

ABSTRACT

Accurate and efficient species-based habitat assessment is in great demand for the marine environment. In light of declining rockfish stocks, effective tools capable of providing accurate stock assessments of near-shore, high relief habitat would be invaluable to both state and federal resource managers. Multibeam bathymetry, when analyzed with GIS landscape analysis tools, can create effective models capable of predicting "preferred" habitat based on species-specific parameters. For this study, high-resolution multibeam data of the Del Monte shale beds in Monterey Bay, California were analyzed in GIS for slope, rugosity, and relative topographic position to assess and quantify rockfish (Sebastes spp.) habitat preference. Video transects collected by a remotely operated vehicle (ROV) provided habitat ground-truth and fish distribution data for the modeling process. A series of habitat suitability models were created in GIS by combining different suitability factors from multibeam-derived grids: slope, rugosity, topographic position index (TPI) and depth. "Distance to preferred" categories for each of the parameters were determined for 8 rockfish species. Of these, "Distance to Peak" features identified by TP₆₀ proved to be the most effective means of modeling fish distribution, and successfully predicted an average of 80% of the 8 rockfish species. distribution information collected from the ROV, stock estimates were calculated for the shale beds study area. By combining GIS landscape analysis tools with multibeam bathymetry and ROV video data, we have created a predictive tool that can locate areas of "most suitable" habitat given rockfish-specific parameters.

INTRODUCTION

There is a great need for accurate and efficient species-based identification and classification of marine habitats. The health of marine ecosystems depends on the abundance and diversity of life within the ecosystem, as well as the quality of habitat associated with the area (Adams et al. 1995). Understanding the link between marine resources and their habitat can help reveal ecosystem dynamics affecting both large- and small-scale patterns of species distribution and abundance.

Over the past several decades, marine resources have been declining, and many species have reached critically low levels (Starr 1998, 2002; Mason 1999). The National Marine Fisheries Service (NMFS) manages 61 of the 96 species of rockfish (genus *Sebastes*) found along the Pacific Coast from Washington to California. Of these species, 9 are currently listed as "overfished." Other species often caught as "bycatch" during the harvest of