

Data Structures and Algorithms

Prof. Ganesh Ramakrishnan,
Prof. Ajit Diwan,
Prof. D.B. Phatak

Department of Computer Science and Engineering
IIT Bombay

Session: Shortest Path Algorithm
(Bellman-Ford Algorithm)

Bellman-Ford Algorithm

1. Computes shortest paths from a source vertex to all other vertices in a weighted directed graph.
2. Dijkstra's Algorithm does not work for negative edges.
3. Solves the problem of negative edge weights but is slower than Dijkstra's Algorithm.
4. Running time: $O(VE)$


Bellman-Ford Shortest Path Algorithm

Algorithm ComputeBellman-FordSPs(G, s, w)


Output: Returns false for negative-weight cycle, else produces shortest paths with predecessor.

```
for  $v \in G.getVertices()$  do
  if  $v = s$  then
     $d[v] = 0$ 
     $predecessor[v] = NULL$ 
  else
     $d[v] = \infty$ 
  end if
end for
for  $i \in \{1, \dots, G.getVertices() - 1\}$  do
  for  $e \in G.edges()$  do
    if  $d[u] + w < d[v]$  then
       $d[v] = d[u] + w$ 
       $predecessor[v] = u$ 
    end if
  end for
end for
for  $e \in G.edges()$  do
  if  $d[u] + w < d[v]$  then
    return FALSE
  end if
end for
return  $d[], predecessor[]$ 
```


Bellman-Ford




Bellman-Ford




Bellman-Ford




Bellman-Ford




Bellman-Ford



Bellman-Ford



Bellman-Ford



Analysis of Bellman-Ford Shortest Path Algorithm

Algorithm ComputeBellman-FordSPs(G, s, w)

Output: Returns false for negative-weight cycle, else produces shortest paths with predecessor.

```
for  $v \in G.getVertices()$  do
  if  $v = s$  then
     $d[v] = 0$ 
     $predecessor[v] = NULL$ 
  else
     $d[v] = \infty$ 
  end if
end for  $\implies c_1 \times |V|$  times
for  $i \in \{1, \dots, G.getVertices() - 1\}$  do
  for  $e \in G.edges()$  do
    if  $d[u] + w < d[v]$  then
       $d[v] = d[u] + w$ 
       $predecessor[v] = u$ 
    end if  $\implies c_2 \times |V|$  times
  end for  $\implies c_3 \times |E|$  times
end for  $\implies c_4 \times |V|$  times
for  $e \in G.edges()$  do
  if  $d[u] + w < d[v]$  then
    return FALSE
  end if
end for  $\implies c_5 \times |E|$  times
return  $d[], predecessor[]$ 
```

$$T(n) = c_1|V| + c_2c_3c_4|V||E| + c_5|E| = O(|V||E|)$$

Thank you