

Data Structures and Algorithms

Prof. Ganesh Ramakrishnan,
Prof. Ajit Diwan,
Prof. D.B. Phatak

Department of Computer Science and Engineering
IIT Bombay

Session: Newton-Raphson Method


Introduction

- As compared to bisection method, it requires only one initial guess of the root
- If the method converges, it performs faster than bisection¹

¹Content adapted from

http://mathforcollege.com/nm/mws/gen/03nle/mws_gen_nle_txt_newton.pdf and
https://en.wikipedia.org/wiki/Newton%27s_method

Newton-Raphson Method: Illustration



Principle of Newton-Raphson Method

- For a nonlinear function $f(x) = 0$, consider x_i , the initial guess of the root
- Find an improved estimate x_{i+1} as the x -intercept of the tangent to the curve at $f(x_i)$
- Using the slope definition

$$\begin{aligned}f'(x_i) &= \tan \theta \\ &= \frac{f(x_i)}{x_i - x_{i+1}}\end{aligned}$$

$$x_{i+1} = x_i - \frac{f(x_i)}{f'(x_i)}$$

- Iteratively repeat the process till you get closer to the root with desirable tolerance

Algorithm for Newton-Raphson Method

Algorithm Newton-RaphsonMethod($f(x)$)

Input Given a function $f(x) = 0$

Evaluate $f'(x)$ symbolically

x_i = Initial guess of the root

$NMAX$ = max number of iterations

TOL = tolerance limit

$N = 1$

while $N < NMAX$ & $|f'(x)| < TOL$ **do**

$$x_{i+1} = x_i - \frac{f(x_i)}{f'(x_i)}$$

$$x_i = x_{i+1}$$

$$N = N + 1$$

end while

Figure: Newton-Raphson Algorithm

Problems with Newton-Raphson Method

- Difficulty in calculating derivative of a function
- Failure of the method to converge to the root in the following cases:
 - ▶ overshooting
 - ▶ division by zero
 - ▶ wrong initial estimate
 - ▶ oscillation

Thank you