

# Data Structures and Algorithms

Prof. Ganesh Ramakrishnan,  
Prof. Ajit Diwan,  
Prof. D.B. Phatak

Department of Computer Science and Engineering  
IIT Bombay

Session: Convex Hull

# Introduction <sup>1</sup>

- The **convex hull** of a set  $Q$  of points, denoted  $CH(Q)$ , is the smallest convex polygon  $P$  for which each point in  $Q$  is either on the boundary of  $P$  or in its interior.
- Convex hull may be visualized as the shape enclosed by a rubber band stretched around all the points in  $Q$
- Can be computed using a technique called rotational sweep

---

<sup>1</sup>Chapter 33, CLRS, Third Edition

# Computing convex hull: Graham's scan

- Input: set of points  $Q$
- Choose point  $p_0$  as the point with the lowest y-coordinate (or leftmost such point in case of a tie)

# Computing convex hull: Graham's scan

- Input: set of points  $Q$
- Choose point  $p_0$  as the point with the lowest y-coordinate (or leftmost such point in case of a tie)
- Sort the remaining points of  $Q$  by polar angle relative to  $p_0$  in counterclockwise order, by comparing the cross products. Designate the sorted sequence as  $p_0, p_1, \dots, p_m$

# Computing convex hull: Graham's scan

- Input: set of points  $Q$
- Choose point  $p_0$  as the point with the lowest y-coordinate (or leftmost such point in case of a tie)
- Sort the remaining points of  $Q$  by polar angle relative to  $p_0$  in counterclockwise order, by comparing the cross products. Designate the sorted sequence as  $p_0, p_1, \dots, p_m$
- Push three points  $p_0, p_1$ , and  $p_2$  on to the stack  $S$


# Computing convex hull: Graham's scan

- Input: set of points  $Q$
- Choose point  $p_0$  as the point with the lowest y-coordinate (or leftmost such point in case of a tie)
- Sort the remaining points of  $Q$  by polar angle relative to  $p_0$  in counterclockwise order, by comparing the cross products. Designate the sorted sequence as  $p_0, p_1, \dots, p_m$
- Push three points  $p_0, p_1$ , and  $p_2$  on to the stack  $S$
- If the angle formed by points  $p_i$  (initially  $i = 3$ ) and the first 2 points on a stack (in that order) is in the clockwise direction, then pop the topmost element from the stack, else push  $p_i$  on the stack

# Computing convex hull: Graham's scan


- Input: set of points  $Q$
- Choose point  $p_0$  as the point with the lowest y-coordinate (or leftmost such point in case of a tie)
- Sort the remaining points of  $Q$  by polar angle relative to  $p_0$  in counterclockwise order, by comparing the cross products. Designate the sorted sequence as  $p_0, p_1, \dots, p_m$
- Push three points  $p_0, p_1$ , and  $p_2$  on to the stack  $S$
- If the angle formed by points  $p_i$  (initially  $i = 3$ ) and the first 2 points on a stack (in that order) is in the clockwise direction, then pop the topmost element from the stack, else push  $p_i$  on the stack
- Finally, the stack  $S$  contains all the points, from bottom to top, exactly the vertices of  $CH(Q)$

# Illustration







# Illustration




# Illustration




# Illustration




# Illustration




# Illustration




# Illustration



# Illustration




# Illustration







# Illustration



# Illustration



# Illustration



# Algorithm for finding Convex Hull

## **Algorithm** GrahamScanAlgorithm( $Q$ )

Let  $p_0$  be the point in  $Q$  with the minimum  $y$ -coordinate, or leftmost such point in case of tie  
let  $\langle p_1, p_2, \dots, p_m \rangle$  be the remaining points in  $Q$ , sorted by polar angle in counter-clockwise order around  $p_0$  (if more than one point has the same angle, remove all but the one that is farthest from  $p_0$ )  
let  $S$  be an empty stack  
PUSH( $p_0, S$ )  
PUSH( $p_1, S$ )  
PUSH( $p_2, S$ )  
**for**  $i \in (3 \dots m)$  **do**  
    **while** the angle formed by points  $NextToTOP(S)$ ,  $TOP(S)$ , and  $p_i$  makes a non-left turn **do**  
        POP( $S$ )  
    **end while**  
    PUSH( $p_i, S$ )  
**end for**  
**return**  $S$

Figure: Graham-Scan-Algorithm

**Thank you**