

ASCII — all 128 characters

ASCII is a **7-bit** code: **0–127**, and that is the whole of it. Codes **0–31** and **127** are *control codes* — instructions to a machine, not characters — and **32–126** are the printing characters. Anything numbered 128–255 belongs to some later 8-bit *extension*, and those extensions disagree with each other. Below 128 everything agrees.

DEC	ABBR	NAME
0	NUL	Null
1	SOH	Start of heading
2	STX	Start of text
3	ETX	End of text
4	EOT	End of transmission
5	ENQ	Enquiry
6	ACK	Acknowledge
7	BEL	Bell
8	BS	Backspace
9	HT	Horizontal tab
10	LF	Line feed
11	VT	Vertical tab
12	FF	Form feed
13	CR	Carriage return
14	SO	Shift out
15	SI	Shift in
16	DLE	Data link escape
17	DC1	Device control 1 (XON)
18	DC2	Device control 2
19	DC3	Device control 3 (XOFF)
20	DC4	Device control 4
21	NAK	Negative acknowledge
22	SYN	Synchronous idle
23	ETB	End of transmission block
24	CAN	Cancel
25	EM	End of medium
26	SUB	Substitute
27	ESC	Escape
28	FS	File separator
29	GS	Group separator
30	RS	Record separator
31	US	Unit separator

DEC	CHAR
32	space
33	!
34	"
35	#
36	\$
37	%
38	&
39	'
40	(
41	)
42	*
43	+
44	,
45	-
46	.
47	/
48	0
49	1
50	2
51	3
52	4
53	5
54	6
55	7
56	8
57	9
58	:
59	;
60	<
61	=
62	>
63	?

DEC	CHAR
64	@
65	A
66	B
67	C
68	D
69	E
70	F
71	G
72	H
73	I
74	J
75	K
76	L
77	M
78	N
79	O
80	P
81	Q
82	R
83	S
84	T
85	U
86	V
87	W
88	X
89	Y
90	Z
91	[
92	\
93	]
94	^
95	_

DEC	CHAR
96	`
97	a
98	b
99	c
100	d
101	e
102	f
103	g
104	h
105	i
106	j
107	k
108	l
109	m
110	n
111	o
112	p
113	q
114	r
115	s
116	t
117	u
118	v
119	w
120	x
121	y
122	z
123	{
124	
125	}
126	~
127	DEL