![GOSUNCN 高新兴物联]

LTE/TD-SCDMA/WCDMA/CDMA/GSM Module

ME3630-W PCIE

- PCIE Form Factor
- GNSS
- Rx diversity
- LTE FDD & LTE TDD
- TD-SCDMA & WCDMA & EVDO
- CDMA 1x & GSM
- LTE FDD: DL 150Mbps / UL 50Mbps
- UART
- USB 2.0
- TCP&UDP&FTP &HTTP
- -40℃ ~ 85 ℃
- Auto suspend & remote wakeup

For M2M Applications

ME3630-W PCIE 系列无线通讯模组是LTE Cat.4 七模全网通LTE模组。在LTE制式下，该模组可以提供最大50Mbps上行速率和150Mbps下行速率，并支持回退到3G或2G网络。

　　该模组支持分集接收，分集接收是终端产品支持双天线以提高通讯质量和通讯可靠性无线连接技术。

　　该模组支持多种网络协议（PAP、CHAP、PPP）和多种功能GNSS, Remote wakeup, SMS、GNSS、支持FoTA空中升级。这些协议和功能可以让它用在很多物联网应用场景里。

　　该模组支持宽温工作，产品可广泛应用于智能抄表、安防信息采集、工业路由器、各种车载产品上比如：车载跟踪，车载通讯，车载监控等M2M领域。

型号:ME3630-W PID:C2C
TD-LTE无线数据终端
CMIIT ID: 2017CP6940
IMEI: 860053030191181
MEID: A0000099F0000B4
S/N: 26080001000B
中国制造
深圳高新兴物联科技有限公司

备注：图片仅供参考。

![Welink rnsrght™ Welink your smart]

LTE/TD-SCDMA/WCDMA/CDMA/GSM Module

ME3630-W PCIE

基本属性

- Pin-to-Pin with PCIE
- Dimensions: 51mm ✕ 31mm ✕ 4.75mm
- Weight: About 10.0g
- Frequency Band :
  - LTE FDD/LTE TDD/WCDMA/TD-SCDMA/GSM/CDMA EVDO/CDMA 1x
- BD/GLONASS/GPS

电气以及灵敏度

- Transmit Power:
  - LTE: 23 ±2.7dBm (Power Class 3)
  - WCDMA : 24 +1/-3dBm (Power Class 3)
  - TD-SCDMA : 24 +1/-3dBm
  - GSM900 : 33±2dBm (Power Class 4)
  - GSM1800: 30±2dBm (Power Class 1)
  - CDMA:24 ±1dBm @ All up bits
- Receiving sensitivity:
  - Rx Diversity
- Power Supply :
  - 3.0V -- 4.0V(3.3V /3.8V is recommended)

环境适应性

- Operation temperature: -30°C to +75°C
  - Extreme Operating temperature: -40°C to +85°C
- Storage temperature: -40°C to +85°C
- Humidity: 5%~ 95%

数据特性

- LTE FDD
  - Uplink 50Mbps / Downlink 150 Mbps
- TD-LTE
  - Uplink30Mbps / Downlink 112Mbps
- WCDMA
  - Uplink 5.76Mbps / Downlink 42Mbps
- TD-SCDMA
  - Uplink 2.2Mbps / Downlink 2.8Mbps
- EDGE (Multi-slot Class 12)
  - Uplink 236.8 kbps / Downlink: 236.8 kbps
- GPRS (Multi-slot Class 10)
  - Uplink 85.6 kbps / Downlink 85.6 kbps
- CDMA2000 EVDO
  - Uplink 1.8Mbps / Downlink 3.1Mbps
- CDMA2000 1X
  - Uplink 153.6 kbps / Downlink 153.6 kbps

短信特性

- Support Text and PDU mode
- Point to point MO and MT
- SMS Status Report
- SMS centre address setting
- Management of SMS

模组接口

- USB 2.0
- UART
- SIM interface (1.8/3.0V)
- Antenna (RF PAD for Primary, Diversity and GPS)
- LED indication
- Reset & Power-on
- WAKE-IN & WAKE-OUT

应用功能

- Support embedded TCP & UDP &FTP &HTTP protocols
- Support protocols PAP and CHAP used for PPP connection
- USB Selective Suspend & Remote wakeup
- RAS /ECM/NDIS
- Control Via AT Commands according to 3GPP TS27.005, 27.007 and GOSUNCN extended AT commands

驱动和工具

- Drivers
  - Windows XP, Vista, 7 , 8, Win CE, Windows Mobile
  - Linux
  - Android
- Diag-log Tool
- Firmware Update Tool

ME3630-W PCIE系列频段信息

型号	支持频段	分集	GNSS	Category
C2A_MP01 C2A_MP11	GSMB3/8 , CDMA1X CDMA EVDO 800M , WCDMA B1/5/8 TD-SCDMA B34/39 , LTE FDD B1/3/5/8 , LTE TDD B38/39/40/41	支持	支持	CAT4
C2B_MP01 C2B_MP11		不支持	不支持	CAT4
C2C_MP01 C2C_MP11		支持	支持	CAT4
C3B_MP01 C3B_MP11	LTE FDD: B1, B3, B5, B8 LTE TDD: B38, B39, B40, B41 WCDMA: B1, B5, B8 TD SCDMA: B34, B39 GSM: B3, B8 CDMA EVDO/ 1x: 800M	不支持	不支持	CAT4
C3C_MP01 C3C_MP11		支持	支持	CAT4
U1A_MP0 U1A_MP1	WCDMA B2/5 , LTE FDD B2/4/5/12/17	支持	支持	CAT4
U1C_MP0 U1C_MP1				CAT1
E1C_MP0 E1C_MP1	GSMB3/8 , WCDMA B1/8 , LTE FDD B1/3/7/8/20	支持	支持	CAT4
E2C_MP0 E2C_MP1	GSMB3/8 , WCDMA B1/8 , LTE FDD B1/3/7/8/20	支持	支持	CAT1
J2A_MP0 J2A_MP1	LTE FDD: B1, B3, B5, B7,B8, B18, B19, B21 WCDMA: B1, B5, B6, B8, B19	支持	支持	CAT4
J2AS_MP0 J2AS_MP1		支持	支持	CAT1