

# String diagrams for regular logic

David I. Spivak (joint with Brendan Fong)

Presented on 2018/10/27

Octoberfest

# Outline

## 1 Introduction

- Application: playing with logic
- Implications for string diagrams
- String diagrams for regular logic

## 2 Regular categories and regular logic

## 3 Bringing it all together

# Minority Report

The 2002 movie *Minority report* showed detective Tom Cruise playing seamlessly with logic.

- A computer database held relevant information.
- Cruise could pull it up, and manipulate it, to solve crimes.

# Minority Report

The 2002 movie *Minority report* showed detective Tom Cruise playing seamlessly with logic.

- A computer database held relevant information.
- Cruise could pull it up, and manipulate it, to solve crimes.


Let's imagine such a detective scenario. The knowledge base says:

- Any two people who work in the same tiny company are acquainted.
- *Categorical Informatics* is a tiny company.
- David works at *Categorical Informatics*.
- Ryan works at *Categorical Informatics*.

We of course want to conclude that David and Ryan are acquainted.



# Sample scenario

Assume:




# Sample scenario

Assume:





# Sample scenario

Assume:




# Sample scenario

Assume:




Show:






# Picture proof



Combine!

# Picture proof


Combined:



Group two Ci's!

# Picture proof


Ci's grouped:



Substitute!

# Picture proof


Substituted:



Group two Ci's!

# Picture proof


Two Ci's grouped:



Substitute!

# Picture proof


Substituted:



Group Ci!

# Picture proof


Ci grouped:



Discard group!

# Picture proof

Group discarded:




Group!



# Picture proof


Grouped:



Substitute!

# Picture proof

Substituted:




Done!

# Two-dimensional manipulation of string diagrams

In this talk we discuss a 2-dimensional language for wiring diagrams.

- It includes all the sorts of operations shown above.
- Together with operations like discarding and breaking wires:



# Comparing to other string diagram languages

Let's compare to string diagram calculus for traced SMCs and hypercats.

# Comparing to other string diagram languages



Let's compare to string diagram calculus for traced SMCs and hypercats.

- In traced SMCs, you can compose, tensor, swap, and trace.
  - You can do these anywhere in the diagram, with axioms.

# Comparing to other string diagram languages

Let's compare to string diagram calculus for traced SMCs and hypercats.



- In traced SMCs, you can compose, tensor, swap, and trace.
  - You can do these anywhere in the diagram, with axioms.
  - These can be considered generators and relations for an operad.
  - Traced categories are algebras on the operad 1-Cob.



# Comparing to other string diagram languages

Let's compare to string diagram calculus for traced SMCs and hypercats.

- In traced SMCs, you can compose, tensor, swap, and trace.
  - You can do these anywhere in the diagram, with axioms.
  - These can be considered generators and relations for an operad.
  - Traced categories are algebras on the operad 1-Cob.
- In hypergraph categories, add Frobenius maps, plus axioms.
  - Hypergraph categories are algebras on the operad Cospan.



# Comparing to other string diagram languages

Let's compare to string diagram calculus for traced SMCs and hypercats.

- In traced SMCs, you can compose, tensor, swap, and trace.
  - You can do these anywhere in the diagram, with axioms.
  - These can be considered generators and relations for an operad.
  - Traced categories are algebras on the operad 1-Cob.
- In hypergraph categories, add Frobenius maps, plus axioms.
  - Hypergraph categories are algebras on the operad Cospan.
- In our picture proof, we had more operations and relations.
  - Order on elements of each arity, preserved by substitution.
  - Meet-semilattice structures on elements of each arity.
  - Top element (true) can be discarded; corresponding structure for  $\wedge$ .
  - Removing dots, breaking wires.

We will see that this is a 2-dimensional structure.




# Formal presentation of the calculus I.

The graphical calculus shown above can be understood as follows.

- Fix a set  $\Lambda$  (elements will be string labels).
- Consider the monoidal bicategory  $\mathcal{C}ospan_{\Lambda}^{co}$ .

# Formal presentation of the calculus I.

The graphical calculus shown above can be understood as follows.

- Fix a set  $\Lambda$  (elements will be string labels).
- Consider the monoidal bicategory  $\mathcal{C}ospan_{\Lambda}^{\text{co}}$ .
  - Objects: arities  $\underline{n} \xrightarrow{v} \Lambda$ , i.e. lists  $(v(1), \dots, v(n)) \in \Lambda^n$ .
  - 1-morphisms:
 
  - 2-morphisms: opposite of usual direction (hence  $-\text{co}$ )
  - Monoidal structure:  $(0, +)$ .

# Formal presentation of the calculus I.

The graphical calculus shown above can be understood as follows.

- Fix a set  $\Lambda$  (elements will be string labels).
- Consider the monoidal bicategory  $\mathcal{Cosp}_{\Lambda}^{\text{co}}$ .
  - Objects: arities  $\underline{n} \xrightarrow{v} \Lambda$ , i.e. lists  $(v(1), \dots, v(n)) \in \Lambda^n$ .
  - 1-morphisms:
 

$$\begin{array}{ccccc}
 n_1 & \xrightarrow{\quad} & n_{12} & \xleftarrow{\quad} & n_2 \\
 & \searrow v_1 & \downarrow & \swarrow v_2 & \\
 & & \Lambda & & 
 \end{array}$$
  - 2-morphisms: opposite of usual direction (hence  $-^{\text{co}}$ )
  - Monoidal structure:  $(0, +)$ .
- Consider the (locally posetal) monoidal bicategory  $\mathcal{P}\text{oset}$ .
  - Obj: posets; 1-morphisms: monotone maps; 2-morphisms: nat. trans.
  - Monoidal structure:  $(1, \times)$ .

# Formal presentation of the calculus II.

We have monoidal bicategories  $\mathcal{C}ospan$  and  $\mathcal{P}oset$ .

## Definition

A *regular hypergraph category* is a lax monoidal 2-functor

$$T: \mathcal{C}ospan_{\Lambda}^{\text{co}} \rightarrow \mathcal{P}oset$$

such that the laxators are right adjoints.

# Formal presentation of the calculus II.

We have monoidal bicategories  $\mathcal{C}ospan$  and  $\mathcal{P}oset$ .

## Definition

A *regular hypergraph category* is a lax monoidal 2-functor

$$T: \mathcal{C}ospan_{\Lambda}^{\text{co}} \rightarrow \mathcal{P}oset$$

such that the laxators are right adjoints.

Silly terminology: *ajax* monoidal functors: the laxators

$$1 \xrightarrow{\rho_1} T(0) \quad \text{and} \quad T(v) \times T(v') \xrightarrow{\rho_{v,v'}} T(v + v')$$

# Formal presentation of the calculus II.

We have monoidal bicategories  $\mathcal{C}ospan$  and  $\mathcal{P}oset$ .

## Definition

A *regular hypergraph category* is a lax monoidal 2-functor

$$T: \mathcal{C}ospan_{\Lambda}^{\text{co}} \rightarrow \mathcal{P}oset$$

such that the laxators are right adjoints.

Silly terminology: *ajax* monoidal functors: the laxators are adjoints

$$1 \begin{array}{c} \xrightarrow{\rho_1} \\ \overleftarrow{\top} \\ \xleftarrow{\lambda_1} \end{array} T(0) \quad \text{and} \quad T(v) \times T(v') \begin{array}{c} \xrightarrow{\rho_{v,v'}} \\ \overleftarrow{\top} \\ \xleftarrow{\lambda_{v,v'}} \end{array} T(v + v')$$

# Aside: we're pushing this notation for adjunctions

Throughout this talk, I'll use a new notation for adjunctions.

■ Usual notation:  $C \begin{array}{c} \xrightarrow{R} \\ \top \\ \xleftarrow{L} \end{array} D \quad C \begin{array}{c} \xleftarrow{L} \\ \perp \\ \xrightarrow{R} \end{array} D \quad D \begin{array}{c} \xrightarrow{L} \\ \perp \\ \xleftarrow{R} \end{array} C.$

- Note that  $\top$  is sometimes used as the name of a monad, but...
- ... it really doesn't indicate where the monad is (it's on  $D$ ).

# Aside: we're pushing this notation for adjunctions

Throughout this talk, I'll use a new notation for adjunctions.

■ Usual notation:  $C \begin{array}{c} \xrightarrow{R} \\ \top \\ \xleftarrow{L} \end{array} D \quad C \begin{array}{c} \xleftarrow{L} \\ \perp \\ \xrightarrow{R} \end{array} D \quad D \begin{array}{c} \xrightarrow{L} \\ \perp \\ \xleftarrow{R} \end{array} C.$

- Note that  $\top$  is sometimes used as the name of a monad, but...
- ... it really doesn't indicate where the monad is (it's on  $D$ ).

■ Our notation:  $C \begin{array}{c} \xrightarrow{R} \\ \Leftarrow \\ \xleftarrow{L} \end{array} D \quad C \begin{array}{c} \xleftarrow{L} \\ \Leftarrow \\ \xrightarrow{R} \end{array} D \quad D \begin{array}{c} \xrightarrow{L} \\ \Rightarrow \\ \xleftarrow{R} \end{array} C$

- The 2-arrow points in the direction of the left adjoint.
- Reason: it tells you the direction of the unit and counit.



# Aside: we're pushing this notation for adjunctions

Throughout this talk, I'll use a new notation for adjunctions.

■ Usual notation:  $C \begin{array}{c} \xrightarrow{R} \\ \top \\ \xleftarrow{L} \end{array} D$

- Note that  $\top$  is sometimes used as the name of a monad, but...
- ... it really doesn't indicate where the monad is (it's on  $D$ ).

■ Our notation:  $C \begin{array}{c} \xrightarrow{R} \\ \Leftarrow \\ \xleftarrow{L} \end{array} D$

- The 2-arrow points in the direction of the left adjoint.
- Reason: it tells you the direction of the unit and counit.

$$\begin{array}{ccc} C & & \\ \parallel & \swarrow R & \\ C & \Leftarrow & D \\ & \nwarrow L & \end{array}$$

$$\begin{array}{ccc} & & D \\ & \swarrow R & \\ C & \Leftarrow & \\ & \nwarrow L & \end{array}$$

# Regular hypergraph categories and regular categories

Denote by  $\mathcal{C}\text{ospan-Alg}$  the category of regular hypergraph categories, i.e. sets  $\Lambda$  and ajax 2-functors

$$T: \mathcal{C}\text{ospan}_{\Lambda}^{\text{co}} \rightarrow \mathcal{P}\text{oset}.$$

# Regular hypergraph categories and regular categories

Denote by  $\mathcal{C}\text{ospan-Alg}$  the category of regular hypergraph categories, i.e. sets  $\Lambda$  and ajax 2-functors

$$T: \mathcal{C}\text{ospan}_{\Lambda}^{\text{co}} \rightarrow \mathcal{P}\text{oset}.$$

## Theorem

*There is an adjunction*

$$\mathcal{C}\text{ospan-Alg} \begin{array}{c} \xrightarrow{\Phi} \\ \Rrightarrow \\ \xleftarrow{\Psi} \end{array} \text{RegCat} ,$$

*such that for any regular category  $\mathcal{R}$ , the counit  $\Psi(\Phi(\mathcal{R})) \rightarrow \mathcal{R}$  is an equivalence of categories.*

# Plan

- We'll return to the theorem shortly.
- First we want to recall the definition of regular categories.
- We also want to make the connection to regular logic.
  - The *Cospan*-algebra story is a graphical representation of the logic.
  - This will be evident, but one can take the theorem as justification.
- Then we'll unpack the theorem and conclude.

# Outline

- 1 Introduction
- 2 Regular categories and regular logic**
  - Regular categories
  - Regular logic
- 3 Bringing it all together

# Regular categories

## Definition

A *regular category* is a category for which

- all finite limits exist,
- the kernel pair of any morphism admits a coequalizer, and
- coequalizers are stable under pullback.

# Regular categories

## Definition

A *regular category* is a category for which

- all finite limits exist,
- the kernel pair of any morphism admits a coequalizer, and
- coequalizers are stable under pullback.

Examples of regular categories:

- Set, and more generally any topos;
- $\text{Set}^{\text{op}}$ , opposite of any topos,  $\text{TopSp}^{\text{op}}$ ;
- The category of models of any Lawvere theory (Groups, Rings, ...);
- The slice (also the coslice) of any regular category over any object;
- Exponential ideal: if  $\mathcal{R}$  regular and  $\mathcal{C}$  a category, then  $\mathcal{R}^{\mathcal{C}}$  is regular.

# How to think of regular categories

Regular categories are those with a good *bicategory of relations*.

- A relation in  $\mathcal{R}$  is a subobject  $S \subseteq A \times B$ .
- When  $\mathcal{R}$  is regular, pullbacks and images play nicely...



# How to think of regular categories

Regular categories are those with a good *bicategory of relations*.

- A relation in  $\mathcal{R}$  is a subobject  $S \subseteq A \times B$ .
- When  $\mathcal{R}$  is regular, pullbacks and images play nicely...
- ... so that relations form a posetal bicategory  $\mathcal{Rel}_{\mathcal{R}}$ .
  - That is, relations can be composed and compared.
  - One can recover the morphisms in  $\mathcal{R}$  as the adjunctions in  $\mathcal{Rel}_{\mathcal{R}}$  !

# How to think of regular categories

Regular categories are those with a good *bicategory of relations*.

- A relation in  $\mathcal{R}$  is a subobject  $S \subseteq A \times B$ .
- When  $\mathcal{R}$  is regular, pullbacks and images play nicely...
- ... so that relations form a posetal bicategory  $\mathcal{Rel}_{\mathcal{R}}$ .
  - That is, relations can be composed and compared.
  - One can recover the morphisms in  $\mathcal{R}$  as the adjunctions in  $\mathcal{Rel}_{\mathcal{R}}$  !
- Every young category theorist should prove to themselves that  $\mathbf{Set}$  is the category of adjunctions in  $\mathbf{Rel}$ .

# How to think of regular categories

Regular categories are those with a good *bicategory of relations*.

- A relation in  $\mathcal{R}$  is a subobject  $S \subseteq A \times B$ .
- When  $\mathcal{R}$  is regular, pullbacks and images play nicely...
- ... so that relations form a posetal bicategory  $\mathcal{Rel}_{\mathcal{R}}$ .
  - That is, relations can be composed and compared.
  - One can recover the morphisms in  $\mathcal{R}$  as the adjunctions in  $\mathcal{Rel}_{\mathcal{R}}$  !
- Every young category theorist should prove to themselves that  $\mathbf{Set}$  is the category of adjunctions in  $\mathbf{Rel}$ .

Regular categories have enough structure to do regular logic.

# Regular logic and regular categories

In regular logic, one has

- A set of *types*  $\Lambda$

# Regular logic and regular categories

In regular logic, one has

- A set of *types*  $\Lambda$
- A set of *relation symbols*  $\vdash_{a_1:A_1, \dots, a_k:A_k} R_1(a_1, \dots, a_k) : Prop$

# Regular logic and regular categories

In regular logic, one has

- A set of *types*  $\Lambda$
- A set of *relation symbols*  $\vdash_{a_1:A_1, \dots, a_k:A_k} R_1(a_1, \dots, a_k) : Prop$
- Operations  $\wedge$ ,  $\text{true}$ ,  $=$ , and  $\exists$ , from which to build up formulas  $\varphi, \psi$ .

# Regular logic and regular categories

In regular logic, one has

- A set of *types*  $\Lambda$
- A set of *relation symbols*  $\vdash_{a_1:A_1, \dots, a_k:A_k} R_1(a_1, \dots, a_k) : Prop$
- Operations  $\wedge$ ,  $\text{true}$ ,  $=$ , and  $\exists$ , from which to build up formulas  $\varphi, \psi$ .
- A notion of entailment:  $\varphi \vdash_{a:A, b:B} \psi$ .
- A set of axioms involving entailment.

# Regular logic and regular categories

In regular logic, one has

- A set of *types*  $\Lambda$
- A set of *relation symbols*  $\vdash_{a_1:A_1, \dots, a_k:A_k} R_1(a_1, \dots, a_k) : Prop$
- Operations  $\wedge$ ,  $\text{true}$ ,  $=$ , and  $\exists$ , from which to build up formulas  $\varphi, \psi$ .
- A notion of entailment:  $\varphi \vdash_{a:A, b:B} \psi$ .
- A set of axioms involving entailment.

Example: the regular theory of “two sets and a function”:



# Regular logic and regular categories

In regular logic, one has

- A set of *types*  $\Lambda$
- A set of *relation symbols*  $\vdash_{a_1:A_1, \dots, a_k:A_k} R_1(a_1, \dots, a_k) : Prop$
- Operations  $\wedge$ ,  $\text{true}$ ,  $=$ , and  $\exists$ , from which to build up formulas  $\varphi, \psi$ .
- A notion of entailment:  $\varphi \vdash_{a:A, b:B} \psi$ .
- A set of axioms involving entailment.


Example: the regular theory of “two sets and a function”:

- $\Lambda = \{A, B\}$ , one relation symbol:  $\vdash_{a:A, b:B} f(a, b) : Prop$
- Axioms:

$f$  is “total”:  $\text{true} \vdash_{a:A} \exists(b : B). f(a, b)$


$f$  is “deterministic”:  $\exists(a : A). f(a, b) = f(a, b') \vdash_{b, b':B} b = b'$

# Regular logic and cospan-algebras




$$\text{true} \vdash_{a:A} \exists(b : B). f(a, b)$$

# Regular logic and cospan-algebras



$$\text{true} \vdash_{a:A} \exists(b : B). f(a, b)$$



$$\exists(a : A). f(a, b_1) = f(a, b_2) \vdash_{b_1, b_2 : B} b_1 = b_2$$

# Outline

- 1 Introduction
- 2 Regular categories and regular logic
- 3 Bringing it all together**
  - Where are we?
  - Recalling and justifying the theorem
  - Concluding

# Where are we?

We have regular categories, regular logic, and cospan-algebras.

- They are three different perspectives on the same subject.
- Regular logic is an “internal language” for regular categories.

# Where are we?

We have regular categories, regular logic, and cospan-algebras.

- They are three different perspectives on the same subject.
- Regular logic is an “internal language” for regular categories.
- The bicategory of cospans is a “string diagram language” for regcats.

# Where are we?

We have regular categories, regular logic, and cospan-algebras.

- They are three different perspectives on the same subject.
- Regular logic is an “internal language” for regular categories.
- The bicategory of cospans is a “string diagram language” for regcats.

Next we'll recall the theorem, give one slide of justification, and conclude.

# Recalling the theorem

Recall that a Cospan-algebra is an ajax 2-functor  $T: \text{Cospan}_{\Lambda}^{\text{co}} \rightarrow \text{Poset}$ .

## Theorem

*There is an adjunction  $\text{Cospan-Alg} \rightleftarrows \text{RegCat}$ , such that  $\Psi(\Phi(\mathcal{R})) \rightarrow \mathcal{R}$  is an equivalence for any regular category  $\mathcal{R}$ .*



# Recalling the theorem

Recall that a Cospan-algebra is an ajax 2-functor  $T: \text{Cospan}_{\Lambda}^{\text{co}} \rightarrow \text{Poset}$ .

## Theorem

*There is an adjunction  $\text{Cospan-Alg} \rightleftarrows \text{RegCat}$ , such that  $\Psi(\Phi(\mathcal{R})) \rightarrow \mathcal{R}$  is an equivalence for any regular category  $\mathcal{R}$ .*

Comments:

- We can beef this up to a 2-reflection  $\text{RegCat} \subseteq \text{Cospan-Alg}$ .

# Recalling the theorem

Recall that a Cospan-algebra is an ajax 2-functor  $T: \text{Cospan}_{\Lambda}^{\text{co}} \rightarrow \text{Poset}$ .

## Theorem

*There is an adjunction  $\text{Cospan-Alg} \xrightleftharpoons{\quad} \text{RegCat}$ , such that  $\Psi(\Phi(\mathcal{R})) \rightarrow \mathcal{R}$  is an equivalence for any regular category  $\mathcal{R}$ .*

Comments:

- We can beef this up to a 2-reflection  $\text{RegCat} \subseteq \text{Cospan-Alg}$ .
- Cospan algebras and regular categories look different on the surface.
  - Remember how complicated the def. of regcats was?
  - Finite limits, coequalizers of kernel pairs, pullback stability.
  - $\text{Cospan-Alg}$  is certain functors  $\text{Cospan} \rightarrow \text{Poset}$ .

# Recalling the theorem

Recall that a Cospan-algebra is an ajax 2-functor  $T: \text{Cospan}_{\Lambda}^{\text{co}} \rightarrow \text{Poset}$ .

## Theorem

*There is an adjunction  $\text{Cospan-Alg} \xrightleftharpoons{\quad} \text{RegCat}$ , such that  $\Psi(\Phi(\mathcal{R})) \rightarrow \mathcal{R}$  is an equivalence for any regular category  $\mathcal{R}$ .*

Comments:

- We can beef this up to a 2-reflection  $\text{RegCat} \subseteq \text{Cospan-Alg}$ .
- Cospan algebras and regular categories look different on the surface.
  - Remember how complicated the def. of regcats was?
  - Finite limits, coequalizers of kernel pairs, pullback stability.
  - $\text{Cospan-Alg}$  is certain functors  $\text{Cospan} \rightarrow \text{Poset}$ .
- Easier to see posets and adjunctions in  $\text{RegCat}$ : subobject lattices.

# Why it works


One can form the *syntactic category*  $\mathcal{R}_T$  of  $T: \mathcal{C}\text{ospan}_\Lambda \rightarrow \mathcal{P}\text{oset}$ .

■  $\text{Ob}(\mathcal{R}_T) := \{(\nu, \varphi) \mid \underline{n} \xrightarrow{\nu} \Lambda, \varphi \in T(\nu)\}.$




# Why it works

One can form the *syntactic category*  $\mathcal{R}_T$  of  $T: \text{Cospan}_\Lambda \rightarrow \text{Poset}$ .

- $\text{Ob}(\mathcal{R}_T) := \{(v, \varphi) \mid \underline{n} \xrightarrow{v} \Lambda, \varphi \in T(v)\}$ . 
- $\mathcal{R}_T((v, \varphi), (v', \varphi')) := \{\theta \in T(v+v') \mid \theta \vdash \varphi, \theta \vdash \varphi', \theta \text{ is functional}\}$



$\vdash$




$\vdash$



+ another logical condition


# Why it works

One can form the *syntactic category*  $\mathcal{R}_T$  of  $T: \text{Cospan}_\Lambda \rightarrow \text{Poset}$ .

- $\text{Ob}(\mathcal{R}_T) := \{(v, \varphi) \mid \underline{n} \xrightarrow{v} \Lambda, \varphi \in T(v)\}$ . 
- $\mathcal{R}_T((v, \varphi), (v', \varphi')) := \{\theta \in T(v+v') \mid \theta \vdash \varphi, \theta \vdash \varphi', \theta \text{ is functional}\}$



$\vdash$



$\vdash$




+ another logical condition

One shows that this syntactic category is regular.

- E.g. for each  $v$ , the poset  $T(v)$  is automatically a meet-semilattice.


# Why it works

One can form the *syntactic category*  $\mathcal{R}_T$  of  $T: \mathcal{C}\text{ospan}_\Lambda \rightarrow \mathcal{P}\text{oset}$ .

- $\text{Ob}(\mathcal{R}_T) := \{(v, \varphi) \mid \underline{n} \xrightarrow{v} \Lambda, \varphi \in T(v)\}$ . 
- $\mathcal{R}_T((v, \varphi), (v', \varphi')) := \{\theta \in T(v+v') \mid \theta \vdash \varphi, \theta \vdash \varphi', \theta \text{ is functional}\}$



$\vdash$



$\vdash$




+ another logical condition

One shows that this syntactic category is regular.

- E.g. for each  $v$ , the poset  $T(v)$  is automatically a meet-semilattice.
  - Why? Any function  $v \xrightarrow{f} w$  is an adjoint in  $\mathcal{C}\text{ospan}...$
  - ... so  $T(f)$  will be an adjoint in  $\mathcal{P}\text{oset}$ . Thus we get adjunctions:

# Why it works

One can form the *syntactic category*  $\mathcal{R}_T$  of  $T: \mathcal{C}ospan_\Lambda \rightarrow \mathcal{P}oset$ .

- $\text{Ob}(\mathcal{R}_T) := \{(v, \varphi) \mid \underline{n} \xrightarrow{v} \Lambda, \varphi \in T(v)\}$ . 
- $\mathcal{R}_T((v, \varphi), (v', \varphi')) := \{\theta \in T(v+v') \mid \theta \vdash \varphi, \theta \vdash \varphi', \theta \text{ is functional}\}$



+ another logical condition

One shows that this syntactic category is regular.


- E.g. for each  $v$ , the poset  $T(v)$  is automatically a meet-semilattice.
  - Why? Any function  $v \xrightarrow{f} w$  is an adjoint in  $\mathcal{C}ospan...$
  - ... so  $T(f)$  will be an adjoint in  $\mathcal{P}oset$ . Thus we get adjunctions:

$$1 \xrightleftharpoons[\leftarrow]{\rho_1} T(0) \xrightleftharpoons[\leftarrow]{} T(v)$$



# Why it works

One can form the *syntactic category*  $\mathcal{R}_T$  of  $T: \mathcal{C}ospan_\Lambda \rightarrow \mathcal{P}oset$ .

- $\text{Ob}(\mathcal{R}_T) := \{(v, \varphi) \mid \underline{n} \xrightarrow{v} \Lambda, \varphi \in T(v)\}$ . 
- $\mathcal{R}_T((v, \varphi), (v', \varphi')) := \{\theta \in T(v+v') \mid \theta \vdash \varphi, \theta \vdash \varphi', \theta \text{ is functional}\}$



+ another logical condition

One shows that this syntactic category is regular.

- E.g. for each  $v$ , the poset  $T(v)$  is automatically a meet-semilattice.
  - Why? Any function  $v \xrightarrow{f} w$  is an adjoint in  $\mathcal{C}ospan...$
  - ... so  $T(f)$  will be an adjoint in  $\mathcal{P}oset$ . Thus we get adjunctions:

$$1 \xrightleftharpoons[\rho_1]{\rho_1} T(0) \xrightleftharpoons{\quad} T(v)$$

$$T(v) \times T(v) \xrightleftharpoons[\rho_{v,v}]{\rho_{v,v}} T(v+v) \xrightleftharpoons{\quad} T(v)$$

# Conjecture and outlook

We conjecture that this story extends to coherent and geometric logic.

# Conjecture and outlook

We conjecture that this story extends to coherent and geometric logic.

## Conjecture

The 2-category of coherent categories is reflective in that of:

# Conjecture and outlook

We conjecture that this story extends to coherent and geometric logic.

## Conjecture

The 2-category of coherent categories is reflective in that of: lax monoidal 2-functors  $\mathcal{C}\text{ospan}^{\text{co}} \rightarrow \mathcal{J}\text{Lat}$

# Conjecture and outlook

We conjecture that this story extends to coherent and geometric logic.

## Conjecture

The 2-category of coherent categories is reflective in that of: lax monoidal 2-functors  $\mathcal{C}\text{ospan}^{\text{co}} \rightarrow \mathcal{J}\text{Lat}$  whose composite with  $\mathcal{J}\text{Lat} \rightarrow \mathcal{P}\text{oset}$  is ajax.

# Conjecture and outlook

We conjecture that this story extends to coherent and geometric logic.

## Conjecture

The 2-category of **geometric** categories is reflective in that of: lax monoidal 2-functors  $\mathcal{C}ospan^{co} \rightarrow \mathbf{SupLat}$  whose composite with  $\mathbf{SupLat} \rightarrow \mathcal{P}oset$  is ajax.

# Conjecture and outlook

We conjecture that this story extends to coherent and geometric logic.

## Conjecture

The 2-category of geometric categories is reflective in that of: lax monoidal 2-functors  $\mathcal{C}ospan^{co} \rightarrow \mathcal{S}upLat$  whose composite with  $\mathcal{S}upLat \rightarrow \mathcal{P}oset$  is ajax.

- Dropping the ajax condition may give something like quantaloids.

# Conjecture and outlook

We conjecture that this story extends to coherent and geometric logic.

## Conjecture

The 2-category of geometric categories is reflective in that of: lax monoidal 2-functors  $\mathcal{C}ospan^{\text{co}} \rightarrow \mathcal{S}upLat$  whose composite with  $\mathcal{S}upLat \rightarrow \mathcal{P}oset$  is ajax.

- Dropping the ajax condition may give something like quantaloids.
- Landing in categories other than  $\mathcal{P}oset$  gives “fuzzy regcats.”
  - E.g.  $\mathcal{C}ospan \rightarrow \mathcal{L}awvMetSp$ : “distance to entailment”  $\varphi \vdash^{17} \psi$ .
  - Other quantales (e.g. powerset of a monoid) give other fuzz.



# Summary

- Formulas in regular logic looks like this:


$$\exists b. f(a, b) \wedge g(b, a') \vdash_{a, a'} \exists c. h(c, a) \wedge a = a'.$$

# Summary

- Formulas in regular logic looks like this:

$$\exists b. f(a, b) \wedge g(b, a') \vdash_{a, a'} \exists c. h(c, a) \wedge a = a'.$$

- Such things can be represented pictorially in a regular hypercat:



i.e. as an inequality of elements in an ajax monoidal 2-functor


$$T: \mathcal{Cospan}^{\text{co}} \rightarrow \mathcal{Poset}.$$

# Summary

- Formulas in regular logic looks like this:

$$\exists b. f(a, b) \wedge g(b, a') \vdash_{a, a'} \exists c. h(c, a) \wedge a = a'.$$

- Such things can be represented pictorially in a regular hypercat:



i.e. as an inequality of elements in an ajax monoidal 2-functor

$$T: \mathcal{Cospan}^{\text{co}} \rightarrow \mathcal{Poset}.$$

- We have 2-reflectivity, suggesting that the diagram language is robust.

*Thanks! Comments and questions welcome.*