

/status Command Documentation

Summary: The `/status` command provides a fast, concise status check of the current project state.

Generated: 2026-01-12 05:36 UTC | Ideas Extracted: 18

What Happened

The `/status` command provides a fast, concise status check of the current project state. It focuses on essential information: git status, active work, recent changes, and quick health indicators. Designed for immediate awareness without comprehensive analysis.

Speed First: Get status in seconds, not minutes
Essentials Only: Focus on what matters right now
Actionable: Information you can act on immediately
No Analysis: Just facts, no deep analysis
Current State: What's happening now, not history.

Execution Time: < 5 seconds
Output: Console display only (no files created)
Purpose: Quick status awareness without interrupting workflow.

Actions: Check for active work efforts (via MCP or file system)
List active work effort names
Check for recent devlog entries
Identify current working directory context.

Recent Activity: Last Commit: 2 hours ago - "Created /deep-analyze command"
Recent Files: `.cursor/commands/deep-analyze.md` (new) `.cursor/commands/status.md` (new) `workefforts/devlog.md` (modified)
Devlog: Last entry 2 hours ago.

Command	Speed	Detail	Use Case	----- ----- ----- -----	/status	⚡ Fast (< 5s)	Minimal
Quick check	/checkpoint	🐢 Slow (~30s)	Comprehensive	Full snapshot	/waft-status	🐢 Slow (~60s)	Very Detailed
System analysis	/spin-up	🐢 Slow (~30s)	Detailed	Orientation	/stats	⚡ Fast (< 5s)	Session stats
Session metrics							

`/checkpoint`: Comprehensive status (`/status` is quick snapshot)
`/waft-status`: Detailed system status (`/status` is minimal)
`/spin-up`: Orientation (`/status` is just current state)
`/verify`: Verification (`/status` is just status check)
`/stats`: Session statistics (`/status` is project state).

Use /status when:  Need quick status check (< 5 seconds)  Want immediate awareness  Need current state snapshot  Checking before starting work  Want minimal output.

Don't use /status when:  Need comprehensive analysis (use /checkpoint or /waft-status)  Need historical trends (use /analyze)  Need detailed documentation (use /waft-status --docs)  Need session statistics (use /stats).

Additional Details

Git Commands: `git status --short` - Quick git status `git branch --show-current` - Current branch `git log --oneline -5` - Recent commits.

MCP Servers (if available): `mcpwork-effortslstworkefforts` - Active work efforts
`mcpfilesystemlist_directory` - Directory contents.

Git Errors: Show "Git unavailable" and continue File Errors: Show "Unable to check" and continue MCP Errors: Fall back to file system checks Always Complete: Always show what's available.

Run Frequently: Check status regularly during work Use Before Commits: Check status before committing Use at Session Start: Quick check when starting work Keep It Quick: Don't add analysis, keep it fast Focus on Now: Current state, not history.

Created: 2026-01-11 Status:  Active Location: `./cursor/commands/status.md` Global: Available in all Cursor instances via `~/.cursor/commands/`.

Scenario: Want to see what's changed before committing.

Scenario: Need to understand current context quickly.

File System: `find` - Recent file modifications `ls -lt` - File timestamps.

Status is displayed in console only. No files are created.

Content Breakdown

Type	Count
Decisions	0
Insights	0
Actions	5
Concepts	7
Questions	6