AI-Driven Approaches for Improved Detection and Diagnosis of Pancreatic Cancer

1st Rupam Sah
Computer Science and Engineering
Dr B R Ambedkar NIT Jalandhar
Jalandhar, India
rupamsah2002@gmail.com

2nd Renu Dhir
Computer Science and Engineering
Dr B R Ambedkar NIT Jalandhar
Jalandhar, India
dhirr@nitj.ac.in

3rd Suchi Jain
Computer Science and Engineering
Dr B R Ambedkar NIT Jalandhar
Jalandhar, India
suchij.cs.22@nitj.ac.in

2025 International Conference on Ambient Intelligence in Health Care (ICAIHC) | 979-8-3315-3025-9/25/$31.00 ©2025 IEEE | DOI: 10.1109/ICAIHC64101.2025.10956704

***Abstract*— Pancreatic Cancer, although one of the most dangerous cancers, has an unfavorable prognosis because of the fact that there are no particular symptoms and it is usually diagnosed on a later stage. This review discusses the possibilities offered by artificial intelligence and especially machine learning and deep learning techniques for the enhancement of detecting and diagnosing pancreatic cancer. The review emphasizes advanced AI models for pancreatic tumor's classification and outlining which include convolutional neural networks (CNNs) as well as segmentation methods. These AI enhanced approaches aim at achieving accurate, early diagnosis by integrating multiple image modalities including contrast-enhanced computed tomography (CT), magnetic resonance imaging (MRI), endoscopic ultrasound (EUS) and histopathological images as well as biomarkers CA19-9 and genetic information. Besides, the paper analyses some optimization methods that ensure model performance and data security in a cooperative multi-institutional environment, such as federated learning and genetic algorithms. It is also important to consider how intelligence can reduce misdiagnosis, reduce the number of clinics, and save money for patients. This article addresses the challenges in image analysis, provides a comprehensive review of AI applications in cancer diagnosis, and offers suggestions for future research on how to create AI systems that can be easily integrated.**

Keywords*— *Pancreatic cancer, Early discovery, Artificial Intelligence (AI), Machine learning (ML), Restorative imaging.

I. Introduction

One of the deadliest types of cancer is pancreatic cancer, characterized by movement and symptoms. Although it is the 12th most common cancer worldwide, it is the fourth leading cause of cancer deaths due to its often-delayed diagnosis and limited treatment options in advanced stages. After five years, the survival rate is still below 10%, highlighting the urgent need for early diagnosis [1][2][3] the deep anatomical location of the pancreas and the need for early indications, traditional imaging modalities such as computed tomography (CT), magnetic resonance imaging (MRI), and endoscopic ultrasound (EUS) are not useful, especially in identifying small tumours in pancreatic cancer [4][5][6].

The inadequacy of traditional presentation methods has led to interest in artificial intelligence (AI) as a revolutionary approach to advance pancreatic cancer diagnosis. Artificial Intelligence (AI), especially in machine learning (ML) and deep learning (DL) models, holds promise for improving the suitability, accuracy, and efficiency of cinema technology by evaluating data recovery images. To improve the accuracy of image segmentation and cancer detection, U-Net and its derivatives are used in CT and MRI images (a type of artificial intelligence representation) neural network (CNN) [7] [8] [9]. Studies have shown that this model can detect fine details such as biliary dilatation and can help detect pancreatic problems at an early stage [3] [5].

New work has been published that investigates mixed AI platforms, which combine more than one imaging modality and biomarker for a holistic diagnostic view. Combining imaging (CT, MRI and EUS) with biomarkers such as CA19-9 or genetic markers has the potential of improving diagnostic accuracy and specificity [10]. With the added use of biomarkers and imaging, these same AI models can identify tumours early on than what traditional tools will inevitably fail to capture translating into better outcomes for patients [8][11]. Such a solution is especially important in the context of cancer subtypes such as pancreatic and provides more comprehensive coverage of tumour attributes (multimodal). Despite the positive developments in AI applications, there remain hurdles to scale [2][3]. One of the most important obstacles to proper AI show planning is having enormous, organized and well-labelled datasets [12].

In the absence of these datasets, models perform poorly across demographics and imaging scenarios leading to poor generalizability rendering them unreliable for real-world clinical settings. Furthermore, deep learning models—especially CNNs—are often treated as "black boxes," that is it remains unclear why they are making their choices [3, 4]. This lack of transparency is a barrier to their wider acceptance in the medical community. The inability of models to generalize across multiple imaging conditions and patient demographics is thus likely the cause behind limited improvement in reliability within clinical settings [3][4]. Especially CNNs can be regarded as black-box models, since it is often unclear for which reasons decisions have been made. This transparency limits the application of health-care usage as doctors have to understand these systems and trust them before applying it through diagnosis processes [3].

The field is now trying to develop explainable AI (XAI) models to make it easier for doctors understand an AI system and improve trust between them. Now, XAI methods illustrate the reason behind why an AI concluded what it did and thus they place more trust into these results in a healthcare context [7][11]. Federated learning is also being used to enhance data privacy of the AI model by enabling it to learn from patient data which are not necessarily shared in one location. This process ensures we can develop AI systems that are effective while protecting patient privacy.

The incorporation of AI with multi-modal data fusing imaging modalities with biomarkers and genetic information provides a route toward further improvement in diagnostic precision. In fact, multi-modal models proved to be capable of

979-8-3315-3025-9/25/$31.00 ©2025 IEEE

Authorized licensed use limited to: NATIONAL INSTITUTE OF TECHNOLOGY CALICUT. Downloaded on January 08,2026 at 17:09:29 UTC from IEEE Xplore. Restrictions apply.

significantly improving rates of early detection by integrating multiple sources of data in the same diagnostic tool [13][14]. An example would be the intelligent systems that have been proved to not only increase the accuracy of diagnosis but also predict patient outcomes and provide individualized treatment plans by integrating MRI scans with genetic markers [3][5]. However, the deployment of AI in clinical practice raises ethical and regulatory concerns. Data privacy and security become very important, especially for sensitive health care information. In the development of more extensive, diverse datasets that would improve AI models' performance, collaborative efforts among institutions would be required to standardize protocols in the management and sharing of data [1][6]. Furthermore, bias within the AI models should be dealt with, among other aspects, for the said tool to be expected to provide the same quality care to populations of varied demographics [15][16].

This study is set to unveil the novel application of artificial intelligence in the detection of pancreatic cancer, discussing the potency of artificial intelligence in improving diagnostic efficiency, and it went ahead to highlight the existing challenges and room for improvement [10][11]. The paper opens up transformative tendencies through synthesis and multiple studies undertaken. This thrusts into significance the role AI might be playing in revolutionizing the diagnostics of pancreatic cancer, especially on how advanced techniques in ML and DL are applied across the imaging modality and biomarker analyses for the early detection of pancreatic cancer [3][4]. The review also talks about future research directions geared towards optimizing the clinical implementation of AI in improving patient outcomes, as well as ensuring the safety, effectiveness, and access of these technologies [5][6].

II. Research Paper

A. Research Questions

This review outlines some of the necessary critical questions that need to be raised in research related to the application of AI-based techniques in the early detection and diagnosis of pancreatic cancer, and which are as follows:

1) Which type of AI technique; deep learning or machine learning, would be the most appropriate one in early diagnosing pancreas cancer?

This will evaluate and measure the performance of ML and DL models, specifically CNNs, U-Net or any of its variants on images acquired through CT scans, MRI, EUS, and PET imaging modalities which are meant to be used for pancreas cancer segmentation and classification operations. The models and algorithms will then be evaluated based on how well they produce diagnostic reliability and accuracy.

2) What Potentials Can Be Realized by the Multimodality Imaging Data in Case These Are Combined with AI Potentiation Toward Advanced Accuracy in Diagnostic and Early Detection of Pancreatic Cancer?

This question has probed whether a lot of the imaging modalities, such as CT, MRI, EUS, and PET could all be potentially combined into AI frameworks to guide research to assess ways in which these data sources might be combined in order to enhance their sensitivity and specificity at the earliest stage possible for the detection of pancreatic cancer.

3) Biomarkers and even genetic information, for instance, genetic profiling will be integrated into the development of AI models in order to diagnose pancreatic cancer?

This is how the inclusion of biomarker and genetic information, such as in CA 19-9 and gene variants, can be further extended to enhance the earlier diagnosis through AI models. It carries a connotation basically which understands that with the inclusion of molecular information, along with imaging, help predictions and makes it better than before, and thus, the individually customized approaches for screening pancreatic cancer.

4) What is the limitation, challenge, and ethical issue in deploying AI-based diagnostic tools for pancreatic cancer?

This discussion is based on technical challenges: data quality, model explainability, the in-dietic integration of AI into clinical work and reflects some practical challenges with the use of AI in real life, clinical practice. This paper therefore deals with issues like the biasness of the AI model, data-privacy issues, among others, and standardized protocols would also be needed, allowing for the responsible application of AI in the process of diagnosing pancreatic cancer. Further, the research would dive into these four broad key areas to ensure that the reader has a good understanding of how AI developments might be employed in helping towards early detection and diagnosis of pancreatic cancer.

B. Data Source

The databases that are respectable in this regard include IEEE Xplore, ScienceDirect, Springer Connect, MDPI, and Elsevier, that would provide information for this audit. Articles were selected from 2019 to 2024 years of publication on the use of AI, particularly ML and DL for the diagnosis of pancreatic cancer. Pancreatic Cancer Discovery by AI, Profound Learning in Restorative Imaging for Pancreatic Cancer, Biomarkers and AI in Pancreatic Cancer Conclusion, and Multi-Modal Imaging in Pancreatic Cancer Discovery were some of the words used in the search.

C. Paper Selection Criteria

While reading this type of document, some choice criteria have been employed, including:

- Articles or conference papers in any medium, but peer-reviewed between 2020 and 2024.
- Research area: AI applied in ML and DL approaches toward early diagnosis of pancreatic cancer, but not at its later stages.
- Articles that comprise multimodality imaging techniques, such as CT, MRI, EUS, PET, and markers that enhance the sensitivity and specificity of the AI model.
- Experimental investigations with performance assessments such as precision, sensitivity, and specificity, etc. and comparison of several AI models, particularly for CNN and U-Net variants and multiple other versions for other algorithms in segmentations.
- Technical, limitation, and ethical boundaries of the implementation of AI-based diagnostic systems in a clinical setting to pancreatic cancer.

Authorized licensed use limited to: NATIONAL INSTITUTE OF TECHNOLOGY CALICUT. Downloaded on January 08,2026 at 17:09:29 UTC from IEEE Xplore. Restrictions apply.

D. Related Work

The most theme of this part of the research incorporates deep learning and machine learning approach strategies for pancreatic cancer detection and analysis.

1) AI Techniques and Models for Pancreatic Cancer Detection

Advanced AI models, particularly CNNs and U-Net architectures, are applied in studies in order to enhance the process of pancreatic cancer diagnostics. Using CNNs, such as VGG16, ResNet, and DenseNet, revealed an accuracy level from 96% to 99% for the classification of pancreatic tumours [9, 10]. This model helps in analysing CT and MRI scans and distinguishing between benign and malignant lesions.

U-Net and its derivatives have been the most popular architecture in segmentation tasks. Zhang et al discuss applying U-Net for the task of segmentation of pancreatic CT images and some of the major challenges encountered by them in these images are low contrast of images and complexity of anatomy of the pancreas [14]. Here, accuracy in segmentation improves but the problem persists that specific boundary of tumours cannot be correctly highlighted.

2) Integration of Multi-Modal Images

Other articles highlighted an integration with more imaging modalities comprising CT, MRI, EUS, and PET with AI to enhance diagnostic accuracy. Liu et al. presented a review of the combination of such techniques, which can improve detection to subtle lesions otherwise missed using the single imaging modality [15]. These integrations help in providing a complete view of the pancreatic structures for easier recognition at the early stages of tumours [8].

The multi-modal approach does present difficulties in terms of standardizing the data obtained from various imaging modalities as well as the consistency of outputs from AI models [13]. Researchers show that, although it is a strategy that holds a lot of promise, more work is required in order for the findings to be both robust and reliable under different clinical settings.

3) Biomarker Integration in AI Models

New biomarkers such as CA19-9 and ctDNA have been researched for utilization as a supplementary source of data through AI models. Goggins discusses the integration opportunities for biomarkers to make AI systems even more accurate in early detection. Biomarkers provide useful information, but their limitations on sensitivity and specificity are indicated when used alone.

Other researchers have suggested using AI to combine genotypic and imaging data to build much more accurate models of diagnosis. Combining biomarkers with imaging data has shown great potential for tailoring the approach to diagnosis and the risk for pancreatic cancer in the patient with a genetic risk factor [10].

4) Optimization Techniques for Better Performance

Optimization algorithms are used widely for optimizing the performance of AI models. For instance, both GWO and BHO have been implemented to optimize CNN and U-Net architectures [9][11]. These techniques achieve adjusting the model parameters so that the developed models improve in accuracy, sensitivity, and specificity toward the detection of pancreatic tumours.

According to Mallipudi et al., such optimization is highly relevant in processing noisy medical data and improving the insensitivity of AI to variations in image quality [12]. The algorithms further help limit overfitting conditions characteristic of DL models trained on restricted datasets of medical imaging [8].

5) Current Challenges and Limitations

Some of the results have been somewhat promising. However, there are some challenges. Zhang et al. detail the limitation with the use of U-Net models on the anatomy of the pancreas, mainly when trying to outline the boundaries of the tumours, due to the weak contrast of pancreatic tissue within CT images [14]. Liu et al. also report that one of the biggest challenges for integrating the various AI models is the heterogeneity of imaging data [15].

Ethical considerations also emerge as a significant one. Tripathi et al. discuss the use of AI in the diagnosis of pancreatic cancer, outlining problems with data privacy and expected bias in AI models towards certain patient groups and lack of transparency in AI-related decision-making [11]. Indeed, many studies highlight that those issues represent critical concerns with AI application, so it is timely to consider them in the pursuit of creating confidence and responsible usage in clinical practice [16].

6) New AI Techniques and Future Direction

New techniques are attention-based models and transformers, which are being researched to mitigate some of the limitations pancreatic segmentation faces today [14]. These models promise to increase the accuracy and flexibility of the model. Another promising direction is the use of AI models that combine imaging data with genetic information for the early detection of pancreatic cancer and tailor treatment plans to a patient based on genetic predispositions to pancreatic cancer [13].

7) Dataset Utilization and Development

This stream of research is dominated by the use of datasets, such as the NIH Pancreas Dataset, consisting of annotated CT images of the pancreas. The datasets are highly used for the training and validation of AI models, such as U-Net, on segmentation tasks [9][14]. However, research highlights that there is still a need for more inclusive and diverse datasets containing multi-modal imaging data and biomarker information to enhance the generalizability and performance of AI models [15] .

E. Paper Analysis

Table 1 presents a structured comparison of the various studies carried out by different researchers on the different technologies, methods, and datasets that were used in. After comparison, each study's outcomes and limitations are discussed in the form of tables for an overall comprehension of how the research progresses in this area of interest, as it reflects both the merits and lacunae for the purpose of guiding future researches. The structured presentation also clarifies the best approaches and areas that need further exploration, as shown in Table 1.

Authorized licensed use limited to: NATIONAL INSTITUTE OF TECHNOLOGY CALICUT. Downloaded on January 08,2026 at 17:09:29 UTC from IEEE Xplore. Restrictions apply.

TABLE 1. ANALYSIS OF PAPER

Study	Dataset	Methodology	Outcomes	Limitations
Kumar et al. (2024)	NIH Pancreas Dataset	CNN models (VGG16, ResNet, DenseNet) for tumor classification	DenseNet achieved the highest accuracy (99%) in distinguishing benign and malignant tumors	Challenges with imbalanced datasets; needed further optimization for varying image quality
Nithisha and Praylin (2024)	NIH Pancreas Dataset, CT images from Bethlehem Institute	GWO with CNNs for segmenting and classifying pancreatic tumors	High accuracy (92.5%) in pancreatic cancer classification with GWO-CNN model	Difficulties with low-contrast images and noise affecting segmentation accuracy
Zhang et al. (2024)	Multiple public CT datasets, including NIH	Review of U-Net and its variants for CT image segmentation	U-Net showed strengths in segmenting complex structures, but had limitations with pancreas anatomy	U-Net struggled with precise segmentation; required modifications for better performance
Liu et al. (2024)	Various datasets (NIH Pancreas, MRI, PET)	Review of AI applications in multi-modal imaging	Integration of multiple imaging modalities improved diagnostic accuracy	Challenges in standardizing data from different sources and ensuring consistent model outputs
Goggins (2024)	Familial Pancreatic Cancer, NIH Pancreas Dataset	Investigated biomarkers (CA19-9, ctDNA) and their integration into AI models	Combining biomarkers with imaging data improved early detection rates	Standalone biomarkers showed limited sensitivity without imaging/genetic support
Devi et al. (2024)	NIH Pancreas Dataset, urinary biomarker datasets	Compared classifiers (SVM, Extra Tree, Decision Tree, Random Forest)	Random Forest showed highest diagnostic accuracy (86%) among methods tested	Biomarker models struggled to achieve high specificity without imaging data
Mikdadi et al. (2023)	NIH Pancreas Dataset, proprietary CT scan data	Review of AI models for PDAC diagnosis and prognosis	AI showed potential in accurately staging and predicting PDAC outcomes	Limited access to diverse datasets constrained model generalizability
Pereira et al. (2023)	Multi-modal datasets (MRI, CT, PET)	Analysis of AI techniques for PDAC detection	Multi-modal approaches enhanced early detection accuracy	Difficulties in consistently merging multi-modal data across different hospital systems
Cazacu et al. (2022)	EUS and CT datasets from multi-centre studies	Explored CNN models for differentiating pancreatic cancer from chronic pancreatitis	AI models significantly improved diagnostic accuracy	Performance varied with data quality; lack of data standardization led to inconsistencies
Schlanger et al. (2022)	Surgical and imaging datasets from multi-centre studies	Review of AI applications in pancreatic surgery	AI showed potential in improving surgical outcomes	Limited real-time applicability and lack of integration with surgical tools were key barriers

III. CURRENT CHALLENGES

Although highly promising AI-driven techniques for the early diagnosis and detection of pancreatic cancer, several major challenges need to be addressed before such technologies can be fully translated into clinical settings. Therefore, a few points brought forward below highlighted.

A. Data Heterogeneity and Quality

Medical imaging data vary across institutions and the types of the devices, which poses a challenge to AI models. There are concerns about the lack of standardized imaging protocols and the method with which data will be collected as it has the effect of ensuring proper uniform and quality input to ML and DL models. The need to address heterogeneity is imperative in developing models that can generalize to varied settings in a clinical setup.

B. Model Interpretability and Explainability

Transparency and interpretability in DL models still constitute an essential challenge. Explainability of AI outputs represent an important precursor to trust, and clinicians need to be integrated into decision-making processes. The key need in adapting clinical usage would be the development of XAI techniques conveying clear visual and logical explanations of model predictions.

C. Multimodal Data Integration

While integrating imaging modalities such as CT, MRI, PET and EUS with biomarkers has shown excellent promise for improving the accuracy of diagnosis, integration of the sources remains challenging. For instance, integration of data from different types of modalities is challenging due to the variation in resolutions, formats and timings that are available from different types of investigations involving imaging. Accordingly, future research work would be oriented at the homogenization of the sources of the data and development of models which could easily integrate multi-modal information.

D. Computational Efficiency and Scalability

Many DL models, particularly those applied to multi-modal and 3D imaging data, are computationally intensive. The high computational requirements might prove to be a limiting factor to their deployment in clinical environments with real-time expectations. Future work should be on

Authorized licensed use limited to: NATIONAL INSTITUTE OF TECHNOLOGY CALICUT. Downloaded on January 08,2026 at 17:09:29 UTC from IEEE Xplore. Restrictions apply.

optimization without the compromise of precision in these models so that AI systems can be scaled across health facilities.

E. Validation and Real-World Testing

While AI models may show high accuracy in controlled and retrospective studies, it is not easily translated to real-world clinical practice. Most of these results require important validation using large, relevant patient datasets and multi-centre trials to be sure that the models developed are robust and reliable in more diverse populations.

F. Clinical Integration

Even now, it is still challenging to well-integrate the AI models into existing clinical flows. The developed models should easily interact with clinical systems like EHRs and produce outputs in formats that are easy for clinicians to understand. Training programs for health professionals to understand and use these AI tools also need to be developed.

G. Access to High-Quality, Diverse Dataset

There are very few datasets with multi-modal imaging and biomarker data that are as comprehensive. But large, diverse datasets are absolutely necessary for AI models to train efficiently. It would be great if such data are made available in the future while keeping data security and privacy in mind.

Success over these hurdles will depend on the continuous improvement and down-to-earth application of AI-driven strategies for pancreatic cancer discovery and determination.

IV. Tackle the Challenges

To tackle for the AI-based pancreatic cancer detection we can use Convolutional Nural Network (CNN) in tumour detection and segmentation from CT scans as CNN perform well with image processing. Multi-input CNNs can deal with multimodal data, which process images and biomarkers individually before fusing their outputs to be diagnosed more effective. Methods such as Grad-CAM can be used to create heatmaps of an image which tells us about the most contributing areas of that image towards AI predictions hence these methods lead to increasing the transparency around model which need to be understands easily. We find that fine-tuning on pre-trained CNNs such as ResNet or DenseNet over pancreas data helps in getting better accuracy and robust model. The data quality problems they addressed in this study, with the integrated deep learning techniques are definitely beneficial for clinical adoption and result-based early diagnosis of pancreatic cancer.

V. Methodology

A. Method about implementation

The following steps illustrate the methodology for early detection and diagnosis of pancreatic cancer using AI, as depicted in Figure 1. Data will be accumulated and prepared in a multi-modal imaging modality, primarily concentrating on CECT scans. Preparing the data includes normalization of data; reduction of noise and data augmentation techniques for uniformity and enhanced model reliability.

First, I will use a deep learning model with CNN architecture for the effective identification and segmentation of lesions in images from the pancreas. Advanced methods such as hyperparameter tuning, evolutionary algorithms, and even ensemble methods will be applied to achieve good accuracy and performance for the model.

My next step would be to divide the dataset into training, validation, and testing sets so that I could accurately evaluate the model. I'd utilize accuracy, sensitivity, and specificity metrics for the validation process, ensuring that it is reliable and efficient. After developing the model, it would be placed in a cloud-based environment for real-time diagnosis, its outputs to be integrated into the clinical workflows. During the implementation of this project, I shall use safe implementation techniques such as federated learning, in addition to my provision aligning with data protection laws. This is a much-needed, multi-centre dataset for training and benchmarking ML and DL models.



Fig. 1. Flow diagram for using AI to analyse pancreatic images.

B. About Dataset

Close to 3,000 contrast-enhanced CT (CECT) checks of different centres within the Netherlands, Sweden, and Norway will be added to the dataset for the early distinction and conclusion of pancreatic cancer based on AI-driven strategies. Three cohorts can be identified from the dataset: 2,238 scans in an open training and development set-including data from the Medical Segmentation Decathlon and NIH-a hidden validation and tuning cohort with 100 cases for model selection, and a hidden testing cohort with over 400 cases for final benchmarking and hypothesis testing. All scans are anonymized, taken during the portal-venous phase, the most common phase in abdominal imaging. Relevant clinical parameters, such as age and sex, in addition to scanner information, contain missing values: this is attributed to the inherent nature of the dataset being a collection of data from a retrocession effort. It represents an important multi-centre complete.

C. Future Scope

Early detection and diagnosis of pancreatic cancer, with great potential for future breakthroughs by using AI-driven methods are expected to offer considerable improvements in accuracy and efficiency within diagnostics of medical diagnostics. The rapidly growing larger, diverse multi-modal

Authorized licensed use limited to: NATIONAL INSTITUTE OF TECHNOLOGY CALICUT. Downloaded on January 08,2026 at 17:09:29 UTC from IEEE Xplore. Restrictions apply.

datasets- allied imaging, genetic, and biomarkers-combined data will help build more precise and tailored diagnostic tools. Advances in explainable AI will increase model transparency, hence boosting clinician trust and subsequently allowing AI to seamlessly integrate into healthcare workflows. Techniques of federated learning will also strengthen data privacy and security measures to enable the possibility of collaboration among institutions without compromising confidentiality of patients. Real-time AI diagnostic systems are also likely to increase with the provision of instant insights that will facilitate time-sensitive interventions. Future studies may also be aimed at how AI can be integrated with predictive analytics in relation to assessing the outcome of the patient and working on improving their treatment plan. This would greatly contribute to the betterment of patient care and transform the management of pancreatic cancer.

VI. Conclusion

Early detection and diagnosis of pancreatic cancer may dramatically improve with the emergence of AI, more specifically with ML and DL models. Indeed, these models can dramatically increase the rate of accuracy with which physicians detect the condition through the integration of several imaging techniques and through the use of a biomarker for more personalized medical treatments.

Yet, despite these effective models, in many ways, they are still problematic to implement in a real clinical scenario. Among the pivotal aspects in this pursuit of better models are the need to eliminate the challenges that range from the unequal quality of the data, model simplification, and the aspect of the solution to the issues on ethics such as personal data privacy and avoidance of bias. The research areas outlined in this review should be undertaken in future for deploying AI-based pancreatic cancer diagnostic systems that are effective both ethically and dependable and broadly applicable. Conclusion Although much promise holds for AI techniques, still more research and development are required to overcome the existing hurdles into full realization of their potential application to pancreatic cancer diagnosis.

References

[1] S. Tripathi, A. Tabari, A. Mansur, H. Dabbara, C. P. Bridge, and D. Daye, "From Machine Learning to Patient Outcomes: A Comprehensive Review of AI in Pancreatic Cancer," Jan. 01, 2024, Multidisciplinary Digital Publishing Institute (MDPI). doi: 10.3390/diagnostics14020174.

[2] M. D. S. Sai, P. Prudhvi, G. M. N. V. S. Gopi, I. G. N. Sai Ram, M. R. Sandeep, and N. Pachhala, "Early Detection: Machine Learning Techniques in Pancreatic Cancer Diagnosis," Journal of Engineering Research and Reports, vol. 26, no. 5, pp. 175–182, Apr. 2024, doi: 10.9734/jerr/2024/v26i51144.

[3] M. Goggins, "The role of biomarkers in the early detection of pancreatic cancer," Aug. 01, 2024, Springer Science and Business Media B.V. doi: 10.1007/s10689-024-00381-4.

[4] C. Zhang, A. Achuthan, and G. M. S. Himel, "State-of-the-Art and Challenges in Pancreatic CT Segmentation: A Systematic Review of U-Net and Its Variants," IEEE Access, vol. 12, pp. 78726–78742, 2024, doi: 10.1109/ACCESS.2024.3392595.

[5] W. Liu, B. Zhang, T. Liu, J. Jiang, and Y. Liu, "Artificial Intelligence in Pancreatic Image Analysis: A Review," Jul. 01, 2024, Multidisciplinary Digital Publishing Institute (MDPI). doi: 10.3390/s24144749.

[6] M. Nithisha, S. A. Praylin, and S. Blessy, "Article Title: Pancreatic Cancer Identification using Convolutional Neural Networks Pancreatic Cancer Identification using Convolutional Neural Networks," 2024.

[7] M. Ramaekers et al., "Improved Pancreatic Cancer Detection and Localization on CT Scans: A Computer-Aided Detection Model Utilizing Secondary Features," Cancers (Basel), vol. 16, no. 13, Jul. 2024, doi: 10.3390/cancers16132403.

[8] K. Dodda and G. Muneeswari, "Biomarkers for Early Detection of Pancreatic Cancer: A Review," in Proceedings of 2023 International Conference on Signal Processing, Computation, Electronics, Power and Telecommunication, IConSCEPT 2023, Institute of Electrical and Electronics Engineers Inc., 2023. doi: 10.1109/IConSCEPT57958.2023.10170123.

[9] M. Suneetha, G. Kalhara, M. V. Krishna, K. N. S. Chandana, and V. L. S. Snigdha, "Pancreatic Cancer Prediction through Convolutional Neural Networks," in Proceedings of the 7th International Conference on Intelligent Computing and Control Systems, ICICCS 2023, Institute of Electrical and Electronics Engineers Inc., 2023, pp. 602–607. doi: 10.1109/ICICCS56967.2023.10142618.

[10] J. Chhikara, N. Goel, and N. Rathee, "Deep Learning Techniques for Pancreatic Cancer Analysis: A Systematic Review and Implantation Prerequisites," in Procedia Computer Science, Elsevier B.V., 2024, pp. 3118–3130. doi: 10.1016/j.procs.2024.04.295.

[11] A. Gupta, A. Koul, and Y. Kumar, "Pancreatic Cancer Detection using Machine and Deep Learning Techniques," in Proceedings of 2nd International Conference on Innovative Practices in Technology and Management, ICIPTM 2022, Institute of Electrical and Electronics Engineers Inc., 2022, pp. 151–155. doi: 10.1109/ICIPTM54933.2022.9754010.

[12] K. Upreti, M. S. Nasir, M. S. Alam, F. I. Shahi, P. Vats, and A. K. Saini, "Advancing Pancreatic Cancer Diagnosis with Artificial Neural Networks: Current Research and Future Prospects," in Proceedings of the 7th International Conference on Intelligent Computing and Control Systems, ICICCS 2023, Institute of Electrical and Electronics Engineers Inc., 2023, pp. 524–529. doi: 10.1109/ICICCS56967.2023.10142920.

[13] G. Deepthi, A. M. Anusha Bamini, and Y. J. Praveen, "A Comparative Analysis of Pancreatic Tumor Detection using VGG16, ResNet, and DenseNet," in Proceedings of the 3rd International Conference on Applied Artificial Intelligence and Computing, ICAAIC 2024, Institute of Electrical and Electronics Engineers Inc., 2024, pp. 1303–1308. doi: 10.1109/ICAAIC60222.2024.10575802.

[14] K. Dodda and G. Muneeswari, "IANFIS: a machine learning–based optimized technique for the classification and segmentation of pancreatic cancer," Research on Biomedical Engineering, vol. 40, no. 2, pp. 373–385, Jun. 2024, doi: 10.1007/s42600-024-00352-9.reatment episode data set: discharges (TEDS-D): concatenated, 2006 to 2009." U.S. Department of Health and Human Services, Substance Abuse and Mental Health Services Administration, Office of Applied Studies, August, 2013, DOI:10.3886/ICPSR30122.

[15] M. T. Zavalsiz, S. Alhajj, K. Sailunaz, T. Ozyer, and R. Alhajj, "Pancreatic Tumor Detection by Convolutional Neural Networks," in Proceedings - 2022 23rd International Arab Conference on Information Technology, ACIT 2022, Institute of Electrical and Electronics Engineers Inc., 2022. doi: 10.1109/ACIT57182.2022.9994181.

[16] H. V. Ramachandra, P. Chavan, A. Ali, and H. C. Ramaprasad, "Ensemble Machine Learning Techniques for Pancreatic Cancer Detection," in International Conference on Applied Intelligence and Sustainable Computing, ICAISC 2023, Institute of Electrical and Electronics Engineers Inc., 2023. doi: 10.1109/ICAISC58445.2023.10200380.

Authorized licensed use limited to: NATIONAL INSTITUTE OF TECHNOLOGY CALICUT. Downloaded on January 08,2026 at 17:09:29 UTC from IEEE Xplore. Restrictions apply.