

MultiPrecisionArrays.jl: A Julia package for iterative refinement

C. T. Kelley ¹

¹ North Carolina State University, Raleigh NC, USA

DOI: [10.xxxxxx/draft](https://doi.org/10.xxxxxx/draft)

Software

- [Review](#) 
- [Repository](#) 
- [Archive](#) 

Editor: [Open Journals](#) 

Reviewers:

- [@openjournals](#)

Submitted: 01 January 1970

Published: unpublished

License

Authors of papers retain copyright and release the work under a Creative Commons Attribution 4.0 International License ([CC BY 4.0](#)).

Summary

[MultiPrecisionArrays.jl](#), ([Kelley, 2024b, 2024c](#)) provides data structures and solvers for several variations of iterative refinement (IR). IR can speed up an LU matrix factorization for solving linear systems of equations by factoring a low precision copy of the matrix and using that low precision factorization in a iteration loop to solve the system. For example, if high precision is double and low precision is single, then the factorization time is cut in half. The additional storage cost is the low precision copy, so IR is at time vs storage trade off. IR has a long history and a good account of the classical theory is in ([Higham, 1996](#)).

Statement of need

The solution of linear systems of equations is a ubiquitous task in computational science and engineering. A common method for dense systems is Gaussian elimination done via an LU factorization, ([Higham, 1996](#)). Iterative refinement is a way to reduce the factorization time at the cost of additional storage. [MultiPrecisionArrays.jl](#) enables IR with a simple interface in Julia ([Bezanson et al., 2017](#)) with an IR factorization object that one uses in the same way as the one for LU. The package offers several variants of IR, both classical ([Higham, 1996](#); [Wilkinson, 1948](#)), and some from the recent literature ([Amestoy et al., 2024](#); [Carson & Higham, 2017](#)).

Algorithm

This package will make solving dense systems of linear equations faster by using the LU factorization and IR. While other factorizations can be used in IR, the package is limited to LU for now. A very generic description of this for solving a linear system $Ax = b$ in a high (working) precision is

IR(A, b)

- $x = 0$
- $r = b$
- Factor $A = LU$ in a lower precision
- While $\|r\|$ is too large
 - $d = (LU)^{-1}r$
 - $x = x + d$
 - $r = b - Ax$
- end

36 ▪ end

37 In Julia, a code to do this would solve the linear system $Ax = b$ in the working precision,
38 say double, by using a factorization in a lower (factorization) precision, say single, within a
39 residual correction iteration. This means that one would need to allocate storage for a copy of
40 A in the factorization precision and factor that copy.

41 The multiprecision factorization `mplu` makes the low precision copy of the matrix, factors that
42 copy, and allocates some storage for the iteration. The original matrix and the low precision
43 factorization are stored in a factorization object that you can use with `\`.

44 IR is a perfect example of a storage/time trade off. To solve a linear system $Ax = b$ in R^N
45 with IR, one incurs the storage penalty of making a low precision copy of A and reaps the
46 benefit of only having to factor the low precision copy.

47 Installation

48 The standard way to install a package is to type `import Pkg; Pkg.add("MultiPrecisionArrays")`
49 at the Julia prompt. One can run the unit tests with `Pkg.test("MultiPrecisionArrays")`.
50 After installation, type using `MultiPrecisionArrays` when you want to use the functions in
51 the package.

52 There are only two direct dependencies outside of the Julia standard libraries. The factorization
53 in half precision (`Float16`) uses [OhMyThreads.jl](#). The GMRES and Bi-CGSTAB solvers for
54 Krylov-IR methods are taken from [SIAMFANL.jl](#) ([Kelley, 2022c](#)).

55 Example

56 Here is a simple example to show how `mplu` works. We will follow that with some benchmarking
57 on the cost of factorizations. The computations were done with Julia 1.10.4 on an Apple Mac
58 Mini with an M2 pro processor and 32GB RAM. We used OPENBLAS for LAPACK and the
59 BLAS for this example. Other choices, such as the [AppleAccelerate](#) framework would work
60 equally well.

61 In this example high (working) precision is double, `Float64`, and low (factorization) precision is
62 single, `Float32`. The matrix is the sum of the identity and a constant multiple of the trapezoid
63 rule discretization of the Greens operator for $-d^2/dx^2$ on $[0, 1]$

$$Gu(x) = \int_0^1 g(x, y)u(y) dy$$

64 where

$$g(x, y) = \min(x, y)(1 - \max(x, y)).$$

65 The discretization for an N -point discretization is the $N \times N$ maatrix

$$G_{ij} = g(x_i, x_j)/(N + 1)$$

66 where $x_i = i/(N + 1)$.

67 The code for construction G is in the `/src/Examples` directory. The file is `Gmat.jl`. You need
68 to do

```
69 using MultiPrecisionArrays
70 using MultiPrecisionArrays.Examples
```

```

71  to use mpla and Gmat.

72  Now we will see how the results look. In this example we compare the result with iterative
73  refinement with A\b, which is LAPACK's LU. As you can see the results are equally good.
74  Note that a factorization object MPF is the output of mpla. This is analogous to AF=lu(A) in
75  LAPACK.

76  julia> using MultiPrecisionArrays
77
78  julia> using MultiPrecisionArrays.Examples
79
80  julia> using BenchmarkTools
81
82  julia> N=4096;
83
84  julia> # Build G on an N x N grid
85
86  julia> G=Gmat(N);
87
88  julia> # The operator is I - G
89
90  julia> A = I - G;
91
92  julia> # Create a test problem where the solution is x = ones(N)
93
94  julia> x=ones(N); b=A*x;
95
96  julia> # Compute the mpla and lu factorizations of A
97
98  julia> MPF=mpla(A); AF=lu(A);
99
100 julia> # Solve A x = b with both factorizations
101
102 julia> z=MPF\b; w=AF\b;
103
104 julia> # Compute relative errors and residuals for mpla
105
106 julia> mplaerr=norm(z-x,Inf); mplaresid=norm(b-A*z,Inf)/norm(b,Inf);
107
108 julia> # Compute relative errors and residuals for lu
109
110 julia> luerr=norm(w-x,Inf); luresid=norm(b-A*w,Inf)/norm(b,Inf);
111
112 julia> # Print the results
113
114 julia> println("Errors: $mplaerr, $luerr. Residuals: $mplaresid, $luresid")
115 Errors: 4.44089e-16, 6.68354e-14. Residuals: 4.44089e-16, 6.68354e-14

116 So the results are equally good.

117 The compute time for mpla should be roughly half that of lu. A fair comparison is with lu!,
118 which does not allocate new storage for the factorization. mpla factors a low precision array,
119 so the factorization cost is cut in half. Memory is a different story because neither mpla nor
120 lu! allocate storage for a new high precision array, but mpla allocates for a low precision
121 copy, so the memory and allocation cost for mpla is 50% more than lu. One issue with smaller
122 problems is that the triangular solve does not parallelize as well as the factorization, so does
123 not exploit multi-core processor as well. We can see this in the IR solver times because each

```

```
124 iteration of IR needs a matrix-vector multiply and a triangular solve.
125 julia> using BenchmarkTools
126
127 julia> @belapsed mpla($A)
128 8.60945e-02
129
130 julia> @belapsed lu!(AC) setup=(AC=copy($A))
131 1.42840e-01
132
133 # And now for the solve times
134
135 julia> @belapsed ldiv!($AF,bb) setup=(bb = copy($b))
136 4.79117e-03
137
138 julia> @belapsed $MPF\b
139 2.01195e-02
140 So the total solve time (factorization and solve) is less for IR by roughly 40%.
```

141 A Few Subtleties

142 Within the algorithm one has to determine what the line $d = (LU)^{-1}r$ means. Does one
143 cast r into the lower precision before the solve or not? If one casts r into the lower precision,
144 then the solve is done entirely in the factorization precision. If, however, r remains in the
145 working precision, then the LU factors are promoted to the working precision on the fly. This
146 makes little difference if TW is double and TF is single and there is a modest performance
147 benefit to downcasting r into single. Therefore that is the default behavior in that case. If
148 TF is half precision, Float16, then it is best to do the interprecision transfers on the fly and
149 if one is using one of the Krylov-IR algorithms (Amestoy et al., 2024) then one must do the
150 interprecision transfers on the fly and not downcast r .

151 There are two half precision (16 bit) formats. Julia has native support for IEEE 16 bit floats
152 (Float16). A second format (BFloat16) has a larger exponent field and a smaller significand
153 (mantissa), thereby trading precision for range. In fact, the exponent field in BFloat is the
154 same size (8 bits) as that for single precision (Float32). The significand, however, is only 8
155 bits. Compare this to the size of the exponent fields for Float16 (11 bits) and single (24 bits).
156 The size of the significand means that you can get in real trouble with half precision in either
157 format and that IR is more likely to fail to converge. GMRES-IR can mitigate the convergence
158 problems (Amestoy et al., 2024) by using the low-precision solve as a preconditioner. We
159 support both GMRES (Saad & Schultz, 1986) and BiCGSTAB (Vorst, 1992) as solvers for
160 Krylov-IR methods. One should also know that LAPACK and the BLAS do not yet support
161 half precision arrays, so working in Float16 will be slower than using Float64.

162 The classic algorithm from (Wilkinson, 1948) and its recent extension (Carson & Higham,
163 2017) evaluate the residual in a higher precision than the working precision. This can give
164 improved accuracy for ill-conditioned problems at a cost of the interprecision transfers in the
165 residual computation. This needs to be implemented with some care and (Demmel et al.,
166 2006) has an excellent account of the details.

167 **MultiPrecisionArrays.jl** provides infrastructure to manage these things and we refer the reader
168 to (Kelley, 2024c) for the details.

Projects using MultiPrecisionArrays.jl.

This package was motivated by the use of low-precision factorizations in Newton's method Kelley (2022c) and the interface between a preliminary version of this package and the solvers from (Kelley, 2022b) was reported in (Kelley, 2023). That paper used a three precision form of IR (TF=half, TW=single, nonlinear residual computed in double) and required direct use of multiprecision constructors that we do not export in **MultiPrecisionArrays.jl**. We will fully support the application to nonlinear solvers in a future version. We give a detailed account of interprecision transfers in (Kelley, 2024a) and use **MultiPrecisionArrays.jl** to generate the table in that paper.

Other Julia Packages for IR

The package **IterativeRefinement.jl** is an implementation of the IR method from (J.Dongarra et al., 1983). It has not been updated in four years.

The unregistered package **ltref.jl** implements IR and the GMRES-IR method from (Amestoy et al., 2024) and was used to obtain the numerical results in that paper. It does not provide the data structures for preallocation that we do and does not seem to have been updated lately.

Acknowledgements

This work was partially supported by Department of Energy grant DE-NA003967. Any opinions, findings, and conclusions or recommendations expressed in this material are those of the author and do not necessarily reflect the views of the United States Department of Energy.

References

- Amestoy, P., Buttari, A., Higham, N. J., L'Excellent, J.-Y., Mary, T., & Vieublé, B. (2024). Five-precision GMRES-based iterative refinement. *SIAM Journal on Matrix Analysis and Applications*, 45(1), 529–552. <https://doi.org/10.1137/23M1549079>
- Bezanson, J., Edelman, A., Karpinski, S., & Shah, V. B. (2017). Julia: A fresh approach to numerical computing. *SIAM Review*, 59, 65–98. <https://doi.org/10.1137/141000671>
- Carson, E., & Higham, N. J. (2017). A new analysis of iterative refinement and its application of accurate solution of ill-conditioned sparse linear systems. *SIAM Journal on Scientific Computing*, 39(6), A2834–A2856. <https://doi.org/10.1137/17M1122918>
- Demmel, J., Hida, Y., & Kahan, W. (2006). Error bounds from extra-precise iterative refinement. *ACM Trans. Math. Soft.*, 325–351. <https://doi.org/10.1145/1141885.1141894>
- Higham, N. J. (1996). *Accuracy and stability of numerical algorithms* (p. xxviii+688). Society for Industrial; Applied Mathematics. <https://doi.org/10.1137/1.9780898718027>
- J.Dongarra, J., B.Moler, C., & H.Wilkinson, J. (1983). Improving the accuracy of computed eigenvalues and eigenvectors. *SIAM Journal on Numerical Analysis*, 20, 23–45.
- Kelley, C. T. (2022a). Newton's method in mixed precision. *SIAM Review*, 64, 191–211. <https://doi.org/10.1137/20M1342902>
- Kelley, C. T. (2022b). *SIAMFANLEquations.jl*. <https://github.com/ctkelley/SIAMFANLEquations.jl>. <https://doi.org/10.5281/zenodo.4284807>
- Kelley, C. T. (2022c). *Solving Nonlinear Equations with Iterative Methods: Solvers and Examples in Julia*. SIAM. <https://doi.org/10.1137/1.9781611977271>

- 209 Kelley, C. T. (2023). *Newton's method in three precisions*. [https://doi.org/10.48550/arXiv.](https://doi.org/10.48550/arXiv.2307.16051)
210 [2307.16051](https://doi.org/10.48550/arXiv.2307.16051)
- 211 Kelley, C. T. (2024a). *Interprecision transfers in iterative refinement*. [https://arxiv.org/abs/](https://arxiv.org/abs/2407.00827)
212 [2407.00827](https://arxiv.org/abs/2407.00827)
- 213 Kelley, C. T. (2024b). *MultiPrecisionArrays.jl*. [https://github.com/ctkelley/MultiPrecisionAr-](https://github.com/ctkelley/MultiPrecisionArrays.jl)
214 [rays.jl](https://github.com/ctkelley/MultiPrecisionArrays.jl). <https://doi.org/10.5281/zenodo.7521427>
- 215 Kelley, C. T. (2024c). *Using MultiPrecisionArrays.jl: Iterative refinement in Julia*. [https:](https://doi.org/10.48550/arXiv.2311.14616)
216 [//doi.org/10.48550/arXiv.2311.14616](https://doi.org/10.48550/arXiv.2311.14616)
- 217 Saad, Y., & Schultz, M. H. (1986). GMRES a generalized minimal residual algorithm for
218 solving nonsymmetric linear systems. *SIAM J. Sci. Stat. Comp.*, 7, 856–869. [https:](https://doi.org/10.1137/0907058)
219 [//doi.org/10.1137/0907058](https://doi.org/10.1137/0907058)
- 220 Vorst, H. A. van der. (1992). Bi-CGSTAB: A fast and smoothly converging variant to Bi-CG
221 for the solution of nonsymmetric systems. *SIAM J. Sci. Stat. Comp.*, 13, 631–644.
- 222 Wilkinson, J. H. (1948). *Progress report on the automatic computing engine* (No.
223 MA/17/1024). Mathematics Division, Department of Scientific; Industrial Research,
224 National Physical Laboratory, Teddington, UK. [http://www.alanturing.net/turing_archive/](http://www.alanturing.net/turing_archive/archive/I/I10/I10.php)
225 [archive/I/I10/I10.php](http://www.alanturing.net/turing_archive/archive/I/I10/I10.php)

DRAFT