N3Presults

C. T. Kelley

August 2, 2023

Here is an example from [1] and [2], [3], [4], and [5].

This notebook reproduces the results from the paper

C. T. Kelley, Newton's Method in Three Precisions, 2023 [6].

The example is the Chandrasekhar H-equation [7].

All computations were done in Julia [8].

We use the software from [3], [4], and [5]. Our nonlinear solvers from [5] work well with our data structures for iterative refinement. The Julia module with the data structures we use for IR is

The results are in Table 2 and Table 3.

The first computation generates Table 2. This is the ill-conditioned example from [2] and is the well conditioned example from the paper. The function that creates the examples is the Julia function htest1 from the file H_equation_examples.jl. We also put a plot in this notebook.

[6]: htest1(4096,.99)

Maximum iterations (maxit) of 10 exceeded
Convergence failure: residual norm too large 4.05010e-01
Try increasing maxit and checking your function and
Jacobian for bugs.

Give the history array a look to see what's happening.

Norm increased: 1.013279e-6, 1.013279e-6, 1.00000e-06 \begin{tabular}{111111}

		-					
n&	F64&	F32&	F16&	IR	32-16&	IR-GM \\ \h	line
0 &	1.000e+00 &	1.000e+00 &	1.000e+00	&	1.000e+00 8	1.000e+00	\\
1 &	2.289e-01 &	2.289e-01 &	5.065e-01	&	2.289e-01 8	2.289e-01	\\
2 &	3.934e-02 &	3.934e-02 &	2.958e-01	&	3.934e-02 8	3.934e-02	\\
3 &	2.737e-03 &	2.737e-03 &	1.890e-01	&	2.737e-03 8	2.737e-03	\\
4 &	1.767e-05 &	1.767e-05 &	1.255e-01	&	1.767e-05 8	1.767e-05	\\
5 &	7.486e-10 &	7.516e-10 &	8.518e-02	&	7.552e-10 8	7.502e-10	\\
6 &	&	&	6.068e-02	&	8	Ż	\\
7 &	&	&	4.240e-02	&	8	Ż	\\
8 &	&	&	3.195e-02	&	8	Ż	\\
9 &	&	&	2.280e-02	&	8	Ż	\\
10 &	&	&	1.713e-02	&	8	k	\\
\hline							

\end{tabular}
[1.47022e-10 1.28427e-10 5.97601e-02]
[6 6 11 6 6]
2.09064e-06




Table 3 is a very ill-conditioned example.

[7]: htest1(4096,.9999)

Maximum iterations (maxit) of 10 exceeded Convergence failure: residual norm too large 7.07016e-01 Try increasing maxit and checking your function and Jacobian for bugs.

Give the history array a look to see what's happening.

Norm increased: 1.3113022e-6, 1.3113022e-6, 1.00000e-06 Norm increased: 3.516674e-6, 3.516674e-6, 1.00000e-06

Norm increased: 0.60077906, 0.6, 1.00000e-06

Norm increased: 0.00028830767, 0.00028008223, 1.00000e-06

Norm increased: 0.7379273, 0.7238793, 1.00000e-06 Norm increased: 0.90214574, 0.8763197, 1.00000e-06 Norm increased: 0.84842783, 0.8370482, 1.00000e-06 Norm increased: 0.9719259, 0.9010718, 1.00000e-06 Norm increased: 0.5126856, 0.50187343, 1.00000e-06

Maximum iterations (maxit) of 10 exceeded

Convergence failure: residual norm too large 8.53620e-03

Try increasing maxit and checking your function and

Jacobian for bugs.

Give the history array a look to see what's happening.

\begin{tabular}{llllll}

```
F64&
                     F32&
                                F16&
                                       IR 32-16&
                                                     IR-GM \\ \hline
n&
0 & 1.000e+00 & 1.000e+00 & 1.000e+00 & 1.000e+00 & 1.000e+00 \\
1 & 2.494e-01 & 2.494e-01 & 5.182e-01 & 2.494e-01 & 2.494e-01 \\
2 & 6.093e-02 & 6.093e-02 & 3.123e-01 & 6.093e-02 & 6.093e-02 \\
3 & 1.480e-02 & 1.480e-02 & 2.067e-01 & 1.480e-02 & 1.480e-02 \\
4 & 3.454e-03 & 3.454e-03 & 1.421e-01 & 7.500e-03 & 3.454e-03 \\
5 & 6.762e-04 & 6.762e-04 & 1.012e-01 & 1.756e-03 & 6.762e-04 \\
6 & 7.049e-05 & 7.049e-05 & 7.552e-02 & 1.009e-03 & 7.049e-05 \\
7 & 1.223e-06 & 1.223e-06 & 5.773e-02 & 8.345e-04 & 1.223e-06 \\
8 & 3.947e-10 & 3.952e-10 & 4.543e-02 & 7.244e-04 & 3.955e-10 \\
9 &
              &
                          & 3.639e-02 & 6.789e-04 &
                                                                //
                          & 2.949e-02 & 3.560e-04 &
10 &
                                                                //
              &
```


\hline

\end{tabular}

[9.69122e-03 1.03566e-10 2.82749e-01]

[9 9 11 11 9]

1.15802e-06



References

- [1] C. T. Kelley, *Iterative Methods for Linear and Nonlinear Equations*, no. 16 in Frontiers in Applied Mathematics, SIAM, Philadelphia, 1995.
- [2] C. T. Kelley, Newton's method in mixed precision, SIAM Review, 64 (2022), pp. 191–211, doi:10.1137/20M1342902.
- [3] C. T. Kelley, Solving Nonlinear Equations with Iterative Methods: Solvers and Examples in Julia, no. 20 in Fundamentals of Algorithms, SIAM, Philadelphia, 2022.
- [4] C. T. Kelley, Notebook for Solving Nonlinear Equations with Iterative Methods: Solvers and Examples in Julia. https://github.com/ctkelley/NotebookSIAMFANL, 2022, doi:10.5281/zenodo.4284687, https://github.com/ctkelley/NotebookSIAMFANL. IJulia Notebook.
- [5] C. T. Kelley, SIAMFANLEquations.jl. https://github.com/ctkelley/SIAMFANLEquations.jl, 2022, doi:10.5281/zenodo.4284807, https://github.com/ctkelley/SIAMFANLEquations.jl. Julia Package.
- [6] C. T. Kelley, Newton's method in three precisions, 2023, arXiv:2307.16051.
- [7] S. Chandrasekhar, Radiative Transfer, Dover, New York, 1960.

[8] J. Bezanson, A. Edelman, S. Karpinski, and V. B. Shah, *Julia: A fresh approach to numerical computing*, SIAM Review, 59 (2017), pp. 65–98.