Case study: Monocle 3

R/cell data set.R

```
Create a new cell_data_set object.
   @param expression_data expression data matrix for an experiment, can be a
     sparseMatrix.
   @param cell_metadata data frame containing attributes of individual cells,
    where \code{row_names(cell_metadata) = colnames(expression_data)}.
   @param gene_metadata data frame containing attributes of features
    (e.g. genes), where
   \code{row_names(gene_metadata) = row_names(expression_data)}.
#' @return a new cell_data_set object
   @export
   @examples
   small_a549_colData_df <- readRDS(system.file("extdata",</pre>
"small a549 dex pdatarda",
package = "monocle3"))
   small_a549_rowData_df <- readRDS(system.file("extdata",</pre>
# <sup>1</sup>
                                                     "small_a549_dex_fdata.rda",
# <sup>1</sup>
                                                     package = "monocle3"))
   small_a549_exprs <- readRDS(system.file("extdata",</pre>
# <sup>1</sup>
                                               "small_a549_dex_exprs.rda",
package = "monocle3"))
   small_a549_exprs <- small_a549_exprs[,row.names(small_a549_colData_df)]</pre>
   cds <- new_cell_data_set(expression_data = small_a549_exprs,</pre>
# <sup>1</sup>
                               cell_metadata = small_a549_colData_df,
# <sup>1</sup>
                               gene_metadata = small_a549_rowData_df)
# <sup>1</sup>
new_cell_data_set <- function(expression_data,</pre>
                                 cell_metadata = NULL,
                                 gene_metadata = NULL) {
```

The NAMESPACE file defines the API

NAMESPACE

```
export("fData<-")
export("pData<-")</pre>
export("principal_graph<-")
export("principal_graph_aux<-")</pre>
export(size_factors)
export(top_markers)
exportClasses(cell_data_set)
exportMethods("fData<-")</pre>
exportMethods("pData<-")
exportMethods(pseudotime)
import(ggplot2)
importClassesFrom(S4Vectors,List)
importFrom(S4Vectors,"metadata<-")</pre>
importFrom(S4Vectors,SimpleList)
```

Monocle functions that become visible to the user

Functions from other packages that become visible

```
importClassesFrom(S4Vectors,List)
importFrom(S4Vectors,"metadata<-")
importFrom(S4Vectors,SimpleList)
importFrom(S4Vectors,metadata)
importFrom(SingleCellExperiment,"reducedDim<-")
importFrom(SingleCellExperiment,"reducedDims<-")
importFrom(SingleCellExperiment,SingleCellExperiment)</pre>
```