


## SMD Power Inductors (NR series S type)

## NRS8030T4R7MJGJ



## ■ Features

- Item Summary  
4.7uH $\pm$ 20%, 3.6A, 8.0x8.0x3.0mm
- Lifecycle Stage  
Mass Production
- Standard packaging quantity (minimum)  
Taping Embossed 1000pcs

## ■ Products characteristics table


Inductance	4.7 uH $\pm$ 20 %
Case Size (mm)	8.0x8.0
Rated Current (max)	3.6 A
Saturation Current (max)	3.6 A
Temperature Rise Current (max)	4 A
DC Resistance (typ)	22 m $\Omega$
DC Resistance (max)	28.6 m $\Omega$
LQ Measuring Frequency	100 kHz
Self Resonant Frequency (min)	40 MHz
Operating Temp. Range	-25 to +125 °C (Including-self-generated heat)
RoHS2 Compliance	Yes
REACH Compliance	Yes
Soldering	Reflow

## ■ External Dimensions

Dimension L	8.0 $\pm$ 0.2 mm
Dimension W	8.0 $\pm$ 0.2 mm
Dimension H	Max 3.0 mm
Dimension e	1.6 $\pm$ 0.3 mm

## ■ Recommended Land Patterns

<b>【推奨ランドパターン】</b> 実装上の注意 ・実装状態を確認の上ご使用くださいますようお願いいたします。 ・本製品のはんだ付けはリフローはんだ工法に限りま。
<b>【Recommended Land Patterns】</b> Surface Mounting ・Mounting and soldering conditions should be checked beforehand. ・Applicable soldering process to these products is reflow soldering only.






## SMD Power Inductors (NR series S type)

**NRS8030T4R7MJGJ**



Dimension	unit : mm	unit : inch
Length :	8.0 + / - 0.2	( 0.315 + / - 0.008 )
Width :	8.0 + / - 0.2	( 0.315 + / - 0.008 )
Height :	3.0 max.	( 0.118 max. )

Inductance :	4.7	$\mu$ H ( test freq at 0.1MHz )
DC Resistance :	0.022 / 0.0286	ohm ( typ / max )
Saturation Current :	3,600	mA ( max )
Temp. rise Current :	4,000	mA ( max )
Saturation current typical : 30% reduction from initial L value.		
Temp rise Current typical : Temperature will rise by 40 deg C		



The data is reference only. Electrical characteristics vary depending on environment or measurement condition.  
TAIYO YUDEN reserves the right to make change to the data at any time without notice.  
Before making final selection, please check product specification.