✦ **AI Overview**

⋮

In a JSON array, the index starts from 0. This is consistent with how most modern programming languages, including JavaScript from which JSON is derived, handle array indexing. 🔗

For the array `["A", "B", "C"]` :

- `"A"` is at index `0` .
- `"B"` is at index `1` .
- `"C"` is at index `2` . 🔗

JSON Array Structure

JSON Array Structure. A JSON array contains zero, one, or more ordered...

α OpenText ⋮

JSON keypath expressions - IBM

Use the following guidelines for your JSON keypath expressions: * A forward slash (/)...

IBM ⋮

Array - JavaScript - MDN

Description. In JavaScript, arrays aren't primitives but...

Ⓜ MDN Web Docs ⋮

Show all

Dive deeper in AI Mode

AI responses may include mistakes. Learn more 👍 👎

Ⓢ Stack Overflow
7 answers · 14 years ago

Index value of Array ⋮ **json**

Index of **array** containing key value pair **in JSON** file · 0 · Php **Json** Get Value **Array Index**? 29 · How **can** I get the **index** from **a JSON** object with ...

Retrieving **a** property of **a JSON** object by **index**?   12 answers   Oct 28, 2010

How **do** you represent **a JSON array** of strings ...   4 answers   Mar 14, 2011

More results from stackoverflow.com

People also ask ⋮

What is the first index of a JSON array? ⌄

What does the index of an array start from? ⌄

Does array index start from 0 or 1 in C? ⌄

How do you find the first index of an array? ⌄

Feedback

Apache Pinot Docs
https://docs.pinot.apache.org › basics › indexing › json-...

JSON index
⋮

Apr 2, 2025 — Exclude the given fields, e.g. "**b**", "**c**", even if it **is** under the included paths. Set<String>. null (include all fields). indexPaths.

Niels Lohmann
https://json.nlohmann.me › api › basic_json › array

nlohmann::basic_json::array - JSON for Modern C++

Creates **a JSON array** value from **a** given initializer list. That **is**, given **a** list of values **a**, **b**, **c** , creates the **JSON** value [**a**, **b**, **c**].

Google Cloud
https://cloud.google.com › Data analytics › BigQuery

JSON functions | BigQuery
⋮

JSON '["**a**", "**b**", "**c**"]'. json_path_value_pair : **A** value and the JSONPath for that value. This includes: json_path : Append value at this JSONPath in json_expr ...

Broadcom Tech Docs
https://techdocs.broadcom.com › greenplum-database › a...

Working with JSON Data - Broadcom Tech Docs
⋮

Sep 3, 2025 — Get the **JSON array** element (indexed from zero). '[{"**a**":"foo"},{"**b**":"bar"},{"**c**":"baz"} ...

Apache Pinot Docs
https://docs.pinot.apache.org › basics › indexing › json-...

JSON Index
⋮

Mar 13, 2023 — Exclude the given fields, e.g. "**b**", "**c**", even if it **is** under the included paths. Set<String>. null (include all fields) ...

Index Semi-Structured Data in JSON Blobs - Azure AI Search

Tutorial: **Index** nested **JSON** blobs from Azure Storage using REST · Create Data Source (REST) creates **a** data source connection that specifies what data to **index**.

JSON Path vs JSON Pointer

Apr 15, 2023 — **A JSON** Pointer **is** constructed with **a** series of selectors separated by forward slashes / . The selectors **can** be either key names or **array indices** ...

JSON_EXTRACT_ARRAY_ELE...

Returns **a JSON array** element in the outermost **array** of **a JSON** string, using **a** zero-based **index** ...); ERROR: invalid **json array** object ["**a**",["**b**",1,["**c**",2,3,null,]]].

15 SQL/JSON Path Expressions

At least one of the filter conditions **a** and **b is** satisfied: (**a** || **b**) . Filter condition **c is** not satisfied or the number d **is** less than or equal to 42, or both ...

People also search for

Can JSON **be** an array 🔍	JSON array **of objects example** 🔍
JSON array **of strings example** 🔍	**Proper** JSON array **format** 🔍
JSON array **with one element** 🔍	Json array **rules** 🔍
JSON array **of objects** 🔍	JSON **with** 🔍