Linear Programming 2

Sensitivity: Internal

Contents

- Review
- Simplex Method Demonstration
- Problem Based Approach (Python)
- Diet Problem (Tutorial Question 5)
- Formulating with Summation Notation
- Manufacturing Problem (Question 4 Adapted)
- Introduction to:
  - Integer and Mixed-Integer Based Programming

Sensitivity: Internal

Linear Programming Model

A linear programming model can be written as follows

maximise $P = 5x + 7y$


subject to:

$3x + 2y \leq 144$ (C1)

$x \geq 4y$ (C2)

$x \geq 0$

$y \geq 0$



Sensitivity: Internal

Canonical Form (Matrices)

Our linear programming model

maximise $5x + 7y$

subject to:

$$3x + 2y \leq 144$$
$$x \geq 4y$$
$$x \geq 0$$
$$y \geq 0$$

maximise $5x + 7y$

subject to:

$$3x + 2y \leq 144$$
$$-x + 4y \leq 0$$

and

$$x \geq 0$$
$$y \geq 0$$

maximise $\begin{bmatrix} 5 & 7 \end{bmatrix} \begin{bmatrix} x \\ y \end{bmatrix}$

subject to:

$$\begin{bmatrix} 3 & 2 \\ -1 & 4 \end{bmatrix} \begin{bmatrix} x \\ y \end{bmatrix} \leq \begin{bmatrix} 144 \\ 0 \end{bmatrix}$$

and

$$\begin{bmatrix} x \\ y \end{bmatrix} \geq \begin{bmatrix} 0 \\ 0 \end{bmatrix}$$

Sensitivity: Internal

Solution with Python

maximise $\begin{bmatrix} 5 & 7 \end{bmatrix} \begin{bmatrix} x \\ y \end{bmatrix}$

subject to:

$$\begin{bmatrix} 3 & 2 \\ -1 & 4 \end{bmatrix} \begin{bmatrix} x \\ y \end{bmatrix} \leq \begin{bmatrix} 144 \\ 0 \end{bmatrix}$$

and

$$\begin{bmatrix} x \\ y \end{bmatrix} \geq \begin{bmatrix} 0 \\ 0 \end{bmatrix}$$

We are maximising.

The Scipy function `linprog` minimises!

Notice that in the Python code we call `linprog` with the negated objective, `c = [-5, -7]`

```python
from scipy.optimize import linprog

# cost function (row vector) - to minimise we need the negatives
c = [-5, -7]

# linear inequalities
# (no. rows in A = no. rows in b)
A_ub = [[3, 2],
        [-1, 4]]
b_ub = [144, 0]

#  call the linprog function
results = linprog(c, A_ub, b_ub)

print(results.message)
# if results are a success then print out the optimal solution
if results.success:
    for k in range(len(results.x)):
        print(f"x[{k+1}] = {results.x[k]:.2f}")
    print(f"fval = {results.fun:.2f}")
```

Sensitivity: Internal

Solution with Pyomo (Modelling Language)


maximise $5x + 7y$

subject to:

$$3x + 2y \leq 144$$
$$x \geq 4y$$

and

$$x \geq 0$$
$$y \geq 0$$




```python
from pyomo.environ import *

# Create a concrete model
model = ConcreteModel()

# Decision variables (non-negative)
model.x = Var([0, 1], domain=NonNegativeReals)

# Objective function (maximize 5x0 + 7x1)
f = [5, 7]
model.obj = Objective(expr=sum(f[i] * model.x[i] for i in [0, 1]), sense=maximize)

# Constraints
model.c1 = Constraint(expr=3*model.x[0] + 2*model.x[1] <= 144)
model.c2 = Constraint(expr=model.x[0] >= 4*model.x[1])

# Print model before solving
print("Model formulation:")
model.pprint()

# Solve with GLPK
solver = SolverFactory('glpk')
results = solver.solve(model, tee=False)

# Check results
if (results.solver.status == SolverStatus.ok) and \
   (results.solver.termination_condition == TerminationCondition.optimal):
    print("\nOptimal solution found:")
    model.display()
else:
    print("\nSolver did not find an optimal solution. Status:", results.solver.status)
```

Sensitivity: Internal

Diet Problem (Tutorial Question 5a)

Food	Vitamin A	Vitamin B	Vitamin C	Vitamin D	Fat	Cost	Attractiveness
1	18	4	-	6	-	10	6
2	8	6	22	14	-	6	1
3	22	10	-	-	8	8	5
4	6	12	-	6	-	16	5
5	-	14	-	10	-	8	6
6	-	-	20	8	6	3	4
7	8	-	-	6	20	6	10
8	4	-	8	-	40	8	10
9	-	6	10	12	-	12	6
10	12	20	-	4	-	12	7

	Minimum	Maximum
Vitamin A	100	-
Vitamin B	120	-
Vitamin C	200	-
Vitamin D	80	-
Fat	-	300

The meals provided must satisfy certain basic restriction on vitamin and fat content.
The right table gives the target quantities for a sample of 4 vitamins and one fat type.

The quantities of each nutrient contained in one unit of each of 10 foods and the cost and attractiveness of a unit of each food is given in the left table.

Obtain the optimal solution given that the aim is to minimise the cost of the diet.

Sensitivity: Internal

Diet Problem (Tutorial Question 5a)

Food	Vitamin A	Vitamin B	Vitamin C	Vitamin D	Fat	Cost	Attractiveness
1	18	4	-	6	-	10	6
2	8	6	22	14	-	6	1
3	22	10	-	-	8	8	5
4	6	12	-	6	-	16	5
5	-	14	-	10	-	8	6
6	-	-	20	8	6	3	4
7	8	-	-	6	20	6	10
8	4	-	8	-	40	8	10
9	-	6	10	12	-	12	6
10	12	20	-	4	-	12	7

	Minimum	Maximum
Vitamin A	100	-
Vitamin B	120	-
Vitamin C	200	-
Vitamin D	80	-
Fat	-	300

Variables

x_i - Number of food i

Objective:

minimise $10x_1 + 6x_2 + 8x_3 + 16x_4 + 8x_5 + 3x_6 + 6x_7 + 8x_8 + 12x_9 + 12x_{10}$

Vitamin A Constraint:

subject to:

$$18x_1 + 8x_2 + 22x_3 + 6x_4 + 8x_7 + 4x_8 + 12x_{10} \geq 100$$

Sensitivity: Internal

Diet Problem (Tutorial Question 5a)

minimise $10x_1 + 6x_2 + 8x_3 + 16x_4 + 8x_5 + 3x_6 + 6x_7 + 8x_8 + 12x_9 + 12x_{10}$

subject to:

$18x_1 + 8x_2 + 22x_3 + 6x_4 + 8x_7 + 4x_8 + 12x_{10} \geq 100$ (Vitamin A Constraint)

$4x_1 + 6x_2 + 10x_3 + 12x_4 + 14x_5 + 6x_9 + 20x_{10} \geq 120$ (Vitamin B Constraint)

$22x_2 + 20x_6 + 8x_8 + 10x_9 \geq 200$ (Vitamin C Constraint)

$6x_1 + 14x_2 + 6x_4 + 10x_5 + 8x_6 + 6x_7 + 12x_9 + 4x_{10} \geq 80$ (Vitamin D Constraint)

$8x_3 + 6x_6 + 20x_7 + 40x_8 \leq 300$ (Fat Constraint)

and

$x_1, x_2, \dots, x_{10} \geq 0$ (Non-negativity)

Sensitivity: Internal

Diet Problem (Tutorial Question 5a)

Food	Vitamin A	Vitamin B	Vitamin C	Vitamin D	Fat	Cost	Attractiveness
1	18	4	-	6	-	10	6
2	8	6	22	14	-	6	1
3	22	10	-	-	8	8	5
4	6	12	-	6	-	16	5
5	-	14	-	10	-	8	6
6	-	-	20	8	6	3	4
7	8	-	-	6	20	6	10
8	4	-	8	-	40	8	10
9	-	6	10	12	-	12	6
10	12	20	-	4	-	12	7

	Minimum	Maximum
Vitamin A	100	-
Vitamin B	120	-
Vitamin C	200	-
Vitamin D	80	-
Fat	-	300

x_i - Number of food i (Variable)
v_i^A - Amount of vitamin A in food i (Constant)
v_i^B - Amount of vitamin B in food i (Constant)
v_i^C - Amount of vitamin C in food i (Constant)
v_i^D - Amount of vitamin D in food i (Constant)
f_i - Amount of fat in food i (Constant)
c_i - Cost of food i (Constant)
a_i - Attractiveness of food i (Constant)

minimise

$$\sum_i c_i x_i$$

subject to

$$\sum_i v_i^A x_i \geq 100$$

$$\sum_i v_i^B x_i \geq 120$$

$$\sum_i v_i^C x_i \geq 200$$

$$\sum_i v_i^D x_i \geq 80$$

$$\sum_i f_i x_i \leq 300$$

$$x_i \geq 0, \qquad \forall i$$

Sensitivity: Internal

5a Solution via Pyomo (Problem Based)

minimise

$$\sum_i c_i x_i$$

subject to

$$\sum_i v_i^A x_i \geq 100$$

$$\sum_i v_i^B x_i \geq 120$$

$$\sum_i v_i^C x_i \geq 200$$

$$\sum_i v_i^D x_i \geq 80$$

$$\sum_i f_i x_i \leq 300$$

$$x_i \geq 0, \qquad \forall i$$

```python
from pyomo.environ import *

# -------------------------
# Data (simple Python lists)
# -------------------------
cost  = [10, 6, 8, 16, 8, 3, 6, 8, 12, 12]
vita  = [18, 8, 22, 6, 0, 0, 8, 4, 0, 12]
vitb  = [4, 6, 10, 12, 14, 0, 0, 0, 6, 20]
vitc  = [0, 22, 0, 0, 0, 20, 0, 8, 10, 0]
vitd  = [6, 14, 0, 6, 10, 8, 6, 0, 12, 4]
fat   = [0, 0, 8, 0, 0, 6, 20, 40, 0, 0]

n = len(cost)   # number of foods

# -------------------------
# Model
# -------------------------
model = ConcreteModel()

# Decision variables: amount of each food
model.x = Var(range(n), domain=NonNegativeReals)

# Objective: minimize total cost
model.obj = Objective(expr=sum(cost[i] * model.x[i] for i in range(n)),
                      sense=minimize)

# Vitamin and fat constraints
model.vita_min = Constraint(expr=sum(vita[i] * model.x[i] for i in range(n)) >= 100)
model.vitb_min = Constraint(expr=sum(vitb[i] * model.x[i] for i in range(n)) >= 120)
model.vitc_min = Constraint(expr=sum(vitc[i] * model.x[i] for i in range(n)) >= 200)
model.vitd_min = Constraint(expr=sum(vitd[i] * model.x[i] for i in range(n)) >= 80)
model.fat_max  = Constraint(expr=sum(fat[i]  * model.x[i] for i in range(n)) <= 300)
```

Sensitivity: Internal

Diet Problem (Tutorial Question 5b)

x_i - Number of food i
v_i^A - Amount of vitamin A in food i
v_i^B - Amount of vitamin B in food i
v_i^C - Amount of vitamin C in food i
v_i^D - Amount of vitamin D in food i
f_i - Amount of fat in food i
c_i - Cost of food i
a_i - Attractiveness of food i

Obtain the optimal solution given that the aim is to maximise the attractiveness of the diet.

minimise

$$\sum_i c_i x_i$$

subject to

$$\sum_i v_i^A x_i \geq 100$$
$$\sum_i v_i^B x_i \geq 120$$
$$\sum_i v_i^C x_i \geq 200$$
$$\sum_i v_i^D x_i \geq 80$$
$$\sum_i f_i x_i \leq 300$$
$$x_i \geq 0, \qquad \forall i$$

maximise

$$\sum_i a_i x_i$$

subject to

$$\sum_i v_i^A x_i \geq 100$$
$$\sum_i v_i^B x_i \geq 120$$
$$\sum_i v_i^C x_i \geq 200$$
$$\sum_i v_i^D x_i \geq 80$$
$$\sum_i f_i x_i \leq 300$$
$$x_i \geq 0, \qquad \forall i$$

Sensitivity: Internal

Diet Problem (Tutorial Question 5b)

Food	Vitamin A	Vitamin B	Vitamin C	Vitamin D	Fat	Cost	Attractiveness
1	18	4	-	6	-	10	6
2	8	6	22	14	-	6	1
3	22	10	-	-	8	8	5
4	6	12	-	6	-	16	5
5	-	14	-	10	-	8	6
6	-	-	20	8	6	3	4
7	8	-	-	6	20	6	10
8	4	-	8	-	40	8	10
9	-	6	10	12	-	12	6
10	12	20	-	4	-	12	7

	Minimum	Maximum
Vitamin A	100	-
Vitamin B	120	-
Vitamin C	200	-
Vitamin D	80	-
Fat	-	300

maximise

$$\sum_i a_i x_i$$

subject to

$$\sum_i v_i^A x_i \geq 100$$

$$\sum_i v_i^B x_i \geq 120$$

$$\sum_i v_i^C x_i \geq 200$$

$$\sum_i v_i^D x_i \geq 80$$

$$\sum_i f_i x_i \leq 300$$

$$x_i \geq 0, \qquad \forall i$$

What is the issue here?

UNBOUNDED!!

The program is free to pick foods with no fat. As long as the vitamin constraints are satisfied, we are in the feasible region and the objective is unbounded.

Sensitivity: Internal

Fix

Maximum and minimum restrictions on both fat and vitamin content, e.g. maximum content = minimum content + 20%.

	Minimum	Maximum
Vitamin A	100	120
Vitamin B	120	144
Vitamin C	200	240
Vitamin D	80	96
Fat	250	300

maximise

$$\sum_i a_i x_i$$

subject to

$$\sum_i v_i^A x_i \geq 100, \qquad \sum_i v_i^A x_i \leq 120$$

$$\sum_i v_i^B x_i \geq 120, \qquad \sum_i v_i^B x_i \leq 144$$

$$\sum_i v_i^C x_i \geq 200, \qquad \sum_i v_i^C x_i \leq 240$$

$$\sum_i v_i^D x_i \geq 80, \qquad \sum_i v_i^D x_i \leq 96$$

$$\sum_i f_i x_i \geq 250, \qquad \sum_i f_i x_i \leq 300$$

$$x_i \geq 0, \qquad \forall i$$

Sensitivity: Internal

5c Solution via Pyomo (Problem Based)

maximise

$$\sum_i a_i x_i$$

subject to

$$\sum_i v_i^A x_i \geq 100, \qquad \sum_i v_i^A x_i \leq 120$$

$$\sum_i v_i^B x_i \geq 120, \qquad \sum_i v_i^B x_i \leq 144$$

$$\sum_i v_i^C x_i \geq 200, \qquad \sum_i v_i^C x_i \leq 240$$

$$\sum_i v_i^D x_i \geq 80, \qquad \sum_i v_i^D x_i \leq 96$$

$$\sum_i f_i x_i \geq 250, \qquad \sum_i f_i x_i \leq 300$$

$$x_i \geq 0, \qquad \forall i$$

```python
from pyomo.environ import *

# -------------------------
# Data (simple Python lists)
# -------------------------
att   = [6, 1, 5, 5, 6, 4, 10, 10, 6, 7]
vita  = [18, 8, 22, 6, 0, 0, 8, 4, 0, 12]
vitb  = [4, 6, 10, 12, 14, 0, 0, 0, 6, 20]
vitc  = [0, 22, 0, 0, 0, 20, 0, 8, 10, 0]
vitd  = [6, 14, 0, 6, 10, 8, 6, 0, 12, 4]
fat   = [0, 0, 8, 0, 0, 6, 20, 40, 0, 0]

n = len(att)   # number of foods

# -------------------------
# Model
# -------------------------
model = ConcreteModel()

# Decision variables: amount of each food
model.x = Var(range(n), domain=NonNegativeReals)

# Objective: minimize total cost
model.obj = Objective(expr=sum(att[i] * model.x[i] for i in range(n)),
                      sense=maximize)

# Vitamin and fat constraints
model.vita_min = Constraint(expr=sum(vita[i] * model.x[i] for i in range(n)) >= 100)
model.vitb_min = Constraint(expr=sum(vitb[i] * model.x[i] for i in range(n)) >= 120)
model.vitc_min = Constraint(expr=sum(vitc[i] * model.x[i] for i in range(n)) >= 200)
model.vitd_min = Constraint(expr=sum(vitd[i] * model.x[i] for i in range(n)) >= 80)
model.fat_max  = Constraint(expr=sum(fat[i]  * model.x[i] for i in range(n)) <= 300)

# Additional constraints
model.vita_max = Constraint(expr=sum(vita[i] * model.x[i] for i in range(n)) <= 100 * 1.2)
model.vitb_max = Constraint(expr=sum(vitb[i] * model.x[i] for i in range(n)) <= 120 * 1.2)
model.vitc_max = Constraint(expr=sum(vitc[i] * model.x[i] for i in range(n)) <= 200 * 1.2)
model.vitd_max = Constraint(expr=sum(vitd[i] * model.x[i] for i in range(n)) <= 80 * 1.2)
model.fat_min = Constraint(expr=sum(fat[i] * model.x[i] for i in range(n)) >= 300 / 1.2)
```

Sensitivity: Internal

Brief Introduction to Mixed-Integer Linear Programming (MILP)

Sensitivity: Internal

Manufacturing Problem (Tutorial Q4 Adapted)

A firm manufactures 3 products, X, Y and Z.

Each one is processed by a single machine, machine A, which has a capacity of 100 hours per week.

It takes 4.5 hours to make product X, 2 hours to make product Y and 3 hours to make product Z.

- The profit made (per unit) for X, Y and Z is £11.5, £5 and £8 respectively.
- The firm only has enough material a week to make 20 of product Z

How many X's, Y's and Z's should be made per week so that the largest profit is made?

Sensitivity: Internal

Manufacturing Problem (Tutorial Q4 Adapted)

maximise $P = 11.5x + 5y + 8z$ (objective)

subject to:

$4.5x + 2y + 3z \leq 100$ (machine hours constraint)

$z \leq 20$ (product Z constraint)

and

$x, y, z \geq 0$ (non-negativity constraint)

<u>Solution</u>

$$(x, y, z)^* = (8.89, 0, 20)$$
$$P^* = 262.22$$

Sensitivity: Internal

Manufacturing Problem (Tutorial Q4 Adapted)

What if anything that isn't fully manufactured has to be discarded or it would cost the company overtime?

Perhaps we should only allow the solution to be completed products (i.e. whole numbers).

It transpires that if you round the solution up, $(9,0,20)$, you need 100.5 hours (INFEASIBLE). If you round down, $(8,0,20)$, you get a profit of $£252$, with a time taken of 96 hours.

However, if you make $(8,2,20)$, you get a profit of $£262$, with a time taken of 100 hours

Ten pounds might not seem like much, but imagine we are dealing in thousands or millions of pounds!

KEY POINT: Rounding a solution does not necessarily give you the optimal integer solution.

Sensitivity: Internal

Desmos Demonstration

maximise $P = 2x + 3.5y$

subject to:


$$3x + 2y \leq 14$$
$$2x + 3y \leq 12.5$$
$$-x + y \leq 1$$

and

$$x, y \geq 0$$

Optimal Solution

$$\boldsymbol{x}^* = (x, y) = (1.9, 2.9)$$
$$P^* = 13.95$$



Sensitivity: Internal

Rounded Solutions

Optimal Solution

$$\boldsymbol{x}^* = (x, y) = (1.9, 2.9)$$
$$P^* = 13.95$$

$$\boldsymbol{x} = (x, y) = (1,2)$$

$$P = 9$$

$$\boldsymbol{x} = (x, y) = (1,3)$$


Infeasible!

$$\boldsymbol{x} = (x, y) = (2,2)$$

$$P = 11$$

$$\boldsymbol{x} = (x, y) = (2,3)$$

Infeasible!



Sensitivity: Internal

Rounded Solutions

$$\boldsymbol{x} = (x, y) = (1,2)$$

$$P = 9$$


$$\boldsymbol{x} = (x, y) = (2,2)$$

$$P = 11$$

However!

$$\boldsymbol{x}^* = (x, y) = (3,2)$$

$$P^* = 13$$



Sensitivity: Internal

Integer Solution via Pyomo (problem based)

maximise $P = 2x + 3.5y$

subject to:

$$3x + 2y \leq 14$$
$$2x + 3y \leq 12.5$$
$$-x + y \leq 1$$

and

$$x, y \geq 0$$
$$x, y \in \mathbb{Z}$$

Optimal Solution

$$\boldsymbol{x}^* = (x, y) = (3,2)$$
$$P^* = 13$$

```
Optimal solution found:
Model unknown

  Variables:
    x : Size=2, Index=I
        Key : Lower : Value : Upper : Fixed : Stale : Domain
          0 :     0 :   3.0 :  None : False : False : NonNegativeIntegers
          1 :     0 :   2.0 :  None : False : False : NonNegativeIntegers

  Objectives:
    obj : Size=1, Index=None, Active=True
        Key  : Active : Value
        None :   True :  13.0
```

```python
from pyomo.environ import *

# Model
model = ConcreteModel()

# Index set and decision variables (both integer, >= 0)
model.I = Set(initialize=[0, 1])
model.x = Var(model.I, domain=NonNegativeIntegers)

# Objective: maximize 2*x[0] + 3.5*x[1]
f = {0: 2, 1: 3.5}
model.obj = Objective(expr=sum(f[i] * model.x[i] for i in model.I), sense=maximize)

# Constraints
model.c1 = Constraint(expr=3*model.x[0] + 2*model.x[1] <= 14)
model.c2 = Constraint(expr=2*model.x[0] + 3*model.x[1] <= 12.5)
model.c3 = Constraint(expr=-model.x[0] + model.x[1] <= 1)

# Show model formulation
print("Model formulation:")
model.pprint()

# Solve (GLPK supports MIPs)
solver = SolverFactory('glpk')
results = solver.solve(model, tee=False)
```

Mixed-Integer Program


maximise $P = 2x + 3.5y$

subject to:

$$3x + 2y \leq 14$$
$$2x + 3y \leq 12.5$$
$$-x + y \leq 1$$

and

$$x, y \geq 0$$
$$x \in \mathbb{Z}$$



<u>Optimal Solution</u>

$\boldsymbol{x}^* = (x, y) = (2, 2.833)$

$P^* = 13.917$

Sensitivity: Internal

Mixed-Integer Solution (problem based)

maximise $P = 2x + 3.5y$

subject to:

$$3x + 2y \leq 14$$
$$2x + 3y \leq 12.5$$
$$-x + y \leq 1$$

and

$$x, y \geq 0$$
$$x \in \mathbb{Z}$$

Optimal Solution

$\boldsymbol{x}^* = (x, y) = (2, 2.833)$

$P^* = 13.917$

```
Optimal solution found:
Model unknown

  Variables:
    x1 : Size=1, Index=None
        Key  : Lower : Value : Upper : Fixed : Stale : Domain
        None :     0 :   2.0 :  None : False : False : NonNegativeIntegers
    x2 : Size=1, Index=None
        Key  : Lower : Value            : Upper : Fixed : Stale : Domain
        None :     0 : 2.83333333333333 :  None : False : False : NonNegativeReals

  Objectives:
    obj : Size=1, Index=None, Active=True
        Key  : Active : Value
        None :   True : 13.916666666666655
```

```python
from pyomo.environ import *

# Create a concrete model
model = ConcreteModel()

# Decision variables
model.x1 = Var(domain=NonNegativeIntegers, bounds=(0, float('inf')))
model.x2 = Var(domain=NonNegativeReals, bounds=(0, float('inf')))

# Objective function (maximize 2x1 + 3.5x2)
f = [2, 3.5]
model.obj = Objective(expr=f[0]*model.x1 + f[1]*model.x2, sense=maximize)

# Constraints
model.c1 = Constraint(expr=3*model.x1 + 2*model.x2 <= 14)
model.c2 = Constraint(expr=2*model.x1 + 3*model.x2 <= 12.5)
model.c3 = Constraint(expr=-model.x1 + model.x2 <= 1)

# Print model before solving
print("Model formulation:")
model.pprint()

# Solve with GLPK
solver = SolverFactory('glpk')
results = solver.solve(model, tee=False)
```

Demos

https://ctsallis.github.io/operational_research/

Lectures → Semester 1 → Week 03 - Linear Programming 2 → 2 Lecture Demos

Sensitivity: Internal