

Specifies the .cfg file to use when running the APV configuration - note that this file must contain the same set of results which the .cfg file originally used to generate the .apv file contained. Overrides whatever value is present in the .apv file.

-IncidenceAggregation <aggregation level>

Level to aggregate incidence results to before pooling them. Supported values are None, County, State, and Nation. Overrides whatever value is present in the .apv file.

-ValuationAggregation <aggregation level>

Level to aggregate valuation results to before pooling them. Supported values are None, County, State, and Nation (though the value must be greater than or equal to IncidenceAggregation). Overrides whatever value is present in the .apv file.

-RandomSeed <integer>

Random seed to use for all procedures requiring pseudo-random numbers (e.g. monte carlo procedures). Overrides the default behavior, which is to generate a new random seed each time the APV configuration is run.

-DollarYear <integer>

L.3.5 Generate Report

Reports come in three main varieties - Audit Trail Reports, which can be generated from any BenMAP file; Configuration Results Reports, which can be generated from .cfg files; and APV Configuration Results Reports, which can be generated from .apv files. All these report types need an input filename and an output filename. CFGR reports and APVR reports additionally take many optional parameters.

The format for each report type is:

GENERATE REPORT <ReportType>

-InputFile <filename>

-ReportFile <filename>

<optional parameters>

Supported ReportType values are: AuditTrail, CFGR, and APVR.

L.3.5.1 Audit Trail

Audit trail reports require only the parameters described in the “Generate Report” section.

L.3.5.2 CFGR Report

A CFGR report may be generating using only the parameters described in the “Generate Report” section. However, there are also a number of additional options, described below.

Optional Parameters

-GridFields <comma separated field names>

Specifies the set of grid fields to include in the report. Grid fields include Column and Row. If this parameter is not present, all fields will be included in the report.

-CustomFields <comma separated field names>

Specifies the set of custom fields (C-R Function identifiers, in this case) to include in the report. Custom fields include DataSet, Endpoint Group, Endpoint, Pollutant, Metric, Seasonal Metric, Metric Statistic, Author, Year, Location, Other Pollutants, Qualifier, Reference, Race, Ethnicity, Gender, Start Age, End Age, Function, Incidence Dataset, Prevalence Dataset, Beta, Disbeta, P1Beta, P2Beta, A, NameA, B, NameB, C, NameC, and Geographic Area. If this parameter is not present, all fields will be included in the report.

-ResultFields <comma separated field names>

Specifies the set of result fields to include in the report. Result fields include Point Estimate, Population, Delta, Mean, Baseline, Percent of Baseline, Standard Deviation, Variance, and All Percentiles. If this parameter is not present, all fields will be included in the report. If All Percentiles is not chosen, BenMAP will only export the 2.5th and 97.5th percentiles.

L.3.5.3 APVR Report

Required Parameters

APVR Reports require one additional parameter beyond those required for Audit Trail or CFGR Reports.

-ResultType <result type>

Specifies the result type for which a report should be created. Supported result types are: IncidenceResults, PooledIncidence, PooledValuation.

Optional Parameters

All of the CFGR report parameters are supported for APVR reports as well, except that Population and Delta are not supported ResultField elements.

-Totals <total type>

Specifies the type of totals which should be included in the report. Supported types are Dependent and Independent. Totals can only be generated for valuation results (Valuation, AggregatedValuation, and PooledValuation result types).

-ResultFields <comma separated field names>

Specifies the set of result fields to include in the report. For IncidenceResults reports, all fields will be included by default. For PooledIncidence reports, supported fields are: Point Estimate, Population, Delta, Mean, Baseline, Percent of Baseline, Standard Deviation, Variance, and All Percentiles. For PooledValuation reports, supported fields are: Point Estimate, Mean, Standard Deviation, Variance, Percentiles. If All Percentiles is not chosen, BenMAP will only export the 2.5th and 97.5th percentiles.

L.4 Example 1

VARIABLES

%CFG%	C:\BenMAP\CommandLine\Configurations\PM25 Wizard.cfgx
%APV%	C:\BenMAP\CommandLine\Configurations\PM25 Wizard.apvx
%RESULTSDIR%	C:\BenMAP\Temp
%REPORTDIR%	C:\BenMAP\Temp
%AQG%	C:\BenMAP\CommandLine\Air Quality Grids

COMMANDS

SETACTIVESETUP

-ActiveSetup United States

CREATE AQG

-Filename	%AQG%\PM25_2002Baseline_50km.aqgx
-GridType	CMAQ 12km
-Pollutant	PM2.5

MonitorDirect

-InterpolationMethod VNA

-MonitorDataType	Library
-MonitorDataSet	EPA Standard Monitors
-MonitorYear	2002
-MaxDistance	50

CREATE AQG

-Filename	%AQG%\PM25_2002Control_50km.aqgx
-GridType	CMAQ 12km
-Pollutant	PM2.5

MonitorRollback

-InterpolationMethod	VNA
-MonitorDataType	Library
-MonitorDataSet	EPA Standard Monitors
-MonitorYear	2002
-RollbackGridType	State
-MaxDistance	50

RollbackToStandardOptions

-Stanard	65
-Metric	D24HourMean
-InterdayRollbackMethodIncremental	

RUN CFG

-CFGFilename	%CFG%
-ResultsFilename	%RESULTSDIR%\PM25_2002_50km.aqgx
-BaselineAQG	%AQG%\PM25_2002Baseline_50km.aqgx
-ControlAQG	%AQG%\PM25_2002Control_50km.aqgx

RUN APV

-APVFilename	%APV%
-ResultsFilename	%RESULTSDIR%\PM25_2002_50km.apvr
-CFGRFilename	%RESULTSDIR%\PM25_2002_50km.cfgr
-IncidenceAggregation	Nation
-ValuationAggregation	Nation

GENERATE REPORT APVR

-InputFile	%RESULTSDIR%\PM25_2002_50km.apvr
-ReportFile	%REPORTDIR%\PM25_2002_50km_IncidenceNation.csv
-ResultType	PooledIncidence