


# **Recap-1**

## **The Compilers' Front End**

# Front End of Compilers



# **PART I: Regex $\rightarrow$ NFA $\rightarrow$ (Min) DFA**

# Regular Expression (Regex)

- Regex describes a language

# Regular Expression (Regex)

- Regex describes a language
- Primitive regex
  - $\emptyset, \epsilon, a$

# Regular Expression (Regex)

- Regex describes a language
- Primitive regex
  - $\emptyset, \epsilon, a$
- Given two regex:  $r_1, r_2$ , the following are regex
  - $r_1|r_2$
  - $r_1r_2$
  - $r_1^*$
  - $(r_1)$

# Regular Expression (Regex)

- Regex describes a language
- Primitive regex
  - $\emptyset, \epsilon, a$
- Given two regex:  $r_1, r_2$ , the following are regex
  - $r_1|r_2$
  - $r_1r_2$
  - $r_1^*$
  - $(r_1)$
- **Example:**  $(a|b)^*c$

# Language by Regex

- The language represented by regex are defined below
- Primitive regex
  - $L(\emptyset) = \emptyset$ ;  $L(\epsilon) = \{\epsilon\}$ ;  $L(a) = \{a\}$



# Language by Regex

- The language represented by regex are defined below
- Primitive regex
  - $L(\emptyset) = \emptyset$ ;  $L(\epsilon) = \{\epsilon\}$ ;  $L(a) = \{a\}$
- Given two regex:  $r_1, r_2$ , the following are regex
  - $L(r_1|r_2) = L(r_1) \cup L(r_2)$
  - $L(r_1r_2) = L(r_1)L(r_2)$
  - $L(r_1^*) = (L(r_1))^*$
  - $L((r_1)) = L(r_1)$


# Regex to NFA (DFA)

- Primitive regex
  - $L(\emptyset) = \emptyset$ ;  $L(\epsilon) = \{\epsilon\}$ ;  $L(a) = \{a\}$

# Regex to NFA (DFA)

- Primitive regex

- $L(\emptyset) = \emptyset$ ;  $L(\epsilon) = \{\epsilon\}$ ;  $L(a) = \{a\}$




# Regex to NFA (DFA)

- Primitive regex

- $L(\emptyset) = \emptyset$ ;  $L(\epsilon) = \{\epsilon\}$ ;  $L(a) = \{a\}$

- Given two regex:  $r_1, r_2$ , the following are regex

- $L(r_1|r_2) = L(r_1) \cup L(r_2)$
- $L(r_1r_2) = L(r_1)L(r_2)$
- $L(r_1^*) = (L(r_1))^*$
- $L((r_1)) = L(r_1)$






# Example

- Build the NFA for the regex:  $(a|b)^*c$
- $L((a|b)^*c) = (L(a|b))^*L(c) = (L(a) \cup L(b))^*L(c)$


# Example

- Build the NFA for the regex:  $(a|b)^*c$
- $L((a|b)^*c) = (L(a|b))^*L(c) = (L(a) \cup L(b))^*L(c)$




# Example

- Build the NFA for the regex:  $(a|b)^*c$
- $L((a|b)^*c) = (L(a|b))^*L(c) = (L(a) \cup L(b))^*L(c)$



# Example


- Build the NFA for the regex:  $(a|b)^*c$
- $L((a|b)^*c) = (L(a|b))^*L(c) = (L(a) \cup L(b))^*L(c)$





# Example



- Build the NFA for the regex:  $(a|b)^*c$
- $L((a|b)^*c) = (L(a|b))^*L(c) = (L(a) \cup L(b))^*L(c)$





# From NFA to DFA

- **Subset Construction**
- A subset of NFA states is a DFA state



# From NFA to DFA





# From NFA to DFA





# From NFA to DFA





# From NFA to DFA



# From NFA to DFA





# From NFA to DFA





# From NFA to DFA




# DFA Minimization

- Minimizing DFA can improve the efficiency of computation

# DFA Minimization


- Minimizing DFA can improve the efficiency of computation



	<i>a</i>	<i>b</i>
<i>q</i> <sub>0</sub>	<i>q</i> <sub>1</sub>	<i>q</i> <sub>2</sub>
<i>q</i> <sub>1</sub>	<i>q</i> <sub>0</sub>	<i>q</i> <sub>3</sub>
<i>q</i> <sub>2</sub>	<i>q</i> <sub>4</sub>	<i>q</i> <sub>5</sub>
<i>q</i> <sub>3</sub>	<i>q</i> <sub>4</sub>	<i>q</i> <sub>5</sub>
<i>q</i> <sub>4</sub>	<i>q</i> <sub>4</sub>	<i>q</i> <sub>5</sub>
<i>q</i> <sub>5</sub>	<i>q</i> <sub>5</sub>	<i>q</i> <sub>5</sub>

# DFA Minimization

- Minimizing DFA can improve the efficiency of computation




	<i>a</i>	<i>b</i>
<i>q</i> <sub>0</sub>	<i>q</i> <sub>1</sub>	<i>q</i> <sub>2</sub>
<i>q</i> <sub>1</sub>	<i>q</i> <sub>0</sub>	<i>q</i> <sub>3</sub>
<i>q</i> <sub>2</sub>	<i>q</i> <sub>4</sub>	<i>q</i> <sub>5</sub>
<i>q</i> <sub>3</sub>	<i>q</i> <sub>4</sub>	<i>q</i> <sub>5</sub>
<i>q</i> <sub>4</sub>	<i>q</i> <sub>4</sub>	<i>q</i> <sub>5</sub>
<i>q</i> <sub>5</sub>	<i>q</i> <sub>5</sub>	<i>q</i> <sub>5</sub>

Step 1	$\{q_0, q_1, q_5\}, \{q_2, q_3, q_4\}$	Distinguish final and non-final states
Step 2		
Step 3		

# DFA Minimization

- Minimizing DFA can improve the efficiency of computation




	<i>a</i>	<i>b</i>
<i>q</i> <sub>0</sub>	<i>q</i> <sub>1</sub>	<i>q</i> <sub>2</sub>
<i>q</i> <sub>1</sub>	<i>q</i> <sub>0</sub>	<i>q</i> <sub>3</sub>
<i>q</i> <sub>2</sub>	<i>q</i> <sub>4</sub>	<i>q</i> <sub>5</sub>
<i>q</i> <sub>3</sub>	<i>q</i> <sub>4</sub>	<i>q</i> <sub>5</sub>
<i>q</i> <sub>4</sub>	<i>q</i> <sub>4</sub>	<i>q</i> <sub>5</sub>
<i>q</i> <sub>5</sub>	<i>q</i> <sub>5</sub>	<i>q</i> <sub>5</sub>

<b>Step 1</b>	$\{q_0, q_1, q_5\}, \{q_2, q_3, q_4\}$	Distinguish final and non-final states
<b>Step 2</b>	$\{q_0, q_1\}, \{q_5\}$	$\delta(q_0, a/b)$ and $\delta(q_1, a/b)$ are in the same set, but $\delta(q_5, a/b)$ not
<b>Step 3</b>		

# DFA Minimization

- Minimizing DFA can improve the efficiency of computation




	<i>a</i>	<i>b</i>
<i>q</i> <sub>0</sub>	<i>q</i> <sub>1</sub>	<i>q</i> <sub>2</sub>
<i>q</i> <sub>1</sub>	<i>q</i> <sub>0</sub>	<i>q</i> <sub>3</sub>
<i>q</i> <sub>2</sub>	<i>q</i> <sub>4</sub>	<i>q</i> <sub>5</sub>
<i>q</i> <sub>3</sub>	<i>q</i> <sub>4</sub>	<i>q</i> <sub>5</sub>
<i>q</i> <sub>4</sub>	<i>q</i> <sub>4</sub>	<i>q</i> <sub>5</sub>
<i>q</i> <sub>5</sub>	<i>q</i> <sub>5</sub>	<i>q</i> <sub>5</sub>

<b>Step 1</b>	$\{q_0, q_1, q_5\}, \{q_2, q_3, q_4\}$	Distinguish final and non-final states
<b>Step 2</b>	$\{q_0, q_1\}, \{q_5\}$	$\delta(q_0, a/b)$ and $\delta(q_1, a/b)$ are in the same set, but $\delta(q_5, a/b)$ not
<b>Step 3</b>		

# DFA Minimization

- Minimizing DFA can improve the efficiency of computation




	<i>a</i>	<i>b</i>
<i>q</i> <sub>0</sub>	<i>q</i> <sub>1</sub>	<i>q</i> <sub>2</sub>
<i>q</i> <sub>1</sub>	<i>q</i> <sub>0</sub>	<i>q</i> <sub>3</sub>
<i>q</i> <sub>2</sub>	<i>q</i> <sub>4</sub>	<i>q</i> <sub>5</sub>
<i>q</i> <sub>3</sub>	<i>q</i> <sub>4</sub>	<i>q</i> <sub>5</sub>
<i>q</i> <sub>4</sub>	<i>q</i> <sub>4</sub>	<i>q</i> <sub>5</sub>
<i>q</i> <sub>5</sub>	<i>q</i> <sub>5</sub>	<i>q</i> <sub>5</sub>

<b>Step 1</b>	$\{q_0, q_1, q_5\}, \{q_2, q_3, q_4\}$	Distinguish final and non-final states
<b>Step 2</b>	$\{q_0, q_1\}, \{q_5\}, \{q_2, q_3, q_4\}$	$\delta(q_0, a/b)$ and $\delta(q_1, a/b)$ are in the same set, but $\delta(q_5, a/b)$ not
<b>Step 3</b>		

# DFA Minimization

- Minimizing DFA can improve the efficiency of computation





	<i>a</i>	<i>b</i>
<i>q</i> <sub>0</sub>	<i>q</i> <sub>1</sub>	<i>q</i> <sub>2</sub>
<i>q</i> <sub>1</sub>	<i>q</i> <sub>0</sub>	<i>q</i> <sub>3</sub>
<i>q</i> <sub>2</sub>	<i>q</i> <sub>4</sub>	<i>q</i> <sub>5</sub>
<i>q</i> <sub>3</sub>	<i>q</i> <sub>4</sub>	<i>q</i> <sub>5</sub>
<i>q</i> <sub>4</sub>	<i>q</i> <sub>4</sub>	<i>q</i> <sub>5</sub>
<i>q</i> <sub>5</sub>	<i>q</i> <sub>5</sub>	<i>q</i> <sub>5</sub>

<b>Step 1</b>	$\{q_0, q_1, q_5\}, \{q_2, q_3, q_4\}$	Distinguish final and non-final states
<b>Step 2</b>	$\{q_0, q_1\}, \{q_5\}, \{q_2, q_3, q_4\}$	$\delta(q_0, a/b)$ and $\delta(q_1, a/b)$ are in the same set, but $\delta(q_5, a/b)$ not
<b>Step 3</b>	$\{q_0, q_1\}, \{q_5\}, \{q_2, q_3, q_4\}$	The result does not change and the algorithm completes



# DFA Minimization



- Minimizing DFA can improve the efficiency of computation



<b>Step 1</b>	$\{q_0, q_1, q_5\}, \{q_2, q_3, q_4\}$	Distinguish final and non-final states
<b>Step 2</b>	$\{q_0, q_1\}, \{q_5\}, \{q_2, q_3, q_4\}$	$\delta(q_0, a/b)$ and $\delta(q_1, a/b)$ are in the same set, but $\delta(q_5, a/b)$ not
<b>Step 3</b>	$\{q_0, q_1\}, \{q_5\}, \{q_2, q_3, q_4\}$	The result does not change and the algorithm completes

# DFA Minimization

- Minimizing DFA can improve the efficiency of computation



<b>Step 1</b>	$\{q_0, q_1, q_5\}, \{q_2, q_3, q_4\}$	Distinguish final and non-final states
<b>Step 2</b>	$\{q_0, q_1\}, \{q_5\}, \{q_2, q_3, q_4\}$	$\delta(q_0, a/b)$ and $\delta(q_1, a/b)$ are in the same set, but $\delta(q_5, a/b)$ not
<b>Step 3</b>	$\{q_0, q_1\}, \{q_5\}, \{q_2, q_3, q_4\}$	The result does not change and the algorithm completes

# **PART II: CFG and Parsing**

# Context Free Grammar (CFG)

- A context-free grammar is a tuple  $G = (N, T, S, P)$ 
  - $N$ : a finite set of non-terminals
  - $T$ : a finite set of terminals, such that  $N \cap T = \emptyset$
  - $S \in N$ : start non-terminals
  - $P$ : production rules in the form of  $A \rightarrow a$ , where  $A \in N$  and  $a \in (N \cup T)^*$

assignment  $\rightarrow$  identifier = expression  
 expression  $\rightarrow$  term + term  
     term  $\rightarrow$  identifier  
     term  $\rightarrow$  identifier \* number

assignment  $\rightarrow$  identifier = expression  
 expression  $\rightarrow$  term + term  
     term  $\rightarrow$  identifier  
           | identifier \* number

# Exercises

$S \rightarrow aSb \mid \epsilon$  is the grammar for  $a^n b^n$

- Write a context-free grammar for the following languages
  - $0^*1^*$

# Exercises

$S \rightarrow aSb \mid \epsilon$  is the grammar for  $a^n b^n$

- Write a context-free grammar for the following languages
  - $0^n 1^{2n}$

# Exercises

$S \rightarrow aSb \mid \epsilon$  is the grammar for  $a^n b^n$

- Write a context-free grammar for the following languages
  - $L = \{ w \mid w \text{ is a string of balanced parentheses} \}$

# Exercises

$S \rightarrow aSb \mid \epsilon$  is the grammar for  $a^n b^n$

- Write a context-free grammar for the following languages
  - $a^i b^j c^k$  where  $i = j$  or  $j = k$



# Exercises

$S \rightarrow aSb \mid \epsilon$  is the grammar for  $a^n b^n$

- Write a context-free grammar for the following languages
  - $a^i b^j c^k$  where  $i \neq j$  or  $j \neq k$

# Building a Parser in Practice

- Each non-terminal has a procedure or function for parsing
- => Recursive-Descent Parser
- **Problem 1: A left-recursive grammar can cause infinite loops**
  - when expanding a non-terminal, we may find itself and expand it again
- **Problem 2: Backtracking may be necessary**
  - when one derivation does not work, we may try others

# Eliminating Left-Recursion


- A grammar is left-recursive if it has a non-terminal  $A$  such that there is a derivation  $A \Rightarrow^+ A\alpha$

# Eliminating Left-Recursion

- A grammar is left-recursive if it has a non-terminal  $A$  such that there is a derivation  $A \Rightarrow^+ A\alpha$
- **Example:**  $A \rightarrow A\alpha \mid \beta$  is left-recursive

# Eliminating Left-Recursion


- A grammar is left-recursive if it has a non-terminal  $A$  such that there is a derivation  $A \Rightarrow^+ A\alpha$
- **Example:**  $A \rightarrow A\alpha \mid \beta$  is left-recursive, can be transformed into



$\beta\alpha^*$

# Eliminating Left-Recursion

- A grammar is left-recursive if it has a non-terminal  $A$  such that there is a derivation  $A \Rightarrow^+ A\alpha$
- **Example:**  $A \rightarrow A\alpha \mid \beta$  is left-recursive, can be transformed into



# Eliminating Left-Recursion

- A grammar is left-recursive if it has a non-terminal  $A$  such that there is a derivation  $A \Rightarrow^+ A\alpha$
- **Example:**  $A \rightarrow A\alpha \mid \beta$  is left-recursive, can be transformed into

$$\begin{array}{l} A \rightarrow \beta A' \\ A' \rightarrow \alpha A' \mid \epsilon \end{array}$$

$$A \rightarrow A\alpha_1 \mid A\alpha_2 \mid \cdots \mid A\alpha_m \mid \beta_1 \mid \beta_2 \mid \cdots \mid \beta_n$$

?????

# Eliminating Left-Recursion

- A grammar is left-recursive if it has a non-terminal  $A$  such that there is a derivation  $A \Rightarrow^+ A\alpha$
- **Example:**  $A \rightarrow A\alpha \mid \beta$  is left-recursive, can be transformed into


$$\begin{array}{l} A \rightarrow \beta A' \\ A' \rightarrow \alpha A' \mid \epsilon \end{array}$$

$$A \rightarrow A\alpha_1 \mid A\alpha_2 \mid \cdots \mid A\alpha_m \mid \beta_1 \mid \beta_2 \mid \cdots \mid \beta_n$$

$$\begin{array}{l} A \rightarrow \beta_1 A' \mid \beta_2 A' \mid \cdots \mid \beta_n A' \\ A' \rightarrow \alpha_1 A' \mid \alpha_2 A' \mid \cdots \mid \alpha_m A' \mid \epsilon \end{array}$$



# Building a Parser in Practice

- Each non-terminal has a procedure or function for parsing
- => Recursive-Descent Parser
-  **Problem 1:** A **left-recursive** grammar can cause **infinite loops**
  - when expanding a non-terminal, we may find itself and expand it again
- **Problem 2:** Backtracking may be necessary
  - when one derivation does not work, we may try others

# Predictive Parsing

- Predictive parsers are recursive descent parser **w/o backtracking**

# Predictive Parsing

- Predictive parsers are recursive descent parser **w/o backtracking**
- LL(1)
  - L: scanning input from left to right
  - L: leftmost derivation
  - 1: Using one input symbol of lookahead at each step

# Predictive Parsing

- Predictive parsers are recursive descent parser w/o backtracking
- LL(1)
  - L: scanning input from left to right
  - L: leftmost derivation
  - 1: Using one input symbol of lookahead at each step
- LL(1) grammar (Not ambiguous! Not left-recursive!)
  - **Rich enough** to cover most programming constructs

# Predictive Parsing

- Predictive Parsing

- LL(1)

- L:  $S \rightarrow E$

- L:  $E' \rightarrow TE' \mid \epsilon$

- 1:  $T \rightarrow FT' \mid \epsilon$

NON - TERMINAL	INPUT SYMBOL					
	id	+	*	(	)	\$
$E$	$E \rightarrow TE'$			$E \rightarrow TE'$		
$E'$		$E' \rightarrow +TE'$			$E' \rightarrow \epsilon$	$E' \rightarrow \epsilon$
$T$	$T \rightarrow FT'$			$T \rightarrow FT'$		
$T'$		$T' \rightarrow \epsilon$	$T' \rightarrow *FT'$		$T' \rightarrow \epsilon$	$T' \rightarrow \epsilon$
$F$	$F \rightarrow \text{id}$			$F \rightarrow (E)$		

- LL(1) grammar (Not ambiguous! Not left-recursive!)

- Rich enough to cover most programming constructs

# Predictive Parsing

• Predictive Parsing

• LL(1)

• L: S

• L: E

• 1: T

NON - TERMINAL	INPUT SYMBOL					
	id	+	*	(	)	\$
$E$	$E \rightarrow TE'$			$E \rightarrow TE'$		
$E'$		$E' \rightarrow +TE'$			$E' \rightarrow \epsilon$	$E' \rightarrow \epsilon$
$T$	$T \rightarrow FT'$			$T \rightarrow FT'$		
$T'$		$T' \rightarrow \epsilon$	$T' \rightarrow *FT'$		$T' \rightarrow \epsilon$	$T' \rightarrow \epsilon$
$F$	$F \rightarrow \text{id}$			$F \rightarrow (E)$		

backtracking

• LL(1) grammar (Not ambiguous! Not left-recursive!)

- **Rich enough** to cover most programming constructs
- To build the predictive table, let's define **FIRST( $\alpha$ )**; **FOLLOW( $\alpha$ )**

# First() and Follow()

- $\text{FIRST}(\alpha)$ :
  - A set of terminals that  $\alpha$  may start with

# First() and Follow()

- $\text{FIRST}(\alpha)$ :
  - A set of terminals that  $\alpha$  may start with
- $\text{FOLLOW}(\alpha)$ :
  - A set of terminals that can appear immediately to the right of  $\alpha$



# First()

- **Example:**  $S \rightarrow c A b; A \rightarrow a b \mid a$
- $\text{FIRST}(a) = \{a\}$
- $\text{FIRST}(b) = \{b\}$
- $\text{FIRST}(c) = \{c\}$

# First()

- **Example:**  $S \rightarrow c A b; A \rightarrow a b \mid a$
- $\text{FIRST}(a) = \{a\}$
- $\text{FIRST}(b) = \{b\}$
- $\text{FIRST}(c) = \{c\}$
- $\text{FIRST}(S) = \{c\}$
- $\text{FIRST}(A) = \{a\}$

# Follow()

- FOLLOW( $\alpha$ ):
  - A set of terminals that can appear immediately to the right of  $\alpha$
  - $\$ \in \text{FOLLOW}(S)$ , where  $\$$  is string's end marker,  $S$  the start non-terminal

# Follow()

- **Example:**  $S \rightarrow c A b; A \rightarrow a b \mid a$
- $\text{FOLLOW}(S) = \{\$ \}$
- $\text{FOLLOW}(A) = \{b\}$

# Follow()

- **Example:**  $S \rightarrow c A b; A \rightarrow a b \mid a$
- $\text{FOLLOW}(S) = \{\$ \}$
- $\text{FOLLOW}(A) = \{b\}$
- **Example:**  $S \rightarrow c A A; A \rightarrow a b \mid a$
- $\text{FOLLOW}(S) = \{\$ \}$

# Follow()

- **Example:**  $S \rightarrow c A b; A \rightarrow a b \mid a$
- $\text{FOLLOW}(S) = \{\$ \}$
- $\text{FOLLOW}(A) = \{b\}$
- **Example:**  $S \rightarrow c A A; A \rightarrow a b \mid a$
- $\text{FOLLOW}(S) = \{\$ \}$
- $\text{FOLLOW}(A) \supseteq \text{FIRST}(A) \setminus \{\epsilon\} = \{a\}$

# Follow()

- **Example:**  $S \rightarrow c A b; A \rightarrow a b \mid a$
- $\text{FOLLOW}(S) = \{\$ \}$
- $\text{FOLLOW}(A) = \{b\}$
- **Example:**  $S \rightarrow c A A; A \rightarrow a b \mid a$
- $\text{FOLLOW}(S) = \{\$ \}$
- $\text{FOLLOW}(A) \supseteq \text{FIRST}(A) \setminus \{\epsilon\} = \{a\}$
- $\text{FOLLOW}(A) \supseteq \text{FOLLOW}(S) = \{\$ \}$

# Predictive Parsing Table

- To build a parsing table  $M[A, a]$ , for each  $A \rightarrow \alpha$ 
  - $\forall a \in \text{FIRST}(\alpha): M[A, a] = A \rightarrow \alpha$
  - $\epsilon \in \text{FIRST}(\alpha) \Rightarrow \forall b \in \text{FOLLOW}(A): M[A, b] = A \rightarrow \alpha$

$E$	$\rightarrow$	$T E'$
$E'$	$\rightarrow$	$+ T E' \mid \epsilon$
$T$	$\rightarrow$	$F T'$
$T'$	$\rightarrow$	$* F T' \mid \epsilon$
$F$	$\rightarrow$	$( E ) \mid \text{id}$

NON - TERMINAL	INPUT SYMBOL					
	id	+	*	(	)	\$
$E$	$E \rightarrow T E'$			$E \rightarrow T E'$		
$E'$		$E' \rightarrow + T E'$			$E' \rightarrow \epsilon$	$E' \rightarrow \epsilon$
$T$	$T \rightarrow F T'$			$T \rightarrow F T'$		
$T'$		$T' \rightarrow \epsilon$	$T' \rightarrow * F T'$		$T' \rightarrow \epsilon$	$T' \rightarrow \epsilon$
$F$	$F \rightarrow \text{id}$			$F \rightarrow ( E )$		



# Predictive Parsing Table

- To build a parsing table  $M[A, a]$ , for each  $A \rightarrow \alpha$ 
  - $\forall a \in \text{FIRST}(\alpha): M[A, a] = A \rightarrow \alpha$
  - $\epsilon \in \text{FIRST}(\alpha) \Rightarrow \forall b \in \text{FOLLOW}(A): M[A, b] = A \rightarrow \alpha$

$E$	$\rightarrow$	$T E'$
$E'$	$\rightarrow$	$+ T E' \mid \epsilon$
$T$	$\rightarrow$	$F T'$
$T'$	$\rightarrow$	$* F T' \mid \epsilon$
$F$	$\rightarrow$	$( E ) \mid \text{id}$

NON - TERMINAL	INPUT SYMBOL					
	id	+	*	(	)	\$
$E$	$E \rightarrow T E'$			$E \rightarrow T E'$		
$E'$		$E' \rightarrow + T E'$			$E' \rightarrow \epsilon$	$E' \rightarrow \epsilon$
$T$	$T \rightarrow F T'$			$T \rightarrow F T'$		
$T'$		$T' \rightarrow \epsilon$	$T' \rightarrow * F T'$		$T' \rightarrow \epsilon$	$T' \rightarrow \epsilon$
$F$	$F \rightarrow \text{id}$			$F \rightarrow ( E )$		

# Predictive Parsing Table

- To build a parsing table  $M[A, a]$ , for each  $A \rightarrow \alpha$ 
  - $\forall a \in \text{FIRST}(\alpha): M[A, a] = A \rightarrow \alpha$
  - $\epsilon \in \text{FIRST}(\alpha) \Rightarrow \forall b \in \text{FOLLOW}(A): M[A, b] = A \rightarrow \alpha$

$E$	$\rightarrow$	$T E'$
$E'$	$\rightarrow$	$+ T E' \mid \epsilon$
$T$	$\rightarrow$	$F T'$
$T'$	$\rightarrow$	$* F T' \mid \epsilon$
$F$	$\rightarrow$	$( E ) \mid \text{id}$

NON - TERMINAL	INPUT SYMBOL					
	id	+	*	(	)	\$
$E$	$E \rightarrow T E'$			$E \rightarrow T E'$		
$E'$		$E' \rightarrow + T E'$			$E' \rightarrow \epsilon$	$E' \rightarrow \epsilon$
$T$	$T \rightarrow F T'$			$T \rightarrow F T'$		
$T'$		$T' \rightarrow \epsilon$	$T' \rightarrow * F T'$		$T' \rightarrow \epsilon$	$T' \rightarrow \epsilon$
$F$	$F \rightarrow \text{id}$			$F \rightarrow ( E )$		

# Predictive Parsing Table



- To build a parsing table  $M[A, a]$ , for each  $A \rightarrow \alpha$ 
  - $\forall a \in \text{FIRST}(\alpha): M[A, a] = A \rightarrow \alpha$
  - $\epsilon \in \text{FIRST}(\alpha) \Rightarrow \forall b \in \text{FOLLOW}(A): M[A, b] = A \rightarrow \alpha$

$E$	$\rightarrow$	$T E'$
$E'$	$\rightarrow$	$+ T E' \mid \epsilon$
$T$	$\rightarrow$	$F T'$
$T'$	$\rightarrow$	$* F T' \mid \epsilon$
$F$	$\rightarrow$	$( E ) \mid \text{id}$

NON - TERMINAL	INPUT SYMBOL					
	id	+	*	(	)	\$
$E$	$E \rightarrow T E'$			$E \rightarrow T E'$		
$E'$		$E' \rightarrow + T E'$			$E' \rightarrow \epsilon$	$E' \rightarrow \epsilon$
$T$	$T \rightarrow F T'$			$T \rightarrow F T'$		
$T'$		$T' \rightarrow \epsilon$	$T' \rightarrow * F T'$		$T' \rightarrow \epsilon$	$T' \rightarrow \epsilon$
$F$	$F \rightarrow \text{id}$			$F \rightarrow ( E )$		

- Choose the production rule as per the table; empty means error

# Building a Parser in Practice

- Each non-terminal has a procedure or function for parsing
- => Recursive-Descent Parser
-  **Problem 1: A left-recursive grammar can cause infinite loops**
  - when expanding a non-terminal, we may find itself and expand it again
-  **Problem 2: Backtracking may be necessary**
  - when one derivation does not work, we may try others

# **PART III: IR Generation**

# Three-Address Code

- `do i = i + 1; while (a[i + 2] < v);`

```
L:  t1 = i + 1
    i = t1
    t2 = i + 2
    t3 = a [ t2 ]
    if t3 < v goto L
```

Symbolic Labels

```
100:  t1 = i + 1
101:  i = t1
102:  t2 = i + 2
103:  t3 = a [ t2 ]
104:  if t3 < v goto 100
```

Numeric Labels

- Implementation methods: *quadruples*, *triples*, etc.

# Static Single-Assignment

- **Feature 1:** Every variable has only one definition
- **Feature 2:** Using  $\phi$  to merge definitions from multi paths
- $\Rightarrow$  Direct def-use chains

```
if ( flag ) x = -1; else x = 1;
y = x * a;
```



```
if ( flag ) x1 = -1; else x2 = 1;
x3 =  $\phi$  (x1, x2);
y = x3 * a
```

# Dominance Relations

- **A dom B**
  - if all paths from Entry to B goes through A
- **A post-dom B**
  - if all paths from B to Exit goes through A
- **Strict** (post-)dominance – A (post-)dom B but  $A \neq B$
- **Immediate** dominance – A strict-dom B, but there's no C, such that A strict-dom C, C strict-dom B




# Dominator Tree


- Almost linear time to build a dominator tree.

- Node: Block
- Edge: Immediate dom relation

- Why is it a tree?




Flow Graph



Dominator Tree

# Dominance Frontier

- $DF(B) = \{ \dots \}$  for the block B
  - The immediate successors of the blocks dominated by B
  - Not strictly dominated by B



# Dominance Frontier

- $DF(B) = \{ \dots \}$  for the block  $B$ 
  - The immediate successors of the blocks dominated by  $B$
  - Not strictly dominated by  $B$
- $DF(\mathbb{B}) = \{ \dots \}$  for a set of blocks  $\mathbb{B}$ 
  - $DF(\mathbb{B}) = \bigcup_{B \in \mathbb{B}} DF(B)$

# Iterated Dominance Frontier

- Iterated DF of a block set  $\mathbb{B}$ 
  - $DF_1 = DF(\mathbb{B}); \mathbb{B} = \mathbb{B} \cup DF_1$
  - $DF_2 = DF(\mathbb{B}); \mathbb{B} = \mathbb{B} \cup DF_2$
  - .....
  - until fixed point! (i.e.,  $DF_n = DF_{n-1}$ )

# THANKS!