

# PBKDF2: how not to do it<sup>1</sup>

Joseph Birr-Pixton  
@jpixton  
<http://jbp.io/>

---

<sup>1</sup>describe a crypto algorithm

# PBKDF2: quick intro

## Purpose

Slowly convert a password + salt into a symmetric key of some length

# PBKDF2: quick intro

## Purpose

Slowly convert a password + salt into a symmetric key of some length

## Origin

RSA labs, 1999. Described in PKCS#5 and then RFC2898

# PBKDF2: quick intro

## Usage

- ▶ Password verification (web sites, network services, etc.)
- ▶ Key derivation (disk encryption, key management, etc.)

# PBKDF2: quick intro

## Usage

- ▶ Password verification (web sites, network services, etc.)
- ▶ Key derivation (disk encryption, key management, etc.)

## Performance

Performance profile is *important* for defenders. Aim: to maximise attacker work for defender computation budget.

# PBKDF2: quick intro

## Usage

- ▶ Password verification (web sites, network services, etc.)
- ▶ Key derivation (disk encryption, key management, etc.)

## Performance

Performance profile is *important* for defenders. Aim: to maximise attacker work for defender computation budget.

## PBKDF2 can produce arbitrary length output

We're going to ignore this capability from here on in: only considering the first block of output.

## PBKDF2: how it was described

$$\text{PBKDF2}_{\text{PRF}}(\text{pw}, \text{salt}, i) := U_1 \oplus U_2 \oplus \cdots \oplus U_i$$

## PBKDF2: how it was described

$$\text{PBKDF2}_{\text{PRF}}(\text{pw}, \text{salt}, i) := U_1 \oplus U_2 \oplus \cdots \oplus U_i$$

where

$$U_1 := \text{PRF}(\text{pw}, \text{salt} \parallel 0_{32})$$

$$U_n := \text{PRF}(\text{pw}, U_{n-1})$$



## PBKDF2: how it was described

$$\text{PBKDF2}_{\text{PRF}}(\text{pw}, \text{salt}, i) := U_1 \oplus U_2 \oplus \cdots \oplus U_i$$

where

$$U_1 := \text{PRF}(\text{pw}, \text{salt} \parallel 0_{32})$$

$$U_n := \text{PRF}(\text{pw}, U_{n-1})$$

and typically

$$\text{PRF}(\text{pw}, x) := \text{HMAC-H}(\text{pw}, x)$$

$$H := \text{SHA-1, SHA-256 or SHA-512}$$

## Zoom, enhance

The function  $\text{PBKDF2}_{\text{HMAC-SHA-256}}$  is slow because it executes the SHA-256 compression function many times.

## Zoom, enhance

The function  $\text{PBKDF2}_{\text{HMAC-SHA-256}}$  is slow because it executes the SHA-256 compression function many times.

### How many times?

Assumption: password and salt much shorter than SHA-256's 64-byte block size.

$$\text{HMAC-H}(k, m) := H(k \oplus \text{opad} \parallel H(k \oplus \text{ipad} \parallel m))$$

## Zoom, enhance

The function  $\text{PBKDF2}_{\text{HMAC-SHA-256}}$  is slow because it executes the SHA-256 compression function many times.

### How many times?

Assumption: password and salt much shorter than SHA-256's 64-byte block size.

$$\text{HMAC-H}(k, m) := H(k \oplus \text{opad} \parallel H(k \oplus \text{ipad} \parallel m))$$

$$\text{block 1} : k \oplus \text{ipad}$$

# Zoom, enhance

The function  $\text{PBKDF2}_{\text{HMAC-SHA-256}}$  is slow because it executes the SHA-256 compression function many times.

## How many times?

Assumption: password and salt much shorter than SHA-256's 64-byte block size.

$$\text{HMAC-H}(k, m) := H(k \oplus \text{opad} \parallel H(k \oplus \text{ipad} \parallel m))$$

block 1 :  $k \oplus \text{ipad}$

block 2 :  $m$

## Zoom, enhance

The function  $\text{PBKDF2}_{\text{HMAC-SHA-256}}$  is slow because it executes the SHA-256 compression function many times.

### How many times?

Assumption: password and salt much shorter than SHA-256's 64-byte block size.

$$\text{HMAC-H}(k, m) := \text{H}(k \oplus \text{opad} \parallel \text{H}(k \oplus \text{ipad} \parallel m))$$

block 1 :  $k \oplus \text{ipad}$

block 2 :  $m$

block 3 :  $k \oplus \text{opad}$

## Zoom, enhance

The function  $\text{PBKDF2}_{\text{HMAC-SHA-256}}$  is slow because it executes the SHA-256 compression function many times.

### How many times?

Assumption: password and salt much shorter than SHA-256's 64-byte block size.

$$\text{HMAC-H}(k, m) := H(k \oplus \text{opad} \parallel H(k \oplus \text{ipad} \parallel m))$$

block 1 :  $k \oplus \text{ipad}$

block 2 :  $m$

block 3 :  $k \oplus \text{opad}$

block 4 : block 2 output

## Zoom, enhance

The function  $\text{PBKDF2}_{\text{HMAC-SHA-256}}$  is slow because it executes the SHA-256 compression function many times.

### How many times?

Assumption: password and salt much shorter than SHA-256's 64-byte block size.

$$\text{HMAC-H}(k, m) := H(k \oplus \text{opad} \parallel H(k \oplus \text{ipad} \parallel m))$$

block 1 :  $k \oplus \text{ipad}$

block 2 :  $m$

block 3 :  $k \oplus \text{opad}$

block 4 : block 2 output

Therefore, we need to compute 4i SHA-256 blocks.



# Nope!

This is actually badly wrong. Neither PKCS#5 nor RFC2898 mention this.

# Nope!

This is actually badly wrong. Neither PKCS#5 nor RFC2898 mention this.

$$U_1 \oplus U_2 \oplus \cdots \oplus U_i$$

# Nope!

This is actually badly wrong. Neither PKCS#5 nor RFC2898 mention this.

$$U_1 \oplus U_2 \oplus \cdots \oplus U_i$$

with

$$U_1 := \text{HMAC-H}(\text{pw}, \text{salt} \parallel 0_{32})$$

$$U_n := \text{HMAC-H}(\text{pw}, U_{n-1})$$

# Nope!

This is actually badly wrong. Neither PKCS#5 nor RFC2898 mention this.

$$U_1 \oplus U_2 \oplus \cdots \oplus U_i$$

with

$$U_1 := \text{HMAC-H}(\text{pw}, \text{salt} \parallel 0_{32})$$

$$U_n := \text{HMAC-H}(\text{pw}, U_{n-1})$$

(or equivalently)

$$U_1 := \text{H}(\text{pw} \oplus \text{opad} \parallel \text{H}(\text{pw} \oplus \text{ipad} \parallel \text{salt} \parallel 0_{32}))$$

$$U_n := \text{H}(\text{pw} \oplus \text{opad} \parallel \text{H}(\text{pw} \oplus \text{ipad} \parallel U_{n-1}))$$

# Nope!

This is actually badly wrong. Neither PKCS#5 nor RFC2898 mention this.

$$U_1 \oplus U_2 \oplus \cdots \oplus U_i$$

with

$$U_1 := \text{HMAC-H}(\text{pw}, \text{salt} \parallel 0_{32})$$

$$U_n := \text{HMAC-H}(\text{pw}, U_{n-1})$$

(or equivalently)

$$U_1 := \text{H}(\text{pw} \oplus \text{opad} \parallel \text{H}(\text{pw} \oplus \text{ipad} \parallel \text{salt} \parallel 0_{32}))$$

$$U_n := \text{H}(\text{pw} \oplus \text{opad} \parallel \text{H}(\text{pw} \oplus \text{ipad} \parallel U_{n-1}))$$

We can precompute these blocks!

# Nope!

This is actually badly wrong. Neither PKCS#5 nor RFC2898 mention this.

$$U_1 \oplus U_2 \oplus \cdots \oplus U_i$$

with

$$U_1 := \text{HMAC-H}(\text{pw}, \text{salt} \parallel 0_{32})$$

$$U_n := \text{HMAC-H}(\text{pw}, U_{n-1})$$

(or equivalently)

$$U_1 := \text{H}(\text{pw} \oplus \text{opad} \parallel \text{H}(\text{pw} \oplus \text{ipad} \parallel \text{salt} \parallel 0_{32}))$$

$$U_n := \text{H}(\text{pw} \oplus \text{opad} \parallel \text{H}(\text{pw} \oplus \text{ipad} \parallel U_{n-1}))$$

We can precompute these blocks!

## How many times?

Actually, we only need compute  $2 + 2i$  SHA-256 blocks.

# Our survey says...

## Good: compute $2 + 2i$ blocks

- ▶ OpenSSL (after Nov 2013)
- ▶ Python core ( $\geq 3.4$ )
- ▶ Django (CVE-2013-1443)
- ▶ SJCL
- ▶ BouncyCastle ( $\geq 1.49$ )

# Our survey says...

## Good: compute $2 + 2i$ blocks

- ▶ OpenSSL (after Nov 2013)
- ▶ Python core ( $\geq 3.4$ )
- ▶ Django (CVE-2013-1443)
- ▶ SJCL
- ▶ BouncyCastle ( $\geq 1.49$ )

## Bad: compute $4i$ blocks

- ▶ FreeBSD
- ▶ GRUB
- ▶ Android (BouncyCastle)



# Our survey says...

## Good: compute $2 + 2i$ blocks

- ▶ OpenSSL (after Nov 2013)
- ▶ Python core ( $\geq 3.4$ )
- ▶ Django (CVE-2013-1443)
- ▶ SJCL
- ▶ BouncyCastle ( $\geq 1.49$ )

## Bad: compute $4i$ blocks

- ▶ FreeBSD
- ▶ GRUB
- ▶ Android (BouncyCastle)

## Bad: compute $4i$ blocks

- ▶ Python (pypi pbkdf2)
- ▶ Ruby (pbkdf2 gem)
- ▶ Go (go.crypto)
- ▶ OpenBSD
- ▶ PolarSSL
- ▶ CyaSSL
- ▶ Java (OpenJDK)
- ▶ Common Lisp (ironclad)
- ▶ Perl (Crypt::PBKDF2)
- ▶ PHP
- ▶ C#

## Parting thoughts...

- ▶ PBKDF2 is not wonderfully designed.

## Parting thoughts...

- ▶ PBKDF2 is not wonderfully designed.
- ▶ Described in an unhelpful way by its authors.

## Parting thoughts...

- ▶ PBKDF2 is not wonderfully designed.
- ▶ Described in an unhelpful way by its authors.
- ▶ Most implementations gift a 2x advantage to attackers.

# Thank you!

Questions?

Twitter: @jpixton

Mail: jbp@jbp.io

Web: <http://jbp.io/>