

PBKDF2: performance matters

Joseph Birr-Pixton
@jpixton
<http://jbp.io/>



1. Quick intro to PBKDF2



1. Quick intro to PBKDF2
2. The standard is bad





1. Quick intro to PBKDF2
2. The standard is bad
3. Your implementation is bad





1. Quick intro to PBKDF2
2. The standard is bad
3. Your implementation is bad
4. A faster PBKDF2



PBKDF2: quick intro



Purpose

Slowly convert a password + salt into a symmetric key of some length

PBKDF2: quick intro



Purpose

Slowly convert a password + salt into a symmetric key of some length

Origin

RSA labs, 1999. Described in PKCS#5 and then RFC2898

PBKDF2: quick intro



Usage

- ▶ Password verification (web sites, network services, etc.)
- ▶ Key derivation (disk encryption, key management, etc.)

PBKDF2: quick intro



Usage

- ▶ Password verification (web sites, network services, etc.)
- ▶ Key derivation (disk encryption, key management, etc.)

Performance

Performance profile is *important* for defenders. Aim: to maximise attacker work for defender computation budget.

PBKDF2: quick intro



Usage

- ▶ Password verification (web sites, network services, etc.)
- ▶ Key derivation (disk encryption, key management, etc.)

Performance

Performance profile is *important* for defenders. Aim: to maximise attacker work for defender computation budget.

Simplification

PBKDF2 can produce arbitrary length output.

We're going to ignore this capability from here on in: only considering the first block of output.

PBKDF2: how it was described



$$\text{PBKDF2}_{\text{PRF}}(\text{pw}, \text{salt}, i) := U_1 \oplus U_2 \oplus \cdots \oplus U_i$$

PBKDF2: how it was described



$$\text{PBKDF2}_{\text{PRF}}(\text{pw}, \text{salt}, i) := U_1 \oplus U_2 \oplus \cdots \oplus U_i$$

where

$$U_1 := \text{PRF}(\text{pw}, \text{salt} \parallel 0_{32})$$

$$U_n := \text{PRF}(\text{pw}, U_{n-1})$$

PBKDF2: how it was described



$$\text{PBKDF2}_{\text{PRF}}(\text{pw}, \text{salt}, i) := U_1 \oplus U_2 \oplus \cdots \oplus U_i$$

where

$$U_1 := \text{PRF}(\text{pw}, \text{salt} \parallel 0_{32})$$

$$U_n := \text{PRF}(\text{pw}, U_{n-1})$$

and typically

$$\text{PRF}(\text{pw}, x) = \text{HMAC-H}(\text{pw}, x)$$

$H = \text{SHA-1, SHA-256, SHA-512, or ...}$

Zoom, enhance



The function $\text{PBKDF2}_{\text{HMAC-SHA-256}}$ is slow because it executes the SHA-256 compression function many times.

Zoom, enhance



The function $\text{PBKDF2}_{\text{HMAC-SHA-256}}$ is slow because it executes the SHA-256 compression function many times.

How many times?

Assumption: password and salt much shorter than SHA-256's 64-byte block size.

$$\text{HMAC-H}(key, msg) := H(key \oplus \text{opad} \parallel H(key \oplus \text{ipad} \parallel msg))$$

Zoom, enhance



The function $\text{PBKDF2}_{\text{HMAC-SHA-256}}$ is slow because it executes the SHA-256 compression function many times.

How many times?

Assumption: password and salt much shorter than SHA-256's 64-byte block size.

$$\begin{aligned} \text{HMAC-H}(key, msg) &:= H(key \oplus \text{opad} \parallel H(\text{key} \oplus \text{ipad} \parallel msg)) \\ \text{block 1} &: key \oplus \text{ipad} \end{aligned}$$

Zoom, enhance



The function $\text{PBKDF2}_{\text{HMAC-SHA-256}}$ is slow because it executes the SHA-256 compression function many times.

How many times?

Assumption: password and salt much shorter than SHA-256's 64-byte block size.

$$\text{HMAC-H}(key, msg) := H(key \oplus opad \parallel H(key \oplus ipad \parallel msg))$$

block 1 : $key \oplus ipad$

block 2 : msg

Zoom, enhance



The function $\text{PBKDF2}_{\text{HMAC-SHA-256}}$ is slow because it executes the SHA-256 compression function many times.

How many times?

Assumption: password and salt much shorter than SHA-256's 64-byte block size.

$$\text{HMAC-H}(key, msg) := H(\text{key} \oplus \text{opad} \parallel H(\text{key} \oplus \text{ipad} \parallel msg))$$

block 1 : $key \oplus \text{ipad}$

block 2 : msg

block 3 : $key \oplus \text{opad}$

Zoom, enhance



The function $\text{PBKDF2}_{\text{HMAC-SHA-256}}$ is slow because it executes the SHA-256 compression function many times.

How many times?

Assumption: password and salt much shorter than SHA-256's 64-byte block size.

$$\text{HMAC-H}(key, msg) := H(key \oplus \text{opad} \parallel H(key \oplus \text{ipad} \parallel msg))$$

block 1 : $key \oplus \text{ipad}$

block 2 : msg

block 3 : $key \oplus \text{opad}$

block 4 : block 2 output

Zoom, enhance



The function $\text{PBKDF2}_{\text{HMAC-SHA-256}}$ is slow because it executes the SHA-256 compression function many times.

How many times?

Assumption: password and salt much shorter than SHA-256's 64-byte block size.

$$\text{HMAC-H}(key, msg) := H(key \oplus \text{opad} \parallel H(key \oplus \text{ipad} \parallel msg))$$

block 1 : $key \oplus \text{ipad}$

block 2 : msg


block 3 : $key \oplus \text{opad}$

block 4 : block 2 output

Therefore, we need to compute $4i$ SHA-256 blocks.

Nope!

This is suboptimal. Neither of the standards mention this, or even describe the expected performance :(



Nope!

This is suboptimal. Neither of the standards mention this, or even describe the expected performance :(

$$U_1 \oplus U_2 \oplus \cdots \oplus U_i$$

Nope!

This is suboptimal. Neither of the standards mention this, or even describe the expected performance :(

$$U_1 \oplus U_2 \oplus \cdots \oplus U_i$$

with

$$U_1 := \text{HMAC-H}(\text{pw}, \text{salt} \parallel 0_{32})$$

$$U_n := \text{HMAC-H}(\text{pw}, U_{n-1})$$

Nope!

This is suboptimal. Neither of the standards mention this, or even describe the expected performance :(

$$U_1 \oplus U_2 \oplus \cdots \oplus U_i$$

with

$$U_1 := \text{HMAC-H}(\text{pw}, \text{salt} \parallel 0_{32})$$

$$U_n := \text{HMAC-H}(\text{pw}, U_{n-1})$$

(or equivalently)

$$U_1 := \text{H}(\text{pw} \oplus \text{opad} \parallel \text{H}(\text{pw} \oplus \text{ipad} \parallel \text{salt} \parallel 0_{32}))$$

$$U_n := \text{H}(\text{pw} \oplus \text{opad} \parallel \text{H}(\text{pw} \oplus \text{ipad} \parallel U_{n-1}))$$

Nope!

This is suboptimal. Neither of the standards mention this, or even describe the expected performance :(

$$U_1 \oplus U_2 \oplus \cdots \oplus U_i$$

with

$$U_1 := \text{HMAC-H}(\text{pw}, \text{salt} \parallel 0_{32})$$

$$U_n := \text{HMAC-H}(\text{pw}, U_{n-1})$$

(or equivalently)

$$U_1 := \text{H}(\text{pw} \oplus \text{opad} \parallel \text{H}(\text{pw} \oplus \text{ipad} \parallel \text{salt} \parallel 0_{32}))$$

$$U_n := \text{H}(\text{pw} \oplus \text{opad} \parallel \text{H}(\text{pw} \oplus \text{ipad} \parallel U_{n-1}))$$

We can compute these blocks once.

Nope!

This is suboptimal. Neither of the standards mention this, or even describe the expected performance :(

$$U_1 \oplus U_2 \oplus \dots \oplus U_i$$

with

$$U_1 := \text{HMAC-H}(\text{pw}, \text{salt} \parallel 0_{32})$$

$$U_n := \text{HMAC-H}(\text{pw}, U_{n-1})$$

(or equivalently)

$$U_1 := \text{H}(\text{pw} \oplus \text{opad} \parallel \text{H}(\text{pw} \oplus \text{ipad} \parallel \text{salt} \parallel 0_{32}))$$

$$U_n := \text{H}(\text{pw} \oplus \text{opad} \parallel \text{H}(\text{pw} \oplus \text{ipad} \parallel U_{n-1}))$$

We can compute these blocks once.

How many times?

Actually, we only need compute $2 + 2i$ SHA-256 blocks.

Survey of defender implementations

I looked at the following PBKDF2s:

- ▶ FreeBSD 10
- ▶ GRUB 2.0
- ▶ Truecrypt 7.1a
- ▶ Android (disk encryption)
- ▶ Android (BouncyCastle)
- ▶ Django
- ▶ OpenSSL
- ▶ Python core (≥ 3.4)
- ▶ Python (pypi pbkdf2)
- ▶ Ruby (pbkdf2 gem)
- ▶ Go (go.crypto)
- ▶ OpenBSD
- ▶ PolarSSL/mbedTLS
- ▶ CyaSSL/wolfSSL
- ▶ SJCL
- ▶ Java
- ▶ Common Lisp (ironclad)
- ▶ Perl (Crypt::PBKDF2)
- ▶ PHP5
- ▶ .NET framework
- ▶ scrypt/yescrypt¹
- ▶ BouncyCastle

¹never called for scrypt/yescrypt with iterations != 1

Our survey says...

Good: compute $2 + 2i$ blocks

- ▶ SJCL

Our survey says...

Good: compute $2 + 2i$ blocks

- ▶ SJCL
- ▶ OpenSSL (after Nov 2013)
- ▶ Python core (≥ 3.4)
- ▶ Django (CVE-2013-1443, sc00bz)
- ▶ BouncyCastle (≥ 1.49)

Our survey says...

Good: compute $2 + 2i$ blocks

- ▶ SJCL
- ▶ OpenSSL (after Nov 2013)
- ▶ Python core (≥ 3.4)
- ▶ Django (CVE-2013-1443, sc00bz)
- ▶ BouncyCastle (≥ 1.49)

Slow: compute $4i$ blocks

- ▶ FreeBSD 10
- ▶ GRUB 2.0
- ▶ Android (BouncyCastle)

Our survey says...

Good: compute $2 + 2i$ blocks

- ▶ SJCL
- ▶ OpenSSL (after Nov 2013)
- ▶ Python core (≥ 3.4)
- ▶ Django (CVE-2013-1443, sc00bz)
- ▶ BouncyCastle (≥ 1.49)

Slow: compute $4i$ blocks

- ▶ FreeBSD 10
- ▶ GRUB 2.0
- ▶ Android (BouncyCastle)

Slow: compute $4i$ blocks

- ▶ Python (pypi pbkdf2)
- ▶ Ruby (pbkdf2 gem)
- ▶ Go (go.crypto)
- ▶ OpenBSD
- ▶ PolarSSL/mbedTLS
- ▶ CyaSSL/wolfSSL
- ▶ Java (OpenJDK)
- ▶ Common Lisp (ironclad)
- ▶ Perl (Crypt::PBKDF2)
- ▶ PHP
- ▶ .NET framework
- ▶ ...

Selected performance measurements

- ▶ Question: how much practical difference does this make?

Selected performance measurements

- ▶ Question: how much practical difference does this make?
- ▶ Let's measure PBKDF2-HMAC-SHA1 for large iteration count (2^{22})

Selected performance measurements




Figure : PBKDF2-HMAC-SHA1, one block output, 2^{22} iterations

Selected performance measurements




Figure : PBKDF2-HMAC-SHA1, one block output, 2^{22} iterations

Selected performance measurements




Figure : PBKDF2-HMAC-SHA1, one block output, 2^{22} iterations

Selected performance measurements




Figure : PBKDF2-HMAC-SHA1, one block output, 2^{22} iterations

Selected performance measurements




Figure : PBKDF2-HMAC-SHA1, one block output, 2^{22} iterations

Selected performance measurements




Figure : PBKDF2-HMAC-SHA1, one block output, 2^{22} iterations

fastpbkdf2

A faster PBKDF2-HMAC- $\{\text{SHA-1}, \text{SHA-256}, \text{SHA-512}\}$ for defenders.

- ▶ About 400 lines of C99.

fastpbkdf2

A faster PBKDF2-HMAC- $\{\text{SHA-1}, \text{SHA-256}, \text{SHA-512}\}$ for defenders.

- ▶ About 400 lines of C99.
- ▶ Uses OpenSSL libcrypto's hash functions.

fastpbkdf2

A faster PBKDF2-HMAC- $\{\text{SHA-1}, \text{SHA-256}, \text{SHA-512}\}$ for defenders.

- ▶ About 400 lines of C99.
- ▶ Uses OpenSSL libcrypto's hash functions.
- ▶ CC0.

fastpbkdf2

A faster PBKDF2-HMAC- $\{\text{SHA-1}, \text{SHA-256}, \text{SHA-512}\}$ for defenders.

- ▶ About 400 lines of C99.
- ▶ Uses OpenSSL libcrypto's hash functions.
- ▶ CC0.
- ▶ <https://github.com/ctz/fastpbkdf2/>

Parting thoughts...

- ▶ PBKDF2 is a poor design, and described in an unhelpful way by its authors.

Parting thoughts...

- ▶ PBKDF2 is a poor design, and described in an unhelpful way by its authors.
- ▶ Most implementations waste time and power.

Parting thoughts...

- ▶ PBKDF2 is a poor design, and described in an unhelpful way by its authors.
- ▶ Most implementations waste time and power.
- ▶ If you use PBKDF2, you can probably drop in a faster implementation.

Parting thoughts...

- ▶ PBKDF2 is a poor design, and described in an unhelpful way by its authors.
- ▶ Most implementations waste time and power.
- ▶ If you use PBKDF2, you can probably drop in a faster implementation and either increase security margin, or improve time/power performance.
- ▶ Please try not to use PBKDF2 any more.

Thank you!

Questions?

Twitter: @jpixton

Mail: jbp@jbp.io

Web: <https://jbp.io/>

Slides and benchmarking code: <https://github.com/ctz/talks/>