

## PBKDF2: performance matters

Joseph Burr-Pixton

@jpixton

<http://jbp.io/>



1. Quick intro to PBKDF2





1. Quick intro to PBKDF2
2. The standard is bad





1. Quick intro to PBKDF2
2. The standard is bad
3. Your implementation is bad






1. Quick intro to PBKDF2
2. The standard is bad
3. Your implementation is bad
4. A faster PBKDF2



# Intro: Merkle-Damgård hash functions




Basic construction of most hash functions: MD5, SHA-1, SHA-2.



# Intro: Merkle-Damgård hash functions




Basic construction of most hash functions: MD5, SHA-1, SHA-2.



# Intro: HMAC




Making secure symmetric signatures out of MD hash functions.





# Intro: HMAC innards




$$\text{HMAC-H}(key, message) := H(key \oplus opad \parallel H(key \oplus ipad \parallel message))$$
  
(for messages shorter than a block!)

# Intro: PBKDF2




Slowly derive a key from a password and salt.



## Intro: PBKDF2



Slowly derive a key from a password and salt.




- ▶ Parameterised with a PRF, usually HMAC.

# Intro: PBKDF2



Slowly derive a key from a password and salt.




- ▶ Parameterised with a PRF, usually HMAC.
- ▶ Tunable computation cost, with iteration count.

## Intro: PBKDF2



Slowly derive a key from a password and salt.



- ▶ Parameterised with a PRF, usually HMAC.
- ▶ Tunable computation cost, with iteration count.
- ▶ Origin: RSA labs, 1999. Described in PKCS#5 and then RFC2898.

# Intro: PBKDF2



## Iteration count choice

1. Choose computation budget (say, 50ms).
2. Find iteration count which takes that long with your implementation.

# Intro: PBKDF2



## Iteration count choice

1. Choose computation budget (say, 50ms).
2. Find iteration count which takes that long with your implementation.

## Performance

Performance profile is *important* for defenders. Aim: to maximise attacker work for defender computation budget.

# Intro: PBKDF2



## Iteration count choice

1. Choose computation budget (say, 50ms).
2. Find iteration count which takes that long with your implementation.

## Performance

Performance profile is *important* for defenders. Aim: to maximise attacker work for defender computation budget.


## Simplification

PBKDF2 can produce arbitrary length output.

We're going to ignore this capability: assume it produces the same length output as the underlying hash.



## Intro: PBKDF2<sub>HMAC</sub> with 3 iterations



$$\text{PBKDF2}_{\text{HMAC}}(\text{password}, \text{salt}, i) := U_1 \oplus U_2 \oplus \dots \oplus U_i$$

where


$$U_1 := \text{HMAC}(\text{password}, \text{salt})$$

$$U_n := \text{HMAC}(\text{password}, U_{n-1})$$

## PBKDF2: perf vs. iteration count




One HMAC per iteration.




How many compression function applications?

## PBKDF2: perf vs. iteration count




## PBKDF2: perf vs. iteration count



Conclusion:  $4i$  compression function applications for  $i$  iterations.


## Nope!


This is suboptimal. Neither of the standards mention this, or even describe the expected performance :(




## Nope!

This is suboptimal. Neither of the standards mention this, or even describe the expected performance :(







Actually  $2 + 2i$  compression function applications for  $i$  iterations.



# Survey of defender implementations

I looked at the following PBKDF2s:

- ▶ FreeBSD 10
- ▶ GRUB 2.0
- ▶ Truecrypt 7.1a
- ▶ Android (disk encryption)
- ▶ Android (BouncyCastle)
- ▶ Django
- ▶ OpenSSL
- ▶ Python core ( $\geq 3.4$ )
- ▶ Python (pypi pbkdf2)
- ▶ Ruby (pbkdf2 gem)
- ▶ Go (go.crypto)
- ▶ OpenBSD
- ▶ PolarSSL/mbedTLS
- ▶ CyaSSL/wolfSSL
- ▶ SJCL
- ▶ Java
- ▶ Common Lisp (ironclad)
- ▶ Perl (Crypt::PBKDF2)
- ▶ PHP5
- ▶ .NET framework
- ▶ scrypt/yescrypt<sup>1</sup>
- ▶ BouncyCastle

---

<sup>1</sup>never called for scrypt/yescrypt with iterations  $\neq 1$

## Our survey says...

**Good: compute  $2 + 2i$  blocks**

- ▶ SJCL

## Our survey says...

### Good: compute $2 + 2i$ blocks

- ▶ SJCL
- ▶ OpenSSL (after Nov 2013)
- ▶ Python core ( $\geq 3.4$ )
- ▶ Django (CVE-2013-1443, sc00bz)
- ▶ BouncyCastle ( $\geq 1.49$ )

## Our survey says...

### Good: compute $2 + 2i$ blocks

- ▶ SJCL
- ▶ OpenSSL (after Nov 2013)
- ▶ Python core ( $\geq 3.4$ )
- ▶ Django (CVE-2013-1443, sc00bz)
- ▶ BouncyCastle ( $\geq 1.49$ )

### Slow: compute $4i$ blocks

- ▶ FreeBSD 10
- ▶ OpenBSD
- ▶ GRUB 2.0

# Our survey says...

## Good: compute $2 + 2i$ blocks

- ▶ SJCL
- ▶ OpenSSL (after Nov 2013)
- ▶ Python core ( $\geq 3.4$ )
- ▶ Django (CVE-2013-1443, sc00bz)
- ▶ BouncyCastle ( $\geq 1.49$ )

## Slow: compute $4i$ blocks

- ▶ FreeBSD 10
- ▶ OpenBSD
- ▶ GRUB 2.0

## Slow: compute $4i$ blocks

- ▶ Python (pypi pbkdf2)
- ▶ Ruby (pbkdf2 gem)
- ▶ Go (go.crypto)
- ▶ PolarSSL/mbedTLS
- ▶ CyaSSL/wolfSSL
- ▶ Java (OpenJDK)
- ▶ Common Lisp (ironclad)
- ▶ Perl (Crypt::PBKDF2)
- ▶ PHP
- ▶ .NET framework
- ▶ ...

## Selected performance measurements

- ▶ Question: how much practical difference does this make?

## Selected performance measurements

- ▶ Question: how much practical difference does this make?
- ▶ Let's measure PBKDF2-HMAC-SHA1 for large iteration count ( $2^{22}$ )


## Selected performance measurements

- ▶ Question: how much practical difference does this make?
- ▶ Let's measure PBKDF2-HMAC-SHA1 for large iteration count ( $2^{22}$ )

Measured on Intel Atom N2800 (1.86GHz), best of five runs, CPU time in user mode.




## Selected performance measurements




PBKDF2-HMAC-SHA1, one block output,  $2^{22}$  iterations

## Selected performance measurements




## Selected performance measurements




PBKDF2-HMAC-SHA1, one block output,  $2^{22}$  iterations

## Selected performance measurements




PBKDF2-HMAC-SHA1, one block output,  $2^{22}$  iterations

## Selected performance measurements



PBKDF2-HMAC-SHA1, one block output,  $2^{22}$  iterations

## Selected performance measurements



PBKDF2-HMAC-SHA1, one block output,  $2^{22}$  iterations

## fastpbkdf2

A faster PBKDF2-HMAC- $\{\text{SHA-1}, \text{SHA-256}, \text{SHA-512}\}$  for defenders.

- ▶ About 400 lines of C99.

## fastpbkdf2

A faster PBKDF2-HMAC- $\{\text{SHA-1}, \text{SHA-256}, \text{SHA-512}\}$  for defenders.

- ▶ About 400 lines of C99.
- ▶ Uses OpenSSL libcrypto's hash functions.



## fastpbkdf2

A faster PBKDF2-HMAC- $\{\text{SHA-1}, \text{SHA-256}, \text{SHA-512}\}$  for defenders.


- ▶ About 400 lines of C99.
- ▶ Uses OpenSSL libcrypto's hash functions.
- ▶ CC0.

# fastpbkdf2

A faster PBKDF2-HMAC- $\{\text{SHA-1}, \text{SHA-256}, \text{SHA-512}\}$  for defenders.

- ▶ About 400 lines of C99.
- ▶ Uses OpenSSL libcrypto's hash functions.
- ▶ CC0.
- ▶ <https://github.com/ctz/fastpbkdf2/>

# fastpbkdf2



OpenSSL



fastpbkdf2

## Parting thoughts...

- ▶ PBKDF2 is a poor design, and described in an unhelpful way by its authors.

## Parting thoughts...

- ▶ PBKDF2 is a poor design, and described in an unhelpful way by its authors.
- ▶ Most implementations waste time and power.

## Parting thoughts...

- ▶ PBKDF2 is a poor design, and described in an unhelpful way by its authors.
- ▶ Most implementations waste time and power.
- ▶ If you use PBKDF2, you can probably drop in a faster implementation (and either increase security margin, or improve time/power performance.)

# Thank you!

Questions?

Twitter: @jpixton

Mail: jbp@jbp.io

Web: <https://jbp.io/>

Slides and benchmarking code: <https://github.com/ctz/talks/>

fastpbkdf2 code: <https://github.com/ctz/fastpbkdf2/>