

L02 — Algorithm Complexity: Time and Space; Time-Space Tradeoff

Unit: 1 | Chapter: Fundamentals of Data Structures & Arrays | BT Level: BT4 | CO: CO1

Learning Objectives

- Explain what algorithm complexity means and why it matters
- Differentiate between A Priori (theoretical) and A Posteriori (experimental) algorithm analysis
- Differentiate between time complexity and space complexity
- Analyze simple algorithms for their time and space usage
- Understand and apply the time-space tradeoff concept

1. What is Algorithm Complexity?


Algorithm complexity measures the resources (time and memory) an algorithm consumes relative to the size of its input, denoted n .

We study complexity because:

- Hardware is finite — we cannot run an $O(2^n)$ algorithm on $n = 100$
- Scalability matters — an algorithm working for $n = 1000$ may be unusable for $n = 10^6$
- Complexity helps us compare algorithms **independent of hardware**

2. Approaches to Algorithm Analysis: A Priori vs. A Posteriori

Algorithm analysis can be performed at two different stages: before coding (theoretical) or after implementation (experimental).



2.1 Comparison Summary

Feature	A Posteriori Analysis (Experimental / Relative)	A Priori Analysis (Theoretical / Absolute)
Definition	Analysis done after implementing and running the algorithm.	Analysis done before coding, using mathematical reasoning.
Method	Measures actual resources (time, space) used on specific hardware.	Measures how resource usage grows relative to input size (n).
Also Called	Experimental or Relative Analysis.	Theoretical, Independent, or Absolute Analysis.
Pros	• Realistic data for specific setup. • Accurate for that specific instance.	• Independent of hardware, OS, or programming language. • Allows direct comparison before writing code.
Cons	• Dependent on specific compiler, OS, and machine (CPU speed). • Can only be done after coding. • Inconsistent across different systems.	• Only provides an approximation (Big O notation). • Hard to account for constant factors.
Example	Running "Sorting 10,000 numbers on Laptop X."	Analyzing nested loops to estimate $O(n^2)$ time complexity.

In Short:

- Use **A Priori Analysis** for overall efficiency comparison.
 - Use **A Posteriori Analysis** for tuning and performance on specific devices.
-

3. Time Complexity

Time complexity counts the number of basic operations (comparisons, assignments, arithmetic) an algorithm performs as a function of input size n.

3.1 Types of Analysis

Type	Definition	Example
Best Case	Minimum operations (most favorable input)	Linear search: element is at index 0 → $O(1)$
Worst Case	Maximum operations (least favorable input)	Linear search: element not found → $O(n)$
Average Case	Expected operations over all inputs	Linear search: element at middle → $O(n/2) = O(n)$

In practice, we focus on **worst-case analysis** — it gives an upper bound guarantee.

3.2 Counting Operations Example

```
# Find maximum in an array
```

```
def find_max(arr):
    max_val = arr[0]          # 1 operation
    for i in range(1, n):     # n-1 iterations
        if arr[i] > max_val:  # 1 comparison per iteration
            max_val = arr[i]  # at most 1 assignment
    return max_val            # 1 operation
```

Total operations $\approx 1 + 3(n-1) + 1 = 3n - 1 \rightarrow O(n)$

4. Space Complexity

Space complexity measures the amount of memory an algorithm uses relative to input size n .

It includes:

- **Input space:** Memory for storing the input
- **Auxiliary space:** Extra memory used by the algorithm (variables, stack frames, temporary arrays)

Usually we care about **auxiliary space** (extra space beyond input).

4.1 Space Complexity Examples

$O(1)$ auxiliary space – only a few variables

```
def sum_array(arr, n):
    total = 0
    for x in arr:
        total += x
    return total
```

$O(n)$ auxiliary space – stores a copy of input

```
def reverse_array(arr, n):
    result = [0] * n          #  $O(n)$  space
    for i in range(n):
        result[n-1-i] = arr[i]
    return result
```

5. Common Complexity Classes

Notation	Name	Example
$O(1)$	Constant	Array access by index
$O(\log n)$	Logarithmic	Binary search
$O(n)$	Linear	Linear search
$O(n \log n)$	Linearithmic	Merge sort, heap sort
$O(n^2)$	Quadratic	Bubble sort, insertion sort
$O(n^3)$	Cubic	Naive matrix multiplication
$O(2^n)$	Exponential	Subset enumeration

$O(n!)$ Factorial Brute-force TSP

Growth Rate Comparison (for $n = 1000$):

Complexity	Operations
$O(1)$	1
$O(\log n)$	~ 10
$O(n)$	1,000
$O(n \log n)$	$\sim 10,000$
$O(n^2)$	1,000,000
$O(2^n)$	$\sim 10^{301}$ (impossible)

6. Time-Space Tradeoff

A **time-space tradeoff** is a situation where using more memory allows an algorithm to run faster, or using less memory forces it to run slower.

Core idea: You can often trade space for time or time for space depending on your system's constraints.

6.1 Examples of Time-Space Tradeoff

Example 1: Lookup Table (Memoization)

```
# Without memoization -  $O(2^n)$  time,  $O(n)$  space (call stack)
def fib_slow(n):
    if n <= 1: return n
    return fib_slow(n-1) + fib_slow(n-2)

# With memoization -  $O(n)$  time,  $O(n)$  space
memo = {}
def fib_fast(n):
    if n in memo: return memo[n]
    if n <= 1: return n
    memo[n] = fib_fast(n-1) + fib_fast(n-2)
    return memo[n]
```

By storing previously computed results (extra $O(n)$ space), we reduce time from $O(2^n)$ to $O(n)$.

Example 2: Precomputed Prefix Sums

```
# Without prefix sums:  $O(n)$  per query
def range_sum_slow(arr, l, r):
    return sum(arr[l:r+1]) #  $O(r-l+1)$  per query

# With prefix sums:  $O(n)$  precomputation,  $O(1)$  per query
def precompute(arr, n):
    prefix = [0] * (n+1)
```

```

for i in range(n):
    prefix[i+1] = prefix[i] + arr[i]
return prefix

def range_sum_fast(prefix, l, r):
    return prefix[r+1] - prefix[l]    # O(1)

```

Example 3: Hash Table vs Binary Search

Approach	Space	Search Time
Binary Search on sorted array	$O(1)$ extra	$O(\log n)$
Hash Table	$O(n)$	$O(1)$ average

7. Factors Affecting Time Complexity

1. **Algorithm design** — the dominant factor
2. **Data structures used** — linked list vs array vs hash table
3. **Input size and characteristics** — sorted vs unsorted, dense vs sparse
4. **Platform** — interpreted vs compiled language (constant factor, not asymptotic)

8. Practical Guidelines

- Prefer $O(n \log n)$ over $O(n^2)$ for $n > 10^4$
- If space is unlimited: use memoization/caching to speed up repetitive computation
- If memory is limited: accept slower algorithms or streaming approaches
- Profile before optimizing — find the real bottleneck

Summary

- **A Priori vs. A Posteriori analysis:** A Priori provides hardware-independent mathematical bounds before coding; A Posteriori measures actual runtime and memory on specific hardware after execution.
- **Time complexity** measures operations as a function of n ; analyzed in best, worst, and average cases.
- **Space complexity** measures memory usage (focus on auxiliary space).
- Common classes: $O(1) < O(\log n) < O(n) < O(n \log n) < O(n^2) < O(2^n)$.
- **Time-space tradeoff:** Trading extra memory for faster execution (memoization, lookup tables, prefix sums).

References

- Cormen et al., *Introduction to Algorithms*, Ch. 3 (MIT Press, 2022)
- Skiena, *The Algorithm Design Manual*, Ch. 2 (Springer, 2020)
- Laaksonen, *Guide to Competitive Programming*, Ch. 2 (Springer, 2024)