

# Day 1 – Environment & Project Setup

---

## Setup & Prerequisites

---

### 1. Setup Checklist:

- **Install Python 3.12+:** Ensure Python 3.12 or higher is installed on your local machine. You can check your version by running `python3 --version` or `python --version` in your terminal.
- **Prepare Your Workspace:** Create an empty project directory on your computer and open a clean terminal window pointing to this folder.
- **Web Browser Ready:** Have a modern web browser open and ready to navigate to the local server address: `http://127.0.0.1:8000/`.

### 2. Prerequisites:

- You must have a working terminal environment suitable for your operating system:
  - **macOS/Linux:** Standard Terminal or Zsh.
  - **Windows:** Git Bash or PowerShell (avoid using command prompt `cmd` as some unix-like commands will not be supported).

## Learning Objectives

---

By the end of this class, you will be able to:

- Install and configure modern Python package management using `uv`.
- Initialize and activate a virtual environment.
- Scaffold a new Django project and custom app.
- Securely configure environment variables using `python-decouple`.
- Initialize a Git repository and prevent secrets leaks using `.gitignore`.
- Run the Django development server and verify the default setup.

## Classroom Timeline (45 min)

---

| Segment               | Duration | Focus                                                                                |
|-----------------------|----------|--------------------------------------------------------------------------------------|
| 1. Hook & Big Picture | 7 min    | Interactive overview of the bootcamp outcome (game key expiry & publisher webhooks). |

---

|                                          |        |                                                                                         |
|------------------------------------------|--------|-----------------------------------------------------------------------------------------|
| <b>2. Key Concepts &amp; Core Ideas</b>  | 7 min  | Introduction to MTV, API backends, package management (uv), and configuration security. |
| <b>3. Live Coding Walkthrough</b>        | 23 min | Live setup of python environment, Django, and decoupling configuration.                 |
| <b>4. Check for Understanding</b>        | 5 min  | Q&A on virtual environments, secrets management, and DEBUG mode.                        |
| <b>5. Class Wrap-up &amp; Checkpoint</b> | 3 min  | Verification of students' local environments.                                           |



## Lecture Step-by-Step Delivery Plan

### 1. Hook & Big Picture (7 min)

The business problem: digital game key marketplaces need to deliver keys to users, track their expirations, and automatically notify publishers when a key expires so they can deactivate it on their servers.

- **Big Picture:** The finished flow: User buys key → key expires → Celery fires webhook → publisher receives it.
- **Q&A:**
  - **Question:** Why do we need webhooks instead of polling?
    - **Answer:** Polling is inefficient because clients have to repeatedly query the database (creating high traffic and latency). Webhooks are event-driven: our system pushes notifications only when an event happens, reducing server load and ensuring near-instant updates.
  - **Question:** Why is this a production-grade problem?
    - **Answer:** It involves cross-system communication, payload security (signing), concurrency (race conditions), reliability (retries, queues), and audit logging.

### 2. Key Concepts & Core Ideas (7 min)

Introduce the following definitions to you:

- **What is Django?** MTV (Model-Template-View) framework. Mention that we'll use it purely as a REST API backend with no HTML templates.
- **What is DRF?** Django REST Framework. A toolkit built on top of Django that gives us serializers, viewsets, and routers for building RESTful APIs.
- **Virtual environments:** Why isolation matters (preventing dependency conflicts and ensuring reproducibility across developers' machines).
  - *Note - Why do we isolate?* Without virtual environments, installing packages globally can overwrite

dependencies needed by other projects on the same machine, causing conflicts and breaking applications.

- **DEBUG=True vs False:** Django displays highly detailed error pages containing traceback information. Explain that this is crucial for development but a critical security leak in production.
  - *Note - Why is it a leak?* It exposes database queries, settings, system file paths, configurations, and environment variables to the end user.
- **Why python-decouple?** Reading from `os.environ.get()` is functional but `decouple` simplifies casting types (e.g. converting a string `"True"` to boolean `True`) and handling defaults and local `.env` files in a clean API.

### 3. Live Coding Walkthrough (23 min)

#### Step 3.1: Tooling Installation & Scaffolding

- **Concept:** Contrast standard `pip + venv` with `uv`. We use `uv` for speed, lockfiles, and reproducibility. `uv` is an extremely fast Python package installer and resolver written in Rust. It serves as a drop-in replacement for `pip`, `pip-tools`, and `virtualenv`. Run the installation and scaffolding commands.
- **Code:**

```
# Install uv (macOS/Linux)
# This command downloads the uv binary installation script and executes it via the shell.
curl -LsSf https://astral.sh/uv/install.sh | sh

# Create and activate virtual environment
# uv venv creates a local virtual environment named '.venv' in the current working directory
uv venv

# Activate the environment so your terminal uses the virtual environment's Python interpreter
source .venv/bin/activate

# Add dependencies
# uv add automatically adds packages to your environment and manages a project lockfile.
# Packages installed:
# - django: The core web framework.
# - djangorestframework: Toolkit for building RESTful APIs on top of Django.
# - python-decouple: Utility for separating settings configuration from source code.
# - celery: Task runner for asynchronous and background execution.
# - redis: Python client for connecting to the Redis database (used as Celery's broker).
# - pytest-django: Django integration helper for testing with pytest.
uv add django djangorestframework python-decouple celery redis pytest-django

# Scaffold project and app
# django-admin startproject creates a folder structure containing core settings.
# The '.' at the end is CRITICAL: it creates the project in the CURRENT directory, preventing
django-admin startproject gamekey_platform .

# startapp creates a custom Django application named 'games' containing models, views, and con
```

```
python manage.py startapp games
```

- **Verify:** Confirm that you see `(.venv)` in your command line prompt. Ensure you are inside the active virtual environment before moving on. Run `which python` (or `where python` in Windows PowerShell) to verify it points to the `.venv` directory.
- **⚠ Common Pitfalls I will flag:**
  - **Forgetting to activate the venv:** If you skip `source .venv/bin/activate`, you will install dependencies globally or get "django not found". Run `which python` to verify the path points to `.venv`.
  - **Windows path differences:** Note that on Windows, the activation command is `.venv\Scripts\activate` rather than `source .venv/bin/activate`.

### Step 3.2: Environment Variable Configuration

- **Concept:** Secrets (such as the Django `SECRET_KEY` or database passwords) should never go into version control (source code). If you push a secret key to a public GitHub repository, bots will scan it within seconds and exploit it. We extract these values into a local environment file called `.env`.
- **Code:** Create `.env` in the project root directory:

```
SECRET_KEY=your-secret-key-here
DEBUG=True
```

- **Verify:** Check that the `.env` file is created and contains the correct key-value pairs.

### Step 3.3: Django settings.py Decoupling

- **Concept:** Now we need to modify Django's settings to read our newly created `.env` file rather than having hardcoded variables. `python-decouple` provides a helper function `config()` that searches for the variable in the `.env` file first, and falls back to system environment variables if not found.
- **Code:** Update `gamekey_platform/settings.py` to import and use `python-decouple`:

```
# Add this import at the top of the file
from decouple import config

# Replace the hardcoded SECRET_KEY line with this:
SECRET_KEY = config('SECRET_KEY')

# Replace the hardcoded DEBUG line with this:
# The default is set to False for safety, and cast=bool converts the environment string "True"
DEBUG = config('DEBUG', default=False, cast=bool)
```

- **Verify:** Run the development server to verify the configuration is loaded correctly:

```
# Verify setup
python manage.py runserver
```

Navigate to

and verify the Django welcome page loads.

*environments isolate dependencies per project, allowing each to run its required version independently.*

**Question:** "What does `DEBUG=True` change about how Django behaves?"

**Answer:** When `DEBUG=True`, Django displays detailed error traceback pages to the client (useful for debugging but a huge security leak in production because it exposes database queries, settings, and path variables). It also runs the built-in development server's auto-reloader and serves static/media files automatically. In production (`DEBUG=False`), it returns a generic 500 error page, requires `ALLOWED_HOSTS` to be set, and disables automated static file serving.

---

## 5. Daily Checkpoint & Wrap-up (3 min)

- **Verification Criteria:**

- ☐ You can access the Django welcome rocket page running locally at `http://127.0.0.1:8000/`.
- ☐ The `.env` file exists and contains `SECRET_KEY` and `DEBUG`.
- ☐ Running `git status` shows `.env` is untracked (not staged) and excluded.
- ☐ Running `git log --oneline` shows at least one commit.