Suyash Singh Tomar
Section-B

Full stack
60
Cu24250178

DOMS. Page No.
Date / /

Q1

A
D
C
B

A, D will run first because they are synchronous then C and B.

Q2

Addition: 9
subtraction: -1
] Output

```
function add (a,b) {
return a+b;
}
function subtract (a,b) {
return a-b;
}
module.exports = {
add, subtract
};

const calc = require('./calc');
console.log("Addition:", calc.add(4,5));
console.log("Substraction:", calc.substract(4,5));
```

Q3

```
const express = require('express');
const app = express();
app.use(express.json());
function requireAuth(req, res, next){
const apiKey = req.headers['x-api-key']
if (apiKey !== 'secreat123'){
 return res.status(401).json({
 error : Unauthorized'
});
next();
}

app.get('/api/books', (req, res) => {
 res.json({ message : 'Public Get route'});
});
app.post('/api/books', requireAuth, (req, res) =>
{ res.status(201).json({
        message : Book created;
        book: req.body
    });
});
    app.listen(5000, () => {
    console.log('Server running on port 5000');
});
```

DOMS. Page No.
Date / /

(5) i) req.params.id is a string, while book.id may be a number.

ii) if the book doesn't exist, book is undefined, so book.title causes an error

Correct code:

```
app.get('/api/books/:id', (req, res) => {
const id = parseInt(req.params.id);
const book = books.find(b => b.id === id);
if (!book) {
return res.status(404).json({
error: 'Book not found'
});
}

res.json(book);
});
```

DOMS. Page No.
Date / /

(7) Post man is not restricted by the browser's same origin policy and the React run inside the browser.

```
Const express = require ('express');
const cors = require ('cors');
const app = express ();
app.use (cors ({
  origin : 'http://local host : 3000'
})));
app use ( express.json ());
app.get ('/api/books; (req, res) => {
res.json ([
{ id: 1, title ' JavaScript '},
{ id: 2, title ' Node.js '}
]);
});

app.listen( 5000, () => {
console.log ('Server running on a port 5000 ');
});
```