

Odometry Data

Grup 11-H:

Estudiants:

- Pol Casacuberta Gil

- Marta Granero I Martí

Table of Contents

Load Data.....	1
Visualizing L&R info.....	1
Visualize increment displacement.....	2
Visualize increment velocity.....	3
Odometry.....	4
Pose integration.....	4
Adding noise.....	6
Odometry displacement and orientation visualization with noise.....	7

Load Data


```
clear
clf
load('Encoder_Data.mat')
```

Visualizing L&R info

Use time values


```
plot(R_acu(:,1),R_acu(:,2))
hold on
plot(L_acu(:,1),L_acu(:,2))

title('Wheels displacement')
ylabel('Displacement')
xlabel('Time')
legend('Right Wheel', 'Left Wheel');
L_inc = diff(L_acu(:,2));
R_inc = diff(R_acu(:,2));
hold off
```



Visualize increment displacement


```
plot(R_acu(2:3004,2),R_inc(:))  
hold on  
plot(L_acu(2:3004,2), L_inc(:))  
  
title('Wheels displacement increment')  
ylabel('displacement increment [m]')  
xlabel('Time [s]')  
legend('Right Wheel', 'Left Wheel');  
hold off
```



Visualize increment velocity

```
plot(R_acu(2:3004,2),R_inc(:)/Ts)
hold on
plot(L_acu(2:3004,2), L_inc(:)/Ts)

title('Wheels velocity')
ylabel('Velocity [m/s]')
xlabel('Time [s]')
legend('Right Wheel', 'Left Wheel');
hold off
```



```
clf % delete previous plots so we can hold on later and they don't all show up
```

Odometry

Compute δ_x and δ_ψ

```
delta_x= (R_inc+L_inc)/2;
delta_psi= (R_inc-L_inc)/(W);
```

Pose integration

Compare your results

Next pose; $\xi_{k+1} = \xi_k \tan sl_x(\delta_d) Rot_Z(\delta_\theta)$

Initial_pose = 4x4

0	1.0000	0	8.6500
-1.0000	0	0	17.2000
0	0	1.0000	0
0	0	0	1.0000

or using

$$\xi_{k+1} = \begin{pmatrix} p_{k+1} \\ \theta_{k+1} \end{pmatrix} = \begin{pmatrix} x_k + \delta_d c \theta_k \\ y_k + \delta_d s \theta_k \\ \theta_k + \delta_\theta \end{pmatrix}$$

```
Initial_pose = transl(8.65,17.2,0)*trotz(-pi/2)
```

```
Initial_pose = 4x4
    0    1.0000    0    8.6500
   -1.0000    0    0    17.2000
    0    0    1.0000    0
    0    0    0    1.0000
```

```
time = R_acu(:,1);
Initial_position=transl(Initial_pose);
% Preallocate for speed
x = zeros(1,length(time)-1);
y = zeros(1,length(time)-1);
o = zeros(1,length(time)-1);

x(1)=Initial_position(1);
y(1)= Initial_position(2);
o(1)= -pi/2;


for i = 1:length(time)-1
    x(i+1) = x(i) + delta_x(i)*cos(o(i));
    y(i+1) = y(i) + delta_x(i)*sin(o(i));
    o(i+1) = mod(o(i) + delta_psi(i),pi*2);
end
```

```
plot(x,y)
```

```

title('Trajectory')
ylabel('X [m]')
xlabel('Y [m]')
legend('Robot Trajectory');
hold on

```



Adding noise

Add noise to odometry

See the effect on the trajectory

```

% Add gaussian noise
noise_std = 0.002; % adjust as needed
delta_x_noisy = delta_x + noise_std * randn(size(delta_x));
delta_psi_noisy = delta_psi + noise_std * randn(size(delta_psi));

x_noisy = zeros(1,length(time)-1);
y_noisy = zeros(1,length(time)-1);
o_noisy = zeros(1,length(time)-1);

x_noisy(1) = Initial_position(1);
y_noisy(1) = Initial_position(2);
o_noisy(1) = -pi/2;

for i = 1:length(time)-1

```


```

x_noisy(i+1) = x_noisy(i) + delta_x_noisy(i)*cos(o_noisy(i));
y_noisy(i+1) = y_noisy(i) + delta_x_noisy(i)*sin(o_noisy(i));
o_noisy(i+1) = mod(o_noisy(i) + delta_psi_noisy(i),pi*2);
end

plot(x_noisy,y_noisy)

title('Trajectory')
ylabel('X [m]')
xlabel('Y [m]')
legend({'Ideal Trajectory', 'Noisy Trajectory'});

```




Odometry displacement and orientation visualization with noise

```

figure
hold on
grid on

plot(time(2:end),delta_x_noisy,'r')
title('Odometry displacement with noise')
xlabel('t [s]')
ylabel('\delta_d [m]')
plot(time(2:end),delta_x,'b')

```



```
figure
hold on
grid on

plot(time(2:end),delta_psi_noisy,'r')
title('Odometry change of orientation with noise')
xlabel('t [s]')
ylabel('\delta_o [m]')
plot(time(2:end),delta_psi,'b')
```