

This course material is now made available for public usage.
Special acknowledgement to School of Computing, National University of Singapore
for allowing Steven to prepare and distribute these teaching materials.



CS3233

Competitive Programming

Dr. Steven Halim

Week 04 – Problem Solving Paradigms
(Dynamic Programming 1)

Outline

- Mini Contest 3 + Break + Discussion
- Admins
- Dynamic Programming – Introduction
 - Treat this as **revision** for ex CS2010/CS2020 students
 - **Listen carefully** for other group of students!
- Dynamic Programming
 - Some Classical Examples
- PS: I will use the term **DP** in this lecture
 - OOT: DP is NOT [Down Payment](#)!

Wedding Shopping

EXAMPLE 1

Motivation

- How to solve UVa [11450](#) (Wedding Shopping)?
 - Given $1 \leq \mathbf{C} \leq 20$ classes of garments
 - e.g. shirt, belt, shoe
 - Given $1 \leq \mathbf{K} \leq 20$ different models for each class of garment
 - e.g. three shirts, two belts, four shoes, ..., each with its own price
 - Task: Buy **just one** model of **each class** of garment
 - Our budget $1 \leq \mathbf{M} \leq 200$ is limited
 - We cannot spend more money than it
 - But we want to spend the maximum possible
 - What is our maximum possible spending?
 - Output “no solution” if this is impossible

- Budget $M = 100$

– Answer: 75

Model Garment	0	1	2	3
0	8	6	4	
1	5	10		
2	1	3	3	7
$C = 3$	50	14	23	8

- Budget $M = 20$

– Answer: 19

- Alternative answers are possible

Model Garment	0	1	2	3
0	4	6	8	
1	5	10		
$C = 2$	1	3	5	5

- Budget $M = 5$

– Answer: no solution

Model Garment	0	1	2	3
0	6	4	8	
1	10	6		
$C = 2$	7	3	1	7


Greedy Solution?

- What if we buy the most expensive model for each garment which still fits our budget?
- Counter example:
 - $M = 12$
 - Greedy will produce:
 - no solution
 - **Wrong answer!**
 - The correct answer is 12
 - (see the **green dotted highlights**)
 - Q: Can you spot one more potential optimal solution?

Model Garment	0	1	2	3
0	6	4	8	
1	5	10		
C = 2	1	5	3	5

Divide and Conquer?

- Any idea?



Complete Search? (1)

- What is the potential state of the problem?
 - g (which garment?)
 - id (which model?)
 - money (money left?)
- Answer:
 - (money, g) or (g, money)
- Recurrence:

```
shop(money, g)
  if (money < 0) return -INF
  if (g == C - 1) return M - money
  return max(shop(money - price[g][model], g + 1),  $\forall \text{model} \in [1..K]$ )
```



Complete Search? (2)

- But, how to solve this?
 - $M = 1000$
- Time Complexity: 20^{20}
 - Too many for 3s time limit ☹️

Model Garment	0	1	...	19
0	32	12		55
1	2	53		4
2	1	3		7
3	50	14		8
4	3	1		5
5	4	3		1
6	5	2		5
...				
19	22	11		99

Overlapping Sub Problem Issue

- In simple 20^{20} Complete Search solution, we observe **many overlapping sub problems!**
 - Many ways to reach state (money, g), e.g. see below, $M = 12$



Model Garment	0	1	2
0	6	4	
1	4	6	
C = 2	1	2	3

DP to the Rescue (1)

- DP = Dynamic Programming
 - Programming here is not writing computer code, but a “**tabular method**”!
 - a.k.a. **table** method
 - A programming paradigm that you must know!
 - And hopefully, master...

DP to the Rescue (2)

- Use DP when the problem exhibits:
 - Optimal sub structure
 - Optimal solution to the original problem contains optimal solution to sub problems
 - This is similar as the requirement of Greedy algorithm
 - If you can formulate complete search recurrences, you have this
 - Overlapping sub problems
 - Number of **distinct sub problems** are actually “small”
 - But they are **repeatedly computed**
 - This is different from Divide and Conquer

DP Solution – Implementation (1)

- There are two ways to implement DP:
 - Top-Down
 - Bottom-Up
- Top-Down (Demo):
 - Recursion as per normal + **memoization table**
 - It is just a simple change from backtracking (complete search) solution!

Turn Recursion into Memoization

initialize memo table in main function (use 'memset')

```
return_value recursion(params/state) {  
    if this state is already calculated,  
        simply return the result from the memo table  
    calculate the result using recursion(other_params/states)  
    save the result of this state in the memo table  
    return the result  
}
```

Dynamic Programming (Top-Down)

- For our example:

```
shop(money, g)
  if (money < 0) return -INF
  if (g == C - 1) return M - money
  if (memo[money][g] != -1) return memo[money][g];
  return memo[money][g] = max(shop(money - price[g][model], g + 1),
     $\forall \text{model} \in [1..K]$ )
```

- As simple as that 😊

DP Solution – Implementation (2)

- Another way: Bottom-Up:
 - Prepare a table that has size equals to the number of distinct states of the problem
 - Start to fill in the table with base case values
 - Get **the topological order** in which the table is filled
 - Some topological orders are natural and can be written with just (nested) loops!
 - Different way of thinking compared to Top-Down DP
- Notice that both DP variants use “table”!

Dynamic Programming (Bottom-Up)

- For our example:
 - Start with with table **can_reach** of size 201 (money) * 20 (g)
 - Initialize all entries to 0 (false)
 - Fill in the first column with money left (row) reachable after buying models from the first garment
 - Use the information of current column c to update the values at column $c + 1$

	0	1	2		0	1	2		0	1	2
0	0	0	0		0	0	0		0	0	0
1	0	0	0		1	0	0		1	0	1
2	0	0	0		2	0	1		2	0	1
3	0	0	0		3	0	0		3	0	1
4	0	0	0		4	0	1		4	0	1
5	0	0	0		5	0	0		5	0	1
6	0	0	0		6	0	1		6	0	1
7	0	0	0		7	0	1		7	0	1
8	0	0	0		8	0	0		8	0	1
9	0	0	0		9	0	1		9	0	1
10	0	0	0		10	0	0		10	0	1
11	0	0	0		11	0	1		11	0	1
12	1	0	0		12	1	0		12	1	0
13	0	0	0		13	0	0		13	0	0
14	1	0	0		14	1	0		14	1	0
15	0	0	0		15	0	0		15	0	0
16	1	0	0		16	1	0		16	1	0
17	0	0	0		17	0	0		17	0	0
18	0	0	0		18	0	0		18	0	0
19	0	0	0		19	0	0		19	0	0
20	0	0	0		20	0	0		20	0	0

Top-Down or Bottom-Up?

- Top-Down

- Pro:

- Natural transformation from normal recursion
 - Only compute sub problems when necessary

- Cons:

- Slower if there are many sub problems due to recursive call overhead
 - Use exactly $O(\text{states})$ table size (MLE?)

- Bottom Up

- Pro:

- Faster if many sub problems are visited: no recursive calls!
 - Can save memory space^

- Cons:

- Maybe not intuitive for those inclined to recursions?
 - If there are X states, bottom up visits/fills the value of all these X states

Flight Planner (study this on your own)

EXAMPLE 2

Motivation




- How to solve this: [10337](#) (Flight Planner)?
 - Unit: 1 mile altitude and 1 (x100) miles distance
 - Given wind speed map
 - Fuel cost: {**climb** (+60), **hold** (+30), **sink** (+20)} - wind speed $wsp[alt][dis]$
 - Compute **min** fuel cost from (0, 0) to (0, X = 4)!

1	1	1	1		9
1	1	1	1		8
1	1	1	1		7
1	1	1	1		6
1	1	1	1		5
1	1	1	1		4
1	1	1	1		3
1	1	1	1		2
1	9	9	1		1
1	-9	-9	1		0
=====					
0	1	2	3	4	(x100)

Complete Search? (1)

- First guess:
 - Do complete search/brute force/**backtracking**
 - Find *all possible* flight paths and pick the one that yield the minimum fuel cost



Complete Search? (2)

- Recurrence of the Complete Search

- `fuel(alt, dis) =`
 `min3(60 - wsp[alt][dis] + fuel(alt + 1, dis + 1),`
 `30 - wsp[alt][dis] + fuel(alt, dis + 1),`
 `20 - wsp[alt][dis] + fuel(alt - 1, dis + 1))`

- Stop when we reach final state (base case):

- $\text{alt} = 0$ and $\text{dis} = X$, i.e. $\text{fuel}(0, X) = 0$

- Prune infeasible states (also base cases):

- $\text{alt} < 0$ or $\text{alt} > 9$ or $\text{dis} > X!$, i.e. return INF*

- Answer of the problem is **fuel(0, 0)**

Complete Search Solutions (1)

- Solution 1

1	1	1	1		9
1	1	1	1		8
1	1	1	1		7
1	1	1	1		6
1	1	1	1		5
1	1	1	1		4
1	1	1	1		3
1	1	1	1		2
1	9	9	1		1
1	-9	-9	1		0
=====					
0	1	2	3	4	(x100)

$$29 + 39 + 39 + 29 = \mathbf{136}$$

- Solution 2

1	1	1	1		9
1	1	1	1		8
1	1	1	1		7
1	1	1	1		6
1	1	1	1		5
1	1	1	1		4
1	1	1	1		3
1	1	1	1		2
1	9	9	1		1
1	-9	-9	1		0
=====					
0	1	2	3	4	(x100)

$$29 + 39 + 69 + 19 = \mathbf{156}$$

Complete Search Solutions (2)

- Solution 3

1	1	1	1		9
1	1	1	1		8
1	1	1	1		7
1	1	1	1		6
1	1	1	1		5
1	1	1	1		4
1	1	1	1		3
1	1	1	1		2
1	9	9	1		1
1	-9	-9	1		0
=====					
0	1	2	3	4	(x100)

$$29 + 69 + 11 + 29 = \mathbf{138}$$

- Solution 4

1	1	1	1		9
1	1	1	1		8
1	1	1	1		7
1	1	1	1		6
1	1	1	1		5
1	1	1	1		4
1	1	1	1		3
1	1	1	1		2
1	9	9	1		1
1	-9	-9	1		0
=====					
0	1	2	3	4	(x100)

$$59 + 11 + 39 + 29 = \mathbf{138}$$

Complete Search Solutions (3)

- Solution 5

1	1	1	1		9
1	1	1	1		8
1	1	1	1		7
1	1	1	1		6
1	1	1	1		5
1	1	1	1		4
1	1	1	1		3
1	1	1	1		2
1	9	9	1		1
1	-9	-9	1		0
=====					
0	1	2	3	4	(x100)

$$29 + 69 + 21 + 19 = \mathbf{138}$$

- Solution 6

1	1	1	1		9
1	1	1	1		8
1	1	1	1		7
1	1	1	1		6
1	1	1	1		5
1	1	1	1		4
1	1	1	1		3
1	1	1	1		2
1	9	9	1		1
1	-9	-9	1		0
=====					
0	1	2	3	4	(x100)

$$59 + 21 + 11 + 29 = \mathbf{120(OPT)}$$

Complete Search Solutions (4)

- Solution 7

1	1	1	1		9
1	1	1	1		8
1	1	1	1		7
1	1	1	1		6
1	1	1	1		5
1	1	1	1		4
1	1	1	1		3
1	1	1	1		2
1	9	9	1		1
1	-9	-9	1		0
=====					
0	1	2	3	4	(x100)

59+ 21+ 21+ 19=**120 (OPT)**

- Solution 8

1	1	1	1		9
1	1	1	1		8
1	1	1	1		7
1	1	1	1		6
1	1	1	1		5
1	1	1	1		4
1	1	1	1		3
1	1	1	1		2
1	9	9	1		1
1	-9	-9	1		0
=====					
0	1	2	3	4	(x100)


59+ 51+ 19+ 19=**148**

Complete Search? (3)

- How large is the search space?
 - Max distance is 100,000 miles
Each distance step is 100 miles
That means we have **1,000** distance columns!
 - Note: this is an example of “coordinate compression”
 - Branching factor per step is 3... (climb, hold, sink)
 - That means complete search can end up performing $3^{1,000}$ operations...
 - Too many for 3s time limit 😞

Overlapping Sub Problem Issue

- In simple $3^{1,000}$ Complete Search solution, we observe **many overlapping sub problems!**
 - Many ways to reach coordinate (alt, dis)



DP Solution

- Recurrence* of the Complete Search

- `fuel(alt, dis) =`
 `min3(60 - wsp[alt][dis] + fuel(alt + 1, dis + 1),`
 `30 - wsp[alt][dis] + fuel(alt, dis + 1),`
 `20 - wsp[alt][dis] + fuel(alt - 1, dis + 1))`

- Sub-problem `fuel(alt, dis)` can be **overlapping!**


- There are only 10 alt and 1,000 dis = **10,000** states
 - A lot of time saved if these are not re-computed!
 - Exponential $3^{1,000}$ to polynomial $10 \cdot 1,000$!

alt > 2 not shown

2	-1	-1	-1	∞	∞
1	-1	-1	40	19	∞
0	-1	-1	-1	29	0
	0	1	2	3	4

DP Solution (Top Down)

- Create a 2-D table of size $10 * (X/100)$ ← Save Space!
 - Set “-1” for unexplored sub problems (memset)
 - Store the computation value of sub problem
 - **Simply reuse when it is needed again!**



DP Solution (Bottom Up)

```
fuel(alt, dis) =
    min3(20 - wsp[alt + 1][dis - 1] + fuel(alt + 1, dis - 1),
         30 - wsp[alt      ][dis - 1] + fuel(alt      , dis - 1),
         60 - wsp[alt - 1][dis - 1] + fuel(alt - 1, dis - 1))
```

1	1	1	1		9
1	1	1	1		8
1	1	1	1		7
1	1	1	1		6
1	1	1	1		5
1	1	1	1		4
1	1	1	1		3
1	1	1	1		2
1	9	9	1		1
1	-9	-9	1		0
=====					
0	1	2	3	4	(x100)

Tips:
(space-saving trick)

We can reduce one storage dimension by only keeping 2 recent columns at a time...

But the time complexity is unchanged:
 $O(10 * X / 100)$

2	∞	∞			
1	∞	59			
0	0	29			
	0	1	2	3	4

2	∞	∞	110		
1	∞	59	80		
0	0	29	68		
	0	1	2	3	4

2	∞	∞	110	131	
1	∞	59	80	101	
0	0	29	68	91	
	0	1	2	3	4

2	∞	∞	110	131	-
1	∞	59	80	101	-
0	0	29	68	91	120
	0	1	2	3	4

If Optimal Solution(s) are Needed

- Although not often, sometimes this is asked!
- As we build the DP table, record which option is taken in each cell!
 - Usually, this information is stored in different table
 - Then, do recursive scan(s) to output solution
 - Sometimes, there are more than one solutions!


2	∞	∞	110	131	-
1	∞	59	80	101	-
0	0	29	68	91	120
	0	1	2	3	4

Shortest Path Problem? (1)

- Hey, I have alternative solution:
 - Model the problem as a **DAG**
 - Vertex is each position in the unit map
 - Edges connect vertices reachable from vertex (alt, dis) , i.e. $(alt+1, dis+1)$, $(alt, dis+1)$, $(alt-1, dis)$
 - Weighted according to flight action and wind speed!
 - Do not connect infeasible vertices
 - $alt < 0$ or $alt > 9$ or $dis > X$

Visualization of the DAG

1	1	1	1		9
1	1	1	1		8
1	1	1	1		7
1	1	1	1		6
1	1	1	1		5
1	1	1	1		4
1	1	1	1		3
1	1	1	1		2
1	9	9	1		1
1	-9	-9	1		0
=====					
0	1	2	3	4	(x100)



Source

What is the
shortest path
from source
to destination?

Shortest Path Problem? (2)

- The problem: find the **shortest path** from vertex $(0, 0)$ to vertex $(0, X)$ on this DAG...
- $O(V + E)$ solution exists!
 - V is just $10 * (X / 100)$
 - E is just $3V$
 - Thus this solution is as good as the DP solution

Break

- In the next part, we will strengthen our DP concepts by looking at **more** examples...
 - For this lecture: Classical Ones First
 - Longest Increasing Subsequence (LIS)
 - Max Sum (1-D and 2-D)
 - 0-1 Knapsack / Subset Sum
 - Coin Change (General Case)
 - Traveling Salesman Problem (TSP)

Let's discuss several problems that are solvable using DP
First, let's see some classical ones...

LEARNING VIA EXAMPLES

Longest Increasing Subsequence (1)



- Problem Description (Abbreviated as LIS):
 - As implied by its name....
Given a sequence $\{X[0], X[1], \dots, X[N-1]\}$,
determine the Longest Increasing Subsequence
 - Subsequence is not necessarily contiguous
 - Example: $N = 8$, sequence = $\{-7, 10, 9, 2, 3, 8, 8, 1\}$
 - LIS is $\{-7, 2, 3, 8\}$ of length 4
 - Variants:
 - Longest Decreasing Subsequence
 - Longest Non Decreasing[^] Subsequence


Longest Increasing Subsequence (2)

- Let $LIS(i)$ be the LIS ending in index i
- Complete Search Recurrence:
 - $LIS(0) = 1$ // base case
 - $LIS(i) = \text{longestLIS}$
 - ```
int longestLIS = 1;
for (int j = 0; j < i; j++)
 if (X[i] > X[j])
 longestLIS = max(longestLIS, 1 + LIS(j))
```
  - The answer is  $\max(LIS(k))$ , for  $k \in [0..N-1]$

# Longest Increasing Subsequence (3)

- Many overlapping sub problems, but there are only  $N$  states, LIS ending at index  $i$ , for all  $i \in [0..N-1]$

| Index  | 0  | 1  | 2 | 3 | 4 | 5 | 6 | 7 |
|--------|----|----|---|---|---|---|---|---|
| X      | -7 | 10 | 9 | 2 | 3 | 8 | 8 | 1 |
| LIS(i) | 1  | 2  | 2 | 2 | 3 | 4 | 4 | 2 |



- This is  $O(n^2)$  algorithm
  - Solutions can be reconstructed: follow the arrows



# Max Sum (1D)

- Given array  $X = \{10, -1, 6, 3, 2, -2, -6, 7, 1\}$  of length  $n$ 
  - Find a **contiguous** sequence with **maximum sum**
    - The answer is  $\{6, 3, 2\}$  with max sum  $6 + 3 + 2 = 11$
  - Naïve solution in  $O(N^3)$ 
    - Try all starting and ending indices  $i$  &  $j$ ,  $O(N^2)$
    - Sum the values between index  $i$  and  $j$ ,  $O(N)$
    - Report the best starting and ending indices
  - DP solution in  $O(N^2)$ 
    - Try all starting and ending indices  $i$  &  $j$ ,  $O(N^2)$
    - **Get the range sum between index  $i$  and  $j$  in  $O(1)$** 
      - Use Fenwick Tree idea (Week02) =  $RSQ(i, j) = RSQ(0, j) - RSQ(0, i - 1)$
    - Report the best starting and ending indices
  - Q: Do you know the Greedy solution (Kadane's algorithm) in  $O(N)$ ?



# Max Sum (2D)

- What if we are given 2D matrix instead?
  - Use similar technique as in 1D matrix
  - But this time we divide the matrix into 4 sub regions
    - See the diagrams below for explanation

**A**

|    |    |    |    |
|----|----|----|----|
| 0  | -2 | -7 | 0  |
| 9  | 2  | -6 | 2  |
| -4 | 1  | -4 | 1  |
| -1 | 8  | 0  | -2 |

**B**


|   |    |     |    |
|---|----|-----|----|
| 0 | -2 | -9  | -9 |
| 9 | 9  | -4  | 2  |
| 5 | 6  | -11 | -8 |
| 4 | 13 | -4  | -3 |

**C**

|   |    |     |    |
|---|----|-----|----|
| 0 | -2 | -9  | -9 |
| 9 | 9  | -4  | 2  |
| 5 | 6  | -11 | -8 |
| 4 | 13 | -4  | -3 |

# 0-1 Knapsack / Subset Sum

- Standard state:
  - $\text{value}(\text{id}, w)$
- Standard transition:
  - Take item 'id' (only if  $W[\text{id}] \leq w$ )
    - Go to state:  $V[\text{id}] + \text{value}(\text{id} + 1, w - W[\text{id}])$
  - Ignore item 'id'
    - Go to state:  $\text{value}(\text{id} + 1, w)$
  - Stop when
    - $\text{id} = N$  (all items taken care of)
    - $w = 0$  (cannot carry anything else)



# Coin Change (1)



- Problem Description:
  - Given an amount **V** cents and a list of **N** coins:
    - We have `coinValue[i]` for coin type  $i \in [0..N-1]$
  - What is the **minimum** *number of coins* that we must use to obtain amount **V**?
  - Assume that we have **unlimited** supply of coins of any type!
  - UVa: [166](#)

# Coin Change (2)

- Example:
  - $V = 10$ ,  $N = 2$ ,  $\text{coinValue} = \{1, 5\}$
  - We can use:
    - **Ten** 1 cent coins =  $10 * 1 = 10$ 
      - Total coins used = 10
    - **One** 5 cents coin + **Five** 1 cent coins =  $1 * 5 + 5 * 1 = 10$ 
      - Total coins used = 6
    - **Two** 5 cents coins =  $2 * 5 = 10$ 
      - Total coins used = 2  $\rightarrow$  Optimal
  - Is Greedy Algorithm Possible?^

# Coin Change (3)

- Complete Search Recurrence:
  - `coin(0) = 0` // 0 coin to produce 0 cent
  - `coin(<0) = INFINITY` (infeasible solution)
  - `coin(value) = 1 + min(coin(value - coinValue[i]))` for all  $i \in [0..N-1]$
- How many possible states of parameter value?
  - Only  $O(V)$  and  $V$  is usually small

| <0       | 0 | 1 | 2 | 3 | 4 | 5 | 6 | 7 | 8 | 9 | 10 | $V = 10, N = 2,$<br>$\text{coinValue} = \{1, 5\}$ |
|----------|---|---|---|---|---|---|---|---|---|---|----|---------------------------------------------------|
| $\infty$ | 0 | 1 | 2 | 3 | 4 | 1 | 2 | 3 | 4 | 5 | 2  |                                                   |

Both bottom up and top down DP happen to produce the same table...

# Traveling Salesman Problem (TSP)

- Standard state:
  - $dp(pos, bitmask)$
- Standard transition:
  - If every cities have been visited
    - $tsp(pos, 2^N - 1) = dist[pos][0]$
  - Else, try visiting unvisited cities one by one
    - $tsp(pos, bitmask) = \min(dist[pos][nxt] + tsp(nxt, bitmask | (1 \ll nxt)))$   
for all possible  $nxt$  in  $[0..N-1]$ ,  $nxt \neq pos$ ,  
and  $bitmask \& (1 \ll nxt)$  is off



# Summary

- We have seen:
  - Basic DP concepts
  - DP on some **classical** problems
- We will see more DP in Week06:
  - DP and its relationship with DAG
  - DP on **non classical** problems
  - Plus some other “cool” DP techniques