

```

import gurobipy as gp
from gurobipy import GRB
import re

def readinfiles(mpsfilename, constrfilename):
    """
    This function takes the mps file to extract the information about the problem
    and uses the file containing information about hard constraints to slice the
    constraints
    :param mpsfilename: the name of the mps file
    :param constrfilename: the file about the hard constraints
    :return: A1, b1: the hard constraints and rhs values
            A2, b2: the soft constraints and rhs values
            objcoeff: the coefficient for variables from the objective function
            lpr.objVal: objective value from Linear relaxed program
            -1*mipexact.ObjVal: objective value by solving exactly
            directopt: objective value by solving the mps file exactly
    """
    m = gp.read(mpsfilename)
    m.Params.LogToConsole = 0
    m.optimize()
    directopt = m.objVal

    # convert the constraint information from mps file into matrix type
    num_rows = m.numconstrs
    num_col = m.numvars
    coeffmatrix = [None] * num_rows

    for k in range(num_rows):
        constrslist = [None] * num_col
        for i in range(num_col):
            constrslist[i] = m.getCoeff(m.getConstrs()[k], m.getVars()[i])
        coeffmatrix[k] = constrslist

    rhside = m.rhs # right hand side values of the constraints
    objcoeff = m.obj # coefficient in the objective function

    # print(objcoeff)
    # print(coeffmatrix[0])
    # print(rhside)

    # Now solve the Mixed-integer Program exactly, and check if the output is the
    same as directly running the mps file
    mipexact = gp.Model()
    mipexact.Params.LogToConsole = 0
    x = []
    for i in range(len(objcoeff)):
        x.append(mipexact.addVar(vtype=GRB.BINARY))

    for j in range(len(rhside)):
        mipexact.addConstr(sum(coeffmatrix[j][i] * x[i] for i in range(len(x))) <=
        rhside[j])

    mipexact.setObjective(-1*sum(objcoeff[m] * x[m] for m in range(len(x))),
    GRB.MAXIMIZE)
    mipexact.optimize()

    print("Successfully draw information from the mps file!")
    print("For mixed-integer program, optimal solution is: ", mipexact.X)

```

```

# Next solve the relaxed version
lpr = gp.Model()
lpr.Params.LogToConsole = 0
x = []
for i in range(len(objcoeff)):
    x.append(lpr.addVar(vtype=GRB.CONTINUOUS))

for j in range(len(rhside)):
    lpr.addConstr(sum(coeffmatrix[j][i] * x[i] for i in range(len(x))) <=
rhside[j])

lpr.setObjective(sum(objcoeff[m] * x[m] for m in range(len(x))))
lpr.optimize()

print("For LP relaxation, optimal solution is: ", lpr.X)

# Suppose we have a file that indicates which constraints are hard
hardconstridx = []
with open(constrfilename, 'r') as file:
    # Loop over each line in the file
    for line in file:
        # Use regular expressions to find the numbers in the line
        numbers = re.findall(r'\d+', line)
        hardconstridx.append(int(numbers[0]))

# separate the constraints into hard ones and soft ones according to the
information above
A1 = coeffmatrix[hardconstridx[0]:hardconstridx[-1] + 1]
b1 = rhside[hardconstridx[0]:hardconstridx[-1] + 1]
A2 = coeffmatrix[hardconstridx[-1] + 1:]
b2 = rhside[hardconstridx[-1] + 1:]

return A1, b1, A2, b2, objcoeff, lpr.objVal, mipexact.ObjVal, directopt

def LagrangianDualSolver(initlmbd,hardcoeff,hardrhs,softcoeff, softrhs, objcoef,
lpopt, mipopt1):
    """
    This is the Lagrangian Dual Solver.
    :param initlmbd: the initial  $\lambda$  we choose
    :param hardcoeff: coefficient matrix for hard constraints
    :param hardrhs: rhs value for hard constraints
    :param softcoeff: coefficient matrix for soft constraints
    :param softrhs: rhs value for soft constraints
    :param objcoef: c for objective function
    :param lpopt: linear relax program objective value
    :param mipopt1: mixed-integer program objective value
    :return:
    """
    Aa1 = hardcoeff
    bb1 = hardrhs
    Aa2 = softcoeff
    bb2 = softrhs
    objc = objcoef
    zlp = lpopt
    zi1 = mipopt1
    # Next solve the Lagrangian dual problem
    ldp = gp.Model()
    ldp.Params.LogToConsole = 0
    x = []

```

```

for i in range(len(objc)):
    x.append(ldp.addVar(vtype=GRB.BINARY))

# Initialize the s subgradient
s_grad = [ldp.addVar() for i in range(len(bb1))]

# Express hard constraints as  $b1 - A1 \cdot x$ 
for j in range(len(bb1)):
    ldp.addConstr(bb1[j] - sum(Aa1[j][i] * x[i] for i in range(len(x))) ==
s_grad[j])

# Add the soft constraints
for j in range(len(bb2)):
    ldp.addConstr(sum(Aa2[j][i] * x[i] for i in range(len(x))) <= bb2[j])

# Initialize the multiplier
lmbd = [initlmbd] * len(bb1)

tol = 1e-6
iter = 0
while True:
    # Set the new objective function each time, here s_gradient is just  $b1 - A1 \cdot x$ 
    ldp.setObjective((-1)*(sum(objc[m] * x[m] for m in range(len(x)))) +
                    sum(lmbd[n] * s_grad[n] for n in range(len(lmbd))),
GRB.MAXIMIZE)

    ldp.optimize()

    print("Iteration ", iter+1)
    print("Obj value is: ", -1*ldp.objVal)

    satisfy = True
    # Check if satisfy the stopping criteria
    for ll, s in zip(lmbd, s_grad):
        if abs(ll) > tol and abs(s.x) > tol:
            satisfy = False
            break
    if satisfy:
        break
    else:
        a = 1/(iter+1) # naive step size
        for i in range(len(lmbd)):
            lmbd[i] = max(lmbd[i] - a * s_grad[i].x, 0.0) # In this case, all
constraints signs are <=,  $\lambda$  is therefore positive

        iter += 1

    print("After extracting information about constraints from mps file and solving
MIP again exactly, obj value is: ", -1*zi1)
    print("Final zLD is ", -1*ldp.objVal)
    print("zLP is ", zlp)
    print("Duality gap is ", (-1*zi1) - zlp)
    print("Sum up, we can observe that  $zI \geq zLD \geq zLP$ . Because this is a
minimization problem, we can conclude that "
        "Lagrangian relaxation provides a bound that is at least as strong as the LP
relaxation." )

# Extract information from the mps file

```

```
[coef1, rhs1, coef2, rhs2, cfobj, lpz, iz1, iz2] = readinfiles('lseu.mps',  
'hardconstraints.txt')  
# Run the solver  
LagrangianDualSolver(4, coef1, rhs1, coef2, rhs2, cfobj,lpz,iz1)
```