

minibeacon V5 广播格式

Apple iBeacon

Offset	Length	Type	Data	Details
0	1	Data Length	0x02	/
1	1	Flag data type	0x01	/
2	1	Flag data	0x06	/
3	1	Data Length	0x1A	/
4	1	Manufacture Data	0xFF	/
5	2	Company ID	0x4C00	(little-endian) 0x004C
7	1	Beacon Type	0x02	(big-endian)0x02
8	1	Data Len	0x15	Beacon Adv data len
9	16	UUID	0x0112233445566778899 AABBCCDDEEFF0	(big-endian) 0x0112233445566778899AA BBCCDDEEFF0
25	2	Major	0x03E8	(big-endian)0x03E8
27	2	Minor	0x07D0	(big-endian)0x07D0
29	1	RSSI at 1m	0xC5	-59dBm

扫描回复包

offset	Length	Type	Data	Details
0	1	Data Length	0x02	/
1	1	Data Type	0x0A	AD 类型为 Tx Power Level
2	1	Power Data	0x00	Tx Power, 0x00 => 0dBm
3	1	Data Length	3	/
4	1	Complete list of 16-bit Service UUIDs	0x03	/
5	2	UUID data	0xF1FF	(little-endian) 0xFFF1
7	1	Data Length	14	/
8	1	Service data	0x16	/
9	2	UUID data	0xF1FF	(little-endian) 0xFFF1
11	1	Battery level	0x64	Battery level is 100%
12	2	Major	0x2715	(big-endian) 10005
14	2	Minor	0xD350	(big-endian)54096
16	6	Mac address	0xAC233F000001	(big-endian) AC:23:3F:00:00:01
22	1	Data Length	6	/
23	1	Device Complete Name	0x09	/
24	5	Name	0x6D696E6577	"minew"