Homework (Simulation)-Tong Cui

This program, process-run.py, allows you to see how process states change as programs run and either use the CPU (e.g., perform an add instruction) or do I/O (e.g., send a request to a disk and wait for it to complete). See the README for details.

Questions

1. Run process-run.py with the following flags: -I 5:100,5:100. What should the CPU utilization be (e.g., the percent of time the CPU is in use?) Why do you know this? Use the -c and -p flags to see if you were right.

```
Produce a trace of what would happen when you run these processes:
Process 0
  cpu
  cpu
  cpu
  cpu
  cpu
Process 1
  cpu
  cpu
  cpu
  cpu
  cpu
Important behaviors:
  System will switch whenthe current process is FINISHED or ISSUES AN IO
  After IOs, the process issuing the IO willrun LATER (when it is its turn)
```

The percent of the time the CPU is in use should be 100%. Because we passed at 5:100 and 5:100 when we run the program. According to the README file, the process we specified is "5:100" which means it should consist of 5 instructions, and the chances that each instruction is a CPU instruction is 100%.

```
1e18@Zuojuns-MacBook-Air file-devices % ./process-run.py -l 5:100,5:100 -c
        PID: 0
Time
                    PID: 1
                                  CPU
                                             I0s
                     READY
       RUN: cpu
                                     1
  1
  2
       RUN: cpu
                     READY
                                     1
                                     1
  3
                     READY
       RUN: cpu
                                     1
  4
       RUN: cpu
                     READY
  5
                                     1
       RUN: cpu
                     READY
  6
           DONE
                  RUN: cpu
                                     1
  7
           DONE
                                     1
                  RUN: cpu
  8
           DONE
                                     1
                   RUN: cpu
                   RUN:cpu
                                     1
  9
           DONE
           DONE
                                     1
 10
                  RUN: cpu
```

```
1e18@Zuojuns-MacBook-Air file-devices % ./process-run.py -l 5:100,5:100 -p
Produce a trace of what would happen when you run these processes:
Process 0
  cpu
  cpu
  cpu
  cpu
  cpu
Process 1
  cpu
  cpu
  cpu
  cpu
  cpu
Important behaviors:
  System will switch whenthe current process is FINISHED or ISSUES AN IO After IOs, the process issuing the IO willrun LATER (when it is its turn)
```

I think my answer is correct. Because from the above pictures, we can see that Process 0 runs first and is done, and then Process 1 run and is done. There is no IOs. As a result, CPU utilization is 100%.

2. Now run with these flags: ./process-run.py -l 4:100,1:0.

These flags specify one process with 4 instructions (all to use the CPU), and one that simply issues an I/O and waits for it to be done. How long does it take to complete both processes? Use -c and -p to find out if you were right.

```
1e18@Zuojuns-MacBook-Air file-devices % ./process-run.py -l 4:100,1:0
Produce a trace of what would happen when you run these processes:
Process 0
   cpu
   cpu
   cpu
   cpu
   cpu
   rocess 1
   io
```

It takes 10 clock ticks to finish both processes.

```
1e18@Zuojuns-MacBook-Air file-devices % ./process-run.py -l 4:100,1:0 -c
Time
        PID: 0
                    PID: 1
                                  CPU
                                             I0s
  1
       RUN: cpu
                    READY
                                    1
  2
                                    1
       RUN: cpu
                     READY
  3
                     READY
                                    1
       RUN: cpu
  4
                                    1
       RUN: cpu
                    READY
  5
                                    1
           DONE
                   RUN:io
  6
           DONE
                  WAITING
                                               1
  7
                                               1
          DONE
                  WAITING
  8
                                               1
          DONE
                  WAITING
  9
           DONE
                  WAITING
                                               1
           DONE
                      DONE
 10*
```

```
1e18@Zuojuns-MacBook-Air file-devices % ./process-run.py -l 4:100,1:0 -p
Produce a trace of what would happen when you run these processes:
Process 0
   cpu
   cpu
   cpu
   cpu
   cpu
   cpu
   io
```

CPU percentage: 50%. I/Os percentage: 40%.

According to the above pictures, Process 0 ran for 4 clock ticks and was done. Then Process 1 posted an I/O request and the CPU received and blocked Process 1, which takes 1 clock tick. Then the CPU waited for the I/O request for 4 clock ticks. Finally, Process 1 received the I/O result and the CPU ran and did Process 1 in 1 clock tick.

3. Switch the order of the processes: -I 1:0,4:100. What happens now? Does switching the order matter? Why? (As always, use -c and -p to see if you were right)

```
1e18@Zuojuns-MacBook-Air file-devices % ./process-run.py -l 1:0,4:100
Produce a trace of what would happen when you run these processes:
Process 0
   io

Process 1
   cpu
   cpu
  cpu
   cpu
   cpu
   cpu
   cpu
   cpu
   cpu
   cpu
   cpu
   cpu
   cpu
   cpu
   cpu
   cpu
   cpu
   cpu
   cpu
   cpu
   cpu
   cpu
   cpu
   cpu
   cpu
   cpu
   cpu
   cpu
   cpu
   cpu
   cpu
   cpu
   cpu
   cpu
   cpu
   cpu
   cpu
   cpu
   cpu
   cpu
   cpu
   cpu
   cpu
   cpu
   cpu
   cpu
   cpu
   cpu
  cpu
   cpu
   cpu
   cpu
   cpu
   cpu
   cpu
   cpu
   cpu
   cpu
   cpu
   cpu
   cpu
   cpu
   cpu
   cpu
   cpu
   cpu
   cpu
   cpu
   cpu
   cpu
   cpu
   cpu
   cpu
   cpu
   cpu
   cpu
   cpu
   cpu
   cpu
   cpu
   cpu
   cpu
   cpu
   cpu
   cpu
   cpu
   cpu
   cpu
   cpu
   cpu
   cpu
   cpu
   cpu
   cpu
   cpu
   cpu
   cpu
   cpu
   cpu
   cpu
   cpu
   cpu
   cpu
  cpu
   cpu
   cpu
   cpu
   cpu
   cpu
   cpu
   cpu
   cpu
   c
```

Yes, switching the order matters. The total time to complete the two processes is 6 clock ticks.

```
1e18@Zuojuns-MacBook-Air file-devices % ./process-run.py -l 1:0,4:100 -c
                                 CPU
Time
        PID: 0
                   PID: 1
                                            I0s
  1
        RUN:io
                    READY
                                   1
  2
       WAITING
                                   1
                                              1
                  RUN: cpu
  3
       WAITING
                  RUN: cpu
                                   1
                                              1
  4
       WAITING
                                   1
                                              1
                  RUN: cpu
                                              1
  5
       WAITING
                  RUN: cpu
                                   1
          DONE
                     DONE
```

CPU percentage: 83.33%. I/Os percentage: 66.67%.

According to the above picture, Process 0 posted an I/O request. The CPU received and blocked Process 0 and started to run Process 1, which takes 1 clock tick. In the next 4 clock ticks, Process 0's I/Os were waiting, while the CPU was running for Process 1. Finally, I/O

finished and the CPU unblocked Process 0 and Process 1 was done. There is a total of 6 clock ticks.

4. We'll now explore some of the other flags. One important flag is -S, which determines how the system reacts when a process issues an I/O. With the flag set to SWITCH ON END, the system will NOT switch to another process while one is doing I/O, instead waiting until the process is completely finished. What happens when you run the following two processes (-I 1:0,4:100 -c -S SWITCH ON END), one doing I/O and the other doing CPU Work?

```
1e18@Zuojuns-MacBook-Air file-devices % ./process-run.py -l 1:0,4:100 -c -S SWITCH_ON_END
        PID: 0
Time
                   PID: 1
                                 CPU
                                            I0s
                    READY
        RUN:io
                                   1
  1
  2
                    READY
                                              1
       WAITING
  3
       WAITING
                    READY
                                              1
  4
       WAITING
                    READY
                                              1
  5
       WAITING
                    READY
                                              1
  6*
                                   1
           DONE
                  RUN: cpu
           DONE
                                   1
  7
                  RUN: cpu
  8
           DONE
                                   1
                  RUN: cpu
           DONE
                  RUN: cpu
```

CPU percentage: 55.56%. I/Os percentage: 44.44%.

It would take 9 clock ticks to finish. Process 0 was doing I/O first, which took 1 clock tick. The CPU won't switch to Process 1 until Process 0 is finished. Once Process 0 completed I/O in 4 clock ticks, the CPU started to run for Process 1. After 4 clock ticks, Process 1 finished. It took a total of 9 clock ticks.

5. Now, run the same processes, but with the switching behavior set to switch to another process whenever one is WAITING for I/O (-I 1:0,4:100 -c -S SWITCH ON IO). What happens now? Use -c and -p to confirm that you are right.

Because we switch it on when I/O starts, the system would switch when Process 0 issues an I/O. It turns to the same situation in question 3.

```
1e18@Zuojuns-MacBook-Air file-devices % ./process-run.py -l 1:0,4:100 -c -S SWITCH_ON_IO
Time
        PID: 0
                   PID: 1
                                 CPU
                                            I0s
                    READY
  1
        RUN:io
                                   1
  2
                                              1
       WAITING
                  RUN: cpu
                                   1
 3
                                              1
                  RUN: cpu
                                   1
       WAITING
                                              1
  4
       WAITING
                  RUN: cpu
                                   1
  5
                  RUN:cpu
                                   1
                                              1
       WAITING
  6*
          DONE
                     DONE
```

CPU percentage: 83.33%. I/Os percentage: 66.67%.

The total time to complete the two processes is 6 clock ticks.

According to the above picture, Process 0 posted an I/O request. The CPU received and blocked Process 0 and switched to run Process 1, which takes 1 clock tick. In the next 4 clock ticks, Process 0's I/Os were waiting, while the CPU was running for Process 1. Finally, I/O

finished and the CPU unblocked Process 0 and Process 1 was done. There is a total of 6 clock ticks.

6. One other important behavior is what to do when an I/O completes. With -I IO RUN LATER, when an I/O completes, the process that issued it is not necessarily run right away; rather, whatever was running at the time keeps running. What happens when you run this combination of processes? (Run ./process-run.py -I 3:0,5:100,5:100,5:100 -S SWITCH ON IO -I IO RUN LATER -c -p) Are system resources being effectively utilized?

```
1e18@Zuojuns-MacBook-Air file-devices % ./process-run.py -l 3:0,5:100,5:100,5:100 -S SWITCH_ON_IO -I IO_RUN_LATER Produce a trace of what would happen when you run these processes:

Process 0
   io
   io
io
Process 1
   cpu
   cpu
   cpu
   cpu
   cpu
 Process 2
   cpu
   cpu
   cpu
   cpu
   cpu
 Process 3
   cpu
   cpu
   cpu
   cpu
   cpu
```

1e18@2	Zuojuns-Mad	cBook-Air	file-devices	% ./pro	cess-run.py -l	3:0,5:10	00,5:100,5:100	-S SI	WITCH_ON_I	0 -I	IO_RUN_LAT	ER -c
Time	PID: 0	PID: 1	PID: 2	PID: 3	CPU	I0s						
1	RUN:io	READY	READY	READY	1							
2	WAITING	RUN:cpu	READY	READY	1	1						
3	WAITING	RUN:cpu	READY	READY	1	1						
4	WAITING	RUN:cpu	READY	READY	1	1						
5	WAITING	RUN:cpu	READY	READY	1	1						
6*	READY	RUN:cpu	READY	READY	1							
7	READY	DONE	RUN:cpu	READY	1							
8	READY	DONE	RUN:cpu	READY	1							
9	READY	DONE	RUN:cpu	READY	1							
10	READY	DONE	RUN:cpu	READY	1							
11	READY	DONE	RUN:cpu	READY	1							
12	READY	DONE		RUN:cpu	1							
13	READY	DONE		RUN:cpu	1							
14	READY	DONE		RUN:cpu	1							
15	READY	DONE	DONE	RUN:cpu	1							
16	READY	DONE		RUN:cpu	1							
17	RUN:io	DONE	DONE	DONE	1							
18	WAITING	DONE	DONE	DONE		1						
19	WAITING	DONE	DONE	DONE		1						
20	WAITING	DONE	DONE	DONE		1						
21	WAITING	DONE	DONE	DONE		1						
22*	RUN:io	DONE	DONE	DONE	1							
23	WAITING	DONE	DONE	DONE		1						
24	WAITING	DONE	DONE	DONE		1						
25	WAITING	DONE	DONE	DONE		1						
26	WAITING	DONE	DONE	DONE		1						
27*	DONE	DONE	DONE	DONE								

CPU percentage: 66.67%.

I/Os percentage: 44.44%.

When we add IO_RUN_LATER, we can see the system resources are not utilized efficiently. There are 27 clock ticks. In the second diagram, when Process 0's first I/O and Process 1's first task was done, the second I/O for Process 0 should have been done immediately. However, it didn't. The same situation happened for the third I/O for Process 0. As a result, it took more clock ticks than the situation that I/O can run immediately.

7. Now run the same processes, but with -I IO RUN IMMEDIATE set, which immediately runs the process that issued the I/O. How does this behavior differ? Why might running a process that just completed an I/O again be a good idea?

1e18@Z	uojuns-Mad	cBook-Air	file-devices	% ./pro	cess-run.py	-l 3:0,5:1	00,5:100,5:100	-S SWITCH_ON	_IO -I I	[O_RUN_IMMEDIATE -c
Time	PID: 0	PID: 1	PID: 2	PID: 3	CPU	I0s				
1	RUN:io	READY	READY	READY	1					
2	WAITING	RUN:cpu	READY	READY	1	1				
3	WAITING	RUN:cpu	READY	READY	1	1				
4	WAITING	RUN: cpu	READY	READY	1	1				
5	WAITING	RUN: cpu	READY	READY	1	1				
6*	RUN:io	READY	READY	READY	1					
7	WAITING	RUN:cpu	READY	READY	1	1				
8	WAITING	DONE	RUN:cpu	READY	1	1				
9	WAITING	DONE	RUN: cpu	READY	1	1				
10	WAITING	DONE	RUN:cpu	READY	1	1				
11*	RUN:io	DONE	READY	READY	1					
12	WAITING	DONE	RUN:cpu	READY	1	1				
13	WAITING	DONE	RUN: cpu	READY	1	1				
14	WAITING	DONE	DONE	RUN:cpu	1	1				
15	WAITING	DONE	DONE	RUN: cpu	1	1				
16*	DONE	DONE	DONE	RUN: cpu	1					
17	DONE	DONE	DONE	RUN: cpu	1					
18	DONE	DONE	DONE	RUN: cpu	1					

CPU percentage: 100%. I/Os percentage: 66.67%.

There are only 18 clock ticks when adding IO_RUN_IMMEDIATE flag. Because I/O can be run immediately after the last I/O is finished. The CPU can accept the new I/O request or run the next process instruction after the last I/O is finished. Then I/O operations and CPU can run simultaneously. Also, because we turn the mode SWITCH_ON_IO on, the CPU starts to run instructions and I/O operations can be executed at the same time, which would save 1 clock tick.

8. Now run with some randomly generated processes: -s 1 -l 3:50,3:50 or -s 2 -l 3:50,3:50 or -s 3 -l 3:50,3:50. See if you can predict how the trace will turn out. What happens when you use the flag -l IO RUN IMMEDIATE vs. -l IO RUN LATER? What happens when you use -S SWITCH ON IO vs. -S SWITCH ON END?

```
1e18@Zuojuns-MacBook-Air file-devices % ./process-run.py -s 1 -l 3:50,3:50 -I IO_RUN_IMMEDIATE -c
Time PID: 0 PID: 1 CPU IOs
1 RUN:cpu READY 1
  2
                       READY
         RUN:io
        WAITING
                     RUN:cpu
        WAITING
                     RUN: cpu
  5
6
7*
8
        WAITING
                     RUN: cpu
        WAITING
                         DONE
                         DONE
         RUN:io
        WAITING
                         DONE
                                                     1
1
1
        WAITING
                         DONE
 10
                         DONE
        WAITING
 11
        WAITING
                         DONE
 12*
            DONE
                         DONE
```

Stats: CPU Busy 6 (50.00%) Stats: IO Busy 8 (66.67%)

1e18@	Zuojuns-Ma	cBook-Air	file-devices s	% ./proc	ess-run.py	-s 1 -l	3:50,3:50	0 -I IO_	RUN_LATER -c
Time	PID: 0	PID: 1	CPU	I0s					
1	RUN:cpu	READY	1						
2	RUN:io	READY	1						
3	WAITING	RUN:cpu	1	1					
4	WAITING	RUN: cpu	1	1					
5	WAITING	RUN: cpu	1	1					
6	WAITING	DONE		1					
7*	RUN:io	DONE	1						
8	WAITING	DONE		1					
9	WAITING	DONE		1					
10	WAITING	DONE		1					
11	WAITING	DONE		1					
12*	DONE	DONE							

Stats: Total Time 12

Stats: CPU Busy 6 (50.00%) Stats: IO Busy 8 (66.67%)

4 40			613 1 1				2 50 2 50	DIII	
			file-devices	% ./proc	cess-run.py	-s 2 -l	3:50,3:50	-I IO_RUN	N_IMMEDIATE -c
Time	PID:	0 PID: 1	CPU	I0s					
1	RUN:i	o READY	1						
2	WAITIN	G RUN:cpu	1	1					
3	WAITIN	G RUN:io	1	1					
4	WAITIN	G WAITING		2					
5	WAITIN	G WAITING		2					
6*	<pre>RUN:i</pre>	o WAITING	1	1					
7	WAITIN	G WAITING		2					
8*	< WAITING	G RUN:io	1	1					
9	WAITIN	G WAITING		2					
10	WAITIN	G WAITING		2					
11*	RUN:cp	u WAITING	1	1					
12	DON	E WAITING		1					
13*	DON	e done		_					

Stats: Total Time 13

Stats: CPU Busy 6 (46.15%) Stats: IO Busy 11 (84.62%)

1e18@	Zuojuns-Ma	acBook-Air	file-devices	% ./prod	cess-run.py	-s 2 -l	3:50,3:50	-I I0_RU	N_LATER -c
Time	PID: 0	PID: 1	CPU	IOs					_
1	RUN:io	READY	1						
2	WAITING	RUN:cpu	1	1					
3	WAITING	RUN:io	1	1					
4	WAITING	WAITING		2					
5	WAITING	WAITING		2					
6*	RUN:io	WAITING	1	1					
7	WAITING	WAITING		2					
8*	WAITING	RUN:io	1	1					
9	WAITING	WAITING		2					
10	WAITING	WAITING		2					
11*	RUN:cpu	WAITING	1	1					
12	DONE	WAITING		1					
13*	DONE	DONE							

Stats: CPU Busy 6 (46.15%) Stats: IO Busy 11 (84.62%)

1e18@	Zuojuns-Ma	cBook-Air	file-devices	% ./proce	ess-run.py	-s 3 -l	3:50,3:50	-I	IO_RUN_	[MMEDIATE	-c
Time	PID: 0	PID: 1	CPU	I0s							
1	RUN:cpu	READY	1								
2	RUN:io	READY	1								
3	WAITING	RUN:io	1	1							
4	WAITING	WAITING		2							
5	WAITING	WAITING		2							
6	WAITING	WAITING		2							
7*	RUN:cpu	WAITING	1	1							
8*	DONE	RUN:io	1								
9	DONE	WAITING		1							
10	DONE	WAITING		1							
11	DONE	WAITING		1							
12	DONE	WAITING		1							
13*	DONE	RUN:cpu	1	_							

Stats: Total Time 13

Stats: CPU Busy 6 (46.15%) Stats: IO Busy 9 (69.23%)

4 400		D A'	C:1 ! :	· /		2 1	2 50 2 50	T TO DIE	
_	_		file-devices		ess-run.py	-s 3 −l	3:50,3:50	-T TO_KOL	I_LATER -C
Time	PID: 0	PID: 1	CPU	I0s					
1	RUN:cpu	READY	1						
2	RUN:io	READY	1						
3	WAITING	RUN:io	1	1					
4	WAITING	WAITING		2					
5	WAITING	WAITING		2					
6	WAITING	WAITING		2					
7*	RUN:cpu	WAITING	1	1					
8*	DONE	RUN:io	1						
9	DONE	WAITING		1					
10	DONE	WAITING		1					
11	DONE	WAITING		1					
12	DONE	WAITING		1					
13*	DONE	RUN:cpu	1	_					

Stats: Total Time 13

Stats: CPU Busy 6 (46.15%) Stats: IO Busy 9 (69.23%) We can see there is no obvious difference between IO_RUN_IMMEDIATE and IO_RUN_END in the above cases. Because the default mode is SWITCH_ON_IO. Usually, the difference between IO_RUN_IMMEDIATE and IO_RUN_END is whether I/O can always grab the CPU once the CPU is idle. However, in these cases, I/Os are not conflicted with CPU executing instructions. Thus, there is no obvious difference in these cases.

1e18@Z	uojuns Ma	cBook-Air	file-devices	% ./proces	s-run.py	-s 1 ·	-l 3:50,3:50	-S SWITCH_	ON_IO -c -p
Time	PID: 0	PID: 1	CPU	I0s					
1	RUN:cpu	READY	1						
2	RUN:io	READY	1						
3	WAITING	RUN:cpu	1	1					
4	WAITING	RUN: cpu	1	1					
5	WAITING	RUN: cpu	1	1					
6	WAITING	DONE		1					
7*	RUN:io	DONE	1						
8	WAITING	DONE		1					
9	WAITING	DONE		1					
10	WAITING	DONE		1					
11	WAITING	DONE		1					
12*	DONE	DONE							

Stats: Total Time 12

Stats: CPU Busy 6 (50.00%) Stats: IO Busy 8 (66.67%)

1e18@	Zuojuns-Ma	cBook-Air	file-devices	% ./proce	ess-run.py	-s 1 -l	3:50,3:50	-S SWITCH	ON_END	-с -р
Time	PID: 0	PID: 1	CPU	I0s						·
1	RUN:cpu	READY	1							
2	RUN:io	READY	1							
3	WAITING	READY		1						
4	WAITING	READY		1						
5	WAITING	READY		1						
6	WAITING	READY		1						
7*	RUN:io	READY	1							
8	WAITING	READY		1						
9	WAITING	READY		1						
10	WAITING	READY		1						
11	WAITING	READY		1						
12*	DONE	RUN:cpu	1							
13	DONE	RUN:cpu	1							
14	DONE	RUN: cpu	1							

Stats: Total Time 14

Stats: CPU Busy 6 (42.86%) Stats: IO Busy 8 (57.14%)

```
1e18@Zuojuns-MacBook-Air file-devices % ./process-run.py -s 2 -l 3:50,3:50 -S SWITCH_ON_IO -c -p Time PID: 0 PID: 1 CPU IOs
                     PID: 1
READY
         RUN:io
        WAITING
                    RUN:cpu
                                        1
                                                   1122121211
  3
                                        1
        WAITING
                     RUN:io
        WAITING
                    WAITING
                    WAITING
WAITING
        WAITING
         RUN:io
  6*
        WAITING
                    WAITING
  8*
        WAITING
                     RUN:io
        WAITING
                    WAITING
 10
        WAITING
                    WAITING
 11*
        RUN:cpu
DONE
                    WAITING
 12
                    WAITING
 13*
            DONE
                        DONE
```

Stats: CPU Busy 6 (46.15%) Stats: IO Busy 11 (84.62%)

1e18@Z	Zuojuns-Ma	cBook-Air	file-devices	% ./proce	ess-run.py	-s 2	2 –1	3:50,3:50	-S	SWITCH_ON_E	ND -c -p
Time	PID: 0	PID: 1	CPU	I0s							
1	RUN:io	READY	1								
2	WAITING	READY		1							
3	WAITING	READY		1							
4	WAITING	READY		1							
5	WAITING	READY		1							
6*	RUN:io	READY	1								
7	WAITING	READY		1							
8	WAITING	READY		1							
9	WAITING	READY		1							
10	WAITING	READY		1							
11*	RUN:cpu	READY	1								
12	DONE	RUN:cpu	1								
13	DONE	RUN:io	1								
14	DONE	WAITING		1							
15	DONE	WAITING		1							
16	DONE	WAITING		1							
17	DONE	WAITING		1							
18*	DONE	RUN:io	1								
19	DONE	WAITING		1							
20	DONE	WAITING		1							
21	DONE	WAITING		1							
22	DONE	WAITING		1							
23*	DONE	DONE									

Stats: Total Time 23

Stats: CPU Busy 6 (26.09%) Stats: IO Busy 16 (69.57%)

```
1e18@Zuojuns-MacBook-Air file-devices % ./process-run.py -s 3 -l 3:50,3:50 -S SWITCH_ON_IO -c -p
Time PID: 0 PID: 1 CPU IOs
                      READY
        RUN: cpu
         RUN:io
                      READY
 3
        WAITING
                     RUN:io
                                       1
                                                   1
2
2
2
1
        WAITING
                    WAITING
 5
6
7*
        WAITING
                    WAITING
        WAITING
                    WAITING
                                       1
        RUN: cpu
                    WAITING
 8*
9
           DONE
                     RUN:io
                                       1
           DONE
                                                   1
1
1
                    WAITING
10
           DONE
                    WAITING
11
           DONE
                    WAITING
                                                   1
12
           DONE
                    WAITING
           DONE
13*
                    RUN: cpu
                                       1
```

Stats: CPU Busy 6 (46.15%) Stats: IO Busy 9 (69.23%)

1e18@	Zuojuns-Mac	:Book-Air	file-devices	% ./process-r	run.py -s	3 -l 3:	50,3:50	-S SWITCH	H_ON_END -c -p
Time	PID: 0	PID: 1	CPU	I0s					
1	RUN:cpu	READY	1						
2	RUN:io	READY	1						
3	WAITING	READY		1					
4	WAITING	READY		1					
5	WAITING	READY		1					
6	WAITING	READY		1					
7*	RUN:cpu	READY	1						
8	DONE	RUN:io	1						
9	DONE	WAITING		1					
10	DONE	WAITING		1					
11	DONE	WAITING		1					
12	DONE	WAITING		1					
13*	DONE	RUN:io	1						
14	DONE	WAITING		1					
15	DONE	WAITING		1					
16	DONE	WAITING		1					
17	DONE	WAITING		1					
18*	DONE	RUN:cpu	1						

Stats: Total Time 18

Stats: CPU Busy 6 (33.33%) Stats: IO Busy 12 (66.67%)

The difference between SWITCH_ON_IO and SWITCH_ON_END is whether the system can switch when a process issues an I/O. When the mode is SWITCH_ON_END, if there is an I/O operation, there won't be other CPU executions or I/O operations. Thus, the time utilization of SWITCH_ON_END would be less efficient.