

Comment	Description	Designator	Footprint	LibRef	Quantity
SSW-104-02-T-D	SQ Post Socket, Through-hole, Vertical, -55 to 105 degC, 2.54mm Pitch, 8-Pin, Female, RoHS	ATTiny	SMTC-SSW-104-02-X-D	CMP-1023-00342-1	1
147694-1	FSM8JRT=SWITCH, PUSHBUTTON,TACT	Button	TE_FSM8JRT	FSM8JRT	1
81R0LFJ0511WPN081T	Aluminum Electrolytic Capacitor, 1 uF +/- 5%, 50 V, -40 to 105 degC, 2 Pin THD, Dia 5 mm, Body Length 11 mm, Tape and Reel	ByCap	FHTE-8-0511-2_M	CMP-0909-00001-1	1
151053RS03000	THT LED round mono-color waterclear, WL-TMRW ,Red	LED	Type 5mm	CMP-1489-00007-1	1
FMP300FRF73-82K	Metal Film Resistor, 82 KOhm +/-1%, 3 W, -55 to 155 degC, 2-Pin THD, RoHS, Tape and Reel	LEDR	YAGO-FMP300-2_V2	CMP-1257-00001-1	1
PHF-102-01-L-S-002	Press Fit Socket, Through-hole, Vertical, -55 to 125 degC, 2.54 mm Pitch, 2-Pin, Female, RoHS	Power	SMTC-PHF-102-01-X-S-002	CMP-1023-00103-1	1
L7805ACV	Positive Voltage Regulator, 5V, 3-Pin TO-220	PowerReg	TO220	CMP-0244-00484-1	1