
Learning Exponential Families

Anonymous Author(s)

Affiliation

Address

email

Abstract

[SLOPPY NOTES STAGE JUST TO GET THOUGHTS DOWN]

Recently much attention has been paid to probabilistic models defined by a deep neural network transformation of a simpler random variable; these implicit generative models have been used to great success across variational inference, generative modeling of complex data types, and more. In essentially all of these settings, the model is specified by the network architecture, and a particular member of that model is chosen to minimize some loss (be it adversarial or information divergence)

We treat the problem of learning an exponential family – the model itself, rather than the typical setting of learning a particular member of that model.

Many intractable distributions encountered in machine learning belong to exponential families. In rare cases these distributions are tractable due to either known conjugacy in the problem setup (such as the normal-inverse-Wishart), or due to careful numerical work historically that has made these distributions computationally indistinguishable from tractable (eg the Dirichlet).

1 Introduction

People use lots of implicit generative models:

Across machine learning, including ABC [?], GANs [1], VAEs [2, 3], and their many follow-ons (too numerous to cite in any detail), models that specify a distribution via the nonlinear transformation of latent random variable. We prefer and use the terminology of [4], calling such a distribution an *implicit generative model*, defined as:

something like eq 1 and 2 in Mohamed:2016aa, defining $q_{\theta}(z)$

Also use the proper notation of the density implied by the pushforward measure of the function $f_{\theta\#}$ if useful. Also reference to this being super standard and widespread [5]. The two central uses are at present generative distributions of interesting data types (as in GANs), and for variational inference. Regardless, all of these use cases specify a *model* (or variational family) $\mathcal{Q} = \{q_{\theta} : \theta \in \Theta\}$, and then minimize a suitable loss $\mathcal{L}(q, p)$ over $q \in \mathcal{Q}$. In the case of VI p is the posterior (or the unnormalized log joint) and \mathcal{L} is the *KL* divergence (or so called ELBO), in GAN p is the sample density of a (large) dataset and \mathcal{L} is the adversarial objective whose details do not matter here.

All these learn a single member of a family

Inherent in all the above approaches is an algorithmic procedure to select a *single* distribution $q_{\theta}(z)$ from among the *model* \mathcal{Q} . Implicit in this effort is the belief that \mathcal{Q} is suitably general to contain the true distribution of interest, or at least an adequately close approximation.

Here we learn the family

We leverage the natural parameterization of exponential families to derive a novel objective that is amenable to stochastic optimization.

31 *A note on amortization*

32 Several have pointed out that these IGMs are in fact strictly less expressive than a mean field, at
33 least in the conventional VI setting. See for example [http://dustintran.com/blog/variational-auto-](http://dustintran.com/blog/variational-auto-encoders-do-not-train-complex-generative-models)
34 [encoders-do-not-train-complex-generative-models](http://dustintran.com/blog/variational-auto-encoders-do-not-train-complex-generative-models) (here I like the line “The neural network used in
35 the encoder (variational distribution) does not lead to any richer approximating distribution. It is a
36 way to amortize inference such that the number of parameters does not grow with the size of the data
37 (an incredible feat, but not one for expressivity!) (Stuhlmuller et al., 2013)”). You have to optimize
38 for every data point individually, or instead you get to do so in aggregate once in advance (at a much
39 higher cost) and then recover that cost over future data points within that distribution (and hence the
40 term amortization, though perhaps there is shared statistical power as well) Etc etc what we are doing
41 here is *amortized* amortized inference, in the sense that we are amortizing not the data points, but the
42 distribution itself.

43 REparameterization trick (Kingma and Welling (2013), Rezende et al. (2014) and Titsias and
44 Lazaro-Gredilla 2014).. See also Archer 2015 / Gao 2016 for clean explanation.

45 Key for obvious norm flow connection but also a good bibliography and some good historical views
46 to Dayan and Gershman and other people who did norm flows. <https://arxiv.org/pdf/1505.05770.pdf>

47 *Our contributions include:*

48 ...

49 This should not be confused with "Learning to learn by gradient descent by gradient descent"
50 (Andrychowicz et. al. 2016) and similar works.

51 ...

52 *Our results demonstrate*

53 ...

54 **2 Learning exponential families**

55 *Why this is important*

56 Exp fams are awesome and fundamental []. Also [?] rightly point out that many many inference
57 problems can be cast as exponential families. Can we cast the VAE encoder network as a suitable
58 exp fam... sure I think that's right; the network parameters of z form the statistics, and then the
59 observations are η 's.

60 *Why this is coherent*

61 Θ defines quite a big \mathcal{Q} , and indeed the subject of compressibility, generalization, etc is of keen
62 interest to many [?]. So actually the space of distributions is quite large, and in many cases certainly
63 larger than it needs be. Why? Well, we know precisely the parameter space of the exponential family;
64 it is defined by the *natural* parameters $\eta \in \mathbb{R}^p$ (or whatever we choose there).

65 *Figure 1*

66 Figure of model space. Yeah that's good. Then graphical model. Note that perhaps \mathcal{Q} is too big,
67 and a simpler model space (the $\|\eta\|$ dimensional subspace of Θ) would be better for the usual
68 robustness/generalization reasons.

69 *Aside*

70 A neat idea is to ask if learning the $\theta(\eta)$ network leads to better VI in terms of inference networks,
71 since it is apparently appropriately regularized and can just take suff stats. That's testable if we have
72 time.

73 *Why Flow Networks*

74 We choose flow networks [] and [] because duh. And "implicit generative models aka density
75 networks" (or rather, density networks are the instantiation of an IGM with deep nets, which is
76 effectively synonymous these days. Gibbs and MacKay Density Networks 1997! And invertible
77 networks In that vein probably definitely cite invertible deep nets in general: Baird et al IJCAI 2005,
78 Ripple and Adams 2013 . Note that what norm flows (the Rezende/Mohamed stuff specifically)




Figure 1: Figure 1: possibly Fig 7.2 bias-variance tradeoff and then benefit of a restricted model from Hastie Book, or similar from W4400 (ask PO for batman permission).

Table 1: Sample table title

Part		
Name	Description	Size (μm)
Dendrite	Input terminal	~ 100
Axon	Output terminal	~ 10
Soma	Cell body	up to 10^6

79 did is make it tractable and scalable and in the modern VAE style. That makes these comparisons
80 legitimate and apples to apples. Any generalization of this is also dandy though, so could use a mean
81 field approach (standard) or any of the things that go beyond mean field, either classically (*Saul*
82 *and Jordan, 1996; Barber and Wierginck, 1999*); *this is called structured variational inference*.
83 *Another way to expand the family is to consider mixtures of variational densities, i.e., additional*
84 *latent variables within the variational family (Bishop et al., 1998).* or newer stuff [] [Tran Copula
85 VI, Hoffman and Blei 2015].

86 Couch this in terms of normalizing flows though point out this is not strictly necessary. Note in
87 particular Tabak, E. G. and Turner, C. V. A family of nonparametric density estimation algorithms.
88 Communications on Pure and Applied Mathematics, 66(2):145?164, 2013. Tabak, E. G and Vanden-
89 Eijnden, E. Density estimation by dual ascent of the log-likelihood. Communications in Mathematical
90 Sciences, 8(1):217?233, 2010. A nice line from Rezende and Mohamed is: Thus, an ideal family of
91 variational distributions $q(z|x)$ is one that is highly flexible, preferably flexible enough to contain the
92 true posterior as one solution. One path towards this ideal is based on the principle of nor- malizing
93 flows (Tabak Turner, 2013; Tabak VandenEijnden, 2010).

94 In many situations, statistical inference attempts to learn, at least approximately, a member of an
95 exponential family. We often consider this exponential family intractable in the sense that we don't
96 know how to normalize or sample from it. Approximate inference, such as variational

97 3 To Do

98 3.1 SRB

- 99 • set up submission at <https://cmt.research.microsoft.com/NIPS2018/>
- 100 • review and conform to style requirements (see website with template); 8 pages not including
- 101 refs and acks and appendices.

102 3.2 JPC

- 103 • Outline
- 104 • Write

105 \usepackage[pdftex]{graphicx} ...

106 \includegraphics[width=0.8\linewidth]{myfile.pdf}

Acknowledgments

Use unnumbered third level headings for the acknowledgments. All acknowledgments go at the end of the paper. Do not include acknowledgments in the anonymized submission, only in the final paper.

References

References

- [1] Ian Goodfellow, Jean Pouget-Abadie, Mehdi Mirza, Bing Xu, David Warde-Farley, Sherjil Ozair, Aaron Courville, and Yoshua Bengio. Generative adversarial nets. In Z. Ghahramani, M. Welling, C. Cortes, N. D. Lawrence, and K. Q. Weinberger, editors, *Advances in Neural Information Processing Systems 27*, pages 2672–2680. Curran Associates, Inc., 2014.
- [2] Diederik P Kingma and Max Welling. Auto-encoding variational bayes. 12 2013.
- [3] Danilo Jimenez Rezende, Shakir Mohamed, and Daan Wierstra. Stochastic backpropagation and approximate inference in deep generative models. *arXiv preprint arXiv:1401.4082*, 2014.
- [4] Shakir Mohamed and Balaji Lakshminarayanan. Learning in implicit generative models. 10 2016.
- [5] Luc Devroye. *Non-uniform random variate generation*. Springer-Verlag, New York, 1986.
- Stuff on wake sleep and the Helmholtz machine
- Stuff on sampling from Gibbs distributions (max ent models), and sampling from exp fams generally, with MCMC and such.
- Flow networks
- Devroye’s book.
- Hoffman et al 2013 SVI
- From Blei review on VI. The development of variational techniques for Bayesian inference followed two parallel, yet separate, tracks. Peterson and Anderson (1987) is arguably the first variational procedure for a particular model: a neural network. This paper, along with insights from statistical mechanics (Parisi, 1988), led to a flurry of variational inference procedures for a wide class of models (Saul et al., 1996; Jaakkola and Jordan, 1996, 1997; Ghahramani and Jordan, 1997; Jordan et al., 1999). In parallel, Hinton and Van Camp (1993) proposed a variational algorithm for a similar neural network model. Neal and Hinton (1999) (first published in 1993) made important connections to the expectation maximization (EM) algorithm (Dempster et al., 1977), which then led to a variety of variational inference algorithms for other types of models (Waterhouse et al., 1996; MacKay, 1997).
- Salimans, T. and Knowles, D. (2014). On using control variates with stochastic approximation for variational Bayes. *arXiv preprint arXiv:1401.1022*.
- Salimans, T., Kingma, D., and Welling, M. (2015). Markov chain Monte Carlo and variational inference: Bridging the gap. In *International Conference on Machine Learning*, pages 1218–1226.
- Ranganath, R., Gerrish, S., and Blei, D. (2014). Black box variational inference. In *Artificial Intelligence and Statistics*.
- Hoffman, M. D. and Blei, D. M. (2015). Structured stochastic variational inference. In *Artificial Intelligence and Statistics*.
- Possibly some of Burda, Y., Grosse, R., & Salakhutdinov, R. (2016). Importance Weighted Autoencoders. In *International Conference on Learning Representations*. Damianou, A. C., & Lawrence, N. D. (2013). Deep Gaussian Processes. In *Artificial Intelligence and Statistics*. Dayan, P., Hinton, G. E., Neal, R. M., & Zemel, R. S. (1995). The Helmholtz Machine. *Neural Computation*, 7(5), 889–904. <http://doi.org/10.1162/neco.1995.7.5.889> Dinh, L., Sohl-Dickstein, J., & Bengio, S. (2016). Density estimation using Real NVP. *arXiv.org*. Harville, D. A (1977). Maximum likelihood approaches to variance component estimation and to related problems. *Journal of the American Statistical Association*, 72(358):320–338. Hinton, G. and Van Camp, D (1993). Keeping the neural networks simple by minimizing the description length of the weights. In *Computational Learning Theory*,

154 pp. 5713. ACM. Johnson, M. J., Duvenaud, D., Wiltchko, A. B., Datta, S. R., & Adams, R. P.
 155 (2016). Composing graphical models with neural networks for structured representations and fast
 156 inference. arXiv.org. Kingma, D. P., & Welling, M. (2014). Auto-Encoding Variational Bayes. In
 157 International Conference on Learning Representations. Kingma, D. P., Salimans, T., & Welling, M.
 158 (2016). Improving Variational Inference with Inverse Autoregressive Flow. arXiv.org. Louizos, C.,
 159 & Welling, M. (2016). Structured and Efficient Variational Deep Learning with Matrix Gaussian
 160 Posteriors. In International Conference on Machine Learning. Maaloe, L., Sonderby, C. K., Sonderby,
 161 S. K., & Winther, O. (2016). Auxiliary Deep Generative Models. In International Conference
 162 on Machine Learning. MacKay, D. J., & Gibbs, M. N. (1999). Density networks. Statistics and
 163 neural networks: advances at the interface. Oxford University Press, Oxford, 129-144. Mnih, A., &
 164 Rezende, D. J. (2016). Variational inference for Monte Carlo objectives. In International Conference
 165 on Machine Learning. Ranganath, R., Tran, D., & Blei, D. M. (2016). Hierarchical Variational
 166 Models. In International Conference on Machine Learning. Rezende, D. J., Mohamed, S., & Wierstra,
 167 D. (2014). Stochastic Backpropagation and Approximate Inference in Deep Generative Models. In
 168 International Conference on Machine Learning. Salimans, T., Kingma, D. P., & Welling, M. (2015).
 169 Markov Chain Monte Carlo and Variational Inference: Bridging the Gap. In International Conference
 170 on Machine Learning. Salakhutdinov, R., Tenenbaum, J. B., and Torralba, A (2013). Learning with
 171 hierarchical-deep models. Pattern Analysis and Machine Intelligence, IEEE Transactions on, 35
 172 (8):1958-1971. Stuhlmüller, A., Taylor, J., & Goodman, N. (2013). Learning Stochastic Inverses.
 173 In Neural Information Processing Systems. Tran, D., Blei, D. M., & Airoldi, E. M. (2015). Copula
 174 variational inference. In Neural Information Processing Systems. Tran, D., Ranganath, R., & Blei, D.
 175 M. (2016). The Variational Gaussian Process. International Conference on Learning Representations.
 176 Waterhouse, S., MacKay, D., and Robinson, T (1996). Bayesian methods for mixtures of experts. In
 177 Neural Information Processing Systems.