

CÚRAM 8.1.3.0

Db2 13 for z/OS Post-installation Steps

Note

Before using this information and the product it supports, read the information in Notices on page 15.

Edition

This edition applies to Merative™ Cúram 8.1.3.0.

© Merative US L.P. 2024

Merative and the Merative Logo are trademarks of Merative US L.P. in the United States and other countries.

Contents

Note..... 2

Edition..... 4

 Overview 7

 Post-installation steps for the EJB Timer Tables..... 8

 Post-installation steps for the SIB tables..... 10

 Verification..... 14

Notices 15

 Privacy policy..... 16

 Trademarks..... 16

Overview

With the introduction of Db2 13 for z/OS, there is an issue with the IBM WebSphere for z/OS application server scripts used to create the SIB and EJB Timer tables. The WebSphere scripts expect to use deprecated non-UTS table space types when completing the creation of these tables in the database. IBM have acknowledged the issue and have been requested to provide a formal solution. Further details on Db2 13 for z/OS table spaces can be found [here](#).

These steps only need to be completed when the customer is using a WebSphere for z/OS application server instance configured using the Cúram OOTB **configure** target (which uses these WebSphere scripts). The following Db2 13 for z/OS database post-installation steps are required to drop the incorrectly configured SIB and EJB Timer tables and create new SIB and EJB Timer tables for use with the WebSphere for z/OS application server instance.

The **configure** target uses the values from the following properties in the *Bootstrap.properties* file for the SQL templates in the following sections.

SQL Template Variable	Bootstrap Property Name
SCHEMA_NAME	curam.db.username
DATABASE_USER	curam.db.username
DATABASE_NAME	curam.db.zos.dbname

Post-installation steps for the EJB Timer Tables

The following SQL statements need to be run against the Db2 13 for z/OS database to drop the incorrectly created EJB Timer tables after the **configure** target runs successfully:

```
DROP INDEX <SCHEMA_NAME>.EJBTIMER_TASK1I;  
DROP TABLE <SCHEMA_NAME>.EJBTIMER_TASK1;  
DROP INDEX <SCHEMA_NAME>.EJBTIMER_TASK_IDX1;  
DROP INDEX <SCHEMA_NAME>.EJBTIMER_TASK_IDX2;  
DROP TABLE <SCHEMA_NAME>.EJBTIMER_TASK;  
DROP TABLE <SCHEMA_NAME>.EJBTIMER_TREG;  
DROP TABLE <SCHEMA_NAME>.EJBTIMER_LMGR;  
DROP TABLE <SCHEMA_NAME>.EJBTIMER_LMPR;
```

The following SQL statements need to be run against the Db2 13 for z/OS database to create EJB Timer tables for the WebSphere for z/OS application server created by the **configure** target:

```
CREATE TABLE <SCHEMA_NAME>.EJBTIMER_TASK  
(  
    TASKID      NUMERIC(19) NOT NULL ,  
    VERSION     VARCHAR(5)  NOT NULL ,  
    ROW_VERSION INTEGER     NOT NULL ,  
    TASKTYPE    INTEGER     NOT NULL ,  
    TASKSUSPENDED SMALLINT  NOT NULL ,  
    CANCELLED   SMALLINT    NOT NULL ,  
    NEXTFIRETIME NUMERIC(19) NOT NULL ,  
    STARTBYINTERVAL VARCHAR(254) ,  
    STARTBYTIME  NUMERIC(19) ,  
    VALIDFROMTIME NUMERIC(19) ,  
    VALIDTOTIME  NUMERIC(19) ,  
    REPEATINTERVAL VARCHAR(254) ,  
    MAXREPEATS   INTEGER    NOT NULL ,  
    REPEATSLEFT  INTEGER    NOT NULL ,  
    TASKINFO     BLOB(102400) ,  
    NAME         VARCHAR(254) NOT NULL ,  
    AUTOPURGE    INTEGER    NOT NULL ,  
    FAILUREACTION INTEGER    ,  
    MAXATTEMPTS  INTEGER    ,  
    QOS          INTEGER    ,  
    PARTITIONID  INTEGER    ,  
    OWNERTOKEN   VARCHAR(200) NOT NULL ,  
    CREATETIME   NUMERIC(19) NOT NULL ,  
    ROW_ID       ROWID      NOT NULL GENERATED ALWAYS,  
    PRIMARY KEY ( TASKID )  
)  
IN DATABASE <DATABASE_NAME>;
```



```
CREATE INDEX <SCHEMA_NAME>.EJBTIMER_TASK_IDX1 ON
<SCHEMA_NAME>.EJBTIMER_TASK
(
    TASKID,OWNERTOKEN
)
USING STOGROUP SYSDEFLT;
```

```
CREATE INDEX <SCHEMA_NAME>.EJBTIMER_TASK_IDX2 ON
<SCHEMA_NAME>.EJBTIMER_TASK
(
    NEXTFIRETIME ASC, REPEATSLEFT, PARTITIONID
)
USING STOGROUP SYSDEFLT;
```

```
CREATE TABLE <SCHEMA_NAME>.EJBTIMER_TREG
(
    REGKEY          VARCHAR(254)    NOT NULL ,
    REGVALUE        VARCHAR(254)    ,
    PRIMARY KEY ( REGKEY )
)
IN DATABASE <DATABASE_NAME>;
```

```
CREATE TABLE <SCHEMA_NAME>.EJBTIMER_LMGR
(
    LEASENAME        VARCHAR(254) NOT NULL,
    LEASEOWNER        VARCHAR(254) NOT NULL,
    LEASE_EXPIRE_TIME NUMERIC(19),
    DISABLED          VARCHAR(5),
    PRIMARY KEY ( LEASENAME )
)
IN DATABASE <DATABASE_NAME>;
```

```
CREATE TABLE <SCHEMA_NAME>.EJBTIMER_LMPR
(
    LEASENAME        VARCHAR(254) NOT NULL,
    NAME              VARCHAR(254) NOT NULL,
    VALUE             VARCHAR(254) NOT NULL
)
IN DATABASE <DATABASE_NAME>;
```

```
CREATE INDEX <SCHEMA_NAME>.EJBTIMER_LMPR_IDX1 ON
<SCHEMA_NAME>.EJBTIMER_LMPR
(
    LEASENAME
)
USING STOGROUP SYSDEFLT;
```

Post-installation steps for the SIB tables

The following SQL statements need to run against the Db2 13 for z/OS database to drop the incorrectly created SIB tables after the **configure** target runs successfully:

```
DROP TABLE <SCHEMA_NAME>.SIBOWNER;  
DROP TABLE <SCHEMA_NAME>.SIBOWNER0;  
DROP TABLE <SCHEMA_NAME>.SIBCLASSMAP;  
DROP TABLE <SCHEMA_NAME>.SIBLISTING;  
DROP TABLE <SCHEMA_NAME>.SIB000;  
DROP TABLE <SCHEMA_NAME>.SIB001;  
DROP TABLE <SCHEMA_NAME>.SIB002;  
DROP TABLE <SCHEMA_NAME>.SIBXACTS;  
DROP TABLE <SCHEMA_NAME>.SIBKEYS;  
  
-- ADDED to clean up explicit LOB tablespaces  
DROP TABLESPACE <SCHEMA_NAME>.SIB000LS;  
DROP TABLESPACE <SCHEMA_NAME>.SIB001LS;  
DROP TABLESPACE <SCHEMA_NAME>.SIB002LS;
```

The following SQL statements need to be run against the Db2 13 for z/OS database to create SIB tables for the WebSphere for z/OS application server created by the **configure** target:

```
CREATE TABLE <SCHEMA_NAME>.SIBOWNER (  
  ME_UUID VARCHAR(16),  
  INC_UUID VARCHAR(16),  
  VERSION INTEGER,  
  MIGRATION_VERSION INTEGER,  
  ME_LUTS TIMESTAMP,  
  ME_INFO VARCHAR(254),  
  ME_STATUS VARCHAR(16)  
) IN DATABASE <DATABASE_NAME>;  
  
CREATE UNIQUE INDEX <SCHEMA_NAME>.SIBOWNER ON <SCHEMA_NAME>.SIBOWNER (  
  ME_UUID  
) USING STOGROUP SIBSG PRIQTY 200 SECQTY 20;  
  
CREATE TABLE <SCHEMA_NAME>.SIBOWNER0 (  
  EMPTY_COLUMN INTEGER  
) IN DATABASE <DATABASE_NAME>;  
  
CREATE TABLE <SCHEMA_NAME>.SIBCLASSMAP (  
  CLASSID INTEGER NOT NULL,  
  URI VARCHAR(2048) NOT NULL,  
  PRIMARY KEY(CLASSID)  
) IN DATABASE <DATABASE_NAME>;
```

```

CREATE TABLE <SCHEMA_NAME>.SIBLISTING (
  ID INTEGER NOT NULL,
  SCHEMA_NAME VARCHAR(10),
  TABLE_NAME VARCHAR(10) NOT NULL,
  TABLE_TYPE CHAR(1) NOT NULL,
  PRIMARY KEY(ID)
) IN DATABASE <DATABASE_NAME>;

SET CURRENT RULES = 'DB2';

CREATE TABLE <SCHEMA_NAME>.SIBXACTS (
  XID VARCHAR(254) NOT NULL,
  STATE CHAR(1) NOT NULL,
  PRIMARY KEY(XID)
) IN DATABASE <DATABASE_NAME>;

CREATE TABLE <SCHEMA_NAME>.SIBKEYS (
  ID VARCHAR(50) NOT NULL,
  LAST_KEY DECIMAL(19) NOT NULL,
  PRIMARY KEY(ID)
) IN DATABASE <DATABASE_NAME>;

SET CURRENT RULES = 'DB2';

CREATE TABLE <SCHEMA_NAME>.SIB000 (
  ID DECIMAL(19) NOT NULL,
  STREAM_ID DECIMAL(19) NOT NULL,
  TYPE CHAR(2),
  EXPIRY_TIME DECIMAL(19),
  STRATEGY INTEGER,
  REFERENCE DECIMAL(19),
  CLASS_ID INTEGER NOT NULL,
  PRIORITY INTEGER,
  SEQUENCE DECIMAL(19),
  PERMANENT_ID INTEGER,
  TEMPORARY_ID INTEGER,
  LOCK_ID DECIMAL(19),
  DATA_SIZE INTEGER NOT NULL,
  DATA VARCHAR(3360) FOR BIT DATA,
  LONG_DATA BLOB(100M),
  LONG_DATA_ID ROWID GENERATED ALWAYS NOT NULL,
  XID VARCHAR(254),
  DELETED SMALLINT,
  REDELIVERED_COUNT INTEGER,
  DELIVERYDELAY_TIME DECIMAL(19,0),
  PRIMARY KEY(ID)
) IN DATABASE <DATABASE_NAME>;

```

```
CREATE INDEX <SCHEMA_NAME>.SIB000STREAMIX ON <SCHEMA_NAME>.SIB000 (  
  STREAM_ID,  
  SEQUENCE  
) USING STOGROUP SIBSG PRIQTY 500 SECQTY 50;
```

```
SET CURRENT RULES = 'DB2';
```

```
CREATE TABLE <SCHEMA_NAME>.SIB001 (  
  ID DECIMAL(19) NOT NULL,  
  STREAM_ID DECIMAL(19) NOT NULL,  
  TYPE CHAR(2),  
  EXPIRY_TIME DECIMAL(19),  
  STRATEGY INTEGER,  
  REFERENCE DECIMAL(19),  
  CLASS_ID INTEGER NOT NULL,  
  PRIORITY INTEGER,  
  SEQUENCE DECIMAL(19),  
  PERMANENT_ID INTEGER,  
  TEMPORARY_ID INTEGER,  
  LOCK_ID DECIMAL(19),  
  DATA_SIZE INTEGER NOT NULL,  
  DATA VARCHAR(3360) FOR BIT DATA,  
  LONG_DATA BLOB(100M),  
  LONG_DATA_ID ROWID GENERATED ALWAYS NOT NULL,  
  XID VARCHAR(254),  
  DELETED SMALLINT,  
  REDELIVERED_COUNT INTEGER,  
  DELIVERYDELAY_TIME DECIMAL(19,0),  
  PRIMARY KEY(ID)  
) IN DATABASE <DATABASE_NAME>;
```

```
CREATE INDEX <SCHEMA_NAME>.SIB001STREAMIX ON <SCHEMA_NAME>.SIB001 (  
  STREAM_ID,  
  SEQUENCE  
) USING STOGROUP SIBSG PRIQTY 500 SECQTY 50;
```

```

SET CURRENT RULES = 'DB2';

CREATE TABLE <SCHEMA_NAME>.SIB002 (
  ID DECIMAL(19) NOT NULL,
  STREAM_ID DECIMAL(19) NOT NULL,
  TYPE CHAR(2),
  EXPIRY_TIME DECIMAL(19),
  STRATEGY INTEGER,
  REFERENCE DECIMAL(19),
  CLASS_ID INTEGER NOT NULL,
  PRIORITY INTEGER,
  SEQUENCE DECIMAL(19),
  PERMANENT_ID INTEGER,
  TEMPORARY_ID INTEGER,
  LOCK_ID DECIMAL(19),
  DATA_SIZE INTEGER NOT NULL,
  DATA VARCHAR(3360) FOR BIT DATA,
  LONG_DATA BLOB(100M),
  LONG_DATA_ID ROWID GENERATED ALWAYS NOT NULL,
  XID VARCHAR(254),
  DELETED SMALLINT,
  REDELIVERED_COUNT INTEGER,
  DELIVERYDELAY_TIME DECIMAL(19,0),
  PRIMARY KEY(ID)
) IN DATABASE <DATABASE_NAME>;

CREATE INDEX <SCHEMA_NAME>.SIB002STREAMIX ON <SCHEMA_NAME>.SIB002 (
  STREAM_ID,
  SEQUENCE
) USING STOGROUP SIBSG PRIQTY 500 SECQTY 50;

GRANT SELECT,INSERT,UPDATE ON <SCHEMA_NAME>.SIBOWNER TO <DATABASE_USER>;
GRANT SELECT,INSERT,UPDATE ON <SCHEMA_NAME>.SIBOWNER0 TO <DATABASE_USER>;
GRANT SELECT,INSERT ON <SCHEMA_NAME>.SIBCLASSMAP TO <DATABASE_USER>;
GRANT SELECT,INSERT ON <SCHEMA_NAME>.SIBLISTING TO <DATABASE_USER>;
GRANT SELECT,INSERT,DELETE,UPDATE ON <SCHEMA_NAME>.SIB000 TO <DATABASE_USER>;
GRANT SELECT,INSERT,DELETE,UPDATE ON <SCHEMA_NAME>.SIB001 TO <DATABASE_USER>;
GRANT SELECT,INSERT,DELETE,UPDATE ON <SCHEMA_NAME>.SIB002 TO <DATABASE_USER>;
GRANT SELECT,INSERT,UPDATE,DELETE ON <SCHEMA_NAME>.SIBXACTS TO <DATABASE_USER>;
GRANT SELECT,INSERT,UPDATE ON <SCHEMA_NAME>.SIBKEYS TO <DATABASE_USER>;

```

Verification

Once the steps have been completed, the customer can verify the tables have been created correctly by starting the WebSphere for z/OS application server instance created by the **configure** target and ensuring there are no errors related to the EJB Timers or SIB connecting to the database tables.

Notices

Permissions for the use of these publications are granted subject to the following terms and conditions.

APPLICABILITY

These terms and conditions are in addition to any terms of use for the Merative website.

PERSONAL USE

You may reproduce these publications for your personal, noncommercial use provided that all proprietary notices are preserved. You may not distribute, display or make derivative work of these publications, or any portion thereof, without the express consent of Merative.

COMMERCIAL USE

You may reproduce, distribute and display these publications solely within your enterprise provided that all proprietary notices are preserved. You may not make derivative works of these publications, or reproduce, distribute or display these publications or any portion thereof outside your enterprise, without the express consent of Merative.

RIGHTS

Except as expressly granted in this permission, no other permissions, licenses or rights are granted, either express or implied, to the publications or any information, data, software or other intellectual property contained therein.

Merative reserves the right to withdraw the permissions granted herein whenever, in its discretion, the use of the publications is detrimental to its interest or, as determined by Merative, the above instructions are not being properly followed.

You may not download, export or re-export this information except in full compliance with all applicable laws and regulations, including all United States export laws and regulations.

MERATIVE MAKES NO GUARANTEE ABOUT THE CONTENT OF THESE PUBLICATIONS. THE PUBLICATIONS ARE PROVIDED "AS-IS" AND WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING BUT NOT LIMITED TO IMPLIED WARRANTIES OF MERCHANTABILITY, NON-INFRINGEMENT, AND FITNESS FOR A PARTICULAR PURPOSE.

Merative or its licensors may have patents or pending patent applications covering subject matter described in this document. The furnishing of this documentation does not grant you any license to these patents.

Information concerning non-Merative products was obtained from the suppliers of those products, their published announcements or other publicly available sources. Merative has not tested those products and cannot confirm the accuracy of performance, compatibility or any other claims related to non-Merative products. Questions on the capabilities of non-Merative products should be addressed to the suppliers of those products.

Any references in this information to non-Merative websites are provided for convenience only and do not in any manner serve as an endorsement of those websites. The materials at those websites are not part of the materials for this Merative product and use of those websites is at your own risk.

This information contains examples of data and reports used in daily business operations. To illustrate them as completely as possible, the examples include the names of individuals, companies, brands, and products. All of these names are fictitious and any similarity to actual people or business enterprises is entirely coincidental.

The licensed program described in this document and all licensed material available for it are provided by Merative under terms of the Merative Client Agreement.

COPYRIGHT LICENSE:

This information contains sample application programs in source language, which illustrate programming techniques on various operating platforms. You may copy, modify, and distribute these sample programs in any form without payment to Merative, for the purposes of developing, using, marketing or distributing application programs conforming to the application programming interface for the operating platform for which the sample programs are written. These examples have not been thoroughly tested under all conditions. Merative, therefore, cannot guarantee or imply reliability, serviceability, or function of these programs. The sample programs are provided "AS IS", without warranty of any kind. Merative shall not be liable for any damages arising out of your use of the sample programs.

Privacy policy

The Merative privacy policy is available at <https://www.merative.com/privacy>.

Trademarks

Merative™ and the Merative™ logo are trademarks of Merative US L.P. in the United States and other countries.

IBM®, the IBM® logo, and ibm.com® are trademarks or registered trademarks of International Business Machines Corp., registered in many jurisdictions worldwide.

Adobe™, the Adobe™ logo, PostScript™, and the PostScript™ logo are either registered trademarks or trademarks of Adobe™ Systems Incorporated in the United States, and/or other countries.

Oracle and Java are registered trademarks of Oracle and/or its affiliates.

The registered trademark Linux® is used pursuant to a sublicense from the Linux Foundation, the exclusive licensee of Linus Torvalds, owner of the mark on a worldwide basis.

Microsoft™, Windows™, and the Windows™ logo are trademarks of Microsoft™ Corporation in the United States, other countries, or both.

UNIX™ is a registered trademark of The Open Group in the United States and other countries.

Other company, product, and service names may be trademarks or service marks of others.