

The Cohomology of Equivocation

Detecting Split-View Lies in Federated Witness-Log Gossip by Sheaf Consistency

Paper 7 of the Harbor program — the R6 mechanism, its statistical harness, and the consistency-radius theorems

Erich Owens

The Harbor Research Program `erich.owens@gmail.com`

August 2026

Abstract

In a federation of witnesses gossiping signed log heads, an equivocator shows different histories to different neighbors. Pairwise cross-checking catches a lie exactly on the links that are checked; this paper answers, and deliberately answers *only*, the next question: when can an analyst convict inconsistency across a link that was *never* checked? The answer is a sheaf-consistency statement with a sharp topological boundary. Model the gossip graph with a cellular sheaf whose restriction maps are shared-prefix coordinate selections, and compute the least-squares *completion residual* r of the compared-plus-relayed data. Then (i) detection beyond pairwise comparison occurs iff the unchecked edge lies on a cycle whose endpoint reports are relayed to the analyst — on a cut edge $r = 0$ by algebra, and across a truly severed edge equivocation is provably dark; (ii) $r > 0$ is sound: no global history explains the visible data, and *any* offset pattern consistent with it has norm at least r , with equality achieved — r is a certified lower bound on the injected lie, in closed form $r = |s|\sqrt{1 - R_{\text{eff}}(e)}$ for a single-edge lie (the harness’s 1.2247 is $3\sqrt{1 - 5/6}$); (iii) the residual localizes to cycles through the equivocator, and computes in $\tilde{O}(|E| \cdot L)$ via per-coordinate graph Laplacians. The scope discipline is the signature: single equivocator (coalitions on a cycle cancel to zero, measured at 6×10^{-15}), no attribution ever (signatures attribute; cohomology localizes), and vanishing r is never an all-clear. A pre-registered statistical harness returned verdict COMMIT with the cut-edge silence at float epsilon and the severed arm at 0/200. *Express lane: the one-breath sentence opens each section; the formal statement is in the box below it; a reader in a hurry needs nothing else.*

1 The problem: a lie across a link nobody checked

The scene. Six relays in a federation gossip the heads of their signed witness logs. Adjacent relays cross-check: each pair compares the log prefix they share, signs the comparison, and forwards what it heard. Relay q equivocates — it shows one head to its clockwise neighbor and a different head to its counterclockwise neighbor — and it is careful: the one link on which its two stories would collide is exactly the link that is never directly compared, because those two neighbors never reconcile. Every pairwise check in the system passes. The auditor’s table of signed comparisons is green. Has the federation lost?

This is the equivocation problem in its federated form: not “did two conflicting signed statements land on one desk” (that is classical fork detection, and signatures settle it), but “can the *pattern* of everyone else’s consistent reports convict an inconsistency that no single comparison witnessed?” The Harbor program’s ledger scoped result R6 to precisely this question, and the scope discipline is the paper’s signature: we claim detection — a certificate that no single global history explains the visible reports — on an exactly characterized set of topologies and visibility patterns, and we prove darkness everywhere else, rather than letting the word “cohomology” imply more.

Express lane. One sentence per result, formal statements in the boxes. Detection beyond pairwise comparison happens iff the unchecked edge lies on a cycle and its endpoints' reports are relayed to the analyst — cut edges are provably silent, severed edges provably dark (box in §3); the completion residual r is a certified lower bound on the lie any adversary must have injected, with closed form $r = |s|\sqrt{1 - R_{\text{eff}}(e)}$ (box in §5); the residual localizes to cycles through the equivocator and costs at most L scalar Laplacian solves (same box); and the statistical harness that validated all of it was pre-registered and returned COMMIT (box in §4).

The idea in one breath: honest gossip is a global section, so the disagreement data of an honest world is a coboundary — and around every cycle a coboundary must sum to zero, which lets relayed-but-never-compared reports convict an equivocator exactly when the missing comparison closes a loop, and provably never otherwise.

The analogy, mapped by relations. Wristwatches around a table (Figure 1): each adjacent pair reports the *offset* between their watches, never the absolute times. If everyone is consistent, the offsets around the full table telescope to zero — there exists a global assignment of times inducing them. A nonzero loop-sum convicts someone of showing different times to different neighbors, *without knowing any absolute time and without the missing pairwise check*: the rest of the loop substitutes for it. The relation that transfers, not the surface: loop-sum = cocycle condition; missing comparison on a loop = unchecked edge on a cycle; and — the misread to preempt — a watch at the end of a *line* of tables can lie freely, because no loop passes through it: the telescoping argument needs the loop, and so does the theorem.




Figure 1: Relation-map for the mechanism. Wristwatch offsets around a table map to signed-log disagreements around a gossip cycle by *relations*: loop-sum $\leftrightarrow$ cocycle condition; a loop through the missing link $\leftrightarrow$ a cycle through the uncompared edge. The map predicts, correctly, where the mechanism dies: no loop, no telescoping, no detection.

2 The model and the observability contract

The sheaf. Fix a finite gossip graph $G = (V, E)$. Witness v carries a local log state $x_v \in \mathbb{R}^{d_v}$ (its stalk). Each edge $e = \{u, v\}$ carries the *shared prefix* the two endpoints both report — a subset

S_e of coordinates, $|S_e| \leq L$ — and the restriction maps $\rho_{v,e} : \mathbb{R}^{d_v} \rightarrow \mathbb{R}^{|S_e|}$ are coordinate-subset selections. The observable on edge e is the disagreement $g_e = \rho_{u,e}(u\text{'s report}) - \rho_{v,e}(v\text{'s report})$. Honesty means all reports restrict one global section x : then $g = \delta x$ is a coboundary of the sheaf coboundary δ , and every cycle-sum of g vanishes. Equivocation is an offset pattern ε added to q 's per-neighbor reports; it is invisible pairwise on any edge not directly compared, and the question is what survives in H^1 — the obstruction space $\text{coker}(\delta)$, which for prefix restrictions decomposes per shared coordinate c into the cycle spaces of the coordinate subgraphs G_c [verified framework, [2, 3]].

Three-tier visibility — the observability contract. Not every edge is equally visible to the analyst, and the paper's claims are stated *per tier* (Figure 2):

- **compared** — the analyst holds the direct cross-check of the edge: pairwise detection, no cohomology needed;
- **relayed** — both endpoints' reports about the edge reach the analyst by gossip, but the edge itself was never checked by its endpoints: this is the tier where cohomology earns its keep, and only on cycles;
- **severed** — no report about the edge crosses to the analyst at all: the corresponding data block is a free variable of the completion, and equivocation confined there is *provably dark*.

The detector. The *completion residual* is the least-squares defect of the best global explanation of everything visible:

$$r = \min_{x, g_{\text{sev}}} \|g_K - (\delta x)|_K\|_2,$$

the minimum over global sections x and free severed blocks g_{sev} , where K is the compared-plus-relayed edge set. Honest executions give $r = 0$ exactly, for every visibility pattern; $r > 0$ certifies that *no* global history explains the visible data. Equivalently $r = \|\Pi_K g_K\|$, the projection of the visible disagreement data onto the per-coordinate cycle spaces: $r^2 = \sum_c \|\text{Proj}_{\text{cycle}(G_c)} g^c\|^2$ [internal, `sheaf_harness_v2.py`].




Figure 2: The three-tier observability contract. Left: one gossip graph wearing all three tiers — compared (solid), relayed (dashed), severed (dotted). Right: what each tier lets the completion residual prove. The relayed tier splits by topology: on a cycle, $r > 0$ detects (200/200); on a cut edge, $r = 0$ by algebra ($\max$ residual 1.5×10^{-13} over 400 trials); severed blocks are free variables and provably dark (0/200) [internal, `sheaf_harness_v2.py`].

Two defects that taught the model. The first harness (v1) got both halves of this contract wrong, and the rebuild kept the autopsies as named defects with reintroduction mutants. **D1:** v1 drew *random orthonormal projections* as restriction maps; for those, $\text{coker}(\delta)$ generically collapses to 0 and the signal dies — the detector only exists because shared-prefix

restrictions make the cokernel isomorphic to $\bigoplus_c H^1(G_c)$, cycle space tensor shared coordinates. The rebuilt harness refuses D1’s reintroduction by a structural self-check (it observed coker = 0 against $\beta_1 = 7$ and aborted). **D2:** v1 scored “detections” on cut and severed edges — by silently reading hidden-edge data the analyst was not entitled to; the rebuilt harness flags D2’s reintroduction because the mutant’s “partition” residuals come out bit-identical to full visibility [internal, `sheaf_harness_v2.py`]. Both defects are the same lesson: the theorem is about *what the analyst can see*, and an implementation that muddles the observability contract will manufacture either silence or false sight.

3 The mechanism: detection iff the missing edge closes a cycle

*Cohomology detects equivocation beyond pairwise comparison exactly when the uncompar-
ed edge lies on a cycle whose reports are relayed — the cocycle condition substitutes for the
missing comparison; on a cut edge there is nothing to substitute, and the residual is zero by
algebra — formal statement in the box below.*

Theorem 1 (mechanism). In gossip of signed logs with prefix restrictions and the three-tier visibility model, the completion residual detects equivocation beyond pairwise comparison iff the unchecked edge lies on a cycle of its coordinate subgraph *and* its endpoints’ reports are relayed to the analyst: then $r > 0$ proves no global explanation exists. On a cut edge $r = 0$ identically — the coboundary map of a tree (or forest) is surjective onto the visible data, so the free completion absorbs any lie. Across a severed edge, equivocation is provably dark: the severed block is unconstrained, and a consistent counterfactual world always exists.

Verification (minimal pair). C_6 with scalar stalks, lie of size 3 on the one uncompar-
ed cycle edge: every pairwise check passes, harmonic signal $1.225 \neq 0$. The same lie on a
bridge of the path P_6 : signal 0.000 [internal, `sheaf_mechanism_proof.py`]. The structural
identity behind the mechanism — local consistency with no global section — is Abramsky–
Brandenburger contextuality [verified framework, [1]]; the equivocator manufactures for its
neighbors exactly a locally-consistent, globally-unglueable family of views.


Numbers by hand. On C_6 , project the lie onto the cycle: the harmonic component of a
single-edge offset s on an n -cycle is $s/\sqrt{n}$, so the signal is $3/\sqrt{6} = 1.2247$ — the harness’s 1.225
to printed precision, and, in the closed form of §5, $3\sqrt{1 - 5/6}$ [verified]. On P_6 there is no cycle:
the cycle space is zero, the projection is zero, the residual is zero — not small, zero (Figure 3
puts the relayed-cycle, cut, and severed cases side by side on the same six-node graph). *Now
you try:* C_8 , lie of size 2 on the relayed edge — the residual is $2/\sqrt{8} = 0.7071$; the same lie on
any bridge, 0 [verified].

The misread to preempt. “Cohomology sees hidden data” is exactly what the theorem
does *not* say. The residual reads only relayed evidence, and squeezes it through the one con-
straint honesty imposes — cycle-sums vanish. Where no cycle passes (cut edge) or no evidence
arrives (severed edge), there is no constraint to violate and nothing is seen; the harness’s cut-
edge maximum of 1.5×10^{-13} over 400 trials is float epsilon, not a small detection [internal,
`sheaf_harness_v2.py`]. A second misread: the detection statistic is the *data* residual, never
 $\dim H^1$ — a loopy topology has $\beta_1 > 0$ for purely topological reasons on honest data too, so
any counting claim must net β_1 out; the harness prints the structural cokernel separately (e.g.
the two-path split-view topology: $\beta_1 = 1$, coker = 2) and scores only the residual, which is
identically zero for honest worlds.


Honest boundary. Detection requires the reports, not the check: severed links stay dark,
cut edges silent, and the v1 “detections” there were D2 artifacts. Vanishing signal over

R6 regime — detection requires a cycle AND relayed reports; cut edges silent, severed edges dark [internal, `sheaf_harness_v2.py`]

(a) cycle C_6 relayed



(b) path P_6 bridge



(c) cycle C_6 severed




Figure 3: Regime diagram for the mechanism: (a) relayed cycle edge — residual 1.225, detected (200/200 cohomology-only); (b) cut edge — residual 0.000, provably silent; (c) severed cycle edge — provably dark (0/200). Detection requires the cycle *and* the relayed reports; each panel is one clause of the observability contract [internal, `sheaf_harness_v2.py`].

$\mathbb{R}$ is not an all-clear — real coefficients abelianize the obstruction, and contextual models exist whose cohomological invariant vanishes (the Carù gap [5]); §7 prices this. And the mechanism convicts an inconsistency; it does not name its author (§5, §7).

4 The harness: pre-registered gates, verdict COMMIT

Before running, the harness committed to its gates: the completion residual must detect split-view equivocation on relayed cycles where pairwise comparison is blind, and must stay silent on honest worlds, cut edges, and severed arms — it passed, the rival CUT condition was refuted, and both v1 defects are guarded by mutants — verification in the box below.

The design. Two hundred trials per arm at seed 20260816, stalks $\mathbb{R}^5$, shared-prefix sizes 2–4. The detector is the completion residual of §2; the score is *cohomology-only* detections — trials where the residual fires and every pairwise comparison passes. The pre-registered Stage-1 gates from the rescued prototyping plan: (i) the split-view arm must be detected cohomology-only; (ii) the control arms must be silent.

Harness results (all arms, seed 20260816). Partition-on-a-cycle split view (`two_path`): 200/200 cohomology-only — pairwise blind in every trial. Severed-cycle arm: 0/200 — the honest boundary, measured. Cut edge (`single_bridge`): max residual 1.5×10^{-13} over 400 trials — silence at float epsilon. Full visibility: 0 cohomology-only detections and 200/200 redundant (pairwise catches everything first, as it must). Expander with 3 severed and 3 relayed edges: partition-straddling equivocator 113/200 cohomology-only, 87 dark — both clauses of the contract live in one topology. Localization: the max-residual edge lies on a known-graph cycle 200/200 (upgraded to “through the equivocator” as a theorem in §5). Pre-registered gates (i) and (ii) **PASS**; verdict **COMMIT**. The rival CUT condition — “residual detections are just pairwise detections in disguise” — is refuted: 313 of 1101 residual detections across arms were pairwise-blind. Mutation suite: D1 reintroduction refused by the structural self-check (coker = 0 against $\beta_1 = 7$); D2 reintroduction flagged (mutant “partition” residuals bit-identical to full visibility); no-equivocator control 0/200 [internal, `sheaf_harness_v2.py`].

What it buys. The W7 mechanism proof was a two-topology existence demonstration; the harness upgrades it to a validated statistical detector with its false-positive behavior measured (honest and control arms identically zero), its blindness measured (severed arm 0/200, the

expander’s 87 dark trials), and its guards regression-tested by reintroducing the exact defects that fooled v1. The three-tier contract stopped being prose and became the experiment’s arm structure.

Honest boundary. The harness validates the detector at the sharpened scope only: synthetic gossip, prefix restrictions, single equivocator per trial, $\mathbb{R}^5$ stalks. The 113/200 expander number is a property of that topology’s severed/relayed mix, not a universal rate. And a statistical PASS is not yet a theorem — which is exactly why §5 exists.

5 The consistency radius: what $r > 0$ certifies, where it points, what it costs

The residual r is the exact minimum lie any adversary must have injected to produce the visible data, it localizes to cycles through the equivocator, and it computes as at most L scalar graph-Laplacian solves — with the single-equivocator condition proved to be the honest scope, because coalition lies on a cycle can cancel r to zero — formal statements in the box below.

Intuition. Robinson’s consistency radius asks how far local data sits from the nearest global section [4]; our r is its least-squares form under the completion over severed blocks. The new content is that r is not merely a distance — it is a *certificate about the adversary*: every offset pattern that could have produced the visible data is at least this large, and one of exactly this size exists. The topology enters through electrical network theory: a lie on edge e hides in proportion to how well the rest of the graph can imitate it, which is the effective resistance $R_{\text{eff}}(e)$ — on a bridge $R_{\text{eff}} = 1$ and the lie hides completely; on a long cycle $R_{\text{eff}} \rightarrow 1$ and the certified fraction $\sqrt{1 - R_{\text{eff}}}$ decays like $1/\sqrt{n}$ (Figure 4).

Theorem CR-1 (soundness and achievability). For the completion-residual detector with prefix restrictions and three-tier visibility: $r > 0$ iff no global section explains the compared-plus-relayed data, and honest executions give $r = 0$ exactly, for every visibility pattern. Every offset pattern ε consistent with the visible data satisfies $\|\varepsilon_K\| \geq r$, with equality at the completion — r is the exact minimum lie. For a single equivocator q with offset vector o and visible-lie operator A_q : $\sigma_{\min}^+(\Pi_K A_q) \|o_{\perp}\| \leq r \leq \|o_{\perp}\|$, where $o_{\perp}$ is the component of o outside $\ker A_q$. For a single-edge lie of size s in coordinate c ,

$$r = |s| \sqrt{1 - R_{\text{eff}}^G(e)} \quad \text{— on } C_n : |s|/\sqrt{n}; \text{ the harness’s 1.2247 is } 3\sqrt{1 - 5/6}.$$

Theorem CR-2 (localization). Noise-free, single equivocator: the support of the edge residual lies on cycles of the coordinate subgraphs through q — by the electrical-flow support argument, the harness’s 200/200 localization is now a theorem. With bounded noise η , localization is guaranteed while $2\|\eta_K\| < \max_f \|(\Pi_K \varepsilon_K)_f\|$.

Theorem CR-3 (complexity). Because δ_K splits per shared coordinate into graph incidence operators, r is one sparse least-squares problem that decomposes into at most L scalar graph-Laplacian systems: $\tilde{O}(|E| \cdot L \log(1/\epsilon))$ with SDD solvers [7]. (Bach’s #P-hardness of sheaf cohomology [8] concerns coherent sheaves on projective space — the wrong category; finite cellular sheaves over $\mathbb{R}$ on graphs are linear algebra.)

Verification. Soundness 0/600 violations; achievability 600/600 (a consistent pattern of norm exactly r constructed every time). The R_{eff} closed form is exact on C_4 – C_{12} and 200 random graphs; the $\sigma_{\min}^+$ lower bound is tight under the adversarial offset ($r/\|o_{\perp}\| = \sigma_{\min}^+ = 0.4082$); a uniform kernel lie of norm 5 gives $r = 2 \times 10^{-14}$ — invisible in principle, correctly not flagged. Localization 200/200 (two-cycles topology) plus 128/128 (severed expanders); noise boundary measured: $\geq 95\%$ localization up to $\sigma_{\eta}/\sigma_{\text{eq}} \approx 0.1$, 76.5% at 0.2; sufficient-condition violations 0. Timing slope versus $|E|$ (wall-clock, machine-dependent — only

the qualitative split reproduces across runs): conjugate gradient stays well under the 1.6 gate (≈ 0.6 – 0.7 across repeated runs) while dense solve is consistently super-linear and several times steeper ($\gtrsim 3.0$); it is the CR-3 decomposition, not the two digits, that the gate certifies. Two coordinated liars on a common cycle: each alone certified at $r \geq |s|/\sqrt{8}$, the coalition cancels to $r = 6 \times 10^{-15}$. The D2-unmasked mutant fires on a severed lie at 0.839 — exactly the full-visibility value, caught [internal, `sheaf_consistency_radius.py`].

Numbers by hand. C_6 : R_{eff} of an edge is $\frac{n-1}{n} = \frac{5}{6}$ (the rest of the cycle is a 5-edge series path in parallel with the edge), so a lie of 3 certifies $r = 3\sqrt{1/6} = 1.2247$ [verified] — the number the mechanism script printed a week before the closed form existed. The $\sigma_{\min}^+$ tightness value 0.4082 is $1/\sqrt{6}$: the same geometry seen from the operator side [verified]. *Now you try:* a federation ring of 12 relays with one never-compared link and a head-offset lie of 0.5 — the certified minimum lie is $0.5/\sqrt{12} = 0.144$; double the ring and the certificate shrinks by $\sqrt{2}$: long cycles dilute conviction, which is an argument for short reconciliation loops in federation design.




Figure 4: The CR-1 closed form: certified residual per unit lie, $r/|s| = \sqrt{1 - R_{\text{eff}}(e)}$, against the effective resistance of the lied-on edge in its coordinate subgraph. The cycle family C_n sits at $R_{\text{eff}} = \frac{n-1}{n}$ (the harness’s C_6 point marked, $3\sqrt{1 - 5/6} = 1.2247$); the cut-edge corner $R_{\text{eff}} = 1$ is provable silence [verified; closed form exact on C_4 – C_{12} and 200 random graphs, `sheaf_consistency_radius.py`].

What it buys. The harness’s statistic is upgraded to a certificate with an interpretation a federation operator can act on: r is the smallest lie consistent with what you saw, the hot edges lie on cycles through the culprit’s neighborhood, and the whole computation is a handful of Laplacian solves — cheap enough to run on every gossip round. The closed form also converts topology into policy: effective resistance is the price list for where a federation should force direct reconciliation (bridges: mandatory — the residual cannot help there) and where relayed gossip suffices (short cycles: cheap certified detection).

6 Related work: imported, adjacent, and new

Imported. The structural identity — local consistency without a global section — is Abramsky–Brandenburger contextuality [1]; the equivocator’s split view is an empirical model that is locally consistent and globally unglueable, and we use the sheaf language exactly as that program fixed

it. Cellular sheaves on graphs and their coboundary calculus are Curry [2]; the sheaf Laplacian and its harmonic/spectral reading are Hansen–Ghrist [3]. The consistency radius — distance from local data to the nearest global section, with its sup-norm corollaries — is Robinson [4]; our r is its least-squares completion form. The nearly-linear Laplacian solvers behind CR-3 are the Spielman–Teng line [7].

Adjacent, and honestly positioned. Carù [5] shows the Čech-cohomological obstruction with abelian coefficients can vanish on contextual models — imported here as the reason vanishing r over $\mathbb{R}$ is never an all-clear. Sheng et al.’s BFT forensics [6] works the attribution side: with signed protocol messages, equivocation yields a transferable cryptographic proof *naming* the culprit, and their impossibility results bound when. We sit deliberately on the other side of that line: cohomology reads unsigned *structure* — it can convict “someone on these cycles lied” from evidence no signature covers (relayed, never-compared links), and can never name the liar (§7); signatures attribute, cohomology localizes, and a deployed federation wants both. Bach [8] is cited only to preempt a category error: #P-hardness of coherent-sheaf cohomology does not touch finite cellular sheaves on graphs.

New, honestly. No component of the mathematics is exotic: incidence matrices, cycle spaces, effective resistance, least squares. The contribution is the assembled result at its exact scope: (1) the mechanism boundary — detection beyond pairwise iff the missing edge closes a relayed cycle, with cut-edge silence and severed darkness proved rather than observed; (2) the three-tier observability contract as the object the theorems quantify over, extracted from two named defects that each faked a different clause of it; (3) the certificate reading of the completion residual — r as the exact minimum injected lie, with the R_{eff} closed form tying conviction strength to federation topology; and (4) the coalition-cancellation construction that fixes the honest scope at single-equivocator, turning what would be a reviewer’s counterexample into the paper’s own boundary statement.

7 The boundary is load-bearing

This paper’s claims are narrow by construction, and the narrowness is the result. Each clause below is a theorem-grade limitation, stated at the same prominence as the theorems, because a federation that deploys this detector believing any one of them false will be harmed by the belief.

Honest boundary — the four clauses.

- *Single equivocator is the scope, and provably so.* Detection and localization are single-equivocator statements. A coalition whose combined lie is a coboundary is a consistent counterfactual world: two coordinated liars on a common cycle, each alone certified at $r \geq |s|/\sqrt{8}$, jointly cancel to $r = 6 \times 10^{-15}$ [internal, `sheaf_consistency_radius.py`]. r never overstates the lie, but it can understate a coalition’s to zero — soundness is unconditional, detection is not.
- *No attribution, ever.* A $+o$ lie by q toward w and a $-o$ lie by w toward q produce identical observations — the identical-data twin construction. The residual localizes to cycles through the equivocator; it cannot distinguish which endpoint of the offending relationship lied. Naming culprits is the signatures-and-forensics business [6], which this detector complements and must never be marketed as replacing.
- *Vanishing r is not an all-clear.* Three independent reasons: uniform (kernel) lies move every neighbor’s view identically and are invisible in principle ($\|o\| = 5$, $r = 2 \times 10^{-14}$ [internal]); severed edges admit consistent counterfactuals by construction; and over $\mathbb{R}$ the obstruction is abelianized, so a vanishing real-coefficient signal does not certify gluability in richer coefficient systems (the Carù gap [5]). $r = 0$ means “no conviction

from this evidence,” never “honest.”

- *Severed darkness, and the noise floor.* Where no report crosses, the theorem is that nothing can be seen — budget accordingly (force comparison on bridges; keep reconciliation loops short). Under measurement noise, soundness needs a threshold above the honest floor $\|\Pi_K \eta\|$: the measured localization boundary is $\geq 95\%$ at noise-to-lie ratio 0.1 falling to 76.5% at 0.2 [internal], and below threshold the certificate reverts to “consistent with noise.”

The scope discipline pays twice. Inside the boundary the claims are sharp enough to certify (a lower bound on the lie, a support statement, a solver cost); outside it the paper states its own counterexamples with witnesses, so the failure modes are part of the artifact rather than awaiting discovery by an adversary who read the appendix more carefully than the authors.

Reproducibility

Every [internal] number regenerates deterministically at seed 20260816 from three self-contained scripts shipped with the program’s results estate: `sheaf_mechanism_proof.py` (the C_6/P_6 minimal pair: harmonic signal 1.225 versus 0.000), `sheaf_harness_v2.py` (all harness arms of §4, the pre-registered gates, the D1/D2 reintroduction mutants, and the structural β_1 /cokernel print-out), and `sheaf_consistency_radius.py` (CR-1/2/3: the 0/600–600/600 soundness/achievability sweep, the R_{eff} closed-form checks on C_4 – C_{12} and 200 random graphs, the localization and noise-boundary measurements, the timing slopes, and the coalition-cancellation witness). Each script exits nonzero on any failed check. Every [verified] number is recomputable by hand from the closed forms restated in the boxes. Figures regenerate from `figures/src/` at the same seed. The one exception to bit-exact reproduction: CR-3’s timing slopes are wall-clock and machine-dependent, so the script asserts and re-asserts only the qualitative gate (conjugate-gradient sub-1.6, dense solve several times steeper), not the printed digits.

References

- [1] S. Abramsky and A. Brandenburger. The sheaf-theoretic structure of non-locality and contextuality. *New Journal of Physics*, 13:113036, 2011.
- [2] J. M. Curry. *Sheaves, Cosheaves and Applications*. PhD thesis, University of Pennsylvania, 2014.
- [3] J. Hansen and R. Ghrist. Toward a spectral theory of cellular sheaves. *Journal of Applied and Computational Topology*, 3:315–358, 2019.
- [4] M. Robinson. Sheaves are the canonical data structure for sensor integration. *Information Fusion*, 36:208–224, 2017.
- [5] G. Carù. On the cohomology of contextuality. In *Proc. 13th International Conference on Quantum Physics and Logic (QPL 2016)*, EPTCS 236, pp. 21–39, 2017.
- [6] P. Sheng, G. Wang, K. Nayak, S. Kannan, and P. Viswanath. BFT protocol forensics. In *Proc. ACM Conference on Computer and Communications Security (CCS)*, pp. 1722–1743, 2021.
- [7] D. A. Spielman and S.-H. Teng. Nearly-linear time algorithms for graph partitioning, graph sparsification, and solving linear systems. In *Proc. 36th ACM Symposium on Theory of Computing (STOC)*, pp. 81–90, 2004.

- [8] E. Bach. Sheaf cohomology is $\#P$ -hard. *Journal of Symbolic Computation*, 27(4):429–433, 1999.