MRDX

Common information repository

Object code	DMC-MRDX-A-00-00-0000-00A-00KA-D	**Issue**	009-00 (revised)
Issue date	2026-06-30	**Language**	en-GB
Responsible partner	AERALIS S.A.S. (U8025)	**Originator**	AERALIS S.A.S. — Technical Data Valmont (U8025)
Security	01 — Unclassified	**Quality assurance**	Second verification (tabtop)
Applicability	All MRDX data modules		

Warning repository

IDENTIFIER	ENTRY
MRDX-W-0001	**WARNING** Make sure that the hydraulic systems are depressurized before you disconnect a hydraulic line. Hydraulic fluid at 206 bar (2988 psi) can cause injury to persons and damage to equipment.
MRDX-W-0002	**WARNING** Make sure that the slat and flap travel areas are clear of persons and equipment before a system test. The surfaces move without a warning when the test is started.
MRDX-W-0014	**WARNING** Do not touch the brake units after a landing until they have cooled. Surface temperatures of more than 300 °C can cause burns.

Caution repository

IDENTIFIER	ENTRY
MRDX-C-0007	**CAUTION** Do not let a line replaceable unit hang on its hydraulic or electrical connections. Damage to the couplings and to the connector shells can occur.
MRDX-C-0011	**CAUTION** Do not use a solvent on a painted surface of the belly fairing. Damage to the protective coating can occur.

Supply repository

IDENTIFIER	ENTRY
MRDX-S-02-004	**Name:** Hydraulic fluid, phosphate ester, type IV **Manufacturer code:** 81349 **Part number:** NSA307110
MRDX-S-19-003	**Name:** Lockwire, corrosion resistant steel, 0.8 mm **Manufacturer code:** 81349 **Part number:** NSA935403-08

Tool repository

IDENTIFIER	ENTRY
MRDX-T-27-001	**Name:** Sling, power control unit handling **Manufacturer code:** U8025 **Part number:** 98D27814500000
MRDX-T-45-002	**Name:** Portable maintenance access terminal **Manufacturer code:** U8025 **Part number:** 98D45111000000