MRDX wiring data

Field definitions

Object code	DMC-MRDX-A-00-00-0000-00A-029A-D	**Issue**	001-00 (new)
Issue date	2026-03-03	**Language**	en-GB
Responsible partner	AERALIS S.A.S. (U8025)	**Originator**	AERALIS S.A.S. — Electrical Design Valmont (U8025)
Security	02 — Restricted	**Quality assurance**	Unverified
Applicability	All MRDX wiring data		

Wiring data field definitions

FIELD	CONTENT	FORMAT	USE
WIRE-ID	Wire identification, unique in the aircraft	AAAAAA-ANN	Mandatory
GAUGE	Wire gauge, American wire gauge	NN	Mandatory
WIRE-TYPE	Insulation and construction standard	AAAAA	Mandatory
FROM	Connector and contact at the origin end	AAAANN-ANN	Mandatory
TO	Connector and contact at the destination end	AAAANN-ANN	Mandatory
LENGTH	Cut length, including the service loop	N.NN m	Optional
HARNESS	Harness the wire is routed in	NNANNN	Mandatory
SHIELD	Shield termination end, F for from, T for to, B for both	A	Optional

These are the fields the MRDX wiring data uses. A wiring data module must populate every field marked mandatory; a field marked optional may be left out when the value is not known at the time of delivery.