libcin

Generated by Doxygen 1.8.13

Contents

1	Fast	CCD Co	ommunication Library (libcin)	1
2	Mod	ule Inde	ex	3
	2.1	Module	es	3
3	Clas	s Index	c	5
	3.1	Class I	List	5
4	File	Index		7
	4.1	File Lis	st	7
5	Mod	ule Doo	cumentation	9
	5.1	Cin Co	ontrol Initialization Routines	9
		5.1.1	Detailed Description	9
		5.1.2	Function Documentation	9
			5.1.2.1 cin_ctl_destroy()	9
			5.1.2.2 cin_ctl_init()	10
			5.1.2.3 cin_data_send_magic()	10
	5.2	Cin Co	ontrol Read/Rwite Routines	12
		5.2.1	Detailed Description	12
		5.2.2	Function Documentation	12
			5.2.2.1 cin_ctl_read()	12
			5.2.2.2 cin_ctl_stream_write()	12
			5.2.2.3 cin_ctl_write()	13
			5.2.2.4 cin ctl write with readback()	13

ii CONTENTS

5.3	CIN Fi	mware Upload Routines	15
	5.3.1	Detailed Description	15
5.4	CIN FO	LK Configuration Routines	16
	5.4.1	Detailed Description	16
5.5	CIN St	tus Routines	17
	5.5.1	Detailed Description	17
5.6	CIN Co	ntrol Bias Routines	18
	5.6.1	Detailed Description	18
5.7	CIN C	Introl Timing Routines	19
	5.7.1	Detailed Description	19
5.8	CIN Da	ta Initialization Routines	20
	5.8.1	Detailed Description	20
	5.8.2	Function Documentation	20
		5.8.2.1 cin_data_destroy()	20
		5.8.2.2 cin_data_init()	20
5.9	CIN Da	ta Framestore Functions	23
	5.9.1	Detailed Description	23
	5.9.2	Function Documentation	23
		5.9.2.1 cin_data_framestore_disable()	23
		5.9.2.2 cin_data_framestore_skip()	23
		5.9.2.3 cin_data_framestore_trigger()	24
		5.9.2.4 cin_data_framestore_trigger_enable()	24
		5.9.2.5 cin_data_get_framestore_counter()	24

CONTENTS

6	Clas	s Documentation	27
	6.1	cin_config_timing Struct Reference	27
		6.1.1 Member Data Documentation	27
		6.1.1.1 cols	27
		6.1.1.2 data	27
		6.1.1.3 data_len	27
		6.1.1.4 fclk_freq	28
		6.1.1.5 framestore	28
		6.1.1.6 name	28
		6.1.1.7 overscan	28
		6.1.1.8 rows	28
	6.2	cin_ctl Struct Reference	28
		6.2.1 Member Data Documentation	29
		6.2.1.1 fclk_time_factor	29
	6.3	cin_ctl_id Struct Reference	29
	6.4	cin_ctl_listener Struct Reference	29
	6.5	cin_ctl_pwr_mon_t Struct Reference	30
	6.6	cin_ctl_pwr_val Struct Reference	30
	6.7	cin_data Struct Reference	30
	6.8	cin_data_callbacks Struct Reference	31
	6.9	cin_data_descramble_map_t Struct Reference	31
	6.10	cin_data_frame Struct Reference	32
	6.11	cin_data_packet Struct Reference	32
	6.12	cin_data_proc Struct Reference	32
	6.13	cin_data_stats Struct Reference	33
	6.14	cin_data_threads Struct Reference	33
	6.15	cin_map_t Struct Reference	33
	6.16	cin_port Struct Reference	34
	6.17	fifo Struct Reference	34

iv CONTENTS

7	File	Docum	entation		35
	7.1	src/cin	.h File Ref	erence	35
		7.1.1	Detailed	Description	40
		7.1.2	LICENSE	=	40
		7.1.3	DESCRI	PTION	41
		7.1.4	Macro De	efinition Documentation	41
			7.1.4.1	CIN_CONFIG_MAX_TIMING_DATA	41
			7.1.4.2	CIN_CONFIG_MAX_TIMING_MODES	41
			7.1.4.3	CIN_CTL_BIAS_OFFSET	41
	7.2	src/cin	_register_r	map.h File Reference	41
		7.2.1	Detailed	Description	46
		7.2.2	LICENSE	E	46
		7.2.3	DESCRI	PTION	47
		7.2.4	TIMING		47
		7.2.5	Macro De	efinition Documentation	47
			7.2.5.1	CMD_DISABLE_CLKS	47
			7.2.5.2	CMD_ENABLE_CLKS	47
			7.2.5.3	CMD_FCLK_250	47
			7.2.5.4	CMD_FCLK_COMMIT	47
			7.2.5.5	CMD_MON_START	47
			7.2.5.6	CMD_MON_STOP	48
			7.2.5.7	CMD_PS_ENABLE	48
			7.2.5.8	CMD_PS_POWERDOWN	48
			7.2.5.9	CMD_READ_REG	48
			7.2.5.10	CMD_RESET_FRAME_COUNT	48
			7.2.5.11	CMD_SEND_FCRIC_CONFIG	48
			7.2.5.12	CMD_SEND_SYNC_PULSE	48
			7.2.5.13	CMD_SYNC_DETECTOR2READOUT	48
			7.2.5.14	CMD_WR_CCD_BIAS_REG	49
			7.2.5.15	CMD_WR_CCD_CLOCK_REG	49

CONTENTS

7.2.5.16	REG_BIASCONFIGREGISTER0_REG	49
7.2.5.17	REG_BIASREGISTERDATAOUT	49
7.2.5.18	REG_CLOCK_EN_REG	49
7.2.5.19	REG_CLOCKCONFIGREGISTER0_REG	49
7.2.5.20	REG_COMMAND	49
7.2.5.21	REG_DEBUGCOUNTER04_REG	49
7.2.5.22	REG_DELAYTOSHUTTERLSB_REG	50
7.2.5.23	REG_ETH_ENABLE	50
7.2.5.24	REG_ETH_RESET	50
7.2.5.25	REG_EXPOSURETIMELSB_REG	50
7.2.5.26	REG_EXPOSURETIMEMSB_REG	50
7.2.5.27	REG_FCLK_I2C_ADDRESS	50
7.2.5.28	REG_FCLK_I2C_DATA_RD	50
7.2.5.29	REG_FCLK_I2C_DATA_WR	51
7.2.5.30	REG_FCLK_SET5	51
7.2.5.31	REG_FPGA_VERSION	51
7.2.5.32	REG_FRM_10GbE_SEL	51
7.2.5.33	REG_FRM_FPGA_VERSION	51
7.2.5.34	REG_FRM_RESET	51
7.2.5.35	REG_FRM_SANDBOX_REG0F	51
7.2.5.36	REG_FRM_STREAM_TYPE	52
7.2.5.37	REG_IMON_ADC0_CHF	52
7.2.5.38	REG_MAC_CFG_VECTOR1	52
7.2.5.39	REG_MAC_CFG_VECTOR2	52
7.2.5.40	REG_MAC_STATS2_FAB2B1	52
7.2.5.41	REG_PHY1_MDIO_CMD	52
7.2.5.42	REG_PS_ENABLE	52
7.2.5.43	REG_PS_SYNC_DIV0	52
7.2.5.44	REG_PS_SYNC_DIV1	53
7.2.5.45	REG_PS_SYNC_DIV2	53
7.2.5.46	REG_PS_SYNC_DIV3	53
7.2.5.47	REG_PS_SYNC_DIV4	53
7.2.5.48	REG_SANDBOX_REG0F	53
7.2.5.49	REG_SI570_REG3	53
7.2.5.50	REG_SRAM_COMMAND	53
7.2.5.51	REG_SRAM_STATUS0	54
7.2.5.52	REG_STREAM_TYPE	54
7.2.5.53	REG_TRIGGERMASK_REG	54
7.2.5.54	REG_TRIGGERREPETITIONTIMELSB_REG	54
7.2.5.55	REG_TRIGGERREPETITIONTIMEMSB_REG	54
		55
		J

Index

Chapter 1

FastCCD Communication Library (libcin)

Introduction

This library, based in C is designed to control the FastCCD detector from Lawrence Berkeley National Laboratory. It controls both camera control functions and data acquisition (frame acquisition). It is separated into two distinct parts, the control part <code>,cin_ctl</code>, and the data (image) part named <code>cin_data</code>. It was written in part for use with areaDetector.

Prerequisites

The library relies on the following:

- libbsd (Used for string manipulation)
- libconfig (Used for nice config files)
- libpthread (Used for threading)
- librt (Used for time functions)

Installation

Installation of the library is like most unix based source packages:

^{./}make ./make doc ./make test

^{./}make install

TCP/IP Stack Tuning

In order for the CIN data to operate efficiently, the 10G interface on the host computer needs to be tuned. This needs to be done by adding the following to the file /etc/sysctl.conf.

```
# Increase the maximum buffer that user programs can request
# 2147483647 = 2048 Mb
net.core.rmem_max=2147483647
net.core.wmem_max=2147483647
# Set a default value 10 times bigger
net.core.rmem_default=1000000
net.core.wmem_default=1000000
# increase the length of the processor input queue
net.core.netdev_max_backlog = 250000
# recommended for hosts with jumbo frames enabled
net.ipv4.tcp_mtu_probing=1
```

These can be reread by the system without rebooting by entering the command:

```
$sudo sysctl --system
```

Versioning

For the versions available, see the tags on this repository.

Authors

• Stuart B. Wilkins - stuwilkins

See also the list of contributors who participated in this project.

License

This project is licensed under the BSD License - see the LICENSE file for details

Acknowledgments

A huge thanks to Peter Dennes, John Joseph and the detector team at LBNL and the team at Sydor Instruments.

Chapter 2

Module Index

2.1 Modules

Here is a list of all modules:

Cin Control Initialization Routines	 9
Cin Control Read/Rwite Routines	 12
CIN Firmware Upload Routines	 15
CIN FCLK Configuration Routines	 16
CIN Status Routines	 17
CIN Control Bias Routines	 18
CIN COntrol Timing Routines	 19
CIN Data Initialization Routines	 20
CIN Data Framestore Functions	 23

4 Module Index

Chapter 3

Class Index

3.1 Class List

Here are the classes, structs, unions and interfaces with brief descriptions:

cin_config_timing	27
	28
$ cin_ctl_id \dots \dots \dots \dots \dots \dots \dots \dots \dots $	29
cin_ctl_listener	29
	30
	30
	30
cin_data_callbacks	31
	31
	32
	32
	32
	33
	33
$cin_{map}\underline{t}\;\ldots\ldots\ldots\ldots\ldots\ldots\ldots$	33
cin_port	34
fifo	34

6 Class Index

Chapter 4

File Index

4.1 File List

Here is a list of all documented files with brief descriptions:

src/cin.h			 							 				 							35
src/cin_register_map.h			 							 				 							41
src/cinregisters.h			 							 				 							??
src/common.h			 							 				 							??
src/config.h			 							 				 							??
src/control.h			 							 				 							??
src/data.h			 							 				 							??
src/descramble.h			 							 				 							??
src/descramble_map.h	l		 							 				 							??
src/fifo.h			 							 				 							??
src/report.h			 							 				 							??

8 File Index

Chapter 5

Module Documentation

5.1 Cin Control Initialization Routines

Functions

- int cin_ctl_init (cin_ctl_t *cin, char *addr, uint16_t port, uint16_t sport, char *bind_addr, uint16_t bind_port, uint16_t bind_sport)
- int cin_ctl_destroy (cin_ctl_t *cin)
- void cin_ctl_message (cin_ctl_t *cin, char *message, int severity)
- void cin_ctl_set_msg_callback (cin_ctl_t *cin, void *msg_callback, void *ptr)
- int cin_data_send_magic (cin_data_t *cin)

5.1.1 Detailed Description

5.1.2 Function Documentation

5.1.2.1 cin_ctl_destroy()

Destroy (close) the cin control library

Close connections, free memory and exit library

Parameters

cin handle to cin library

Returns

Returns 0 on sucsess non-zero if error

5.1.2.2 cin_ctl_init()

Initialize the cin control library

Initialize the control structures and communications with the CIN via the control interface. This function opens the UDP ports and starts a listening thread to recieve packets from the CIN.

Parameters

cin	handle to cin library								
addr	ip address of CIN base address								
port	UDP port of cin								
sport	stream output UDP port of cin								
bind_addr	ip address to bind to								
bind_port	input udp port of cin								
bind_sport	stream input udp port of cin								

Returns

Returns 0 on sucsess non-zero if error

5.1.2.3 cin_data_send_magic()

Send a magic packet to the CIN to initialize data

Parameters

cin	handle to cin library

Returns 0 on sucsess non-zero if error

5.2 Cin Control Read/Rwite Routines

Functions

- int cin_ctl_read (cin_ctl_t *cin, uint16_t reg, uint16_t *val, int wait)
 int cin_ctl_write (cin_ctl_t *cin, uint16_t reg, uint16_t val, int wait)
- int cin_ctl_stream_write (cin_ctl_t *cin, unsigned char *val, int size)
- int cin_ctl_write_with_readback (cin_ctl_t *cin, uint16_t reg, uint16_t val)
- int cin_ctl_pwr (cin_ctl_t *cin, int pwr)
- int cin ctl fp pwr (cin ctl t *cin, int pwr)
- int cin_ctl_fo_test_pattern (cin_ctl_t *cin, int on_off)

5.2.1 Detailed Description

5.2.2 Function Documentation

5.2.2.1 cin_ctl_read()

Read register from CIN

Parameters

cin	handle to cin library
reg	register to read
val	variable to read value of register to
wait	if non-zero, wait a predefined time before read command (for i2c)

Returns

Returns 0 on sucsess non-zero if error

5.2.2.2 cin_ctl_stream_write()

Write stream data to CIN

Parameters

cin	handle to cin library	
val	array of values to write	
size	size of array pointed to by val	

Write stream data to cin in form of 16 bit array.

Returns

Returns 0 on sucsess non-zero if error

5.2.2.3 cin_ctl_write()

Write register to CIN

Parameters

cin	handle to cin library
reg	register to write to
val	value to write to register
wait	if non-zero

Write register value to CIN. If wait is non-zero then wait a sleep time of i CIN_CTL_WRITE_SLEEP before releasing the mutex to add flow control to the cin.

Returns

Returns 0 on sucsess non-zero if error

5.2.2.4 cin_ctl_write_with_readback()

Write register to CIN with readback verification

Parameters

cin	handle to cin library
reg	register to write to
val	value to write to register

Write register value to CIN. Follow write with read of register and compare value. CIN_CTL_WRITE_SLEEP before releasing the mutex to add flow control to the cin.

Returns

Returns 0 on sucsess non-zero if error

5.3 CIN Firmware Upload Routines

Functions

- int cin_ctl_load_config (cin_ctl_t *cin, char *filename)
- int cin_ctl_load_firmware (cin_ctl_t *cin)
- int cin_ctl_load_firmware_file (cin_ctl_t *cin, char *filename)
- int cin_ctl_load_firmware_data (cin_ctl_t *cin, unsigned char *data, int data_len)

5.3.1 Detailed Description

Firmware upload routines

5.4 CIN FCLK Configuration Routines

Functions

- int cin_ctl_get_fclk (cin_ctl_t *cin, int *clkfreq)
- int cin_ctl_set_fclk (cin_ctl_t *cin, int clkfreq)

5.4.1 Detailed Description

FCLK (Internal FPGA Clock) Routines

5.5 CIN Status Routines 17

5.5 CIN Status Routines

Functions

- int cin_ctl_get_cfg_fpga_status (cin_ctl_t *cin, uint16_t *_val)
- int cin_ctl_get_id (cin_ctl_t *cin, cin_ctl_id_t *_val)
- int $cin_ctl_get_dcm_status$ ($cin_ctl_t *cin$, $uint16_t *_val$)
- int cin_ctl_get_power_status (cin_ctl_t *cin, int full, int *pwr, cin_ctl_pwr_mon_t *values)

5.5.1 Detailed Description

Status Routines

5.6 CIN Control Bias Routines

Functions

- int cin_ctl_set_bias (cin_ctl_t *cin, int val)
- int cin_ctl_get_bias (cin_ctl_t *cin, int *val)
- int cin_ctl_set_bias_regs (cin_ctl_t *cin, uint16_t *vals, int verify)
- int cin_ctl_get_bias_regs (cin_ctl_t *cin, uint16_t *vals)
- int cin_ctl_set_bias_voltages (cin_ctl_t *cin, float *voltage, int verify)
- int cin_ctl_get_bias_voltages (cin_ctl_t *cin, float *voltage, uint16_t *regs)

5.6.1 Detailed Description

Initialization group

5.7 CIN COntrol Timing Routines

Functions

- int cin_ctl_set_timing_regs (cin_ctl_t *cin, uint16_t *vals, int vals_len)
- int cin_ctl_get_timing_regs (cin_ctl_t *cin, uint16_t *vals, int vals_len)

5.7.1 Detailed Description

Timing setup group

5.8 CIN Data Initialization Routines

Functions

• int cin_data_init (cin_data_t *cin, char *addr, uint16_t port, char *bind_addr, uint16_t bind_port, int rcvbuf, int packet_buffer_len, int frame_buffer_len, cin_data_callback push_callback, cin_data_callback pop_callback, void *usr_ptr)

```
    void cin_data_destroy (cin_data_t *cin)
```

5.8.1 Detailed Description

Initialization group

5.8.2 Function Documentation

```
5.8.2.1 cin_data_destroy()
```

Close the cin data library and cleanup

Stop all the processing threads and join them to the main thread. This function blocks until all threads have joined the main thread (program). This should be called to clean up the library before the program is exited

Parameters

```
cin Handle to cin data library
```

5.8.2.2 cin_data_init()

Initialize the cin data library

Initialize the data handeling routines and start the threads for listening.

Parameters

cin	Handle to cin data library
addr	IP-Address of cin (if NULL defaults to standard)
port	UDP Port of CIN
bind_addr	IP-Address to bind to (if NULL binds to 0.0.0.0)
bind_port	UDP Port of host
rcvbuf	TCP/IP Kernel recieve buffer size
packet_buffer_len	Length of packet buffer fifo (in units number of packets)
frame_buffer_len	Length of frame (assembler) buffer fifo (in units of number of frames)
push_callback	This function is called when a data structure is needed
pop_callback	This function is called when an image has been processed
usr_ptr	Pointer passed to callback functions

5.9 CIN Data Framestore Functions

Functions

- void cin_data_framestore_trigger (cin_data_t *cin, int count)
- void cin_data_framestore_skip (cin_data_t *cin, int count)
- int cin_data_get_framestore_counter (cin_data_t *cin)
- void cin_data_framestore_disable (cin_data_t *cin)
- void cin_data_framestore_trigger_enable (cin_data_t *cin)

5.9.1 Detailed Description

Framestore Group

5.9.2 Function Documentation

5.9.2.1 cin_data_framestore_disable()

Disable the framestore modes

This function disables the framestore modes (software trigger and skip). If the camera is hardware triggering then the images will start to be processed.

Parameters

```
cin | Handle to the cin library
```

5.9.2.2 cin_data_framestore_skip()

Enable framestore skip mode

Enable the framestore skip mode. This function should be called before hardware triggering the camera. This causes the data processing to skip

Parameters

count	frames from the first images to be read. This is usually done to stop the first few frames from being over exposed.
cin	handle to the cin_data library

5.9.2.3 cin_data_framestore_trigger()

Send a framestore (software) trigger

Send a software trigger to the CIN by timestamping the request time and allow images to be processed when recieved after this time. The count option sets the number of frames to trigger. A value of -1 indicated that the trigger should not count images but run indefinately after the trigger has occured.

Parameters

cin	handle to the cin_data library
count	number of frames to trigger

5.9.2.4 cin_data_framestore_trigger_enable()

Enable the framestore trigger mode

This function enables the framestore trigger mode. It cases the images to not be processed pending a call to the function to (software) trigger the camera.

Parameters

```
cin Handle to the cin library
```

5.9.2.5 cin_data_get_framestore_counter()

Get the value of the framestore counter

Return the number of frames in the framestore counter. In trigger mode, this returns the number of frames to go. In skip mode, this returns the number of frames that have to be skipped.

Parameters

cin handle to the cin_data library

Returns

Number of frames to go in trigger

Chapter 6

Class Documentation

6.1 cin_config_timing Struct Reference

Public Attributes

- uint16_t * data
- int data_len
- char name [40]
- int rows
- int cols
- · int overscan
- int fclk freq
- · int framestore

6.1.1 Member Data Documentation

```
6.1.1.1 cols
```

int cin_config_timing::cols

Cols for this timing setup

6.1.1.2 data

uint16_t* cin_config_timing::data

Pointer to timing data

6.1.1.3 data_len

int cin_config_timing::data_len

timing data length

28 Class Documentation

6.1.1.4 fclk_freq

int cin_config_timing::fclk_freq

FCLK Frequency to use

6.1.1.5 framestore

int cin_config_timing::framestore

Flag (not zero means framestore

6.1.1.6 name

char cin_config_timing::name[40]

String for config name

6.1.1.7 overscan

int cin_config_timing::overscan

Number of overscan cols for this setup

6.1.1.8 rows

int cin_config_timing::rows

Rows for this timing setup

The documentation for this struct was generated from the following file:

• src/cin.h

6.2 cin_ctl Struct Reference

Public Attributes

- char * addr
- char * bind_addr
- int port
- int bind_port
- int sport
- int bind_sport
- cin_port_t ctl_port
- cin_port_t stream_port
- cin_config_timing_t timing [CIN_CONFIG_MAX_TIMING_MODES]
- int timing_num
- cin_config_timing_t * current_timing
- · float fclk_time_factor
- cin_ctl_listener_t * listener
- pthread_mutex_t access
- · pthread mutexattr taccess attr
- void(* msg_callback)(char *, int, void *)
- void * msg_callback_ptr

6.2.1 Member Data Documentation

6.2.1.1 fclk_time_factor

```
float cin_ctl::fclk_time_factor
```

In micro seconds

The documentation for this struct was generated from the following file:

• src/cin.h

6.3 cin_ctl_id Struct Reference

Public Attributes

- uint16_t base_board_id
- uint16_t base_serial_no
- uint16_t base_fpga_ver
- uint16_t fabric_board_id
- uint16_t fabric_serial_no
- uint16_t fabric_fpga_ver

The documentation for this struct was generated from the following file:

• src/cin.h

6.4 cin_ctl_listener Struct Reference

Public Attributes

- struct cin_port * cp
- fifo ctl_fifo
- · pthread_t thread_id
- · pthread_barrier_t barrier

The documentation for this struct was generated from the following file:

• src/cin.h

30 Class Documentation

6.5 cin_ctl_pwr_mon_t Struct Reference

Public Attributes

- · cin_ctl_pwr_val_t bus_12v0
- cin_ctl_pwr_val_t mgmt_3v3
- cin_ctl_pwr_val_t mgmt_2v5
- cin_ctl_pwr_val_t mgmt_1v2
- cin_ctl_pwr_val_t enet_1v0
- cin_ctl_pwr_val_t s3e_3v3
- cin_ctl_pwr_val_t gen_3v3
- cin ctl pwr val t gen 2v5
- cin_ctl_pwr_val_t v6_0v9
- cin_ctl_pwr_val_t v6_1v0
- cin_ctl_pwr_val_t v6_2v5
- cin_ctl_pwr_val_t fp

The documentation for this struct was generated from the following file:

• src/cin.h

6.6 cin_ctl_pwr_val Struct Reference

Public Attributes

- double i
- double **v**

The documentation for this struct was generated from the following file:

• src/cin.h

6.7 cin_data Struct Reference

Public Attributes

- fifo * packet_fifo
- fifo * frame_fifo
- · cin_data_threads_t listen_thread
- · cin_data_threads_t assembler_thread
- cin_data_threads_t descramble_thread
- pthread_mutex_t descramble_mutex
- pthread_mutex_t stats_mutex
- pthread_mutex_t framestore_mutex
- · cin_data_callbacks_t callbacks
- char * addr
- char * bind_addr
- int port

- int bind_port
- int recv_buf
- cin_port_t dp
- · struct timespec framerate
- unsigned long int dropped_packets
- unsigned long int mallformed_packets
- uint16_t last_frame
- cin_data_descramble_map_t map
- int framestore_mode
- struct timespec framestore_trigger
- int framestore_counter

The documentation for this struct was generated from the following file:

• src/cin.h

6.8 cin_data_callbacks Struct Reference

Public Attributes

```
void *(* push )(cin_data_frame_t *, void *usr_ptr)
```

- void *(* pop)(cin_data_frame_t *, void *usr_ptr)
- cin_data_frame_t * frame
- void * usr_ptr

The documentation for this struct was generated from the following file:

• src/cin.h

6.9 cin_data_descramble_map_t Struct Reference

Public Attributes

- uint32_t * map
- int size x
- int size_y
- int overscan
- int rows

The documentation for this struct was generated from the following file:

• src/cin.h

32 Class Documentation

6.10 cin_data_frame Struct Reference

Public Attributes

- uint16_t * data
- uint16_t number
- · struct timespec timestamp
- int size_x
- int size_y

The documentation for this struct was generated from the following file:

• src/cin.h

6.11 cin_data_packet Struct Reference

Public Attributes

- unsigned char * data
- int size
- · struct timespec timestamp

The documentation for this struct was generated from the following file:

• src/data.h

6.12 cin_data_proc Struct Reference

Public Attributes

- void *(* input_get)(void *, int)
- void *(* input_put)(void *, int)
- void * input_args
- · int reader
- void *(* output_put)(void *)
- void *(* output_get)(void *)
- void * output_args
- cin_data_t * parent

The documentation for this struct was generated from the following file:

• src/data.h

6.13 cin_data_stats Struct Reference

Public Attributes

- · int last frame
- · double framerate
- double packet_percent_full
- · double frame percent full
- double image_percent_full
- long int packet_overruns
- long int frame_overruns
- long int image_overruns
- long int packet_used
- long int frame_used
- long int image_used
- long int dropped_packets
- · long int mallformed_packets

The documentation for this struct was generated from the following file:

• src/cin.h

6.14 cin_data_threads Struct Reference

Public Attributes

- pthread_t thread_id
- int started

The documentation for this struct was generated from the following file:

• src/cin.h

6.15 cin_map_t Struct Reference

Public Attributes

- char * name
- uint16_t reg

The documentation for this struct was generated from the following file:

• src/cinregisters.h

34 Class Documentation

6.16 cin_port Struct Reference

Public Attributes

- · int sockfd
- struct timeval tv
- struct sockaddr_in sin_srv
- struct sockaddr_in sin_cli
- socklen_t slen

The documentation for this struct was generated from the following file:

• src/cin.h

6.17 fifo Struct Reference

Public Attributes

- void * data
- void * head
- void * tail
- void * end
- · long int size
- int elem_size
- int full
- · long int overruns
- pthread_mutex_t mutex
- pthread_cond_t signal

The documentation for this struct was generated from the following file:

• src/cin.h

Chapter 7

File Documentation

7.1 src/cin.h File Reference

```
#include <stdint.h>
#include <stdio.h>
#include <sys/socket.h>
#include <netinet/in.h>
#include <netinet/ip.h>
#include <sys/time.h>
#include <pthread.h>
```

Classes

- struct fifo
- struct cin_ctl_listener
- struct cin_port
- struct cin_config_timing
- struct cin_ctl
- struct cin_data_frame
- struct cin_data_stats
- struct cin_data_threads
- · struct cin data callbacks
- struct cin_data_descramble_map_t
- struct cin_data
- struct cin_ctl_id
- struct cin_ctl_pwr_val
- struct cin_ctl_pwr_mon_t

Macros

- #define CIN_OK 0
- #define CIN ERROR -1
- #define CIN_CTL_MSG_OK 0
- #define CIN_CTL_MSG_MINOR 1
- #define CIN_CTL_MSG_MAJOR 2

- #define CIN CTL IP "192.168.1.207"
- #define CIN_CTL_CIN_PORT 49200
- #define CIN_CTL_BIND_PORT 50200
- #define CIN CTL FRMW CIN PORT 49202
- #define CIN CTL FRMW BIND PORT 50202
- #define CIN_CTL_RCVBUF 10
- #define CIN CTL MAX READ TRIES 5
- #define CIN_CTL_MAX_WRITE_TRIES 5
- #define CIN_CTL_WRITE_SLEEP 100
- #define CIN CTL READ SLEEP 100
- #define CIN CTL BIAS SLEEP 100000
- #define CIN CTL FO SLEEP 500000
- #define CIN_CTL_CONFIG_SLEEP 100
- #define CIN_CTL_DCO_SLEEP 1000000
- #define CIN_CTL_FCLK_SLEEP 200000
- #define CIN CTL STREAM CHUNK 512
- #define CIN CTL STREAM SLEEP 5
- #define CIN CTL POWER ENABLE 0x001F
- #define CIN_CTL_POWER_DISABLE 0x0000
- #define CIN_CTL_FP_POWER_ENABLE 0x0020
- #define CIN_CTL_DCM_LOCKED 0x0001
- #define CIN CTL DCM PSDONE 0x0002
- #define CIN CTL DCM STATUS0 0x0004
- #define CIN_CTL_DCM_STATUS1 0x0008
- #define CIN CTL DCM STATUS2 0x0010
- #define CIN_CTL_DCM_TX1_READY 0x0020
- #define CIN_CTL_DCM_TX2_READY 0x0040
- #define CIN CTL DCM ATCA ALARM 0x0080
- #define CIN CTL TRIG INTERNAL 0x0000
- #define CIN_CTL_TRIG_EXTERNAL_1 0x0001
- #define CIN_CTL_TRIG_EXTERNAL_2 0x0002
- #define CIN CTL TRIG EXTERNAL BOTH 0x0003
- #define CIN_CTL_FOCUS_BIT 0x0002
- #define CIN_CTL_FCLK_125 0x0000
- #define CIN_CTL_FCLK_200 0x0001
- #define CIN CTL FCLK 250 0x0002
- #define CIN_CTL_FCLK_125_C 0x0003
- #define CIN_CTL_FCLK_200_C 0x0004
- #define CIN_CTL_FCLK_250_C 0x0005
- #define CIN CTL FCLK 156 C 0x0006
- #define CIN_CTL_FPGA_STS_CFG 0x8000
- #define CIN_CTL_FPGA_STS_FP_PWR 0x0008
- #define CIN_CTL_DCM_STS_ATCA 0x0080
- #define CIN_CTL_DCM_STS_LOCKED 0x0001
- #define CIN_CTL_DCM_STS_OVERIDE 0x0800
- #define CIN CTL MUX1 VCLK1 0x0001
- #define CIN CTL MUX1 VCLK2 0x0002
- #define CIN CTL MUX1 VCLK3 0x0003
- #define CIN_CTL_MUX1_ATG 0x0004
- #define CIN_CTL_MUX1_VFSCLK1 0x0005
- #define CIN CTL MUX1 VFSCLK2 0x0006
- #define CIN_CTL_MUX1_VFSCLK3 0x0007
- #define CIN CTL MUX1 HCLK1 0x0008
- #define CIN CTL MUX1 HCLK2 0x0009
- #define CIN_CTL_MUX1_OSW 0x000A

7.1 src/cin.h File Reference 37

- #define CIN_CTL_MUX1_RST 0x000B
- #define CIN_CTL_MUX1_CONVERT 0x000C
- #define CIN_CTL_MUX1_SHUTTER 0x000D
- #define CIN CTL MUX1 SWTRIGGER 0x000E
- #define CIN CTL MUX1 TRIGMON 0x000F
- #define CIN_CTL_MUX1_EXPOSE 0x0000
- #define CIN CTL MUX2 VCLK1 0x0010
- #define CIN_CTL_MUX2_VCLK2 0x0020
- #define CIN_CTL_MUX2_VCLK3 0x0030
- #define CIN CTL MUX2 ATG 0x0040
- #define CIN CTL MUX2 VFSCLK1 0x0050
- #define CIN CTL MUX2 VFSCLK2 0x0060
- #define CIN_CTL_MUX2_VFSCLK3 0x0070
- #define CIN CTL MUX2 HCLK1 0x0080
- #define CIN_CTL_MUX2_HCLK2 0x0090
- #define CIN CTL MUX2 HCLK3 0x00A0
- #define CIN CTL MUX2 OSW 0x00B0
- #define CIN CTL MUX2 RST 0x00C0
- #define CIN CTL MUX2 CONVERT 0x00D0
- #define CIN_CTL_MUX2_SAVE 0x00E0
- #define CIN_CTL_MUX2_HWTRIG 0x00F0
- #define CIN CTL MUX2 EXPOSE 0x0000
- #define CIN CTL FO REG1 0x821D
- #define CIN_CTL_FO_REG2 0x821E
- #define CIN CTL FO REG3 0x821F
- #define CIN_DATA_IP "10.0.5.207"
- #define CIN DATA BIND PORT 49201
- #define CIN_DATA_CIN_PORT 49203
- #define CIN DATA MAX MTU 9000
- #define CIN_DATA_UDP_HEADER 8
- #define CIN_DATA_MAGIC_PACKET_UINT64_C(0x0000F4F3F2F1F000)
- #define CIN_DATA_MAGIC_PACKET_MASK_UINT64_C(0x0000FFFFFFFFF00)
- #define CIN_DATA_TAIL_MAGIC_PACKET UINT64_C(0x010DF0ADDEF2F1F0)
- #define CIN DATA DROPPED PACKET VAL 0x2000
- #define CIN DATA DATA MASK 0x1FFF
- #define CIN DATA CTRL MASK 0xE000
- #define CIN_DATA_SIGN_MASK 0x1000
- #define CIN_DATA_GAIN_8 0xC000
- #define CIN DATA GAIN 4 0x4000
- #define CIN DATA PACKET LEN 8184
- #define CIN_DATA_MAX_PACKETS 542
- #define CIN_DATA_RCVBUF (100*1024*1024)
- #define CIN_DATA_MAX_FRAME_X 1152
- #define CIN_DATA_MAX_FRAME_Y 2050
- #define CIN DATA MAX STREAM 2400000
- #define CIN DATA CCD COLS 96
- #define CIN DATA CCD COLS PER CHAN 10
- #define CIN_DATA_PIPELINE_FLUSH 1344
- #define CIN_CTL_NUM_BIAS 20
- #define CIN CTL BIAS OFFSET 0x0030
- #define CIN CTL BIAS POSH 0
- #define CIN CTL BIAS NEGH 1
- #define CIN CTL BIAS POSRG 2
- #define CIN_CTL_BIAS_NEGRG 3

- #define CIN_CTL_BIAS_POSSW 4
- #define CIN_CTL_BIAS_NEGSW 5
- #define CIN_CTL_BIAS_POSV 6
- #define CIN_CTL_BIAS_NEGV 7
- #define CIN CTL BIAS POSTG 8
- #define CIN CTL BIAS NEGTG 9
- #define CIN CTL BIAS POSVF 10
- #define CIN CTL BIAS NEGVF 11
- #define CIN_CTL_BIAS_NEDGE 12
- #define CIN CTL BIAS OTG 13
- #define CIN_CTL_BIAS_VDDR 14
- #define CIN CTL BIAS VDD OUT 15
- #define CIN CTL BIAS BUF BASE 16
- #define CIN CTL BIAS BUF DELTA 17
- #define CIN CTL BIAS SPARE1 18
- #define CIN CTL BIAS SPARE2 19
- #define DEBUG_PRINT(fmt, ...) if(_debug_print_flag) { fprintf(stderr, "%s:%d:%s(): " fmt, __FILE__, __LI ← NE__, __func__, __VA_ARGS__); }
- #define DEBUG_COMMENT(fmt) if(_debug_print_flag) { fprintf(stderr, "%s:%d:%s(): " fmt, __FILE__, __
 LINE__, __func__); }
- #define ERROR_COMMENT(fmt) if(_error_print_flag) { fprintf(stderr, "%s:%d:%s(): " fmt, __FILE__, __LI

 NE__, __func__); }
- #define ERROR_PRINT(fmt, ...) if(_error_print_flag) { fprintf(stderr, "%s:%d:%s(): " fmt, __FILE__, __LIN←
 E__, __func__, __VA_ARGS__); }
- #define CIN_CONFIG_MAX_STRING 40
- #define CIN CONFIG MAX TIMING DATA 880
- #define CIN_CONFIG_MAX_TIMING_MODES 20

Typedefs

- typedef struct cin_ctl_listener cin_ctl_listener_t
- typedef struct cin_port cin_port_t
- typedef struct cin config timing cin config timing t
- typedef struct cin ctl cin ctl t
- typedef struct cin_data_frame cin_data_frame_t
- typedef struct cin_data_stats cin_data_stats_t
- typedef struct cin data threads cin data threads t
- typedef struct cin_data_callbacks cin_data_callbacks_t
- typedef struct cin data cin data t
- typedef void(* cin_data_callback) (cin_data_frame_t *, void *usr_ptr)
- typedef struct cin_ctl_id cin_ctl_id_t
- typedef struct cin_ctl_pwr_val cin_ctl_pwr_val_t

Functions

- void cin_set_debug_print (int debug)
- void cin_set_error_print (int error)
- void cin_report (FILE *fp, int details)
- int cin_ctl_init (cin_ctl_t *cin, char *addr, uint16_t port, uint16_t sport, char *bind_addr, uint16_t bind_port, uint16_t bind_sport)
- int cin_ctl_destroy (cin_ctl_t *cin)
- void cin ctl message (cin ctl t *cin, char *message, int severity)
- void cin_ctl_set_msg_callback (cin_ctl_t *cin, void *msg_callback, void *ptr)

7.1 src/cin.h File Reference 39

```
int cin_data_send_magic (cin_data_t *cin)

    int cin_ctl_read (cin_ctl_t *cin, uint16_t reg, uint16_t *val, int wait)

• int cin_ctl_write (cin_ctl_t *cin, uint16_t reg, uint16_t val, int wait)
• int cin ctl stream write (cin ctl t *cin, unsigned char *val, int size)

    int cin ctl write with readback (cin ctl t *cin, uint16 t reg, uint16 t val)

• int cin ctl pwr (cin ctl t *cin, int pwr)
• int cin_ctl_fp_pwr (cin_ctl_t *cin, int pwr)
• int cin ctl fo test pattern (cin ctl t *cin, int on off)
• int cin_ctl_load_config (cin_ctl_t *cin, char *filename)
• int cin ctl load firmware (cin ctl t *cin)
• int cin ctl load firmware file (cin ctl t *cin, char *filename)
• int cin_ctl_load_firmware_data (cin_ctl_t *cin, unsigned char *data, int data_len)
• int cin ctl get fclk (cin ctl t *cin, int *clkfreq)
• int cin ctl set fclk (cin ctl t *cin, int clkfreq)
• int cin ctl get cfg fpga status (cin ctl t *cin, uint16 t * val)

    int cin ctl get id (cin ctl t *cin, cin ctl id t * val)

• int cin_ctl_get_dcm_status (cin_ctl_t *cin, uint16_t *_val)
• int cin ctl get power status (cin ctl t *cin, int full, int *pwr, cin ctl pwr mon t *values)

    int cin ctl set bias (cin ctl t *cin, int val)

    int cin_ctl_get_bias (cin_ctl_t *cin, int *val)

• int cin_ctl_set_bias_regs (cin_ctl_t *cin, uint16_t *vals, int verify)

    int cin ctl get bias regs (cin ctl t *cin, uint16 t *vals)

    int cin ctl set bias voltages (cin ctl t *cin, float *voltage, int verify)

• int cin_ctl_get_bias_voltages (cin_ctl_t *cin, float *voltage, uint16_t *regs)
• int cin ctl set timing regs (cin ctl t *cin, uint16 t *vals, int vals len)
• int cin_ctl_get_timing_regs (cin_ctl_t *cin, uint16 t *vals, int vals_len)

    int cin ctl get camera pwr (cin ctl t *cin, int *val)

    int cin_ctl_set_camera_pwr (cin_ctl_t *cin, int val)

    int cin ctl set clocks (cin ctl t *cin, int val)

    int cin_ctl_get_clocks (cin_ctl_t *cin, int *val)

    int cin_ctl_set_trigger (cin_ctl_t *cin, int val)

• int cin_ctl_get_trigger (cin_ctl_t *cin, int *val)

    int cin ctl set focus (cin ctl t *cin, int val)

    int cin_ctl_get_focus (cin_ctl_t *cin, int *val)

    int cin_ctl_get_triggering (cin_ctl_t *cin, int *trigger)

• int cin_ctl_int_trigger_start (cin_ctl_t *cin, int nimages)
• int cin ctl int trigger stop (cin ctl t *cin)

    int cin_ctl_ext_trigger_start (cin_ctl_t *cin, int trigger_mode)

    int cin_ctl_ext_trigger_stop (cin_ctl_t *cin)

• int cin_ctl_set_exposure_time (cin_ctl_t *cin, float e_time)
• int cin ctl set trigger delay (cin ctl t *cin, float t time)
• int cin ctl set cycle time (cin ctl t *cin, float ftime)
• int cin_ctl_frame_count_reset (cin_ctl_t *cin)

    int cin_ctl_set_mux (cin_ctl_t *cin, int setting)

    int cin_ctl_get_mux (cin_ctl_t *cin, int *setting)

• int cin ctl set fcric clamp (cin ctl t *cin, int clamp)
• int cin_ctl_set_fcric_gain (cin_ctl_t *cin, int gain)
• int cin_ctl_set_fcric_regs (cin_ctl_t *cin, uint16_t *reg, int num_reg)

    int cin ctl set fcric (cin ctl t *cin)

• int cin ctl set fabric address (cin ctl t *cin, char *ip)
• int cin ctl bias dump (cin ctl t *cin, FILE *fp)
• int cin ctl reg dump (cin ctl t *cin, FILE *fp)

    int cin_config_read_file (cin_ctl_t *cin, const char *file)
```

• int cin_data_init (cin_data_t *cin, char *addr, uint16_t port, char *bind_addr, uint16_t bind_port, int rcvbuf, int packet_buffer_len, int frame_buffer_len, cin_data_callback push_callback, cin_data_callback pop_callback, void *usr_ptr)

- void cin_data_destroy (cin_data_t *cin)
- void cin_data_framestore_trigger (cin_data_t *cin, int count)
- void cin data framestore skip (cin data t *cin, int count)
- int cin_data_get_framestore_counter (cin_data_t *cin)
- void cin data framestore disable (cin data t *cin)
- void cin data framestore trigger enable (cin data t *cin)
- struct cin data frame * cin data get next frame (cin data t *cin)
- void cin_data_release_frame (cin_data_t *cin, int free_mem)
- struct cin data frame * cin data get buffered frame (void)
- void cin_data_release_buffered_frame (void)
- void cin data compute stats (cin data t *cin, cin data stats t *stats)
- void cin_data_show_stats (FILE *fp, cin_data_stats_t stats)
- void cin_data_reset_stats (cin_data_t *cin)
- int cin data set descramble params (cin data t *cin, int rows, int overscan)
- void cin data get descramble params (cin data t *cin, int *rows, int *voverscan, int *xsize, int *ysize)
- int cin_com_boot (cin_ctl_t *cin_ctl, cin_data_t *cin_data, char *mode)
- int cin_ctl_upload_bias (cin_ctl_t *cin)

Variables

- const char * cin_build_git_time
- const char * cin_build_git_sha
- · const char * cin build version
- · int debug print flag
- int _error_print_flag

7.1.1 Detailed Description

Author

Stuart B. Wilkins swilkins@bnl.gov

7.1.2 LICENSE

Copyright (c) 2014, Brookhaven Science Associates, Brookhaven National Laboratory All rights reserved.

Redistribution and use in source and binary forms, with or without modification, are permitted provided that the following conditions are met:

- Redistributions of source code must retain the above copyright notice, this list of conditions and the following disclaimer.
- 2. Redistributions in binary form must reproduce the above copyright notice, this list of conditions and the following disclaimer in the documentation and/or other materials provided with the distribution.

THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT OWNER OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

The views and conclusions contained in the software and documentation are those of the authors and should not be interpreted as representing official policies, either expressed or implied, of the FreeBSD Project.

7.1.3 DESCRIPTION

header file for CIN communications

7.1.4 Macro Definition Documentation

7.1.4.1 CIN_CONFIG_MAX_TIMING_DATA

#define CIN_CONFIG_MAX_TIMING_DATA 880

Max = 55 per state, 16 states

7.1.4.2 CIN_CONFIG_MAX_TIMING_MODES

#define CIN_CONFIG_MAX_TIMING_MODES 20

20 states max

7.1.4.3 CIN_CTL_BIAS_OFFSET

#define CIN_CTL_BIAS_OFFSET 0x0030

Offset in address to read bias

7.2 src/cin_register_map.h File Reference

Macros

- #define REG_COMMAND 0x0001
- #define **REG_READ_ADDRESS** 0x0002
- #define REG STREAM TYPE 0x0003
- #define CMD_FCLK_125 0xB000
- #define CMD_FCLK_200 0x7000
- #define CMD_FCLK_250 0x3000
- #define **REG_IF_MAC0** 0x0010
- #define REG_IF_MAC1 0x0011
- #define REG IF MAC2 0x0012
- #define REG_IF_IP0 0x0013
- #define **REG_IF_IP1** 0x0014
- #define REG_IF_CMD_PORT_NUM 0x001A
- #define **REG_IF_STREAM_IN_PORT_NUM** 0x001C
- #define REG_IF_STREAM_OUT_PORT_NUM 0x001D
- #define REG ETH RESET 0x0020
- #define REG_ETH_ENABLE 0x0021
- #define REG_PHY1_MDIO_CMD 0x0022

- #define REG PHY1 MDIO CMD DATA 0x0023
- #define REG PHY1 MDIO STATUS 0x0024
- #define REG_PHY1_MDIO_RD_ADDR 0x0025
- #define REG PHY1 MDIO RD DATA 0x0026
- #define REG MAC CFG VECTOR1 0x0027
- #define REG PHY2 MDIO CMD 0x0028
- #define REG_PHY2_MDIO_CMD_DATA 0x0029
- #define REG_PHY2_MDIO_STATUS 0x002A
- #define REG PHY2 MDIO RD ADDR 0x002B
- #define REG PHY2 MDIO RD DATA 0x002C
- #define REG MAC CFG VECTOR2 0x002D
- #define CMD PS ENABLE 0x0021
- #define CMD_PS_POWERDOWN 0x0022
- #define REG PS ENABLE 0x0030
- #define REG_PS_SYNC_DIV0 0x0031
- #define REG PS SYNC DIV1 0x0032
- #define REG_PS_SYNC_DIV2 0x0033
- #define REG PS SYNC DIV3 0x0034
- #define REG PS SYNC DIV4 0x0035
- #define CMD PROGRAM FRAME 0x0041
- #define REG_FRM_RESET 0x0036
- #define REG_FRM_10GbE_SEL_0x0037;
- #define CMD ENABLE CLKS 0x0031
- #define CMD DISABLE CLKS 0x0032
- #define REG CLOCK EN REG 0x0038
- #define REG_SI570_REG0 0x0039
- #define REG SI570 REG1 0x003A
- #define REG_SI570_REG2 0x003B
- #define REG_SI570_REG3 0x003C
- #define CMD MON STOP 0x0011
- #define CMD MON START 0x0012
- #define REG_VMON_ADC1_CH1 0x0040 /* V12P_BUS Voltage Monitor */
- #define REG_IMON_ADC1_CH0 0x0041 /* V12P_BUS Current Monitor */
- #define REG_VMON_ADC0_CH5 0x0042 /* V3P3_MGMT Voltage Monitor */
- #define REG_IMON_ADC0_CH5 0x0043 /* V3P3_MGMT Current Monitor */
- #define REG_VMON_ADC0_CH4 0x0044 /* V3P3_S3E Voltage Monitor */
- #define REG_IMON_ADC0_CH4 0x0045 /* V3P3_S3E Current Monitor */
- #define REG_VMON_ADC0_CH7 0x0046 /* V2P5_MGMT Voltage Monitor */
- #define REG_IMON_ADC0_CH7 0x0047 /* V2P5_MGMT Current Monitor */
- #define REG_VMON_ADC0_CH6 0x0048 /* V1P8_MGMT Voltage Monitor */
- #define REG_IMON_ADC0_CH6 0x0049 /* V1P8_MGMT Current Monitor */
- #define REG VMON ADC0 CH2 0x004A /* V1P2 MGMT Voltage Monitor */
- #define REG_IMON_ADC0_CH2 0x004B /* V1P2_MGMT Current Monitor */
- #define REG_VMON_ADC0_CH3 0x004C /* V1P0_ENET Voltage Monitor */
- #define REG_IMON_ADC0_CH3 0x004D /* V1P0_ENET Current Monitor */
- #define REG_VMON_ADC0_CH8 0x004E /* V3P3_GEN Voltage Monitor */
- #define REG_IMON_ADC0_CH8 0x004F /* V3P3_GEN Current Monitor */
- #define REG_VMON_ADC0_CH9 0x0050 /* V2P5_GEN Voltage Monitor */
- #define REG_VMON_ADCO_CHE 0x0052 /* V0P9_V6 Voltage Monitor */
- #define $REG_IMON_ADCO_CHE\ 0x0053\ /*\ V0P9_V6\ Current\ Monitor\ */$
- #define REG_VMON_ADC0_CHD 0x0054 /* V2P5_V6 Voltage Monitor */
- #define REG_IMON_ADC0_CHD 0x0055 /* V2P5_V6 Current Monitor */
- #define REG_VMON_ADC0_CHB 0x0056 /* V1P0_V6 Voltage Monitor */
- #define REG IMON ADC0 CHB 0x0057 /* V1P0 V6 Current Monitor */

- #define REG_VMON_ADC0_CHC 0x0058 /* V1P2_V6 Voltage Monitor */
- #define REG_IMON_ADC0_CHC 0x0059 /* V1P2_V6 Current Monitor */
- #define REG_VMON_ADC0_CHF 0x005A /* V5P0_FP Voltage Monitor (1/2) */
- #define REG IMON ADC0 CHF 0x005B /* V5P0 FP Current Monitor (1/2) */
- #define REG DCM STATUS 0x0080
- #define REG_FPGA_STATUS 0x0081
- #define REG BOARD ID 0x008D
- #define REG_HW_SERIAL_NUM 0x008E
- #define REG FPGA VERSION 0x008F
- #define REG SANDBOX REG00 0x00F0
- #define REG SANDBOX REG01 0x00F1
- #define REG SANDBOX REG02 0x00F2
- #define REG SANDBOX REG03 0x00F3
- #define REG SANDBOX REG04 0x00F4
- #define REG_SANDBOX_REG05 0x00F5
- #define REG SANDBOX REG06 0x00F6
- #define REG SANDBOX REG07 0x00F7
- #define REG SANDBOX REG08 0x00F8
- #define REG SANDBOX REG09 0x00F9
- #define REG SANDBOX REG0A 0x00FA
- #define REG_SANDBOX_REG0B 0x00FB
- #define REG SANDBOX REGOC 0x00FC
- #define REG SANDBOX REGOD 0x00FD
- #define REG_SANDBOX_REG0E 0x00FE
- #define REG SANDBOX REG0F 0x00FF
- #define REG_FRM_COMMAND 0x8001
- #define REG_FRM_READ_ADDRESS 0x8002
- #define REG_FRM_STREAM_TYPE 0x8003
- #define CMD SEND SYNC PULSE 0x0100
- #define CMD SYNC DETECTOR2READOUT 0x0101
- #define CMD WR CCD BIAS REG 0x0102
- #define CMD WR CCD CLOCK REG 0x0103
- #define CMD_SEND_FCRIC_CONFIG 0x0105
- #define CMD RESET FRAME COUNT 0x0106
- #define REG IF MAC FAB1B0 0x8010
- #define REG IF MAC FAB1B1 0x8011
- #define REG_IF_MAC_FAB1B2 0x8012
- #define REG_IF_IP_FAB1B0 0x8013
- #define REG_IF_IP_FAB1B1 0x8014
- #define REG IF CMD PORT NUM FAB1B 0x8015
- #define REG IF STREAM IN PORT NUM FAB1B 0x8016
- #define REG_IF_STREAM_OUT_PORT_NUM_FAB1B 0x8017
- #define REG XAUI FAB1B 0x8018
- #define REG_MAC_CONFIG_VEC_FAB1B0 0x8019
- #define REG_MAC_CONFIG_VEC_FAB1B1 0x801A
- #define REG MAC STATS1 FAB1B0 0x801B
- #define REG MAC STATS1 FAB1B1 0x801C
- #define REG MAC STATS2 FAB1B0 0x801D
- #define REG_MAC_STATS2_FAB1B1 0x801E
- #define REG_IF_MAC_FAB2B0 0x8020
- #define REG IF MAC FAB2B1 0x8021
- #define REG IF MAC FAB2B2 0x8022
- #define REG_IF_IP_FAB2B0 0x8023
- #define REG_IF_IP_FAB2B1 0x8024
- #define REG IF CMD PORT NUM FAB2B 0x8025

- #define REG IF STREAM IN PORT NUM FAB2B 0x8026
- #define REG IF STREAM OUT PORT NUM FAB2B 0x8027
- #define REG_XAUI_FAB2B 0x8028
- #define REG MAC CONFIG VEC FAB2B0 0x8029
- #define REG MAC CONFIG VEC FAB2B1 0x802A
- #define REG MAC STATS1 FAB2B0 0x802B
- #define REG MAC STATS1 FAB2B1 0x802C
- #define REG_MAC_STATS2_FAB2B0 0x802D
- #define REG MAC STATS2 FAB2B1 0x802E
- #define REG_SRAM_COMMAND 0x8030
- #define REG SRAM START ADDR1 0x8031
- #define REG SRAM START ADDR0 0x8032
- #define REG_SRAM_STOP_ADDR1 0x8033
- #define REG SRAM STOP ADDR0 0x8034
- #define REG_SRAM_FRAME_DATA_OUT1 0x8035
- #define REG SRAM FRAME DATA OUT0 0x8036
- #define REG_SRAM_FRAME_DATA_IN1_0x8037
- #define REG SRAM FRAME DATA IN0 0x8038
- #define REG SRAM FRAME DV 0x8039
- #define REG SRAM STATUS1 0x803A
- #define REG_SRAM_STATUS0 0x803B
- #define CMD FCLK COMMIT 0x0012
- #define REG FCLK I2C ADDRESS 0x8040
- #define REG_FCLK_I2C_DATA_WR 0x8041
- #define REG FCLK I2C DATA RD 0x8042
- #define REG_TRIGGERSELECT_REG 0x8050
- #define REG_TRIGGERMASK_REG_0x8051
- #define REG_CCDFCLKSELECT_REG 0x8052
- #define REG CDICLKDISABLE REG 0x8053
- #define REG FCLK SET0 0xB007
- #define REG FCLK SET1 0xB008
- #define REG FCLK SET2 0xB009
- #define REG_FCLK_SET3 0xB00A
- #define REG_FCLK_SET4 0xB00B
- #define REG_FCLK_SET5 0xB00C
- #define REG_FRM_DCM_STATUS 0x8080
- #define REG_FRM_FPGA_STATUS 0x8081
- #define REG_FRM_BOARD_ID 0x808D
- #define REG FRM HW SERIAL NUM 0x808E
- #define REG_FRM_FPGA_VERSION 0x808F
- #define REG FRM SANDBOX REG00 0x80F0
- #define REG FRM SANDBOX REG01 0x80F1
- #define REG_FRM_SANDBOX_REG02 0x80F2
- #define REG_FRM_SANDBOX_REG03 0x80F3
 #define REG_FRM_SANDBOX_REG04 0x80F4
- #define REG_FRM_SANDBOX_REG04 0x80F4
 #define REG_FRM_SANDBOX_REG05 0x80F5
- #define REG FRM SANDBOX REG06 0x80F6
- #define REG FRM SANDBOX REG07 0x80F7
- #define **REG FRM SANDBOX REG08** 0x80F8
- #define REG_FRM_SANDBOX_REG09 0x80F9
- #define REG FRM SANDBOX REGOA 0x80FA
- #define REG_FRM_SANDBOX_REG0B 0x80FB
- #define REG_FRM_SANDBOX_REG0C 0x80FC
- #define REG_FRM_SANDBOX_REG0D 0x80FD
- #define REG_FRM_SANDBOX_REG0E 0x80FE

- #define REG FRM SANDBOX REG0F 0x80FF
- #define REG DETECTOR REVISION REG 0x8100
- #define REG_DETECTOR_CONFIG_REG1 0x8101
- #define REG DETECTOR CONFIG REG2 0x8102
- #define REG DETECTOR CONFIG REG3 0x8103
- #define REG_DETECTOR_CONFIG_REG4 0x8104
- #define REG DETECTOR CONFIG REG5 0x8105
- #define REG_DETECTOR_CONFIG_REG6 0x8106
- #define REG_DETECTOR_CONFIG_REG7 0x8107
- #define REG DETECTOR CONFIG REG8 0x8108
- #define REG IMG PROC REVISION REG 0x8120
- #define REG IMG PROC CONFIG REG1 0x8121
- #define REG IMG PROC CONFIG REG2 0x8122
- #define REG IMG PROC CONFIG REG3 0x8123
- #define REG_IMG_PROC_CONFIG_REG4 0x8124
- #define REG IMG PROC CONFIG REG5 0x8125
- #define REG IMG PROC CONFIG REG6 0x8126
- #define REG IMG PROC CONFIG REG7 0x8127
- #define REG IMG PROC CONFIG REG8 0x8128
- #define REG BIASANDCLOCKREGISTERADDRESS 0x8200
- #define REG BIASANDCLOCKREGISTERDATA 0x8201
- #define REG CLOCKREGISTERDATAOUT 0x8202
- #define REG BIASREGISTERDATAOUT 0x8203
- #define REG BIASCONFIGREGISTER0 REG 0x8204
- #define REG_CLOCKCONFIGREGISTER0_REG_0x8205
- #define REG_BIASPARAM_READ_START 0x3000
- #define REG_EXPOSURETIMEMSB_REG_0x8206
- #define REG_EXPOSURETIMELSB_REG_0x8207
- #define REG ALTEXPOSURETIMEMSB REG 0x8306
- #define REG ALTEXPOSURETIMELSB REG 0x8307
- #define REG_TRIGGERREPETITIONTIMEMSB_REG_0x8208
- #define REG_TRIGGERREPETITIONTIMELSB_REG_0x8209
- #define REG_DELAYTOEXPOSUREMSB_REG 0x820A
- #define REG_DELAYTOEXPOSURELSB_REG 0x820B
- #define REG_NUMBEROFEXPOSURE_REG 0x820C
- #define REG_SHUTTERTIMEMSB_REG 0x820D
- #define REG_SHUTTERTIMELSB_REG 0x820E
- #define REG_DELAYTOSHUTTERMSB_REG 0x820F
- #define REG DELAYTOSHUTTERLSB REG 0x8210
- #define REG FCRIC MASK REG1 0x8211
- #define REG FCRIC MASK REG2 0x8212
- #define REG_FCRIC_MASK_REG3 0x8213
- #define REG_LVDS_OVERFLOW_ERROR_REG1 0x8214
- #define REG_LVDS_OVERFLOW_ERROR_REG2 0x8215
- #define REG_LVDS_OVERFLOW_ERROR_REG3 0x8216
- #define REG LVDS PARITY ERROR REG1 0x8217
- #define REG_LVDS_PARITY_ERROR_REG2 0x8218
- #define REG LVDS PARITY ERROR REG3 0x8219
- #define REG_LVDS_STOP_BIT_ERROR_REG1 0x821A
- #define REG_LVDS_STOP_BIT_ERROR_REG2 0x821B
- #define REG LVDS STOP BIT ERROR REG3 0x821C
- #define REG_FCRIC_WRITE0_REG 0x821D
- #define REG FCRIC WRITE1 REG 0x821E
- #define REG FCRIC WRITE2 REG 0x821F
- #define REG FCRIC READO REG 0x8220

- #define REG FCRIC READ1 REG 0x8221
- #define REG FCRIC READ2 REG 0x8222
- #define REG DEBUGVIDEO0 REG 0x8223
- #define REG DEBUGVIDEO1 REG 0x8224
- #define REG_DEBUGVIDEO2_REG 0x8225
- #define REG_DEBUGVIDEO3_REG 0x8226
- #define REG_DEBUGVIDEO4_REG 0x8227
- #define REG_DEBUGVIDEO5_REG 0x8228
- #define REG DEBUGVIDEO6 REG 0x8229
- #define REG_DEBUGVIDEO7_REG_0x822A
- #define REG DEBUGVIDEO8 REG 0x822B
- #define REG DEBUGVIDEO9 REG 0x822C
- #define REG DEBUGVIDEO10 REG 0x822D
- #define **REG DEBUGVIDEO11 REG** 0x822E
- #define REG DEBUGCOUNTER00 REG 0x822F
- #define REG_DEBUGCOUNTER01_REG 0x8230
- #define REG DEBUGCOUNTER02 REG 0x8231
- #define REG DEBUGCOUNTER03 REG 0x8232
- #define REG DEBUGCOUNTER04 REG 0x8233
- #define CMD READ REG 0x0001

7.2.1 Detailed Description

<

Author

Stuart B. Wilkins swilkins@bnl.gov

7.2.2 LICENSE

Copyright (c) 2014, Brookhaven Science Associates, Brookhaven National Laboratory All rights reserved.

Redistribution and use in source and binary forms, with or without modification, are permitted provided that the following conditions are met:

- Redistributions of source code must retain the above copyright notice, this list of conditions and the following disclaimer.
- 2. Redistributions in binary form must reproduce the above copyright notice, this list of conditions and the following disclaimer in the documentation and/or other materials provided with the distribution.

THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT OWNER OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

The views and conclusions contained in the software and documentation are those of the authors and should not be interpreted as representing official policies, either expressed or implied, of the FreeBSD Project.

7.2.3 DESCRIPTION

Control and Frame FPGA Register Map

7.2.4 TIMING

The exposure time is set through the REG_EXPOSURETIMEMSB_REG and REG_EXPOSURETIMELSB_REG registers. Their value in wall time depends on the fclk frequency. At 200 MHz fclk a register value of 0x00000001 corresponds to 20 us. At 125 MHz, a value of 0x00000001 corresponds to 32 us.

7.2.5 Macro Definition Documentation

7.2.5.1 CMD_DISABLE_CLKS

#define CMD_DISABLE_CLKS 0x0032

Disable Frame FPGA clock crystals

7.2.5.2 CMD_ENABLE_CLKS

#define CMD_ENABLE_CLKS 0x0031

Enable selected Frame FPGA clock crystals

7.2.5.3 CMD_FCLK_250

#define CMD_FCLK_250 0x3000

Ethernet Interface

7.2.5.4 CMD_FCLK_COMMIT

#define CMD_FCLK_COMMIT 0x0012

Start I2C Write/Read

7.2.5.5 CMD_MON_START

#define CMD_MON_START 0x0012

Start voltage and current monitor

7.2.5.6 CMD_MON_STOP

#define CMD_MON_STOP 0x0011

Stop voltage and current monitor

7.2.5.7 CMD_PS_ENABLE

#define CMD_PS_ENABLE 0x0021

Enable Selected Power Modules

7.2.5.8 CMD_PS_POWERDOWN

#define CMD_PS_POWERDOWN 0x0022

Start power down sequence

7.2.5.9 CMD_READ_REG

#define CMD_READ_REG 0x0001

Read Register CIN_REGISTER_MAP_H

7.2.5.10 CMD_RESET_FRAME_COUNT

#define CMD_RESET_FRAME_COUNT 0x0106

RESET STATISTICS/DEBUG COUNTERS Ethernet Interface

7.2.5.11 CMD_SEND_FCRIC_CONFIG

#define CMD_SEND_FCRIC_CONFIG 0x0105

SEND CONFIG DATA TO FRIC

7.2.5.12 CMD_SEND_SYNC_PULSE

#define CMD_SEND_SYNC_PULSE 0x0100

ISSUES A SYNC PULSE

7.2.5.13 CMD_SYNC_DETECTOR2READOUT

#define CMD_SYNC_DETECTOR2READOUT 0x0101

COMMAND TO SYNC DETECTOR AND READOUT (SEE IMAGE PROCESSING)

7.2.5.14 CMD_WR_CCD_BIAS_REG

#define CMD_WR_CCD_BIAS_REG 0x0102

WRITE CCD BIAS REGISTERS

7.2.5.15 CMD_WR_CCD_CLOCK_REG

#define CMD_WR_CCD_CLOCK_REG 0x0103

WRITE CCD CLOCK REGISTER

7.2.5.16 REG_BIASCONFIGREGISTER0_REG

#define REG_BIASCONFIGREGISTER0_REG 0x8204

Clock Static Registers

7.2.5.17 REG_BIASREGISTERDATAOUT

#define REG_BIASREGISTERDATAOUT 0x8203

Bias Static Registers

7.2.5.18 REG_CLOCK_EN_REG

#define REG_CLOCK_EN_REG 0x0038

Clock Enable Register Programmable Si570 Clock Registers

7.2.5.19 REG_CLOCKCONFIGREGISTER0_REG

#define REG_CLOCKCONFIGREGISTER0_REG 0x8205

Bias Voltage

7.2.5.20 REG_COMMAND

#define REG_COMMAND 0x0001

< Command Registers

7.2.5.21 REG_DEBUGCOUNTER04_REG

#define REG_DEBUGCOUNTER04_REG 0x8233

CIN Commands

Common Commands

7.2.5.22 REG_DELAYTOSHUTTERLSB_REG

#define REG_DELAYTOSHUTTERLSB_REG 0x8210

Digitizer Registers

7.2.5.23 REG_ETH_ENABLE

#define REG_ETH_ENABLE 0x0021

Enable Eth Hardware 1=Rx, 2=Tx, 3=Both

7.2.5.24 REG_ETH_RESET

#define REG_ETH_RESET 0x0020

Reset Eth Hardware 1=Rx, 2=Tx, 3=Both

7.2.5.25 REG_EXPOSURETIMELSB_REG

#define REG_EXPOSURETIMELSB_REG 0x8207

Exposure time LSB

7.2.5.26 REG_EXPOSURETIMEMSB_REG

#define REG_EXPOSURETIMEMSB_REG 0x8206

Exposure time MSB

7.2.5.27 REG_FCLK_I2C_ADDRESS

#define REG_FCLK_I2C_ADDRESS 0x8040

[Slave Address(7), RD/WRn(1), Reg Adress(8)] Slave adddress Hx58 -> HxB when shifted up by 1

7.2.5.28 REG_FCLK_I2C_DATA_RD

#define REG_FCLK_I2C_DATA_RD 0x8042

[Read Failed (1), Write Failed(1), Toggle bit(1), 0(5), Read Data (8)]

7.2.5.29 REG_FCLK_I2C_DATA_WR

#define REG_FCLK_I2C_DATA_WR 0x8041

[Clock Select(2), Clock Enable (1), 0(5), Write Data (8)] Clock Select: (00): 250 MHz (01): 200 MHz (10): FPGA FCRIC Clk (11): Si570 Programmable

7.2.5.30 REG_FCLK_SET5

#define REG_FCLK_SET5 0xB00C

FRM Status

7.2.5.31 REG_FPGA_VERSION

#define REG_FPGA_VERSION 0x008F

Sandbox Registers

7.2.5.32 REG_FRM_10GbE_SEL

#define REG_FRM_10GbE_SEL 0x0037;

10GbE Link Select Clock Enables

7.2.5.33 REG_FRM_FPGA_VERSION

#define REG_FRM_FPGA_VERSION 0x808F

Sandbox Registers

7.2.5.34 REG_FRM_RESET

#define REG_FRM_RESET 0x0036

Frame Reset

7.2.5.35 REG_FRM_SANDBOX_REG0F

#define REG_FRM_SANDBOX_REGOF 0x80FF

Image Processing Registers

Generated by Doxygen

7.2.5.36 REG_FRM_STREAM_TYPE

#define REG_FRM_STREAM_TYPE 0x8003

List of Commands

7.2.5.37 REG_IMON_ADC0_CHF

#define REG_IMON_ADCO_CHF 0x005B /* V5P0_FP Current Monitor (1/2) */

Status Registers

7.2.5.38 REG_MAC_CFG_VECTOR1

#define REG_MAC_CFG_VECTOR1 0x0027

Ethernet Hardware Conf

7.2.5.39 REG_MAC_CFG_VECTOR2

#define REG_MAC_CFG_VECTOR2 0x002D

Ethernet Hardware Conf Power Supply Control

7.2.5.40 REG_MAC_STATS2_FAB2B1

#define REG_MAC_STATS2_FAB2B1 0x802E

SRAM Test Interface

7.2.5.41 REG_PHY1_MDIO_CMD

#define REG_PHY1_MDIO_CMD 0x0022

Start(1), RnW(1), WDRd(1), PHY Addr(5), REG Addr(5)

7.2.5.42 REG_PS_ENABLE

#define REG_PS_ENABLE 0x0030

Power Supply Enable:

7.2.5.43 REG_PS_SYNC_DIV0

#define REG_PS_SYNC_DIV0 0x0031

2.5V Gen

```
7.2.5.44 REG_PS_SYNC_DIV1
#define REG_PS_SYNC_DIV1 0x0032
3.3V Gen
7.2.5.45 REG_PS_SYNC_DIV2
#define REG_PS_SYNC_DIV2 0x0033
2.5V Frame
7.2.5.46 REG_PS_SYNC_DIV3
#define REG_PS_SYNC_DIV3 0x0034
0.9V Frame
7.2.5.47 REG_PS_SYNC_DIV4
#define REG_PS_SYNC_DIV4 0x0035
5.0V FP Frame FPGA Control
7.2.5.48 REG_SANDBOX_REG0F
#define REG_SANDBOX_REGOF 0x00FF
-----< Frame FPGA Registers > Command Registers
7.2.5.49 REG_SI570_REG3
#define REG_SI570_REG3 0x003C
Power Monitor Registers
7.2.5.50 REG_SRAM_COMMAND
```

1 bit [0] >> Read NOT Write 2 bits [3:2] >> Modes: - Single RW 0x00 - Burst RW 0x01 - Test/Diagnostic 10 -

Generated by Doxygen

#define REG_SRAM_COMMAND 0x8030

Sleep 11 1 bit [4] >> start/stop

7.2.5.51 REG_SRAM_STATUS0

#define REG_SRAM_STATUS0 0x803B

Programmable Clock

7.2.5.52 REG_STREAM_TYPE

#define REG_STREAM_TYPE 0x0003

FCLK Values

7.2.5.53 REG_TRIGGERMASK_REG

#define REG_TRIGGERMASK_REG 0x8051

[00]==SW Trigger, [01]==FP Trigln2, [10]==FP Trigln1, [11]==FP Trigln1OR2

7.2.5.54 REG_TRIGGERREPETITIONTIMELSB_REG

#define REG_TRIGGERREPETITIONTIMELSB_REG 0x8209

Trigger Cycle Time LSB

7.2.5.55 REG_TRIGGERREPETITIONTIMEMSB_REG

#define REG_TRIGGERREPETITIONTIMEMSB_REG 0x8208

Trigger Cycle Time MSB

Index

CIN COntrol Timing Routines, 19	cin_register_map.h, 49
CIN Control Bias Routines, 18	Cin Control Initialization Routines, 9
CIN Data Framestore Functions, 23	cin_ctl_destroy, 9
cin_data_framestore_disable, 23	cin_ctl_init, 10
cin data framestore skip, 23	cin data send magic, 10
cin_data_framestore_trigger, 24	Cin Control Read/Rwite Routines, 12
cin_data_framestore_trigger_enable, 24	cin_ctl_read, 12
cin_data_get_framestore_counter, 24	cin_ctl_stream_write, 12
CIN Data Initialization Routines, 20	cin_ctl_write, 13
cin data destroy, 20	cin ctl write with readback, 13
cin_data_init, 20	cin.h
CIN FCLK Configuration Routines, 16	CIN_CONFIG_MAX_TIMING_DATA, 41
CIN Firmware Upload Routines, 15	CIN_CONFIG_MAX_TIMING_MODES, 41
CIN Status Routines, 17	CIN_CTL_BIAS_OFFSET, 41
CIN_CONFIG_MAX_TIMING_DATA	cin_config_timing, 27
cin.h, 41	cols, 27
CIN CONFIG MAX TIMING MODES	data, 27
cin.h, 41	data_len, 27
CIN CTL BIAS OFFSET	fclk freq, 27
cin.h, 41	framestore, 28
CMD_DISABLE_CLKS	
	name, 28
cin_register_map.h, 47	overscan, 28
CMD_ENABLE_CLKS	rows, 28
cin_register_map.h, 47	cin_ctl, 28
CMD_FCLK_250	fclk_time_factor, 29
cin_register_map.h, 47	cin_ctl_destroy
CMD_FCLK_COMMIT	Cin Control Initialization Routines, 9
cin_register_map.h, 47	cin_ctl_id, 29
CMD_MON_START	cin_ctl_init
cin_register_map.h, 47	Cin Control Initialization Routines, 10
CMD_MON_STOP	cin_ctl_listener, 29
cin_register_map.h, 47	cin_ctl_pwr_mon_t, 30
CMD_PS_ENABLE	cin_ctl_pwr_val, 30
cin_register_map.h, 48	cin_ctl_read
CMD_PS_POWERDOWN	Cin Control Read/Rwite Routines, 12
cin_register_map.h, 48	cin_ctl_stream_write
CMD_READ_REG	Cin Control Read/Rwite Routines, 12
cin_register_map.h, 48	cin_ctl_write
CMD_RESET_FRAME_COUNT	Cin Control Read/Rwite Routines, 13
cin_register_map.h, 48	cin_ctl_write_with_readback
CMD_SEND_FCRIC_CONFIG	Cin Control Read/Rwite Routines, 13
cin_register_map.h, 48	cin_data, 30
CMD_SEND_SYNC_PULSE	cin_data_callbacks, 31
cin_register_map.h, 48	cin_data_descramble_map_t, 31
CMD_SYNC_DETECTOR2READOUT	cin_data_destroy
cin_register_map.h, 48	CIN Data Initialization Routines, 20
CMD_WR_CCD_BIAS_REG	cin_data_frame, 32
cin_register_map.h, 48	cin_data_framestore_disable
CMD WR CCD CLOCK REG	CIN Data Framestore Functions, 23

56 INDEX

cin_data_framestore_skip	REG MAC STATS2 FAB2B1, 52
CIN Data Framestore Functions, 23	REG_PHY1_MDIO_CMD, 52
cin data framestore trigger	REG PS ENABLE, 52
CIN Data Framestore Functions, 24	REG PS SYNC DIV0, 52
cin_data_framestore_trigger_enable	REG PS SYNC DIV1, 52
CIN Data Framestore Functions, 24	REG PS SYNC DIV2, 53
cin_data_get_framestore_counter	REG PS SYNC DIV3, 53
CIN Data Framestore Functions, 24	REG PS SYNC DIV4, 53
cin_data_init	REG_SANDBOX_REG0F, 53
CIN Data Initialization Routines, 20	REG_SI570_REG3, 53
cin_data_packet, 32	REG SRAM COMMAND, 53
cin_data_proc, 32	REG_SRAM_STATUS0, 53
cin_data_send_magic	REG_STREAM_TYPE, 54
Cin Control Initialization Routines, 10	REG_TRIGGERMASK_REG, 54
cin_data_stats, 33	REG_TRIGGERREPETITIONTIMELSB_REG, 54
cin_data_threads, 33	REG_TRIGGERREPETITIONTIMEMSB_REG, 54
cin_map_t, 33	cols
cin_port, 34	cin_config_timing, 27
cin_register_map.h	_ 0_ 0,
CMD_DISABLE_CLKS, 47	data
CMD ENABLE CLKS, 47	cin_config_timing, 27
CMD FCLK 250, 47	data_len
CMD FCLK COMMIT, 47	cin_config_timing, 27
CMD MON START, 47	
CMD MON STOP, 47	fclk_freq
CMD_PS_ENABLE, 48	cin_config_timing, 27
CMD PS POWERDOWN, 48	fclk_time_factor
CMD_READ_REG, 48	cin_ctl, 29
CMD_RESET_FRAME_COUNT, 48	fifo, 34
CMD_SEND_FCRIC_CONFIG, 48	framestore
CMD_SEND_SYNC_PULSE, 48	cin_config_timing, 28
CMD_SYNC_DETECTOR2READOUT, 48	
CMD WR CCD BIAS REG, 48	name
CMD_WR_CCD_CLOCK_REG, 49	cin_config_timing, 28
REG BIASCONFIGREGISTER0 REG, 49	
REG_BIASREGISTERDATAOUT, 49	overscan
REG CLOCK EN REG, 49	cin_config_timing, 28
:	DEC DIACCONFICERCIOTERS DEC
REG_CLOCKCONFIGREGISTER0_REG, 49 REG_COMMAND, 49	REG_BIASCONFIGREGISTER0_REG
REG_DEBUGCOUNTER04_REG, 49	cin_register_map.h, 49
REG DELAYTOSHUTTERLSB REG, 50	REG_BIASREGISTERDATAOUT
REG_ETH_ENABLE, 50	cin_register_map.h, 49
REG ETH RESET, 50	REG_CLOCK_EN_REG
REG_EXPOSURETIMELSB_REG, 50	cin_register_map.h, 49
	REG_CLOCKCONFIGREGISTER0_REG
REG_EXPOSURETIMEMSB_REG, 50	cin_register_map.h, 49
REG_FCLK_I2C_ADDRESS, 50	REG_COMMAND
REG_FCLK_I2C_DATA_RD, 50	cin_register_map.h, 49
REG_FCLK_I2C_DATA_WR, 50	REG_DEBUGCOUNTER04_REG
REG_FCLK_SET5, 51	cin_register_map.h, 49
REG_FPGA_VERSION, 51	REG_DELAYTOSHUTTERLSB_REG
REG_FRM_10GbE_SEL, 51	cin_register_map.h, 50
REG_FRM_FPGA_VERSION, 51	REG_ETH_ENABLE
REG_FRM_RESET, 51	cin_register_map.h, 50
REG_FRM_SANDBOX_REG0F, 51	REG_ETH_RESET
REG_FRM_STREAM_TYPE, 51	cin_register_map.h, 50
REG_IMON_ADC0_CHF, 52	REG_EXPOSURETIMELSB_REG
REG_MAC_CFG_VECTOR1, 52	cin_register_map.h, 50
REG_MAC_CFG_VECTOR2, 52	REG_EXPOSURETIMEMSB_REG

INDEX 57

cin_register_map.h, 50 cin_register_map.h, 54 REG_FCLK_I2C_ADDRESS rows cin_register_map.h, 50 cin_config_timing, 28 REG_FCLK_I2C_DATA_RD src/cin.h, 35 cin register map.h, 50 src/cin_register_map.h, 41 REG_FCLK_I2C_DATA_WR cin_register_map.h, 50 **REG FCLK SET5** cin_register_map.h, 51 REG_FPGA_VERSION cin register map.h, 51 REG_FRM_10GbE_SEL cin_register_map.h, 51 REG_FRM_FPGA_VERSION cin register map.h, 51 REG_FRM_RESET cin_register_map.h, 51 REG FRM SANDBOX REGOF cin_register_map.h, 51 REG_FRM_STREAM_TYPE cin_register_map.h, 51 REG_IMON_ADC0_CHF cin_register_map.h, 52 REG MAC CFG VECTOR1 cin_register_map.h, 52 REG_MAC_CFG_VECTOR2 cin register map.h, 52 REG_MAC_STATS2_FAB2B1 cin_register_map.h, 52 REG_PHY1_MDIO_CMD cin_register_map.h, 52 REG_PS_ENABLE cin_register_map.h, 52 REG_PS_SYNC_DIV0 cin_register_map.h, 52 REG_PS_SYNC_DIV1 cin register map.h, 52 REG_PS_SYNC_DIV2 cin_register_map.h, 53 REG PS SYNC DIV3 cin_register_map.h, 53 REG_PS_SYNC_DIV4 cin register map.h, 53 **REG SANDBOX REGOF** cin_register_map.h, 53 REG SI570 REG3 cin_register_map.h, 53 REG_SRAM_COMMAND cin_register_map.h, 53 REG_SRAM_STATUS0 cin_register_map.h, 53 REG STREAM TYPE cin register map.h, 54 REG_TRIGGERMASK_REG cin_register_map.h, 54 REG TRIGGERREPETITIONTIMELSB REG cin_register_map.h, 54 REG_TRIGGERREPETITIONTIMEMSB_REG