When Does Graph Learning Beat a No-Arbitrage Constraint?

Coherence and Learnability in Kalshi Event Contracts

[Justyn]

Final Year Project — draft for supervisor review

September 27, 2026

Abstract

Mutually exclusive, collectively exhaustive (MECE) baskets of event contracts must be priced to sum to \$1, and threshold ladders must be monotone in strike. These no-arbitrage constraints give free structure that a learned model could exploit. We ask where a spatio-temporal graph attention network (STGAT) adds value over the constraint itself, and where the constraint suffices. Using Kalshi trade data and hourly top-of-book quotes, we find three things. (i) *The baskets are priced coherently.* Where every leg has a two-sided quote, the mid-price sum is within 0.34¢ of \$1. The apparent dislocation in last-trade prices is almost entirely microstructure: 82–87% comes from the side of the book on which trades print, and the rest from one-sided books. (ii) *The constraint is a strong forecaster, and how strong depends on its form.* Shrinking toward \$1 cuts basket forecast error by a third against persistence (shrinkage factor 0.55). The ladder's inequality constraint gives almost no reversion (0.94). (iii) *The STGAT learns traded-price dynamics well, but the skill stops at executable prices.* It forecasts basket trade prices at 0.61× persistence error, and learns settlement convergence without being given time to close; the graph is what lets it compete with the constraint. On the executable bid, however, it is 1.82× the constraint oracle. Its entry timing beats a coin flip but not immediate entry, and no strategy is profitable after fees at quoted prices. The learned model adds value in predicting how prices *trade*; the constraint suffices for what they are *worth*. We also document four evaluation pitfalls that produced false results during the project, and a test that detects each.

1 Introduction

Prediction markets list contracts whose payoffs are tied together by construction. In a MECE basket, such as "Which range will New York's high temperature fall in tomorrow?", exactly one leg pays \$1, so the legs' prices should sum to \$1. In a threshold ladder ("above K_1", "above K_2" with $K_1 < K_2$), the higher strike cannot be worth more than the lower one. These no-arbitrage constraints are known exactly, before any data is seen.

This makes event contracts an unusual test bed for learned forecasting models. In most financial settings, a model must discover cross-asset structure from noisy data. Here the structure is given, and the question becomes sharper:

> *Where does a learned model add value over the constraint itself, and where does the constraint suffice?*

We study this question on Kalshi, a CFTC-regulated exchange, using a spatio-temporal graph attention network (STGAT) whose graph encodes the constraints: basket legs are linked through a basket hub, and ladder strikes are linked in order. We compare it against baselines that use the constraint alone, at two kinds of price: the last traded price, which most studies use, and the executable top-of-book quote, which is what a trader would actually pay or receive.

Contributions.

1. **A coherence measurement.** Using hourly best bid/ask quotes for 10,981 basket legs, we show that Kalshi baskets are priced coherently at the mid. We decompose the apparent last-price dislocation into bid/ask print side and one-sided books. The size of the print-side effect was predicted before it was measured (Section 6.1).
2. **The constraint as a forecaster.** A single shrinkage factor toward \$1 is a strong baseline for baskets and a weak one for ladders. We explain the difference by the constraint's form: an equality pins a level, while an inequality only bounds a half-line (Section 6.2).
3. **Where learning helps.** An ablation ladder runs from persistence, through constraint-only and family-aware shrinkage and a graph-free temporal model, to the full STGAT. It locates the model's value in traded-price dynamics and settlement convergence, and shows that the graph is necessary for it (Section 6.3).
4. **Executable boundaries.** At quoted prices, the model has no forecasting skill on the bid, and its timing beats chance but not immediate entry. No strategy is profitable after fees (Section 6.4).
5. **Evaluation pitfalls.** Four traps, each of which produced a false result during this project, together with the test that detects each (Section 6.5).

2 Background

Prediction markets. Prices of binary event contracts are commonly read as probabilities [13]. They are generally informative, but show systematic biases, most prominently the favourite–longshot bias [11]. On Kalshi specifically, contract prices become more accurate as markets approach close. Takers lose about 32% on average and makers about 10% [1].

Basket dislocations. Saguillo et al. [10] estimate about \$40M of realised profit from MECE baskets on Polymarket priced away from \$1 (April 2024–April 2025). Polymarket was largely fee-free for trading over that period, and the profits went to automated traders acting on the live order book. Whether the same dislocations are executable on a fee-charging, market-maker-intermediated venue is an open empirical question, and one we address.

Microstructure of trade prices. A trade executes at either the bid or the ask, so trade prices "bounce" across the spread even when the efficient price does not move [9]. Trade and quote series can be decomposed into an efficient price plus microstructure noise [2]. Trade direction is classically inferred from quotes [6], with about 85% accuracy [8]. Kalshi instead reports the aggressor side of every trade directly. Constraints spanning several instruments are further affected by non-synchronous trading [7]. Classic put–call parity tests restrict comparisons to near-simultaneous prices for this reason [5, 4].

Graph neural networks for markets. Graph attention [12] and spatio-temporal graph models [14] combine cross-sectional structure with temporal dynamics. In market microstructure, deep models usually forecast *changes* in a reference price, not levels [15]. We use a graph whose edges are the known constraints, not a learned adjacency.

3 Motivation

Early in this project, a model trained on last-trade prices appeared to beat an optimal constraint-based shrinkage forecast by 15%. It also appeared to identify tradeable dislocations. Both claims failed under scrutiny, for reasons that motivate the design of this paper.

- **Last-trade basket sums are dominated by microstructure.** 68.7% of basket trade prints are ask-side. With a half-spread of 2.8¢, that predicts a +6.3¢ mean excess on a 6-leg basket. The measured excess was +5.25¢. A model that forecasts last-trade sums may therefore be forecasting which side the next prints land on, not mispricing.
- **Several pipeline leaks inflated the result.**
  - resolved markets were replayed after close;
  - time-to-close used after-the-fact close times;
  - basket membership was selected with hindsight;
  - baskets were scored on a subset of their legs.

  Section 6.5 quantifies each.

We therefore (a) rebuilt the pipeline causally and pre-registered every re-run before seeing results; (b) scored forecasts against baselines that use the constraint, not only against persistence; and (c) measured executable prices directly from quotes rather than inferring them from trades.

4 Method

4.1 Population and graph

Contracts are nodes on a 2-hour snapshot grid. A *MECE basket* is an event whose legs partition the outcome space. Membership is decided causally in validation and test: a family qualifies only on instances known to have resolved at least 24h earlier, and the event's own outcome is never used. (Training months use a curated membership list.) Each basket has a hub node, linked to its legs by directed edges in both directions. *Ladder* pairs are adjacent strikes of the same underlying, linked by a monotonicity edge. Node features summarise each 2-hour window: last price, VWAP, return, volatility, volume, order flow and hub leg counts. Time-to-close is zeroed as an input in every split, and ladder edge features are zeroed.

4.2 Model

The STGAT has four parts:

- a type-specific input projection;
- a two-channel spatial attention layer, whose channels are MECE hub–leg and ladder;
- per-node *causal* temporal self-attention over the snapshot sequence;
- a residual forecast head, $\hat{p}_{t+h} = p_t + \Delta_h$, with the final layer zero-initialised so training starts exactly at persistence.

Horizons are $h \in \{1, 2, 3, 6, 12\}$ snapshots, i.e. 2–24 hours. The loss combines per-node error with a basket-sum term; the ladder term's weight is zero. Checkpoints are selected on validation MECE error.

4.3 Targets and baselines

For basket b with legs L_b, let $S_t = \sum_{i \in L_b} p_{i,t}$. Under the `whole_settle` rule, a basket is scored only if every listed leg is present. A leg that settles by $t + h$ is valued at its settlement (0 or 1). Baselines:

- **Persistence:** $\hat{S}_{t+h} = S_t$.
- **Constraint oracle:** $\hat{S}_{t+h} = 1 + \alpha(S_t - 1)$, with the single α that minimises squared error *on the scored split*. This is deliberately optimistic.

- **Family oracle:** the same, with one α per series $\times$ horizon. A basket's family is known in advance.

4.4 Executable prices

Hourly best bid and ask for every basket leg come from Kalshi's public historical candlestick endpoint [3], aligned to the snapshot window ends. A bid of 0, or an ask of \$1, is a real one-sided book and is kept as the executable price.

- **Bid-side forecast.** The model's predicted change in the last-trade sum is applied to the quoted bid sum: $\hat{B}_{t+h} = B_t + (\hat{S}_{t+h} - S_t)$. The half-spread cancels in the change if the spread is stable [9].
- **Hold to settlement.** Selling a basket at the bids yields gross $(\sum_i \text{bid}_i - 1)$ per set, and buying at the asks yields $(1 - \sum_i \text{ask}_i)$. Kalshi's taker fee is charged on the executed price.

4.5 Timing control

The model chooses to enter now, or to wait one step if it predicts the dislocation will widen. The control makes the same choice by coin flip, on identical events and sizes, so any gap is due only to the forecast. Confidence intervals come from a cluster bootstrap over baskets.

5 Experimental Setup

- **Data.** Kalshi trades and markets, May–September 2025, with a strictly forward split: train May–June, validation July–August, test September. Hourly quotes cover all 10,982 validation/test basket legs; 10,981 were retrieved.
- **Seeds and reporting.** Four seeds per configuration. We report the mean and range over seeds, with a 95% cluster-bootstrap CI per seed and the cluster count k.
- **Pre-registration.** Every re-run reported here was pre-registered in the repository before results were seen: the protocol, the decision rule and a stated prediction. The test split was scored once per seed per protocol. Deviations are disclosed.
- **Test positions.** 37,392 basket-horizon positions ($k = 348$ baskets), of which 18.6% settle within the horizon.

6 Results

6.1 Baskets are coherent at quoted prices

Table 1: Basket sums on the test split: whole baskets with every leg live. Quotes cover 98.1% of leg-snapshots and 97.1% of basket-snapshots.

	all baskets ($n = 7{,}532$)	every leg two-sided (69%)
Sum of last trades	1.0405	1.0261
Sum of quoted mids	1.0185	**1.0034**
Sum of bids / asks	0.944 / 1.093	0.967 / 1.039
Sell at bids beats \$1	1.8% of snapshots (≈ 2¢)	—

Where every leg has a two-sided quote, the mid-price sum is within 0.34¢ of \$1 (Table 1). The same holds on validation (+0.50¢). In these baskets, 82–87% of the last-trade excess is print side. Across all baskets, the remaining excess sits in legs with no bid, whose mid is inflated.

Executable dislocation is rare and small. Selling at the bids beats \$1 in 1.8% of snapshots, by about 2¢, before a taker fee of 1.3–5.8¢ per basket. The quoted per-leg spread (median 2.0¢, mean 2.9¢) is below our earlier trade-based estimates (4.7–5.6¢). The trade-print bid proxy overstated quoted bids by 1.1¢ per leg on average.

6.2 The constraint as a forecaster

On test, the constraint oracle has 0.67× the error of persistence for basket sums ($\alpha = 0.55$), but 0.985× for ladder gaps ($\alpha = 0.94$). Basket deviations revert strongly to the level the constraint pins. Ladder gaps are only bounded above by zero, so there is no level for them to revert to.

6.3 Where learning helps: the ablation ladder

Table 2: Test error, relative to the single-α constraint oracle unless stated. Mean over 4 seeds (range). "Unsettled" = baskets with no leg settling by $t + h$.

Model	all positions	unsettled	vs. persistence
Persistence	1.49	—	1.00
Constraint oracle (single α)	1.00	1.00	0.67
Temporal model, no graph	1.128	1.106	0.760
STGAT (full)	**0.909** (0.883–0.941)	1.034	**0.613**
STGAT, unsettled-only retrain[a]	—	0.950	0.781
Against the family oracle (per series × horizon), unsettled:			
STGAT, unsettled-only retrain	—	1.052 (1.024–1.074)	—
Temporal model, no graph	—	1.224	—

[a] Settled baskets excluded from the loss and from selection.

Three findings (Table 2):

- **The STGAT forecasts traded basket prices well**, at 0.61× persistence error, consistently across seeds.
- **The graph is necessary.** Without the MECE and ladder edges, the model falls behind even the single-α constraint (1.128×).
- **On test, the margin over the constraint comes from settlement convergence.** Baskets that settle by $t + h$ have a target of exactly \$1, and the model anticipates this even though time-to-close is not an input. Perturbation tests confirm that predictions at t are unchanged when future snapshots or time-to-close are randomised, so this is not leakage. The model's pull toward \$1 rises smoothly as close approaches, with no jump at the settlement boundary, which points to family-level lifecycle learning. On unsettled baskets the model matches, but does not beat, the constraint plus contract family. On validation it does beat it (0.887× single-α unsettled), but that is the selection split.

Ladders (exploratory). On 99,646 test ladder positions, the model scores 0.982–0.993× the oracle and 0.966–0.977× persistence. The graph-free model is marginally better (0.974–0.982×), so the small ladder gain comes from per-contract temporal forecasting, not from ladder structure.

6.4 Executable boundaries

Three results (Table 3):

Table 3: Executable-price results on test (4 seeds, cluster CIs by basket).

Quantity	result	CIs excluding null
Bid-side forecast / oracle, unsettled[a]	1.822× (1.80–1.85)	4/4 above 1
Timing: model − random, last prices[b]	+0.192 (0.179–0.211)	4/4 above 0
Timing: model − random, quoted prices	+0.867	3/4 above 0
Timing: model − enter now, quoted prices	−0.957	4/4 *below* 0
Fee-aware entry at quotes: trades fired / net	1 of 2,090 / +\$0.07	—
Static entry at quotes: net per trade	−\$2.18	—

[a] $n = 30{,}001$ positions, $k = 344$ baskets. [b] \$/trade, $k = 312$ baskets; same units in the rows below.

- **No bid-side skill.** Applied to the quoted bid, the model's forecast is 1.82× the constraint oracle, and worse than persistence. Its predicted change tracks where trades print, not where the bid moves.
- **Timing beats chance, but not the trivial policy.** The model's entry timing beats a coin flip at last prices (4/4 seeds) and at quoted prices (3/4). At quoted prices, however, waiting is costly, and the model loses to entering immediately on every seed.
- **No profit after fees at executable prices.** A rule that enters only when the quoted edge exceeds the fee fired once in 2,090 opportunities. This agrees with evidence that Kalshi takers lose on average [1]. It contrasts with the fee-free Polymarket evidence [10].

6.5 Evaluation pitfalls

Table 4: Traps that produced false results during the project, and the test that detects each.

Trap	Effect	Detection
Settled contracts replayed after close	57% of old ladder test pairs were frozen replays, producing "ladders are unforecastable"	audit of the share of pairs past close
Settlement-pinned targets	all of the 0.909× test margin came from baskets settling within h	stratify by settlement
Last trades treated as executable	bids overstated by 1.1¢ per leg; spreads by ≈40%; bid-side skill assumed	validate against quoted top of book
Ablation scored with the wrong graph	graph-free checkpoints would have been scored *with* the graph	record dropped edges; known-answer test

These were caught by reproduction guards, which check that every re-score reproduces the committed figures exactly, and by pre-registration (Table 4). One headline figure had no log at all, and was recovered and found to have been computed on the selection split. The provenance of every reported number is now logged.

7 Discussion and Limitations

- **Answer to the question.** Graph learning adds value on traded-price dynamics: where trades print, and how baskets converge toward settlement. The graph is necessary for this. Wherever money changes hands, the constraint suffices. This follows from the coherence finding: if baskets are coherent at executable prices, no model should profit there.
- **Limitations.**

  - Top-of-book quotes only, at hourly resolution; no depth, so fills at size are assumed.
  - A single test month, scored for several model variants; the multiple-look caveat applies.
  - The timing control's wait rate is not matched to the model's.
  - Ladder figures are exploratory.
  - The pilot window is five months, and the population is concentrated in weather and sports.

- **Next.** A pre-registered 7-fold walk-forward over November 2024 to November 2025, with the protocol frozen from this study, fresh held-out months, and quotes for all months.

8 Conclusion

Kalshi's MECE baskets are priced coherently once microstructure is accounted for. A no-arbitrage constraint is a strong forecaster where it pins a level, and a weak one where it only bounds an inequality. A constraint-structured STGAT learns traded-price dynamics well, and needs its graph to do so. That skill does not extend to executable prices, where the constraint alone is as good or better.

References

[1] C. Bürgi, W. Deng and K. Whelan. Makers and Takers: The Economics of the Kalshi Prediction Market. CESifo / CEPR Discussion Paper DP20631, 2025.

[2] P. R. Hansen and A. Lunde. Realized variance and market microstructure noise. *Journal of Business & Economic Statistics*, 24(2):127–161, 2006.

[3] Kalshi. Get Market Candlesticks (historical). API documentation, https://docs.kalshi.com/api-reference/market/get-market-candlesticks, accessed 2026-09-27.

[4] A. Kamara and T. W. Miller. Daily and intradaily tests of European put-call parity. *Journal of Financial and Quantitative Analysis*, 30(4):519–539, 1995.

[5] R. C. Klemkosky and B. G. Resnick. Put-call parity and market efficiency. *Journal of Finance*, 34(5):1141–1155, 1979.

[6] C. M. C. Lee and M. J. Ready. Inferring trade direction from intraday data. *Journal of Finance*, 46(2):733–746, 1991.

[7] A. W. Lo and A. C. MacKinlay. An econometric analysis of nonsynchronous trading. *Journal of Econometrics*, 45:181–212, 1990.

[8] E. R. Odders-White. On the occurrence and consequences of inaccurate trade classification. *Journal of Financial Markets*, 3:259–286, 2000.

[9] R. Roll. A simple implicit measure of the effective bid-ask spread in an efficient market. *Journal of Finance*, 39(4):1127–1139, 1984.

[10] O. Saguillo, V. Ghafouri, L. Kiffer and G. Suarez-Tangil. Unravelling the Probabilistic Forest: Arbitrage in Prediction Markets. In *Advances in Financial Technologies (AFT)*, LIPIcs, 2025. arXiv:2508.03474.

[11] E. Snowberg and J. Wolfers. Explaining the favorite-longshot bias: Is it risk-love or misperceptions? *Journal of Political Economy*, 118(4):723–746, 2010.

[12] P. Veličković, G. Cucurull, A. Casanova, A. Romero, P. Liò and Y. Bengio. Graph attention networks. In *ICLR*, 2018.

[13] J. Wolfers and E. Zitzewitz. Prediction markets. *Journal of Economic Perspectives*, 18(2):107–126, 2004.

[14] B. Yu, H. Yin and Z. Zhu. Spatio-temporal graph convolutional networks: A deep learning framework for traffic forecasting. In *IJCAI*, 2018.

[15] Z. Zhang, S. Zohren and S. Roberts. DeepLOB: Deep convolutional neural networks for limit order books. *IEEE Transactions on Signal Processing*, 67(11):3001–3012, 2019.