

UNIVERSITY OF ABERDEEN    SESSION 2015–16

# EX3029

Degree Examination in EX3029

3<sup>rd</sup> June 2016

09.00–12.00

## PLEASE NOTE THE FOLLOWING

- (i) You **must not** have in your possession any material other than that expressly permitted in the rules appropriate to this examination. Where this is permitted, such material **must not** be amended, annotated or modified in any way.
- (ii) You **must not** have in your possession any material that could be determined as giving you an advantage in the examination.
- (iii) You **must not** attempt to communicate with any candidate during the exam, either orally or by passing written material, or by showing material to another candidate, nor must you attempt to view another candidate's work.
- (iv) You **must not** take to your examination desk any electronic devices such as mobile phones or other smart devices. The only exception to this rule is an approved calculator.

**Failure to comply with the above will be regarded as cheating and may lead to disciplinary action as indicated in the Academic Quality Handbook Section 7 and particularly Appendix 7.1**

- Notes:**
- (i) Candidates ARE permitted to use an approved calculator.*
  - (ii) Candidates ARE NOT permitted to use the Engineering Mathematics Handbook.*
  - (iii) Candidates ARE permitted to use thermodynamic tables with saturated fluid properties, which will be provided.*
  - (iv) Data sheets are attached to the paper.*

**Candidates must attempt *all* questions.**

**Question 1**

(a) Air contained in a piston-cylinder system undergoes three consecutive processes,

- Process 1–2: Isobaric cooling with  $P_1=69$  kPa and  $V_1=0.11$  m<sup>3</sup>;
- Process 2–3: Isochoric heating with  $P_3=345$  kPa;
- Process 3–1: Polytropic expansion, with  $PV = \text{constant}$ .

- (i) Calculate  $V_2$  (in m<sup>3</sup>). [3 marks]
- (ii) Calculate the work (in kJ) for each process. [6 marks]
- (iii) Sketch the  $PV$  diagram for these processes. [4 marks]

(b) Calculate the fugacity of steam at 300°C and 80 bar. For your calculations, you should use  $h = 2785$  kJ/kg,  $s = 5.791$  kJ/(kg.K) for steam at 300°C and 80 bar. Specific enthalpy and entropy of ideal gas at 300°C and 0.1 bar are  $h^{\text{IG}} = 3077$  kJ/kg and  $s^{\text{IG}} = 9.281$  kJ/(kg.K), respectively. Given,

$$d\mu = dG = RT d(\ln f) .$$

Also, molar mass of water is 18 g/mol. [7 marks]

**Question 2**

- (a) Develop expressions for the volume expansivity,  $\beta = \frac{1}{V} \left( \frac{\partial V}{\partial T} \right)_P$ , and isothermal compressibility,  $\kappa = -\frac{1}{V} \left( \frac{\partial V}{\partial P} \right)_T$ , for the following equations of state,


(i) ideal gas [4 marks]

(ii)  $V = \frac{RT}{P} + b$  [4 marks]

- (b) Calculate the compressibility factor ( $Z$ ) and molar volume of sulphur dioxide ( $SO_2$ ) vapour at 300 K and 4 bar using the Redlich-Kwong equation of state. Properties of  $SO_2$  are:  $T_c = 430$  K,  $P_c = 78.7$  bar and  $\omega = 0.251$  (acentric factor). In your iterative calculations, use  $Z_0 = 1$  as initial guess of  $Z$ , and stop at the second iteration ( $Z_2$ ). [12 marks]

**Question 3**

- (a) Assuming that all species and their mixtures are ideal gases, derive an equation for the Gibbs energy as a function of the reaction coordinate for the reaction below at 1000K.



Calculate the reaction coordinate,  $\epsilon$ , in the equilibrium. Given  $\Delta G_f^\circ$  (J.gmol<sup>-1</sup>) at 1000K: (a) H<sub>2</sub>O: -192420, (b) CO: -200240 and (c) CO<sub>2</sub>: -395790. [13 marks]

- (b) Saturated ammonia (NH<sub>3</sub>) vapour at  $P_1 = 200$  kPa is compressed by a piston to  $P_2 = 1.6$  MPa in a reversible adiabatic process. Calculate the work done per unit mass. [7 marks]

**Question 4**

Estimate the bubble and dew point temperatures of a 25 mol-% n-pentane ( $nC_5$ ), 45 mol-% n-hexane ( $nC_6$ ) and 30 mol-% n-heptane ( $nC_7$ ) mixture at 1.013 bar. Also calculate the compositions at dew and bubble points. [20 marks]

For This problem, use

$$\ln P_i^{\text{sat}} = A_i - \frac{B_i}{RT}$$

with [P] = bar and [T] = K, and

$$\begin{array}{lll} A_{nC_5} = 10.422 & A_{nC_6} = 10.456 & A_{nC_7} = 11.431 \\ B_{nC_5} = 26799 & B_{nC_6} = 29676 & B_{nC_7} = 35200 \end{array}$$

If you are using an iterative method to solve this problem, do stop at the 5<sup>th</sup> iteration.

**Question 5**

- (a) What is the change in entropy when 700 litres of CO<sub>2</sub> and 300 litres of N<sub>2</sub>, each at 1 bar and 25°C, blend to form a gas mixture at the same conditions? Assume ideal gases, and given

$$\Delta S = -nR \sum_{i=1}^n y_i \ln y_i,$$

where  $S$ ,  $n$  and  $y$  are entropy, number of moles and mole fraction, respectively.

[10 marks]

- (b) Calculate the bubble point pressure and vapour composition for a liquid mixture of 41.2 mol-% of ethanol (1) and n-hexane (2) at 331 K. Given,

$$\ln \gamma_1 = \frac{A}{\left(1 + \frac{Ax_1}{Bx_2}\right)^2}, \quad \ln \gamma_2 = \frac{A}{\left(1 + \frac{Bx_2}{Ax_1}\right)^2}$$

$$\ln P_1^{sat} = C_1 + \frac{D_1}{T + E_1}, \quad \ln P_2^{sat} = C_2 + \frac{D_2}{T + E_2}$$

where  $A = 2.409$ ,  $B = 1.970$ ,  $C_1 = 16.1952$ ,  $C_2 = 14.0568$ ,  $D_1 = -3423.53$ ,  $D_2 = -2825.42$ ,  $E_1 = -55.7152$ ,  $E_2 = -42.7089$ . [P] = kPa and [T] = K. [10 marks]

**END OF PAPER**

## List of Equations

- Generic cubic equation of state:

$$Z = 1 + \beta - q\beta \frac{Z - \beta}{(Z + \varepsilon\beta)(Z + \sigma\beta)} \quad (\text{vapour and vapour-like roots})$$

$$Z = 1 + \beta + (Z + \varepsilon\beta)(Z + \sigma\beta) \left( \frac{1 + \beta - Z}{q\beta} \right) \quad (\text{liquid and liquid-like roots})$$

$$\text{with } \beta = \Omega \frac{P_r}{T_r} \quad \text{and} \quad q = \frac{\Psi \alpha(T_r)}{\Omega T_r}$$

$$\alpha_{\text{SRK}} = \left[ 1 + (0.480 + 1.574\omega - 0.176\omega^2) (1 - \sqrt{T_r}) \right]^2$$

$$\alpha_{\text{PR}} = \left[ 1 + (0.37464 + 1.54226\omega - 0.26992\omega^2) (1 - \sqrt{T_r}) \right]^2$$

EOS	$\alpha$	$\sigma$	$\varepsilon$	$\Omega$	$\Psi$
vdW	1	0	0	1/8	27/64
RK	$T_r^{-1/2}$	1	0	0.08664	0.42748
SRK	$\alpha_{\text{SRK}}$	1	0	0.08664	0.42748
PR	$\alpha_{\text{PR}}$	$1 + \sqrt{2}$	$1 - \sqrt{2}$	0.07780	0.45724

- Newton-Raphson (root-finder) method:  $X_i = X_{i-1} - \frac{\mathcal{F}(X_{i-1})}{d\mathcal{F}/dX(X_{i-1})}$
- Fundamental thermodynamic equations:
 
$$dU = dQ + dW; \quad dH = dU + d(PV); \quad dA = dU - d(TS); \quad dG = dH - d(TS)$$

$$dU = TdS - PdV; \quad dH = TdS + VdP; \quad dA = -SdT - PdV; \quad dG = -SdT + VdP$$

$$dH = C_p dT + \left[ V - T \left( \frac{\partial V}{\partial T} \right)_P \right] dP; \quad dS = C_p \frac{dT}{T} - \left( \frac{\partial V}{\partial T} \right)_P dP$$

$$dU = C_v dT + \left[ T \left( \frac{\partial P}{\partial T} \right)_V - P \right] dV; \quad dS = C_v \frac{dT}{T} - \left( \frac{\partial P}{\partial T} \right)_V dV$$

- Polytropic Relations:

$$\frac{T_2}{T_1} = \left( \frac{P_2}{P_1} \right)^{\frac{\gamma-1}{\gamma}} = \left( \frac{V_1}{V_2} \right)^{\gamma-1}; \quad TV^{\gamma-1} = \text{const}; \quad TP^{\frac{1-\gamma}{\gamma}} = \text{const}; \quad PV^\gamma = \text{const}$$

- Raoult's Law:

$$y_i P = x_i P_i^{\text{sat}} \quad \text{and} \quad y_i P = x_i \gamma_i P_i^{\text{sat}} \quad \text{with } i = 1, 2, \dots, N$$

- Henry's Law:

$$x_i \mathcal{H}_i = y_i P \quad \text{with } i = 1, 2, \dots, N$$

- Antoine Equation:

$$\log_{10} P^* = A - \frac{B}{T + C} \quad \text{with } P^* \text{ in mm-Hg and } T \text{ in } ^\circ\text{C}$$

- Solutions:

$$M^E = M - \sum_{i=1}^N x_i M_i; \quad \overline{M}_1 = M + x_2 \frac{dM}{dx_1}; \quad \overline{M}_2 = M - x_1 \frac{dM}{dx_1}$$



# Appendix A: Physical Constants and Conversion Factors

## PHYSICAL CONSTANTS

Avogadro's number,  $N_A = 6.023 \times 10^{26}$  molecules/kgmole  
 Boltzmann's constant,  $k = 1.381 \times 10^{-23}$  J/(molecule·K)  
 Electron charge,  $e = 1.602 \times 10^{-19}$  C  
 Electron mass,  $m_e = 9.110 \times 10^{-31}$  kg  
 Faraday's constant,  $F = 96,487$  kC/kgmole electrons = 96,487 kJ/(V·kgmole electrons)  
 Gravitational acceleration (standard),  $g = 32.174$  ft/s<sup>2</sup> = 9.807 m/s<sup>2</sup>  
 Gravitational constant,  $k_G = 6.67 \times 10^{-11}$  m<sup>3</sup>/(kg·s<sup>2</sup>)  
 Newton's second law constant,  $g_c = 32.174$  lbm·ft/(lbf·s<sup>2</sup>) = 1.0 kg·m/(N·s<sup>2</sup>)  
 Planck's constant,  $h = 6.626 \times 10^{-34}$  J·s/molecule  
 Stefan-Boltzmann constant,  $\sigma = 0.1714 \times 10^{-8}$  Btu/(h·ft<sup>2</sup>·R<sup>4</sup>) =  $5.670 \times 10^{-8}$  W/(m<sup>2</sup>·K<sup>4</sup>)  
 Universal gas constant  $\mathfrak{R} = 1545.35$  ft·lbf/(lbmole·R) = 8314.3 J/(kgmole·K)  
     = 8.3143 kJ/(kgmole·K) = 1.9858 Btu/(lbmole·R)  
     = 1.9858 kcal/(kgmole·K) = 1.9858 cal/(gmole·K)  
     = 0.08314 bar·m<sup>3</sup>/(kgmole·K) = 82.05 L·atm/(kgmole·K)  
 Velocity of light in a vacuum,  $c = 9.836 \times 10^8$  ft/s =  $2.998 \times 10^8$  m/s

## UNIT DEFINITIONS

1 coulomb (C) = 1 A·s	1 ohm ( $\Omega$ ) = 1 V/A
1 dyne = 1 g·cm/s <sup>2</sup>	1 pascal (Pa) = 1 N/m <sup>2</sup>
1 erg = 1 dyne·cm	1 poundal = 1 lbm·ft/s <sup>2</sup>
1 farad (F) = 1 C/V	1 siemens (S) = 1 A/V
1 henry (H) = 1 Wb/A	1 slug = 1 lbf·s <sup>2</sup> /ft
1 hertz (Hz) = 1 cycle/s	1 tesla (T) = 1 Wb/m <sup>2</sup>
1 joule (J) = 1 N·m	1 volt (V) = 1 W/A
1 lumen = 1 candela·steradian	1 watt (W) = 1 J/s
1 lux = 1 lumen/m <sup>2</sup>	1 weber (Wb) = 1 V·s
1 newton (N) = 1 kg·m/s <sup>2</sup>	

## CONVERSION FACTORS

Length	Energy
1 m = 3.2808 ft = 39.37 in = 10 <sup>2</sup> cm = 10 <sup>10</sup> Å	1 J = 1 N·m = 1 kg·m <sup>2</sup> /s <sup>2</sup> = 9.479 × 10 <sup>-4</sup> Btu
1 cm = 0.0328 ft = 0.394 in = 10 <sup>-2</sup> m = 10 <sup>8</sup> Å	1 kJ = 1000 J = 0.9479 Btu = 238.9 cal
1 mm = 10 <sup>-3</sup> m = 10 <sup>-1</sup> cm	1 Btu = 1055.0 J = 1.055 kJ = 778.16 ft·lbf = 252 cal
1 km = 1000 m = 0.6215 miles = 3281 ft	1 cal = 4.186 J = 3.968 × 10 <sup>-3</sup> Btu
1 in = 2.540 cm = 0.0254 m	1 Cal (in food value) = 1 kcal = 4186 J = 3.968 Btu
1 ft = 12 in = 0.3048 m	1 erg = 1 dyne·cm = 1 g·cm <sup>2</sup> /s <sup>2</sup> = 10 <sup>-7</sup> J
1 mile = 5280 ft = 1609.36 m = 1.609 km	1 eV = 1.602 × 10 <sup>-19</sup> J

(Continued)

**CONVERSION FACTORS** (Continued)**Area**

$$1 \text{ m}^2 = 10^4 \text{ cm}^2 = 10.76 \text{ ft}^2 = 1550 \text{ in}^2$$

$$1 \text{ ft}^2 = 144 \text{ in}^2 = 0.0929 \text{ m}^2 = 929.05 \text{ cm}^2$$

$$1 \text{ cm}^2 = 10^{-4} \text{ m}^2 = 1.0764 \times 10^{-3} \text{ ft}^2 = 0.155 \text{ in}^2$$

$$1 \text{ in}^2 = 6.944 \times 10^{-3} \text{ ft}^2 = 6.4516 \times 10^{-4} \text{ m}^2 = 6.4516 \text{ cm}^2$$

**Volume**

$$1 \text{ m}^3 = 35.313 \text{ ft}^3 = 6.1023 \times 10^4 \text{ in}^3 = 1000 \text{ L} = 264.171 \text{ gal}$$

$$1 \text{ L} = 10^{-3} \text{ m}^3 = 0.0353 \text{ ft}^3 = 61.03 \text{ in}^3 = 0.2642 \text{ gal}$$

$$1 \text{ gal} = 231 \text{ in}^3 = 0.13368 \text{ ft}^3 = 3.785 \times 10^{-3} \text{ m}^3$$

$$1 \text{ ft}^3 = 1728 \text{ in}^3 = 28.3168 \text{ L} = 0.02832 \text{ m}^3 = 7.4805 \text{ gal}$$

$$1 \text{ in}^3 = 16.387 \text{ cm}^3 = 1.6387 \times 10^{-5} \text{ m}^3 = 4.329 \times 10^{-3} \text{ gal}$$

**Mass**

$$1 \text{ kg} = 1000 \text{ g} = 2.2046 \text{ lbm} = 0.0685 \text{ slug}$$

$$1 \text{ lbm} = 453.6 \text{ g} = 0.4536 \text{ kg} = 3.108 \times 10^{-2} \text{ slug}$$

$$1 \text{ slug} = 32.174 \text{ lbm} = 1.459 \times 10^4 \text{ g} = 14.594 \text{ kg}$$

**Force**

$$1 \text{ N} = 10^5 \text{ dyne} = 1 \text{ kg} \cdot \text{m/s}^2 = 0.225 \text{ lbf}$$

$$1 \text{ lbf} = 4.448 \text{ N} = 32.174 \text{ poundals}$$

$$1 \text{ poundal} = 0.138 \text{ N} = 3.108 \times 10^{-2} \text{ lbf}$$

**Power**

$$1 \text{ W} = 1 \text{ J/s} = 1 \text{ kg} \cdot \text{m}^2/\text{s}^3 = 3.412 \text{ Btu/h} = 1.3405 \times 10^{-3} \text{ hp}$$

$$1 \text{ kW} = 1000 \text{ W} = 3412 \text{ Btu/h} = 737.3 \text{ ft} \cdot \text{lbf/s} = 1.3405 \text{ hp}$$

$$1 \text{ Btu/h} = 0.293 \text{ W} = 0.2161 \text{ ft} \cdot \text{lbf/s} = 3.9293 \times 10^{-4} \text{ hp}$$

$$1 \text{ hp} = 550 \text{ ft} \cdot \text{lbf/s} = 33000 \text{ ft} \cdot \text{lbf/min} = 2545 \text{ Btu/h} = 746 \text{ W}$$

**Pressure**

$$1 \text{ Pa} = 1 \text{ N/m}^2 = 1 \text{ kg}/(\text{m} \cdot \text{s}^2) = 1.4504 \times 10^{-4} \text{ lbf/in}^2$$

$$1 \text{ lbf/in}^2 = 6894.76 \text{ Pa} = 0.068 \text{ atm} = 2.036 \text{ in Hg}$$

$$1 \text{ atm} = 14.696 \text{ lbf/in}^2 = 1.01325 \times 10^5 \text{ Pa}$$

$$= 101.325 \text{ kPa} = 760 \text{ mm Hg}$$

$$1 \text{ bar} = 10^5 \text{ Pa} = 0.987 \text{ atm} = 14.504 \text{ lbf/in}^2$$

$$1 \text{ dyne/cm}^2 = 0.1 \text{ Pa} = 10^{-6} \text{ bar} = 145.04 \times 10^{-7} \text{ lbf/in}^2$$

$$1 \text{ in Hg} = 3376.8 \text{ Pa} = 0.491 \text{ lbf/in}^2$$

$$1 \text{ in H}_2\text{O} = 248.8 \text{ Pa} = 0.0361 \text{ lbf/in}^2$$

**MISCELLANEOUS UNIT CONVERSIONS****Specific Heat Units**

$$1 \text{ Btu}/(\text{lbm} \cdot ^\circ\text{F}) = 1 \text{ Btu}/(\text{lbm} \cdot \text{R})$$

$$1 \text{ kJ}/(\text{kg} \cdot \text{K}) = 0.23884 \text{ Btu}/(\text{lbm} \cdot \text{R}) = 185.8 \text{ ft} \cdot \text{lbf}/(\text{lbm} \cdot \text{R})$$

$$1 \text{ Btu}/(\text{lbm} \cdot \text{R}) = 778.16 \text{ ft} \cdot \text{lbf}/(\text{lbm} \cdot \text{R}) = 4.186 \text{ kJ}/(\text{kg} \cdot \text{K})$$

**Energy Density Units**

$$1 \text{ kJ/kg} = 1000 \text{ m}^2/\text{s}^2 = 0.4299 \text{ Btu/lbm}$$

$$1 \text{ Btu/lbm} = 2.326 \text{ kJ/kg} = 2326 \text{ m}^2/\text{s}^2$$

**Energy Flux**

$$1 \text{ W/m}^2 = 0.317 \text{ Btu}/(\text{h} \cdot \text{ft}^2)$$

$$1 \text{ Btu}/(\text{h} \cdot \text{ft}^2) = 3.154 \text{ W/m}^2$$

**Heat Transfer Coefficient**

$$1 \text{ W}/(\text{m}^2 \cdot \text{K}) = 0.1761 \text{ Btu}/(\text{h} \cdot \text{ft}^2 \cdot \text{R})$$

$$1 \text{ Btu}/(\text{h} \cdot \text{ft}^2 \cdot \text{R}) = 5.679 \text{ W}/(\text{m}^2 \cdot \text{K})$$

**Thermal Conductivity**

$$1 \text{ W}/(\text{m} \cdot \text{K}) = 0.5778 \text{ Btu}/(\text{h} \cdot \text{ft} \cdot \text{R})$$

$$1 \text{ Btu}/(\text{h} \cdot \text{ft} \cdot \text{R}) = 1.731 \text{ W}/(\text{m} \cdot \text{K})$$

**Temperature**

$$T(^{\circ}\text{F}) = \frac{9}{5} T(^{\circ}\text{C}) + 32 = T(\text{R}) - 459.67$$

$$T(^{\circ}\text{C}) = \frac{5}{9} [T(^{\circ}\text{F}) - 32] = T(\text{K}) - 273.15$$

$$T(\text{R}) = \frac{9}{5} T(\text{K}) = (1.8)T(\text{K}) = T(^{\circ}\text{F}) + 459.67$$

$$T(\text{K}) = \frac{5}{9} T(\text{R}) = T(\text{R})/1.8 = T(^{\circ}\text{C}) + 273.15$$

**Density**

$$1 \text{ lbm/ft}^3 = 16.0187 \text{ kg/m}^3$$

$$1 \text{ kg/m}^3 = 0.062427 \text{ lbm/ft}^3 = 10^{-3} \text{ g/cm}^3$$

$$1 \text{ g/cm}^3 = 1 \text{ kg/L} = 62.4 \text{ lbm/ft}^3 = 10^3 \text{ kg/m}^3$$

**Viscosity**

$$1 \text{ Pa} \cdot \text{s} = 1 \text{ N} \cdot \text{s}/\text{m}^2 = 1 \text{ kg}/(\text{m} \cdot \text{s}) = 10 \text{ poise}$$

$$1 \text{ poise} = 1 \text{ dyne} \cdot \text{s}/\text{cm}^2 = 1 \text{ g}/(\text{cm} \cdot \text{s}) = 0.1 \text{ Pa} \cdot \text{s}$$

$$1 \text{ poise} = 2.09 \times 10^{-3} \text{ lbf} \cdot \text{s}/\text{ft}^2 = 6.72 \times 10^{-2} \text{ lbm}/(\text{ft} \cdot \text{s})$$

$$1 \text{ centipoise} = 0.01 \text{ poise} = 10^{-3} \text{ Pa} \cdot \text{s}$$

$$1 \text{ lbf} \cdot \text{s}/\text{ft}^2 = 1 \text{ slug}/(\text{ft} \cdot \text{s}) = 47.9 \text{ Pa} \cdot \text{s} = 479 \text{ poise}$$

$$1 \text{ stoke} = 1 \text{ cm}^2/\text{s} = 10^{-4} \text{ m}^2/\text{s} = 1.076 \times 10^{-3} \text{ ft}^2/\text{s}$$

$$1 \text{ centistoke} = 0.01 \text{ stoke} = 10^{-6} \text{ m}^2/\text{s} = 1.076 \times 10^{-5} \text{ ft}^2/\text{s}$$

$$1 \text{ m}^2/\text{s} = 10^4 \text{ stoke} = 10^6 \text{ centistoke} = 10.76 \text{ ft}^2/\text{s}$$

**TABLE A-13** Properties of Saturated Ammonia (Liquid–Vapor): Temperature Table

Temp. °C	Press. bar	Specific Volume m <sup>3</sup> /kg		Internal Energy kJ/kg		Enthalpy kJ/kg			Entropy kJ/kg · K		Temp. °C
		Sat. Liquid $v_f \times 10^3$	Sat. Vapor $v_g$	Sat. Liquid $u_f$	Sat. Vapor $u_g$	Sat. Liquid $h_f$	Evap. $h_{fg}$	Sat. Vapor $h_g$	Sat. Liquid $s_f$	Sat. Vapor $s_g$	
−50	0.4086	1.4245	2.6265	−43.94	1264.99	−43.88	1416.20	1372.32	−0.1922	6.1543	−50
−45	0.5453	1.4367	2.0060	−22.03	1271.19	−21.95	1402.52	1380.57	−0.0951	6.0523	−45
−40	0.7174	1.4493	1.5524	−0.10	1277.20	0.00	1388.56	1388.56	0.0000	5.9557	−40
−36	0.8850	1.4597	1.2757	17.47	1281.87	17.60	1377.17	1394.77	0.0747	5.8819	−36
−32	1.0832	1.4703	1.0561	35.09	1286.41	35.25	1365.55	1400.81	0.1484	5.8111	−32
−30	1.1950	1.4757	0.9634	43.93	1288.63	44.10	1359.65	1403.75	0.1849	5.7767	−30
−28	1.3159	1.4812	0.8803	52.78	1290.82	52.97	1353.68	1406.66	0.2212	5.7430	−28
−26	1.4465	1.4867	0.8056	61.65	1292.97	61.86	1347.65	1409.51	0.2572	5.7100	−26
−22	1.7390	1.4980	0.6780	79.46	1297.18	79.72	1335.36	1415.08	0.3287	5.6457	−22
−20	1.9019	1.5038	0.6233	88.40	1299.23	88.68	1329.10	1417.79	0.3642	5.6144	−20
−18	2.0769	1.5096	0.5739	97.36	1301.25	97.68	1322.77	1420.45	0.3994	5.5837	−18
−16	2.2644	1.5155	0.5291	106.36	1303.23	106.70	1316.35	1423.05	0.4346	5.5536	−16
−14	2.4652	1.5215	0.4885	115.37	1305.17	115.75	1309.86	1425.61	0.4695	5.5239	−14
−12	2.6798	1.5276	0.4516	124.42	1307.08	124.83	1303.28	1428.11	0.5043	5.4948	−12
−10	2.9089	1.5338	0.4180	133.50	1308.95	133.94	1296.61	1430.55	0.5389	5.4662	−10
−8	3.1532	1.5400	0.3874	142.60	1310.78	143.09	1289.86	1432.95	0.5734	5.4380	−8
−6	3.4134	1.5464	0.3595	151.74	1312.57	152.26	1283.02	1435.28	0.6077	5.4103	−6
−4	3.6901	1.5528	0.3340	160.88	1314.32	161.46	1276.10	1437.56	0.6418	5.3831	−4
−2	3.9842	1.5594	0.3106	170.07	1316.04	170.69	1269.08	1439.78	0.6759	5.3562	−2
0	4.2962	1.5660	0.2892	179.29	1317.71	179.96	1261.97	1441.94	0.7097	5.3298	0
2	4.6270	1.5727	0.2695	188.53	1319.34	189.26	1254.77	1444.03	0.7435	5.3038	2
4	4.9773	1.5796	0.2514	197.80	1320.92	198.59	1247.48	1446.07	0.7770	5.2781	4
6	5.3479	1.5866	0.2348	207.10	1322.47	207.95	1240.09	1448.04	0.8105	5.2529	6
8	5.7395	1.5936	0.2195	216.42	1323.96	217.34	1232.61	1449.94	0.8438	5.2279	8
10	6.1529	1.6008	0.2054	225.77	1325.42	226.75	1225.03	1451.78	0.8769	5.2033	10
12	6.5890	1.6081	0.1923	235.14	1326.82	236.20	1217.35	1453.55	0.9099	5.1791	12
16	7.5324	1.6231	0.1691	253.95	1329.48	255.18	1201.70	1456.87	0.9755	5.1314	16
20	8.5762	1.6386	0.1492	272.86	1331.94	274.26	1185.64	1459.90	1.0404	5.0849	20
24	9.7274	1.6547	0.1320	291.84	1334.19	293.45	1169.16	1462.61	1.1048	5.0394	24
28	10.993	1.6714	0.1172	310.92	1336.20	312.75	1152.24	1465.00	1.1686	4.9948	28
32	12.380	1.6887	0.1043	330.07	1337.97	332.17	1134.87	1467.03	1.2319	4.9509	32
36	13.896	1.7068	0.0930	349.32	1339.47	351.69	1117.00	1468.70	1.2946	4.9078	36
40	15.549	1.7256	0.0831	368.67	1340.70	371.35	1098.62	1469.97	1.3569	4.8652	40
45	17.819	1.7503	0.0725	393.01	1341.81	396.13	1074.84	1470.96	1.4341	4.8125	45
50	20.331	1.7765	0.0634	417.56	1342.42	421.17	1050.09	1471.26	1.5109	4.7604	50

Ammonia

Source: Tables A-13 through A-15 are calculated based on equations from L. Haar and J. S. Gallagher, "Thermodynamic Properties of Ammonia," *J. Phys. Chem. Reference Data*, Vol. 7, 1978, pp. 635–792.

**TABLE A-14** Properties of Saturated Ammonia (Liquid–Vapor): Pressure Table

Press. bar	Temp. °C	Specific Volume m <sup>3</sup> /kg		Internal Energy kJ/kg		Enthalpy kJ/kg			Entropy kJ/kg · K		Press. bar
		Sat. Liquid $v_f \times 10^3$	Sat. Vapor $v_g$	Sat. Liquid $u_f$	Sat. Vapor $u_g$	Sat. Liquid $h_f$	Evap. $h_{fg}$	Sat. Vapor $h_g$	Sat. Liquid $s_f$	Sat. Vapor $s_g$	
0.40	−50.36	1.4236	2.6795	−45.52	1264.54	−45.46	1417.18	1371.72	−0.1992	6.1618	0.40
0.50	−46.53	1.4330	2.1752	−28.73	1269.31	−28.66	1406.73	1378.07	−0.1245	6.0829	0.50
0.60	−43.28	1.4410	1.8345	−14.51	1273.27	−14.42	1397.76	1383.34	−0.0622	6.0186	0.60
0.70	−40.46	1.4482	1.5884	−2.11	1276.66	−2.01	1389.85	1387.84	−0.0086	5.9643	0.70
0.80	−37.94	1.4546	1.4020	8.93	1279.61	9.04	1382.73	1391.78	0.0386	5.9174	0.80
0.90	−35.67	1.4605	1.2559	18.91	1282.24	19.04	1376.23	1395.27	0.0808	5.8760	0.90
1.00	−33.60	1.4660	1.1381	28.03	1284.61	28.18	1370.23	1398.41	0.1191	5.8391	1.00
1.25	−29.07	1.4782	0.9237	48.03	1289.65	48.22	1356.89	1405.11	0.2018	5.7610	1.25
1.50	−25.22	1.4889	0.7787	65.10	1293.80	65.32	1345.28	1410.61	0.2712	5.6973	1.50
1.75	−21.86	1.4984	0.6740	80.08	1297.33	80.35	1334.92	1415.27	0.3312	5.6435	1.75
2.00	−18.86	1.5071	0.5946	93.50	1300.39	93.80	1325.51	1419.31	0.3843	5.5969	2.00
2.25	−16.15	1.5151	0.5323	105.68	1303.08	106.03	1316.83	1422.86	0.4319	5.5558	2.25
2.50	−13.67	1.5225	0.4821	116.88	1305.49	117.26	1308.76	1426.03	0.4753	5.5190	2.50
2.75	−11.37	1.5295	0.4408	127.26	1307.67	127.68	1301.20	1428.88	0.5152	5.4858	2.75
3.00	−9.24	1.5361	0.4061	136.96	1309.65	137.42	1294.05	1431.47	0.5520	5.4554	3.00
3.25	−7.24	1.5424	0.3765	146.06	1311.46	146.57	1287.27	1433.84	0.5864	5.4275	3.25
3.50	−5.36	1.5484	0.3511	154.66	1313.14	155.20	1280.81	1436.01	0.6186	5.4016	3.50
3.75	−3.58	1.5542	0.3289	162.80	1314.68	163.38	1274.64	1438.03	0.6489	5.3774	3.75
4.00	−1.90	1.5597	0.3094	170.55	1316.12	171.18	1268.71	1439.89	0.6776	5.3548	4.00
4.25	−0.29	1.5650	0.2921	177.96	1317.47	178.62	1263.01	1441.63	0.7048	5.3336	4.25
4.50	1.25	1.5702	0.2767	185.04	1318.73	185.75	1257.50	1443.25	0.7308	5.3135	4.50
4.75	2.72	1.5752	0.2629	191.84	1319.91	192.59	1252.18	1444.77	0.7555	5.2946	4.75
5.00	4.13	1.5800	0.2503	198.39	1321.02	199.18	1247.02	1446.19	0.7791	5.2765	5.00
5.25	5.48	1.5847	0.2390	204.69	1322.07	205.52	1242.01	1447.53	0.8018	5.2594	5.25
5.50	6.79	1.5893	0.2286	210.78	1323.06	211.65	1237.15	1448.80	0.8236	5.2430	5.50
5.75	8.05	1.5938	0.2191	216.66	1324.00	217.58	1232.41	1449.99	0.8446	5.2273	5.75
6.00	9.27	1.5982	0.2104	222.37	1324.89	223.32	1227.79	1451.12	0.8649	5.2122	6.00
7.00	13.79	1.6148	0.1815	243.56	1328.04	244.69	1210.38	1455.07	0.9394	5.1576	7.00
8.00	17.84	1.6302	0.1596	262.64	1330.64	263.95	1194.36	1458.30	1.0054	5.1099	8.00
9.00	21.52	1.6446	0.1424	280.05	1332.82	281.53	1179.44	1460.97	1.0649	5.0675	9.00
10.00	24.89	1.6584	0.1285	296.10	1334.66	297.76	1165.42	1463.18	1.1191	5.0294	10.00
12.00	30.94	1.6841	0.1075	324.99	1337.52	327.01	1139.52	1466.53	1.2152	4.9625	12.00
14.00	36.26	1.7080	0.0923	350.58	1339.56	352.97	1115.82	1468.79	1.2987	4.9050	14.00
16.00	41.03	1.7306	0.0808	373.69	1340.97	376.46	1093.77	1470.23	1.3729	4.8542	16.00
18.00	45.38	1.7522	0.0717	394.85	1341.88	398.00	1073.01	1471.01	1.4399	4.8086	18.00
20.00	49.37	1.7731	0.0644	414.44	1342.37	417.99	1053.27	1471.26	1.5012	4.7670	20.00

Ammonia

**TABLE A-15** Properties of Superheated Ammonia Vapor

$T$ °C	$v$ m <sup>3</sup> /kg	$u$ kJ/kg	$h$ kJ/kg	$s$ kJ/kg · K	$v$ m <sup>3</sup> /kg	$u$ kJ/kg	$h$ kJ/kg	$s$ kJ/kg · K
$p = 0.4 \text{ bar} = 0.04 \text{ MPa}$ ( $T_{\text{sat}} = -50.36^\circ\text{C}$ )					$p = 0.6 \text{ bar} = 0.06 \text{ MPa}$ ( $T_{\text{sat}} = -43.28^\circ\text{C}$ )			
Sat.	2.6795	1264.54	1371.72	6.1618	1.8345	1273.27	1383.34	6.0186
−50	2.6841	1265.11	1372.48	6.1652				
−45	2.7481	1273.05	1382.98	6.2118				
−40	2.8118	1281.01	1393.48	6.2573	1.8630	1278.62	1390.40	6.0490
−35	2.8753	1288.96	1403.98	6.3018	1.9061	1286.75	1401.12	6.0946
−30	2.9385	1296.93	1414.47	6.3455	1.9491	1294.88	1411.83	6.1390
−25	3.0015	1304.90	1424.96	6.3882	1.9918	1303.01	1422.52	6.1826
−20	3.0644	1312.88	1435.46	6.4300	2.0343	1311.13	1433.19	6.2251
−15	3.1271	1320.87	1445.95	6.4711	2.0766	1319.25	1443.85	6.2668
−10	3.1896	1328.87	1456.45	6.5114	2.1188	1327.37	1454.50	6.3077
−5	3.2520	1336.88	1466.95	6.5509	2.1609	1335.49	1465.14	6.3478
0	3.3142	1344.90	1477.47	6.5898	2.2028	1343.61	1475.78	6.3871
5	3.3764	1352.95	1488.00	6.6280	2.2446	1351.75	1486.43	6.4257
$p = 0.8 \text{ bar} = 0.08 \text{ MPa}$ ( $T_{\text{sat}} = -37.94^\circ\text{C}$ )					$p = 1.0 \text{ bar} = 0.10 \text{ MPa}$ ( $T_{\text{sat}} = -33.60^\circ\text{C}$ )			
Sat.	1.4021	1279.61	1391.78	5.9174	1.1381	1284.61	1398.41	5.8391
−35	1.4215	1284.51	1398.23	5.9446				
−30	1.4543	1292.81	1409.15	5.9900	1.1573	1290.71	1406.44	5.8723
−25	1.4868	1301.09	1420.04	6.0343	1.1838	1299.15	1417.53	5.9175
−20	1.5192	1309.36	1430.90	6.0777	1.2101	1307.57	1428.58	5.9616
−15	1.5514	1317.61	1441.72	6.1200	1.2362	1315.96	1439.58	6.0046
−10	1.5834	1325.85	1452.53	6.1615	1.2621	1324.33	1450.54	6.0467
−5	1.6153	1334.09	1463.31	6.2021	1.2880	1332.67	1461.47	6.0878
0	1.6471	1342.31	1474.08	6.2419	1.3136	1341.00	1472.37	6.1281
5	1.6788	1350.54	1484.84	6.2809	1.3392	1349.33	1483.25	6.1676
10	1.7103	1358.77	1495.60	6.3192	1.3647	1357.64	1494.11	6.2063
15	1.7418	1367.01	1506.35	6.3568	1.3900	1365.95	1504.96	6.2442
20	1.7732	1375.25	1517.10	6.3939	1.4153	1374.27	1515.80	6.2816
$p = 1.5 \text{ bar} = 0.15 \text{ MPa}$ ( $T_{\text{sat}} = -25.22^\circ\text{C}$ )					$p = 2.0 \text{ bar} = 0.20 \text{ MPa}$ ( $T_{\text{sat}} = -18.86^\circ\text{C}$ )			
Sat.	0.7787	1293.80	1410.61	5.6973	0.59460	1300.39	1419.31	5.5969
−25	0.7795	1294.20	1411.13	5.6994				
−20	0.7978	1303.00	1422.67	5.7454				
−15	0.8158	1311.75	1434.12	5.7902	0.60542	1307.43	1428.51	5.6328
−10	0.8336	1320.44	1445.49	5.8338	0.61926	1316.46	1440.31	5.6781
−5	0.8514	1329.08	1456.79	5.8764	0.63294	1325.41	1452.00	5.7221
0	0.8689	1337.68	1468.02	5.9179	0.64648	1334.29	1463.59	5.7649
5	0.8864	1346.25	1479.20	5.9585	0.65989	1343.11	1475.09	5.8066
10	0.9037	1354.78	1490.34	5.9981	0.67320	1351.87	1486.51	5.8473
15	0.9210	1363.29	1501.44	6.0370	0.68640	1360.59	1497.87	5.8871
20	0.9382	1371.79	1512.51	6.0751	0.69952	1369.28	1509.18	5.9260
25	0.9553	1380.28	1523.56	6.1125	0.71256	1377.93	1520.44	5.9641
30	0.9723	1388.76	1534.60	6.1492	0.72553	1386.56	1531.67	6.0014

TABLE A-15 (Continued)

$T$ °C	$v$ m <sup>3</sup> /kg	$u$ kJ/kg	$h$ kJ/kg	$s$ kJ/kg · K	$v$ m <sup>3</sup> /kg	$u$ kJ/kg	$h$ kJ/kg	$s$ kJ/kg · K
$p = 2.5 \text{ bar} = 0.25 \text{ MPa}$ ( $T_{\text{sat}} = -13.67^\circ\text{C}$ )					$p = 3.0 \text{ bar} = 0.30 \text{ MPa}$ ( $T_{\text{sat}} = -9.24^\circ\text{C}$ )			
Sat.	0.48213	1305.49	1426.03	5.5190	0.40607	1309.65	1431.47	5.4554
-10	0.49051	1312.37	1435.00	5.5534				
-5	0.50180	1321.65	1447.10	5.5989	0.41428	1317.80	1442.08	5.4953
0	0.51293	1330.83	1459.06	5.6431	0.42382	1327.28	1454.43	5.5409
5	0.52393	1339.91	1470.89	5.6860	0.43323	1336.64	1466.61	5.5851
10	0.53482	1348.91	1482.61	5.7278	0.44251	1345.89	1478.65	5.6280
15	0.54560	1357.84	1494.25	5.7685	0.45169	1355.05	1490.56	5.6697
20	0.55630	1366.72	1505.80	5.8083	0.46078	1364.13	1502.36	5.7103
25	0.56691	1375.55	1517.28	5.8471	0.46978	1373.14	1514.07	5.7499
30	0.57745	1384.34	1528.70	5.8851	0.47870	1382.09	1525.70	5.7886
35	0.58793	1393.10	1540.08	5.9223	0.48756	1391.00	1537.26	5.8264
40	0.59835	1401.84	1551.42	5.9589	0.49637	1399.86	1548.77	5.8635
45	0.60872	1410.56	1562.74	5.9947	0.50512	1408.70	1560.24	5.8998
$p = 3.5 \text{ bar} = 0.35 \text{ MPa}$ ( $T_{\text{sat}} = -5.36^\circ\text{C}$ )					$p = 4.0 \text{ bar} = 0.40 \text{ MPa}$ ( $T_{\text{sat}} = -1.90^\circ\text{C}$ )			
Sat.	0.35108	1313.14	1436.01	5.4016	0.30942	1316.12	1439.89	5.3548
0	0.36011	1323.66	1449.70	5.4522	0.31227	1319.95	1444.86	5.3731
10	0.37654	1342.82	1474.61	5.5417	0.32701	1339.68	1470.49	5.4652
20	0.39251	1361.49	1498.87	5.6259	0.34129	1358.81	1495.33	5.5515
30	0.40814	1379.81	1522.66	5.7057	0.35520	1377.49	1519.57	5.6328
40	0.42350	1397.87	1546.09	5.7818	0.36884	1395.85	1543.38	5.7101
60	0.45363	1433.55	1592.32	5.9249	0.39550	1431.97	1590.17	5.8549
80	0.48320	1469.06	1638.18	6.0586	0.42160	1467.77	1636.41	5.9897
100	0.51240	1504.73	1684.07	6.1850	0.44733	1503.64	1682.58	6.1169
120	0.54136	1540.79	1730.26	6.3056	0.47280	1539.85	1728.97	6.2380
140	0.57013	1577.38	1776.92	6.4213	0.49808	1576.55	1775.79	6.3541
160	0.59876	1614.60	1824.16	6.5330	0.52323	1613.86	1823.16	6.4661
180	0.62728	1652.51	1872.06	6.6411	0.54827	1651.85	1871.16	6.5744
200	0.65572	1691.15	1920.65	6.7460	0.57322	1690.56	1919.85	6.6796
$p = 4.5 \text{ bar} = 0.45 \text{ MPa}$ ( $T_{\text{sat}} = 1.25^\circ\text{C}$ )					$p = 5.0 \text{ bar} = 0.50 \text{ MPa}$ ( $T_{\text{sat}} = 4.13^\circ\text{C}$ )			
Sat.	0.27671	1318.73	1443.25	5.3135	0.25034	1321.02	1446.19	5.2765
10	0.28846	1336.48	1466.29	5.3962	0.25757	1333.22	1462.00	5.3330
20	0.30142	1356.09	1491.72	5.4845	0.26949	1353.32	1488.06	5.4234
30	0.31401	1375.15	1516.45	5.5674	0.28103	1372.76	1513.28	5.5080
40	0.32631	1393.80	1540.64	5.6460	0.29227	1391.74	1537.87	5.5878
60	0.35029	1430.37	1588.00	5.7926	0.31410	1428.76	1585.81	5.7362
80	0.37369	1466.47	1634.63	5.9285	0.33535	1465.16	1632.84	5.8733
100	0.39671	1502.55	1681.07	6.0564	0.35621	1501.46	1679.56	6.0020
120	0.41947	1538.91	1727.67	6.1781	0.37681	1537.97	1726.37	6.1242
140	0.44205	1575.73	1774.65	6.2946	0.39722	1574.90	1773.51	6.2412
160	0.46448	1613.13	1822.15	6.4069	0.41749	1612.40	1821.14	6.3537
180	0.48681	1651.20	1870.26	6.5155	0.43765	1650.54	1869.36	6.4626
200	0.50905	1689.97	1919.04	6.6208	0.45771	1689.38	1918.24	6.5681

TABLE A-15 (Continued)

$T$ °C	$v$ m <sup>3</sup> /kg	$u$ kJ/kg	$h$ kJ/kg	$s$ kJ/kg · K	$v$ m <sup>3</sup> /kg	$u$ kJ/kg	$h$ kJ/kg	$s$ kJ/kg · K
$p = 5.5 \text{ bar} = 0.55 \text{ MPa}$ ( $T_{\text{sat}} = 6.79^\circ\text{C}$ )					$p = 6.0 \text{ bar} = 0.60 \text{ MPa}$ ( $T_{\text{sat}} = 9.27^\circ\text{C}$ )			
Sat.	0.22861	1323.06	1448.80	5.2430	0.21038	1324.89	1451.12	5.2122
10	0.23227	1329.88	1457.63	5.2743	0.21115	1326.47	1453.16	5.2195
20	0.24335	1350.50	1484.34	5.3671	0.22155	1347.62	1480.55	5.3145
30	0.25403	1370.35	1510.07	5.4534	0.23152	1367.90	1506.81	5.4026
40	0.26441	1389.64	1535.07	5.5345	0.24118	1387.52	1532.23	5.4851
50	0.27454	1408.53	1559.53	5.6114	0.25059	1406.67	1557.03	5.5631
60	0.28449	1427.13	1583.60	5.6848	0.25981	1425.49	1581.38	5.6373
80	0.30398	1463.85	1631.04	5.8230	0.27783	1462.52	1629.22	5.7768
100	0.32307	1500.36	1678.05	5.9525	0.29546	1499.25	1676.52	5.9071
120	0.34190	1537.02	1725.07	6.0753	0.31281	1536.07	1723.76	6.0304
140	0.36054	1574.07	1772.37	6.1926	0.32997	1573.24	1771.22	6.1481
160	0.37903	1611.66	1820.13	6.3055	0.34699	1610.92	1819.12	6.2613
180	0.39742	1649.88	1868.46	6.4146	0.36390	1649.22	1867.56	6.3707
200	0.41571	1688.79	1917.43	6.5203	0.38071	1688.20	1916.63	6.4766
$p = 7.0 \text{ bar} = 0.70 \text{ MPa}$ ( $T_{\text{sat}} = 13.79^\circ\text{C}$ )					$p = 8.0 \text{ bar} = 0.80 \text{ MPa}$ ( $T_{\text{sat}} = 17.84^\circ\text{C}$ )			
Sat.	0.18148	1328.04	1455.07	5.1576	0.15958	1330.64	1458.30	5.1099
20	0.18721	1341.72	1472.77	5.2186	0.16138	1335.59	1464.70	5.1318
30	0.19610	1362.88	1500.15	5.3104	0.16948	1357.71	1493.29	5.2277
40	0.20464	1383.20	1526.45	5.3958	0.17720	1378.77	1520.53	5.3161
50	0.21293	1402.90	1551.95	5.4760	0.18465	1399.05	1546.77	5.3986
60	0.22101	1422.16	1576.87	5.5519	0.19189	1418.77	1572.28	5.4763
80	0.23674	1459.85	1625.56	5.6939	0.20590	1457.14	1621.86	5.6209
100	0.25205	1497.02	1673.46	5.8258	0.21949	1494.77	1670.37	5.7545
120	0.26709	1534.16	1721.12	5.9502	0.23280	1532.24	1718.48	5.8801
140	0.28193	1571.57	1768.92	6.0688	0.24590	1569.89	1766.61	5.9995
160	0.29663	1609.44	1817.08	6.1826	0.25886	1607.96	1815.04	6.1140
180	0.31121	1647.90	1865.75	6.2925	0.27170	1646.57	1863.94	6.2243
200	0.32571	1687.02	1915.01	6.3988	0.28445	1685.83	1913.39	6.3311
$p = 9.0 \text{ bar} = 0.90 \text{ MPa}$ ( $T_{\text{sat}} = 21.52^\circ\text{C}$ )					$p = 10.0 \text{ bar} = 1.00 \text{ MPa}$ ( $T_{\text{sat}} = 24.89^\circ\text{C}$ )			
Sat.	0.14239	1332.82	1460.97	5.0675	0.12852	1334.66	1463.18	5.0294
30	0.14872	1352.36	1486.20	5.1520	0.13206	1346.82	1478.88	5.0816
40	0.15582	1374.21	1514.45	5.2436	0.13868	1369.52	1508.20	5.1768
50	0.16263	1395.11	1541.47	5.3286	0.14499	1391.07	1536.06	5.2644
60	0.16922	1415.32	1567.61	5.4083	0.15106	1411.79	1562.86	5.3460
80	0.18191	1454.39	1618.11	5.5555	0.16270	1451.60	1614.31	5.4960
100	0.19416	1492.50	1667.24	5.6908	0.17389	1490.20	1664.10	5.6332
120	0.20612	1530.30	1715.81	5.8176	0.18478	1528.35	1713.13	5.7612
140	0.21788	1568.20	1764.29	5.9379	0.19545	1566.51	1761.96	5.8823
160	0.22948	1606.46	1813.00	6.0530	0.20598	1604.97	1810.94	5.9981
180	0.24097	1645.24	1862.12	6.1639	0.21638	1643.91	1860.29	6.1095
200	0.25237	1684.64	1911.77	6.2711	0.22670	1683.44	1910.14	6.2171

TABLE A-15 (Continued)

$T$ °C	$v$ m <sup>3</sup> /kg	$u$ kJ/kg	$h$ kJ/kg	$s$ kJ/kg · K	$v$ m <sup>3</sup> /kg	$u$ kJ/kg	$h$ kJ/kg	$s$ kJ/kg · K
$p = 12.0 \text{ bar} = 1.20 \text{ MPa}$ ( $T_{\text{sat}} = 30.94^\circ\text{C}$ )					$p = 14.0 \text{ bar} = 1.40 \text{ MPa}$ ( $T_{\text{sat}} = 36.26^\circ\text{C}$ )			
Sat.	0.10751	1337.52	1466.53	4.9625	0.09231	1339.56	1468.79	4.9050
40	0.11287	1359.73	1495.18	5.0553	0.09432	1349.29	1481.33	4.9453
60	0.12378	1404.54	1553.07	5.2347	0.10423	1396.97	1542.89	5.1360
80	0.13387	1445.91	1606.56	5.3906	0.11324	1440.06	1598.59	5.2984
100	0.14347	1485.55	1657.71	5.5315	0.12172	1480.79	1651.20	5.4433
120	0.15275	1524.41	1707.71	5.6620	0.12986	1520.41	1702.21	5.5765
140	0.16181	1563.09	1757.26	5.7850	0.13777	1559.63	1752.52	5.7013
160	0.17072	1601.95	1806.81	5.9021	0.14552	1598.92	1802.65	5.8198
180	0.17950	1641.23	1856.63	6.0145	0.15315	1638.53	1852.94	5.9333
200	0.18819	1681.05	1906.87	6.1230	0.16068	1678.64	1903.59	6.0427
220	0.19680	1721.50	1957.66	6.2282	0.16813	1719.35	1954.73	6.1485
240	0.20534	1762.63	2009.04	6.3303	0.17551	1760.72	2006.43	6.2513
260	0.21382	1804.48	2061.06	6.4297	0.18283	1802.78	2058.75	6.3513
280	0.22225	1847.04	2113.74	6.5267	0.19010	1845.55	2111.69	6.4488
$p = 16.0 \text{ bar} = 1.60 \text{ MPa}$ ( $T_{\text{sat}} = 41.03^\circ\text{C}$ )					$p = 18.0 \text{ bar} = 1.80 \text{ MPa}$ ( $T_{\text{sat}} = 45.38^\circ\text{C}$ )			
Sat.	0.08079	1340.97	1470.23	4.8542	0.07174	1341.88	1471.01	4.8086
60	0.08951	1389.06	1532.28	5.0461	0.07801	1380.77	1521.19	4.9627
80	0.09774	1434.02	1590.40	5.2156	0.08565	1427.79	1581.97	5.1399
100	0.10539	1475.93	1644.56	5.3648	0.09267	1470.97	1637.78	5.2937
120	0.11268	1516.34	1696.64	5.5008	0.09931	1512.22	1690.98	5.4326
140	0.11974	1556.14	1747.72	5.6276	0.10570	1552.61	1742.88	5.5614
160	0.12663	1595.85	1798.45	5.7475	0.11192	1592.76	1794.23	5.6828
180	0.13339	1635.81	1849.23	5.8621	0.11801	1633.08	1845.50	5.7985
200	0.14005	1676.21	1900.29	5.9723	0.12400	1673.78	1896.98	5.9096
220	0.14663	1717.18	1951.79	6.0789	0.12991	1715.00	1948.83	6.0170
240	0.15314	1758.79	2003.81	6.1823	0.13574	1756.85	2001.18	6.1210
260	0.15959	1801.07	2056.42	6.2829	0.14152	1799.35	2054.08	6.2222
280	0.16599	1844.05	2109.64	6.3809	0.14724	1842.55	2107.58	6.3207
$p = 20.0 \text{ bar} = 2.00 \text{ MPa}$ ( $T_{\text{sat}} = 49.37^\circ\text{C}$ )								
Sat.	0.06445	1342.37	1471.26	4.7670				
60	0.06875	1372.05	1509.54	4.8838				
80	0.07596	1421.36	1573.27	5.0696				
100	0.08248	1465.89	1630.86	5.2283				
120	0.08861	1508.03	1685.24	5.3703				
140	0.09447	1549.03	1737.98	5.5012				
160	0.10016	1589.65	1789.97	5.6241				
180	0.10571	1630.32	1841.74	5.7409				
200	0.11116	1671.33	1893.64	5.8530				
220	0.11652	1712.82	1945.87	5.9611				
240	0.12182	1754.90	1998.54	6.0658				
260	0.12706	1797.63	2051.74	6.1675				
280	0.13224	1841.03	2105.50	6.2665				