



Global Knowledge®

Atos

Angular Module 7 - Forms

Peter Kassenaar –
info@kassenaar.com

WORLDWIDE LOCATIONS


BELGIUM CANADA COLOMBIA DENMARK EGYPT FRANCE IRELAND JAPAN KOREA MALAYSIA MEXICO NETHERLANDS NORWAY QATAR
SAUDI ARABIA SINGAPORE SPAIN SWEDEN UNITED ARAB EMIRATES UNITED KINGDOM UNITED STATES OF AMERICA

Contents

- Form Fundamentals
- (Template Driven Forms)
- Reactive Forms (aka *Model Driven Forms*)
- Subscribing to Form events

Forms in Web Applications - Tasks

- Initialize Default Values




peter@kassenaar.nl

We'll never share your email with anyone else.

Forms in Web Applications - Tasks

- Initialize Default Values
- Validate Data




Enter email

We'll never share your email with anyone else.

The image shows a rectangular form box with a thin black border. Inside the box, there is a text input field with a light gray border and a light gray background. The placeholder text "Enter email" is displayed in a light gray font. To the left of the input field, there is a small orange vertical bar. Below the input field, the text "We'll never share your email with anyone else." is displayed in a small, dark gray font.

Forms in Web Applications - Tasks

- Initialize Default Values
- Validate Data
- Display Validation messages



Angular Connect ID


Connect ID

Please enter ID in the pattern AA-XX where A is letter and X is a number

The image shows a web form titled "Angular Connect ID". It contains a text input field with the placeholder text "Connect ID". Below the input field, there is a red validation message: "Please enter ID in the pattern AA-XX where A is letter and X is a number". The form is enclosed in a black border.

Forms in Web Applications - Tasks


- Initialize Default Values
- Validate Data
- Display Validation messages
- **Serialize User Data**



Forms in Web Applications - Tasks

- Initialize Default Values
- Validate Data
- Display Validation messages
- Serialize User Data
- Dynamic Forms & Dynamic Controls

```
{
  key: 'email',
  type: 'input',
  templateOptions: {
    type: 'email',
    label: 'Email address',
    placeholder: 'Enter email'
  }
},
{
  key: 'password',
  type: 'input',
  templateOptions: {
    type: 'password',
    label: 'Password',
    placeholder: 'Password'
  }
},
}
```



Full Name


EMAIL ADDRESS

Example: john@gmail.com


SEX

☐ Male ☐ Female

DATE OF BIRTH

-- 

TIME OF ARRIVAL

Please select 

Forms in Web Applications - Tasks

- Initialize Default Values
- Validate Data
- Display Validation messages
- Serialize User Data
- Dynamic Forms & Dynamic Controls
- Custom Controls & Custom Validation

Search the table ...							
	Inv No	Date	Name	Amount	Price	Cost	Note
690	Inv No 690	7/15/2012	Name 690	444	671	297924	Note 690
691	Inv No 691	7/15/2012	Name 691	657	865	568305	Note 691
692	Inv No 692	7/15/2012	Name 692	804	92	73968	Note 692
693	Inv No 693	7/15/2012	Name 693	625	135	84375	Note 693
694	Inv No 694	7/15/2012	Name 694	906	608	550848	Note 694
695	Inv No 695	7/15/2012	Name 695	360	393	141480	Note 695
696	Inv No 696	7/15/2012	Name 696	293	600	175800	Note 696
697	Inv No 697	7/15/2012	Name 697	166	309	51294	Note 697

Angular 2 – Types of Forms

**Template
Driven forms**

**Model Driven
forms**

Angular 2 – Types of Forms


Template Driven Forms


- Source of truth is the Template
- Define templates. Angular generates form model o/t fly
- Less descriptive
- Quickly Build simple forms – Less control
- Less testable

Model Driven (Reactive Forms)

- Source of truth is the component class / directive
- Instantiate Form model and Control model yourself
- More Descriptive
- Code all the details. Takes more time, gives more control
- Very good testable

Angular 2 Forms - Fundamentals





```
export abstract class AbstractControl {  
    _value: any;  
  
    ...  
  
    private _status: string;  
    private _errors: {[key: string]: any};  
    private _pristine: boolean = true;  
    private _touched: boolean = false;  
  
    ...  
  
    get value(): any { return this._value; }  
    get valid(): boolean { return this._status === VALID; }  
  
    ...  
  
    abstract setValue(value: any, options?: Object): void;  
  
    ...  
}
```

<https://github.com/angular/angular/blob/master/modules/%40angular/forms/src/model.ts>

Summary – what have we learned so far

1

Template Driven Forms

Less to code

2

Model Driven Forms

More to code

3

Model

Value/Validity/State

Angular 2 – Types of Forms


**Template
Driven forms**

**Model Driven
forms**

Let's build a template driven form!


- Step 1 – Add (or check) `FormsModule` in `app/main.ts`

```
import {platformBrowserDynamic} from '@angular/platform-browser-dynamic';  
import {FormsModule} from '@angular/forms';  
  
import {AppModule} from './app.module';
```




Step 2 – Add FormsModule to app.module.ts

```
import {NgModule}      from '@angular/core';  
import {BrowserModule} from '@angular/platform-browser';  
import {FormsModule}   from '@angular/forms';
```



```
import {AppComponent} from './app.component';
```

```
@NgModule({  
  imports      : [BrowserModule, FormsModule],  
  declarations: [AppComponent],  
  bootstrap    : [AppComponent]  
})  
export class AppModule {  
}
```



Step 3 – write form in HTML

```
<form novalidate>
  <div class="form-group">
    <label for="inputEmail">Email address</label>
    <input type="email" class="form-control" id="inputEmail"
      placeholder="Enter email" name="email">
    <small class="form-text text-muted">
      We'll never share your email with anyone else.
    </small>
  </div>
  <div class="form-group">
    <label for="inputPassword">Password</label>
    <input type="password" class="form-control" id="inputPassword"
      placeholder="Password" name="password">
  </div>

  <button type="submit" class="btn btn-primary">Submit</button>
</form>
```

This is just plain HTML. No Angular stuff here...

Step 4. Defining a Template Driven Form

- Add `#myForm="ngForm"` to the `<form>` tag
 - This declares a local variable with the name `#myForm` to the `<form>` element. It is of type `NgForm`
- Add `ngModel` to each and every form field
 - No value necessary

```
<form #myForm="ngForm">
  <div class="form-group">
    <input type="email" class="form-control" id="inputEmail"
      placeholder="Enter email" name="email" ngModel>
  </div>
  <div class="form-group">
    <input type="password" class="form-control" ngModel
      id="inputPassword" placeholder="Password" name="password">
  </div>
```

Just checking – Sample results pane

```
<div class="form-result">
  <h3>Validity</h3>
  <div class="validity" [ngClass]="{'invalid-form': !myForm.valid}">
    <div *ngIf="myForm.valid">Valid</div>
    <div *ngIf="!myForm.valid">Invalid</div>
  </div>
  <h3>Results</h3>
  <div class="result">
    {{ myForm.value | json }}
  </div>
</div>
```

Just to show runtime results of the Validity and Value of the form using

`myForm.valid`

`myForm.value`

Results so far

17a - Angular 2 - Template Driven Forms

Email address

We'll never share your email with anyone else.

Password

Validity

Valid

Results

```
{ "email": "", "password": "" }
```

Checkpoint

- The `#myForm` exposes the value and the validity of the form as a whole.
- `ngModel` adds the individual controls to the `#myForm`.
- You can now check it's value and state in the results pane
- Try what happens if you remove one of the `ngModel` directives!
- Check for yourself: the value of a form is a JSON-object.



Addressing individual controls

Retrieve values from individual controls

- Do the same as with the form
- Add for example `#email="ngModel"` to input field
- Now, the value, validity and state (i.e. its `ValueAccessors!`) are accessible through the local template variable

```
<label for="inputEmail">Email address</label>
```

```
<pre>value: {{ email.value }} - valid : {{ email.valid}}</pre>
```

```
<input type="email" class="form-control" id="inputEmail"  
      placeholder="Enter email" name="email" ngModel #email="ngModel">
```

```
<small class="form-text text-muted">
```

```
    We'll never share your email with anyone else.
```

```
</small>
```


Required fields

- Add HTML5 attribute required to the input field.
- No checking on type yet!
 - It's just required.

```
<input type="email" class="form-control" id="inputEmail"  
placeholder="Enter email" name="email" ngModel #email="ngModel" required>
```

17a - Template Driven Forms /app.component2.html | .ts

Email address

value: - valid : false

We'll never share your email with anyone else.

Password

Validity

Invalid

Results

```
{"email": "", "password": ""}
```

17a - Template Driven Forms /app.component2.html | .ts

Email address

value: test - valid : true

We'll never share your email with anyone else.

Validity

Valid

Results



Using ngModelGroup

Adding ngModelGroup

- Combining form fields into logical groups

```
<div ngModelGroup="customer" #customer="ngModelGroup">  
  <div class="form-group">  
    ...  
  </div>  
</div>
```

Use a local template variable (i.e. `#customer="ngModelGroup"`) only if you want to have access to the state and validity of the group as a whole.

ngModelGroup creates a nested object

17a - ngModelGroup
/app.component3.html | .ts

Email address

value: info@kassenaar.com - valid : true

info@kassenaar.com

We'll never share your email with anyone else.

Password

value: test - valid : true

....

Prefix

Mr.

First Name

Peter

Last Name

Kassenaar

```
value {  
  "namePrefix": "Mr.",  
  "firstName": "Peter",  
  "lastName": "Kassenaar"  
}  
valid: true
```

Submit

Validity

Valid

Results

```
{ "email": "info@kassenaar.com", "password": "test", "customer":  
  { "namePrefix": "Mr.", "firstName": "Peter", "lastName":  
    "Kassenaar" } }
```



Submitting forms


Define a (click) handler on the button

- Only activate the button if the form is valid
- Pass `myForm` as a parameter
- Note: no actual need for two-way databinding with `[(ngModel)]`

```
<button type="submit" class="btn btn-primary"
        (click)="onSubmit(myForm)"
        [disabled]="!myForm.valid">
    Submit
</button>
```

```
onSubmit(form){
    console.log('Form submitted: ', form.value);
    alert('Form submitted!' + JSON.stringify(form.value))
}
```


More on Template Driven Forms



I'm Todd, a Developer Advocate @Telerik. Co-Founder of @UltimateAngular Creator of the Angular 2 migration guide. JavaScript, Angular, React, conference speaker. Developer Expert at Google.

[Follow @toddmotto](#) 29.5K followers

[Posts](#) [About](#) [Speaking](#) [Styleguide](#) [ngMigrate](#) [Online training](#)

Angular 2 form fundamentals: template-driven forms

POSTED ON OCT 18, 2016 - [Edit this page on GitHub](#)

Angular 2 presents two different methods for creating forms, template-driven (what we were used to in Angular 1.x), or reactive. We're going to explore the absolute fundamentals of the template-driven Angular 2 forms, covering `ngForm` , `ngModel` , `ngModelGroup` , submit events, validation and error messages.

<https://toddmotto.com/angular-2-forms-template-driven>



Model Driven Forms

Or: *Reactive Forms*

Reactive Forms

- Based on *reactive programming* we already know
 - Events, Event Emitters
 - Observables
- Every form control is an observable!

```
export abstract class AbstractControl {  
  
    ...  
    private _valueChanges: EventEmitter<any>;  
    ...  
    get valueChanges(): Observable<any> {  
        return this._valueChanges;  
    }  
    ...  
}
```

Differences - key things to remember

- No more `ngForm` → use `[formGroup]`
- No more `ngModel` → use `formControlName`
- Import `{ReactiveFormsModule}` from `'@angular/forms'`
- Form state lives in the Component, *not* in the View
- Possible validations are in the Component, not in the View
- The view is *not* generated for you.
- You need to write the HTML yourself

Form Controls are observables

- Import & instantiate in the Component
- Build your model in `constructor` or `ngOnInit`.
- Listen to changes (`.subscribe()`) and act accordingly:

```
export class AppComponent1 implements OnInit {
```

```
  myReactiveForm: FormGroup;
```



```
  constructor(private FormBuilder: FormBuilder) {
```



```
  ngOnInit() {
```

```
    this.myReactiveForm = this.FormBuilder.group({
```



```
      email    : '',
```

```
      password: ''
```

```
    })
```

```
  }
```

```
}
```

Subscribe to those observables

// 1. complete form

```
this.myReactiveForm.valueChanges.subscribe((value)=>{  
    console.log(value);  
});
```

// 2. watch just one control

```
this.myReactiveForm.get('email').valueChanges.subscribe((value)=>{  
    console.log(value);  
});
```



Building reactive forms

Step 1 – import ReactiveFormsModule

- app.module.ts

```
import {NgModule}      from '@angular/core';
import {BrowserModule} from '@angular/platform-browser';
import {FormsModule, ReactiveFormsModule} from '@angular/forms';
import
@NgModule({
  imports : [
    BrowserModule,
    FormsModule,
    ReactiveFormsModule,
    ...
  ],
  ...
})
export class AppModule {
}
```


Step 2 – use [formGroup] and formControlName

```
<form novalidate [formGroup]="myReactiveForm">  
  <div class="form-group">  
    <label for="inputEmail">Email address</label>  
    <input type="email" class="form-control" id="inputEmail"  
      placeholder="Enter email" name="email"  
      formControlName="email">  
  </div>  
  ...  
  // all other controls  
</form>
```

Step 3 – Build your form in Component

```
export class AppComponent1 implements OnInit {
  myReactiveForm: FormGroup;
  constructor(private FormBuilder: FormBuilder) {
  }
  ngOnInit() {
    // 1. Define the model of Reactive Form.
    // Notice the nested FormBuilder.group() for group Customer
    this.myReactiveForm = this.FormBuilder.group({
      email    : '',
      password: '',
      customer: this.FormBuilder.group({
        prefix: '',
        firstName: '',
        lastName: ''
      })
    })
  }
}
```

Subscribe to changes

```
ngOnInit() {
```

```
  ...
```

```
  // 2. Subscribe to changes at form level or...
```

```
  this.myReactiveForm.valueChanges.subscribe((value)=>{  
    console.log('Changes at form level: ', value);  
  });
```

```
  // 3. Subscribe to changes at control level.
```

```
  this.myReactiveForm.get('email').valueChanges.subscribe((value)=>{  
    console.log('Changes at control level: ', value);  
  });
```

```
}
```

Submitting a reactive form

- Can be based on `.valueChanges()` (though not very likely) for any given form control or complete form
- Use just `.click()` event handler for submit button

```
<button type="submit" class="btn btn-primary"
  (click)="onSubmit()"
  [disabled]="!myReactiveForm.valid">
  Submit
</button>
```

```
onSubmit() {
  console.log('Form submitted: ', this.myReactiveForm.value);
  // TODO: do something useful with form
}
```



Form Validation

1. Validating Template driven forms

Use HTML5-attributes like `required`, `pattern`,
`minlength` and so on.

Under the hood, these are actually Angular directives!

Angular adds/removes corresponding classes.

```
<input type="password" class="form-control" ngModel  
      id="inputPassword" placeholder="Password" name="password"
```

```
#pw="ngModel" required minlength="6">
```

Validating reactive forms

No more declarative attributes `required`, `minlength`, `maxlength` and so on.

Add `Validator` on the component class instead.

Configure validator per your needs.

Angular built-in validators

[angular/modules/@angular/forms/src/validators.ts](#)

```
export class Validators {  
  
  static required(control: AbstractControl): {[key: string]: boolean} {  
  }  
  
  static minLength(minLength: number): ValidatorFn {  
  }  
  
  static maxLength(maxLength: number): ValidatorFn {  
  }  
  
  static pattern(pattern: string): ValidatorFn {  
  }  
  
  static nullValidator(c: AbstractControl): {  
  }  
  
  . . .  
}
```

Adding default Validators

- Adding Validators to class definition
 - `email : ['', Validators.required],`
- Multiple validations? Add an array of Validators, using `Validators.compose()`

```
this.myReactiveForm = this.formBuilder.group({  
  email : ['', Validators.required],  
  password: ['', Validators.compose([Validators.required, Validators.minLength(6)])],  
  confirm: ['', Validators.compose([Validators.required, Validators.minLength(6)])],  
  ...  
});
```

Adding Custom Validators

- Creating a Password-confirm validator
- Steps:
 1. Create a validation function, taking `AbstractControl` as a parameter
 2. Write your logic
 3. Don't forget: pass the function in as a configuration parameter for the group or form you are validating!

```
function passwordMatcher(control: AbstractControl) {  
    return control.get('password').value === control.get('confirm').value  
        ? null : {'nomatch': true};  
  
    // we *could* return just true/false here, but by returning an object  
    // we're more flexible in composing our validators.  
}
```



```
this.myReactiveForm = this.formBuilder.group({  
    email    : ['', Validators.required],  
    password: ['', Validators.compose([Validators.required, Validators.minLength(6)])],  
    confirm  : ['', Validators.compose([Validators.required, Validators.minLength(6)])],  
    },  
    {validator: passwordMatcher} // pass in the validator function  
);
```

More on FormBuilder class

- <https://angular.io/docs/ts/latest/api/forms/index/FormBuilder-class.html>
- Information on using and configuring FormBuilder

FormBuilder STABLE
CLASS

What it does

Creates an `AbstractControl` from a user-specified configuration.

It is essentially syntactic sugar that shortens the `new FormGroup()`, `new FormControl()`, and `new FormArray()` boilerplate that can build up in larger forms.

How to use

To use, inject `FormBuilder` into your component class. You can then call its methods directly.

```
1. import {Component, Inject} from '@angular/core';
2. import {FormBuilder, FormGroup, Validators} from '@angular/forms';
3.
4. @Component({
5.   selector: 'example-app',
6.   template: `
```



Subscribing to form events

Working with Observables (again). Typeahead demo

Define a form

```
<form novalidate [formGroup]="searchForm">  
  <div class="form-group">  
    <label for="searchYouTube">Search YouTube</label>  
    <input type="text" class="form-control" id="searchYouTube"  
      formControlName="searchYouTube"  
      placeholder="Search YouTube" name="search">  
  </div>  
  
</form>
```

Define component

- Compose a class, subscribe to `.valueChanges()` event

```
import {Http, Response} from '@angular/http';
import {Observable} from 'rxjs/Observable'
import {FormControl, FormGroup} from "@angular/forms";
...
// import just the operators we need, not import 'rxjs/Rx'
import 'rxjs/add/operator/map';
import 'rxjs/add/operator/switchMap';
import 'rxjs/add/operator/debounceTime';

// define some constants
const BASE_URL = 'https://www.googleapis.com/youtube/v3/search';
const API_KEY = 'AIzaSyBdi3LXzf1xWXOAVgAwNkGvjnM1TwSV4VU';
// compose a url to search for, based on a query/keyword
const makeURL = (query: string) => `${BASE_URL}?q=${query}&part=snippet&key=${API_KEY}`;
```



```

@Component({
  selector    : 'component1',
  templateUrl: 'app/component1/app.component1.html'
})
export class AppComponent1 implements OnInit {
  videos: Observable<any[]>;

  // compose our form
  searchYouTube = new FormControl();
  searchForm    = new FormGroup({
    searchYouTube: this.searchYouTube,
  });

  constructor(private http: Http) {
  }


  ngOnInit() {
    // subscribe to Youtube input textbox and bind async (see html)
    this.videos = this.searchYouTube.valueChanges
      .debounceTime(600)           // wait for 600ms to hit the API
      .map(query => makeURL(query)) // turn keyword into a real youtube-URL
      .switchMap(url => this.http.get(url)) // wait for, and switch to the Observable that my http get ...
      .map((res: Response) => res.json())   // map its response to json
      .map(response => response.items);     // unwrap the response and return only the items array
  }
}

```

Reactive forms examples

- See 502 as an example
 - YouTube Search
 - Wikipedia Search

More on Reactive Forms



The screenshot shows the top section of a website. At the top left is a circular profile picture of a man. To its right is a bio: "I'm Todd, a Developer Advocate @Telerik. Co-Founder of @UltimateAngular Creator of the Angular 2 migration guide. JavaScript, Angular, React, conference speaker. Developer Expert at Google." Below the bio is a blue "Follow @toddmotto" button and a grey "29.5K followers" badge. A dark navigation bar contains links: "Posts", "About", "Speaking", "Styleguide", "ngMigrate", and "Online training" with a red Angular logo. Below the navigation bar is a large white box containing the article title "Angular 2 form fundamentals: reactive forms" in a serif font. Under the title is a line with "POSTED ON OCT 19, 2016 - Edit this page on GitHub". The main text begins with "Angular 2 presents two different methods for creating forms, template-driven (what we were used to in Angular 1.x), or reactive. We're going to explore the absolute fundamentals of the reactive Angular 2 forms, covering ngForm , ngModel , ngModelGroup , submit events, validation and error messages."

I'm Todd, a Developer Advocate @Telerik. Co-Founder of @UltimateAngular Creator of the Angular 2 migration guide. JavaScript, Angular, React, conference speaker. Developer Expert at Google.

Follow @toddmotto 29.5K followers

Posts About Speaking Styleguide ngMigrate Online training


Angular 2 form fundamentals: reactive forms

POSTED ON OCT 19, 2016 - [Edit this page on GitHub](#)

Angular 2 presents two different methods for creating forms, template-driven (what we were used to in Angular 1.x), or reactive. We're going to explore the absolute fundamentals of the reactive Angular 2 forms, covering `ngForm` , `ngModel` , `ngModelGroup` , submit events, validation and error messages.

<https://toddmotto.com/angular-2-forms-reactive>

Kara Erickson on Angular Forms



The video player displays a presentation slide comparing **FormsModule** and **ReactiveFormsModule**. The slide has a light blue background with a pattern of geometric shapes. The **FormsModule** section is on the left, and the **ReactiveFormsModule** section is on the right, highlighted with a dark blue background. A small inset video shows Kara Erickson at a podium. The Angular logo is visible in the bottom right of the slide.

FormsModule	ReactiveFormsModule
Implicit creation of FormControl() by directives	Explicit creation of FormControl()
Source of truth: template	Source of truth: component class
Async	Sync

Angular 2 Forms | Kara Erickson


AngularConnect

✓ Geabonneerd 8.523

7.965 weergaven

<https://www.youtube.com/watch?v=xYv9lsrV0s4>

Automated form and template generation, based on a form model:



<https://formly-js.github.io/ngx-formly/>