

RFPC-SMA27-F		CUSTOMER PRODUCT SPECIFICATION SHEET				RoHS Compliant	
RFPC-SMA27-F : SMA Right Angle Bulkhead Jack, PCB Connector, 6GHz							
Material and Plating: Insulator: PTFE Pin: Brass, Gold Body: Brass, Gold Specification: Operating Temperature: -55°C~+125°C Working Frequency Range: DC~6GHz Impedance: 50 Ohm.							
REV. DATE & DRN 1.0 20/05/19 - NYW RELEASE		Scale: NTS Drawn: CC App'd: XXX Date: 17 OCT. '23		THIRD ANGLE Title SMA PCB Connector Revision: 1.0		Unstated Tolerances: .X ±0.2 .XX ±0.1 .XXX ±0.05 ANGLES ±3° Material SEE NOTE NOT TO SCALE Unit: mm	
				 www.gradconn.com		Type: RFPC-SMA27-F RFPC-SMA27-F Drawing Number: Sheet 1 of 2 Drawing © E and O E	
© THIS DRAWING IS CONFIDENTIAL AND MUST NOT BE COPIED OR DISCLOSED WITHOUT WRITTEN CONSENT							

REV. DATE & DRN TO 20/05/79 - NYW RELEASE	Scale: NTS Drawn: CC App'd: XXX Date: 17 OCT. '23	THIRD ANGLE Title SMA PCB Connector Revision: 1.0	Unstated Tolerances: .X ±0.2 .XX ±0.1 .XXX ±0.05 ANGLES ±3° Material SEE NOTE NOT TO SCALE Unit: mm	www.gradconn.com THIS DRAWING IS CONFIDENTIAL AND MUST NOT BE COPIED OR DISCLOSED WITHOUT WRITTEN CONSENT	Type: RFPC-SMA27-F RFPC-SMA27-F Drawing Number: Sheet 1 of 2 Drawing © E and O E	

