

# Computational Algebraic Topology: Lecture 6

Alberto Paoluzzi

March 24, 2017

# Simplicial complexes & Delaunay triangulations

- 1 Delaunay triangulations
- 2 `Scipy.spatial` package in Python
- 3 Julia interface to Python
- 4 'Facet and extrusion operations in  $\text{Simple}_X^n$
- 5 References

# Delaunay triangulations

# Delaunay triangulation

In mathematics and computational geometry, a **Delaunay triangulation** for a set  $P$  of points in  $\mathbb{E}^2$  is a triangulation  $\mathcal{T}(P)$  such that **no point in  $P$  is inside the circumcircle** of any triangle in  $\mathcal{T}(P)$





Figure 1: Delaunay triangulation

# Dual vertices

The Delaunay triangulation of a discrete point set  $P$  in **general position** corresponds to the **dual graph** of the **Voronoi diagram** for  $P$



# Voronoi complex

- a Voronoi complex is a partitioning of a plane into a **cellular complex** based on **distance** to points in a discrete set  $P$
- The regions are called **Voronoi cells**. The Voronoi diagram of a set of points is **dual to its Delaunay triangulation**.
- The 2-cells are **convex**




Figure 3: Delaunay triangulation

# Properties of Delaunay triangulations (from Wikipedia)

- Delaunay triangulations **maximize the minimum angle** of all the angles of the triangles in the triangulation; they tend to **avoid sliver triangles**.
- For a set of points **on the same line** there is **no Delaunay** triangulation (the notion of triangulation is degenerate for this case).
- **For four or more points on the same circle** (e.g., the vertices of a rectangle) the Delaunay triangulation **is not unique**:
  - **each of the two** possible triangulations that split the quadrangle into two triangles **satisfies the “Delaunay condition”**, i.e., the requirement that the circumcircles of all triangles have empty interiors.
- By considering **circumscribed spheres**, the notion of Delaunay triangulation **extends to three and higher dimensions**.

# Scipy.spatial package in Python



# Spatial data structures and algorithms (scipy.spatial)


[SciPy.org](#)
[Docs](#)
[SciPy v0.19.0 Reference Guide](#)
[SciPy Tutorial](#)
[index](#)
[modules](#)
[modules](#)
[next](#)
[previous](#)

## Spatial data structures and algorithms (scipy.spatial)

[scipy.spatial](#) can compute triangulations, Voronoi diagrams, and convex hulls of a set of points, by leveraging the [Qhull](#) library.

Moreover, it contains [KDTree](#) implementations for nearest-neighbor point queries, and utilities for distance computations in various metrics.

### Table Of Contents

- [Spatial data structures and algorithms \(\[scipy.spatial\]\(#\)\)](#)
  - [Delaunay triangulations](#)
    - [Coplanar points](#)
  - [Convex hulls](#)
  - [Voronoi diagrams](#)

## Assignment !!

: Follow step by step the tutorial ...

# Julia interface to Python

# Julia Calling Python Calling Julia...

Leah Hanson

[About](#) | [Posts](#) | [Speaking](#) | [RSS](#)

## Julia Calling Python Calling Julia...

Oct 6, 2013 #julia #projects #code

[Julia](#) is a young programming language. This means that its native libraries are immature. We are in a time when Julia is a mature enough as a language that it is out-pacing its libraries.

One way to use mature libraries from a young language is to borrow them from another language. In this case, we'll be borrowing from Python. (Julia can also easily wrap libraries from C or Fortran. In fact, this capability was important in combination with Python's great C-interface to make calling Python from Julia do-able.)

# Using Python Libraries from Julia

```
using PyCall
@pyimport pylab

x = linspace(0,2*pi,1000);
y = sin(3*x + 4*cos(2*x));

pylab.plot(x, y; color="red", linewidth=2.0, linestyle="--")
pylab.show()
```

# Using Larlib from Julia

cvdlab / LAR.jl
Unwatch 2
Star 1
Fork 0

<> Code
Issues 0
Pull requests 0
Projects 0
Wiki
Pulse
Graphs
Settings

*No description, website, or topics provided.* Edit

[Add topics](#)

139 commits
7 branches
0 releases
1 contributor
MIT

Branch: master
New pull request
Create new file
Upload files
Find file
Clone or download

apaoluzzi crumbs
Latest commit e5575e9 on Jan 24

# Using Larlib from Julia

```
using LAR
```

```
jsonModel = """
    {"V" : [[5.0,0.0],[7.0,1.0],[9.0,0.0],[13.0,2.0],[15.0,4.0],[17.0,
8.0],[14.0,9.0],[13.0,10.0],[11.0,11.0],[9.0,10.0],[5.0,9.0],[7.0,
9.0],[3.0,8.0],[0.0,6.0],[2.0,3.0],[2.0,1.0],[8.0,3.0],[10.0,2.0],
[13.0,4.0],[14.0,6.0],[13.0,7.0],[12.0,10.0],[11.0,9.0],[9.0,7.0],
[7.0,7.0],[4.0,7.0],[2.0,6.0],[3.0,5.0],[4.0,2.0],[6.0,3.0],[11.0,
4.0],[12.0,6.0],[12.0,7.0],[10.0,5.0],[8.0,5.0],[7.0,6.0],[5.0,5.0]],
"FV" : [[0,1,16,28,29],[0,15,28],[1,2,17],[1,16,17,33],[2,3,17],
[3,4,18,19],[3,17,18,30],[4,5,19],[5,6,19],[6,7,20,21,22,32],
[6,19,20],[7,8,21],[8,9,21,22],[9,11,23,24],[9,22,23],
[10,11,24,25],[10,12,25],[12,13,25,26],[13,14,27],[13,26,27],
[14,15,28],[14,27,28,29,36],[16,29,34],[16,33,34],[17,30,33],
[18,19,31],[18,30,31],[19,20,31,32],[22,23,32,33],[23,24,34,35],
[23,33,34],[24,25,27,36],[24,35,36],[25,26,27],[29,34,35],
[29,35,36],[30,31,32,33],[0,1,2,3,4,5,6,7,8,9,10,11,12,13,14,15]]}
    """;
model = json2larmodel(jsonModel);
viewexploded(model.Verts, rebase(model.Lar.FV[1:end-1]))
```

# Using Larlib from Julia

```
# Input of a LAR representation (2-complex in JSON format)
larDict = JSON.parse(jsonModel);
V = larDict["V"];
FV = larDict["FV"];

# extraction of facets (1-cells)
v,ev = p.larFacets((V,FV),2);

# visualization in Julia
viewexploded(v',(ev+1)')
viewLarIndices(v',(ev+1)')
```

## Assignment !!

: look for `viewexploded` in `LAR.jl` and in `Larlib`

# 'Facet and extrusion operations in $\text{Simple}_X^n$



# Extraction of facets from a set of $d$ -simplices

$$\partial \sigma^d = \sum_{k=0}^d (-1)^k \langle v_0, \dots, v_{k-1}, v_{k+1}, \dots, v_d \rangle$$

**Implementation** The `larSimplexFacets` function, for extraction of non-oriented  $(d-1)$ -facets of  $d$ -dimensional simplices, returns a list of  $d$ -tuples of integers, i.e. the input LAR representation of the topology of a cellular complex. The final steps are used to remove the duplicated facets, by transforming the sorted facets into a *set of strings*, so removing the duplicated elements.

$\langle \text{Facets extraction from a set of simplices 8b} \rangle \equiv$

```
def larSimplexFacets(simplices):
    out = []
    d = len(simplices[0])
    for simplex in simplices:
        out += AA(sorted)([simplex[0:k]+simplex[k+1:d] for k in range(d)])
    out = set(AA(tuple)(out))
    return sorted(out)
```

◇

Macro referenced in 10.

# Extraction of facets from a set of $d$ -simplices

```
def larSimplexFacets(simplices):
    """ Extraction of facets from a set of  $d$ -simplices """
    out = []
    d = len(simplices[0])

    for simplex in simplices:
        out += AA(sorted)([simplex[0:k]+simplex[k+1:d] for k in range(d-1)])

    out = set(AA(tuple)(out))
    return sorted(out)
```

# Assignment

In synthesis:

- Prepare a simplicial complex  $T$  using random point in Scipy
- Translate `larSimplexFacets` from Python to Julia
- Generate a Julia representation of 1-cells of  $T$

# Extrusion of a simplicial complex

```
def larExtrude1(model,pattern):
    V, FV = model
    d, m = len(FV[0]), len(pattern)
    coords = list(cumsum([0]+(AA(ABS)(pattern))))
    offset, outcells, rangelimit = len(V), [], d*m
    for cell in FV:
        tube = [v + k*offset for k in range(m+1) for v in cell]
        cellTube = [tube[k:k+d+1] for k in range(rangelimit)]
        outcells += [reshape(cellTube, newshape=(m,d,d+1)).tolist()]

    outcells = AA(CAT)(TRANS(outcells))
    cellGroups = [group for k,group in enumerate(outcells) if pattern[k]>0]
    outVertices = [v+[z] for z in coords for v in V]
    outModel = outVertices, CAT(cellGroups)
    return outModel
```

# Assignment

use Nuweb !!

- 1 Look for the meaning of `pattern` in `Larlib`
- 2 Translate in Julia
- 3 Generate

*two*

test examples

# References